This document was prepared in conjunction with work accomplished under Contract No. DE-AC09-96SR18500 with the U. S. Department of Energy.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available for sale to the public, in paper, from: U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161,
phone: (800) 553-6847,
fax: (703) 605-6900
email: orders@ntis.fedworld.gov
online ordering: http://www.ntis.gov/help/index.asp

Available electronically at http://www.osti.gov/bridge
Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from: U.S. Department of Energy, Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831-0062,
phone: (865)576-8401,
fax: (865)576-5728
email: reports@adonis.osti.gov

Appendix A - References relevant to dual-media contaminant transport and borehole flowmeter testing

Dr. Fred Molz, Stephanie Crisman and Rex Hodges conducted an extensive literature search works related to dual-media contaminant transport and borehole flowmeter testings, as part of a SCUREF contract entitled "Application of Dual-Media Concepts to Contaminant Migration in Heterogeneous Aquifers" (Task Order # WEST054). The citations resulting from this effort and provided in the final report are reproduced below:

Anderson, M. P. and W. W. Woessner. Applied groundwater modeling. New York: Academic Press, Inc. 1992.

Arnold, K. B. and Molz, F. J. 2000. In-well hydraulics of the electromagnetic borehole flowmeter: further studies. Ground Water Monitoring & Remediation. Winter:52-55.

Bai, M. and Roegiers, J.-C. 1997. Triple-porosity analysis of solute transport. Journal of Contaminant Hydrology. 28:247-266.

Bajracharya, K. and Barry, D. A. 1997. Nonequilibrium solute transport parameters and their physical significance: numerical and experimental results. Journal of Contaminant Hydrology. 24:185-204.

Bibby, R. 1981. Mass transport of solutes in dual-porosity media. Water Resources Research. 17(4):1075-1081.

Boman, G. K.; Molz, F. J.; and Boone, K. D. 1997. Borehole flowmeter application in fluvial sediments: methodology, results, and assessment. Ground Water. 35(3):443-450.

Bond, W. J. and Wierenga, P. J. 1990. Immobile water during solute transport in unsaturated sand columns. Water Resources Research. 26(10):2475-2481.

Brusseau, M. L.; Gerstl, Z.; Augustijn, D.; and Rao, P. S. C. 1994. Simulating solute transport in an aggregated soil with the dual-porosity model: measured and optimized parameter values. Journal of Hydrology. 163:187-193.

Carberry, J. J. and Bretton, R. H. 1958. Axial dispersion of mass in flow through fixed beds. American Institute of Chemical Engineers Journal. 4(3):367-375.

Casey, F. X. M.; Logsdon, S. D.; Horton, R.; and Jaynes, D. B. 1997. Immobile water content and mass exchange coefficient of a field soil. Soil Science Society of America Journal. 61:1030-1036.

Casey, F. X. M.; Logsdon, S. D.; Horton, R.; and Jaynes, D. B. 1998. Measurement of field hydraulic and solute transport parameters. Soil Science Society of America Journal. 62:1172-1178.

Clothier, B. E.; Heng, L.; Magesan, G. N.; and Vogeler, I. 1995. The measured mobile-water content of an unsaturated soil as a function of hydraulic regime. Australian Journal of Soil Research. 33:397-414.

Clothier, B. E.; Kirkham, M. B.; and McLean, J. E. 1992. In situ measurement of the effective transport volume for solute moving through soil. Soil Science Society of America Journal. 56:733-736.

Coats, K. H. and Smith, B. D. 1964. Dead-end pore volume and dispersion in porous media. Society of Petroleum Engineers Journal. 4:73-84.

Corapcioglu, M. Y. and Wang, S. 1999. Dual-porosity groundwater contaminant transport in the presence of colloids. Water Resources Research. 35(11):3261-3273.

Deans, H. A. 1963. A mathematical model for dispersion in the direction of flow in porous media. Society of Petroleum Engineers Journal. 228:49-52.

Deans, H. A. and Lapidus, L. 1960. A computational model for predicting and correlating the behavior of fixed-bed reactors: I. Derivation of model for nonreactive systems. American Institute of Chemical Engineers Journal. 6(4):656-663.

Desbarats, A. J. 1992. Spatial averaging of hydraulic conductivity in three-dimensional heterogeneous porous media. Mathematical Geology. 24(3):249-267.

DeSmedt, F. and Wierenga, P. J. 1979. A generalized solution for solute flows in soils with mobile and immobile water. Water Resources Research. 15(5):1137-1141.

Deutsch, C. Estimating block effective permeability with geostatistics and power averaging. SPE 15991: Society of Petroleum Engineers; 1986.

Dinwiddie, C. L.; Foley, N. A.; and Molz, F. J. 1999. In-well hydraulics of the electromagnetic borehole flowmeter. Ground Water. 37(2):305-315.

Dykhuizen, R. C. 1990. A new coupling term for dual-porosity models. Water Resources Research. 26(2):351-356.

Falta, R. W. 2000. Numerical modeling of kinetic interphase mass transfer during air sparging using a dual-media approach. Water Resources Research. 36(12):3391-3400.

Feehley, C. E.; Zheng, C.; and Molz, F. J. 2000. A dual-domain mass transfer approach for modeling solute transport in heterogeneous aquifers: Application to the Macrodispersion Experiment (MADE) site. Water Resources Research. 36(9):2501-2515.

Flach, G. P.; Sappington, F. C.; Johnson, W. P.; and Hiergesell, R. A. 2000. Electromagnetic borehole flowmeter (EBF) testing in R-area (U). WSRC-TR-2000-00170.

Gaudet, J. P.; Jégat, H.; Vachaud, G.; and Wierenga, P. J. 1977. Solute transfer, with exchange between mobile and stagnant water, through unsaturated sand. Soil Science Society of America Journal. 41(4):665-670.

Gelhar, L. W. and Collins, M. A. 1971. General analysis of longitudinal dispersion in nonuniform flow. Water Resources Research. 7(6):1511-1521.

Gerke, H. H. and van Genuchten, M. T. 1993a. Evaluation of a first-order water transfer term for variably saturated dual-porosity flow models. Water Resources Research. 29(4):1225-1238.

Gerke, H. H. and van Genuchten, M. Th. 1993b. A dual-porosity model for simulating the preferential movement of water and solutes in structured porous media. Water Resources Research. 29(2):305-319.

Gerke, H. H. and van Genuchten, M. Th. 1996. Macroscopic representation of structural geometry for simulating water and solute movement in dual-porosity media. Advances in Water Research. 19(6):343-357.

Germann, P. F. and DiPietro, L. 1996. When is porous media flow preferential? A hydromechanical perspective. Geoderma. 74:1-21.

Ghodrati, M. and Jury, W. A. 1990. A field study using dyes to characterize preferential flow of water. Soil Science Society of America Journal. 54:1558-1563.

Gottschlich, C. F. 1963. Axial dispersion in a packed bed. American Institute of Chemical Engineers Journal. 9(1):88-92.

Griffioen, J. W.; Barry, D. A.; and Parlange, J.-Y. 1998. Interpretation of two-region model parameters. Water Resources Research. 34(3):373-384.

Güven, O.; Falta, R. W.; Molz, F. J.; and Melville, J. G. 1985. Analysis and interpretation of single-well tracer tests in stratified aquifers. Water Resources Research. 21(5):676-684.

Haggerty, R. and Gorelick, S. M. 1995. Multiple rate mass transfer for modeling diffusion and surface reactions in media with pore-scale heterogeneity. Water Resources Research. 31(10):2383-2400.

Haggerty, R.; McKenna, S. A.; and Meigs, L. C. 2000. On the late-time behavior of tracer test breakthrough curves. Water Resources Research. 36(12):3467-3479.

Hamm, S.-Y. and Bidaux, P. 1996. Dual-porosity fractal models for transient flow analysis in fissured rocks. Water Resources Research. 32(9):2733-2745.

Hanson, R. T. and Nishikawa, T. 1996. Combined use of flowmeter and time-drawdown data to estimate hydraulic conductivities in a layered aquifer system. Ground Water. 34(1):84-94.

Harvey, C. F. and Gorelick, S. M. 2000. Rate-limited mass transfer or macrodispersion: Which dominates plume evolution at the Macrodispersion Experiment (MADE) site? Water Resources Research. 36(3):637-650.

Hassan, A. E. 2001. Water flow and solute mass flux in heterogeneous porous formations with spatially random porosity. Journal of Hydrology. 242:1-25.

Hemker, C. J. 1999a. Transient well flow in layered aquifer systems: the uniform well-face drawdown solution. Journal of Hydrology. 225:19-44.

Hemker, C. J. 1999b. Transient well flow in vertically heterogeneous aquifers. Journal of Hydrology. 225:1-18.

Hess, A. E. 1986. Identifying hydraulically conductive fractures with a slow-velocity borehole flowmeter. Canadian Geotechnical Journal. 23:69-78.

Hess, K. M.; Wolf, S. M.; and Celia, M. A. 1992. Large-scale natural gradient tracer test in sand and gravel, Cape Cod, Massachusettes, 3. Hydraulic conductivity variability and calculated macrodispersivities. Water Resources Research. 28(8):2011-2027.

Hollenbeck, K. J.; Harvey, C. F.; Haggerty, R.; and Werth, C. J. 1999. A method for estimating distributions of mass transfer rate coefficients with application to purging and batch experiments. Journal of Contaminant Hydrology. 37:367-388.

Hunt, A. G. 2001. Applications of percolation theory to porous media with distributed local conductances. Advances in Water Resources. 24:279-307.

Hutchins, S. R. and Acree, S. D. 2000. Ground water sampling bias observed in shallow, conventional wells. Ground Water Monitoring & Remediation. Winter :86-93.

Hyndman, d. W. and Gorelick, S. M. 1996. Estimating lithologic and transport properties in three dimensions using seismic and tracer data: The Kesterson aquifer. Water Resources Research. 32(9):2659-2670.

Javandel, I. and Witherspoon, P. A. 1969. A method of analyzing transient fluid flow in multilayered aquifers. Water Resources Research. 5:856-869.

Jaynes, D. B. and Horton, R. 1998. Field parameterization of the mobile/immobile domain model. Selim, H. M. and Ma, L., ed. Physical nonequilibrium in soils: Modeling and application. Ann Arbor, MI: Ann Arbor Press; pp. 297-310.

Jaynes, D. B.; Logsdon, S. D.; and Horton, R. 1995. Field method for measuring mobile/immobile water content and solute transfer rate coefficient. Soil Science Society of America Journal. 59:152-356.

Jaynes, D. B. and Shao, M. 1999. Evaluation of a simple technique for estimating two-domain transport parameters. Soil Science. 164(2):82-91.

Julian, H. E.; Boggs, J. M.; Zheng, C.; and Feehley, C. E. 2001. Numerical simulation of a natural gradient tracer experiment for the natural attenuation study: flow and physical transport. Ground Water. 39(4):534-545.

Kabala, Z. J. 1994. Measuring distributions of hydraulic conductivity and specific storativity by the double flowmeter test. Water Resources Research. 30(3):685-690.

Koltermann, C. E. and Gorelick, S. M. 1996. Heterogeneity in sedimentary deposits: A review of structure-imitating, process-imitating, and descriptive approaches. Water Resources Research. 32(9):2617-2658.

Larsson, M. H. and Jarvis, N. J. 1999. Evaluation of a dual-porosity model to predict field-scale solute transport in a macroporous soil. Journal of Hydrology. 215:153-171.

Lee, J.; Horton, R.; and Jaynes, D. B. 2000. A time domain reflectrometry method to measure immobile water content and mass exchange coefficient. Soil Science Society of America Journal. 64(6):1911-1917.

Li, L.; Barry, D. A.; Culligan-Hensley, P. J.; and Bajracharya, K. 1994. Mass tranfer in soils with local stratification of hydraulic conductivity. Water Resources Research. 30(11):2891-2900.

Liu, H. H.; Bodvarsson, G. S.; and Pan, L. 2000. Determination of particle transfer in random walk particle methods for fractured porous media. Water Resources Research. 36(3):707-713.

Maidment, D.R. Handbook of hydrology. New York: McGraw-Hill, Inc. 1993.

McGinley, P. M.; Katz, L. E.; and Weber, W. J. Jr. 1996. Competitive sorption and displacement of hydrophobic organic contaminants in saturated subsurface soil systems. Water Resources Research. 32(12):3571-3577.

Molz, F. J. 1981. Models of water transport in the soil-plant system: A review. Water Resources Research. 17(5):1245-1260.

Molz, F. J.; Bowman, G. K.; Young, S. C.; and Waldrop, W. R. 1994. Borehole flowmeters-Field application and data analysis. Journal of Hydrology. 163:347-371.

Molz, F. J. and Ikenberry, E. 1974. Water transport through plant cells and cell walls: theoretical development. Soil Science Society of America Proceedings. 38:699-704.

Molz, F. J.; Guven, O.; Melville, J. G.; and Cardone, C. 1989a. Hydraulic conductivity measurement at different scales and contaminant transport modeling. Cushman, J. H., ed. Dynamics of fluids in hierarchal porous media. New York: Academic Press; pp. 35-79.

Molz, F. J.; Liu, H. H.; and Szulga, J. 1997. Fractional Brownian motion and fractional Gaussian noise in subsurface hydrology: A review, presentation of fundamental properties, and extensions. Water Resources Research. 33(10):2273-2286.

Molz, F. J.; Morin, R. H.; Hess, A. E.; Melville, J. G.; and Guven, O. 1989b. The impeller meter for measuring aquifer permeability variations: Evaluation and comparison with other tests. Water Resources Research. 25(7):1677-1683.

Molz, F. J. and Young, S. C. 1993. Development and application of borehole flowmeters for environmental assessment. The Log Analyst. 3:13-23.

Montas, H. J.; Shirmohammadi, A.; Haghighi, K.; and Engel, B. 2000. Equivalence of bicontinuum and second-order transport in heterogeneoous soils and aquifers. Water Resources Research. 36(12):3427-3446.

Morin, R. H.; Hess, A. E.; and Paillet, F. L. 1988. Determining the distribution of hydraulic conductivity in a fractured limestone aquifer by simultaneous injection and geophysical logging. Ground Water. 26:387-595.

Niemann, W. L. and Rovey, C. W. I. 2000. Comparison of hydraulic conductivity values obtained from aquifer pumping tests and conservative tracer tests. Ground Water Monitoring & Remediation. Summer:122-128.

Nkedi-Kizza, P.; Biggar, J. W.; Selim, H. M.; van Genuchten, M. Th.; Wierenga, P. J.; Davidson, J. M.; and Nielsen, D. R. 1984. On the equivalence of two conceptual models for describing ion exchange during transport through an aggregated oxisol. Water Resources Research. 20(8):1123-1130.

Nkedi-Kizza, P.; Biggar, J. W.; van Genuchten, M. Th.; Wierenga, P. J.; Selim, H. M.; Davidson, J. M.; and Nielsen, D. R. 1983. Modeling tritium and chloride 36 transport through an aggregated oxisol. Water Resources Research. 19(3):691-700.

Ostensen, R. W. 1998. Tracer tests and contaminant transport rates in dual-porosity formations with application to the WIPP. Journal of Hydrology. 204:197-216.

Paillet, F. L. and Reese, R. S. 2000. Integrating borehole logs and aquifer tests in aquifer characterization. Ground Water. 38(5):713-725.

Painter, S.; Cvetkovic, V.; and Turner, D. R. 2001. Effect of heterogeneity on radionuclide retardation in the alluvial aquifer near Yucca Mountain, Nevada. Ground Water. 39(3):326-338.

Perkins, T. K. and Johnston, O. C. 1963. A review of diffusion and dispersion in porous media. Society of Petroleum Engineers Journal. 228:70-84.

Podgorney, R. K. and Ritzi, R. W. Jr. 1997. Capture zone geometry in a fractured carbonate aquifer. Ground Water. 35(6):1040-1048.

Pruess, K. and Narasimhan, T. N. 1986. A practical method for modeling fluid and heat flow in fractured porous media. Society of Petroleum Engineers Journal(Feb):14-26.

Rao, P. S. C.; Rolston, D. E.; Jessup, R. E.; and Davidson, J. M. 1980. Solute transport in aggregated porous media: theoretical and experimental evaluation. Soil Science Society of America Journal. 44:1139-1146.

Ray, C.; Ellsworth, T. R.; Valocchi, A. J.; and Boast, C. W. 1997. An improved dual porosity model fro chemical transport in macroporous soils. Journal of Hydrology. 193:270-292.

Rehfeldt, K. R.; Hufschmied, P.; Gelhar, L. W.; and Schaefer, M. E. 1989. The borehole flowmeter techniques for measuring hydraulic conductivity variability: Electric Power Research Institute, Interim Report EM-6511, Palo Alto, California.

Rehfeldt, K. R.; Boggs, J. M.; and Gelhar, L. W. 1992. Field study of dispersion in a heterogeneous aquifer 3. Geostatistical analysis of hydraulic conductivity. Water Resources Research. 28(12):3309-3324.

Ruud, N. C. and Kabala, Z. J. 1996. Numerical evaluation of flowmeter test interpretation methodologies. Water Resources Research. 32(4):845-852.

Ruud, N. C. and Kabala, Z. J. 1997a. Numerical evaluation of the flowmeter test in a layered aquifer with skin zone. Journal of Hydrology. 203:101-108.

Ruud, N. C. and Kabala, Z. J. 1997b. Response of a partially penetrating well in a heterogeneous aquifer: Integrated well-face flux versus uniform well-face flux boundary conditions. Journal of Hydrology. 194(1-4):76-94.

Ruud, N. C.; Kabala, Z. J.; and Molz, F. J. 1999. Evaluation of flowmeter-head loss effects in the flowmeter test. Journal of Hydrology. 224:55-63.

Sardin, M.; Schweich, D.; Leij, F. J.; and van Genuchten, M. Th. 1991. Modeling the nonequilibrium transport of linearly interacting solutes in porous media: a review. Water Resources Research. 27(9):2287-2307.

Scheibe, T. and Yabusaki, S. 1998. Scaling of flow and transport behavior in heterogeneous groundwater systems. Advances in Water Resources. 22(3):223-238.

Schwartz, R. C.; Juo, A. S. R.; and McInnes, K. J. 2000. Estimating parameters for a dual-porosity model to describe non-equilibrium, reactive transport in a fine-textured soil. Journal of Hydrology. 229:149-167.

Skopp, J.; Gardner, W. R.; and Tyler, E. J. 1981. Miscible displacement in structured soils: Two region model with small interaction. Soil Science Society of America Journal. 45:837-842.

Skopp, J. and Warrick, A. W. 1974. A two-phase model for the miscible displacement of reactive solutes in soils. Soil Science Society of America Journal. 38(4):545-550.

Sudicky, E. A. 1990. The Laplace Transform Galerkin Technique for efficient time-continuous solution of solute transport in double-porosity media. Geoderma. 46:209-232.

Tang, D. H.; Frind, E. O.; and Sudicky, E. A. 1981. Contaminant transport in fractured porous media: Analytical solution for a single fracture. Water Resources Research. 17(3):555-564.

Turner, G. A. 1958. The flow structure in packed beds a theoretical investigation utilizing frequency response. Chemical Engineering Science. 7:156-165.

van Genuchten, M. Th. 1985. A general approach for modeling solute transport in structured soils. Proceedings 17th International Congress "Hydrogeology of Rocks of Low Permeability". Memoires IAH, 17(2):513-526.

van Genuchten, M. Th. and Dalton, F. N. 1986. Models for simulating salt movement in aggregated field soils. Geoderma. 38:165-183.

van Genuchten, M. Th. and Wagenet, P. J. 1989. Two-site/two-region models for pesticide transport and degradation: Theoretical development and analytical solutions. Soil Science Society of America Journal. 53:1303-1310.

van Genuchten, M. Th. and Wierenga, P. J. 1976. Mass transfer studies in sorbing porous media I. Analytical solutions. Soil Science Society of America Journal. 40(4):473-480.

van Genuchten, M. Th. and Wierenga, P. J. 1977. Mass transfer studies in sorbing porous media: II. Experimental evaluation with tritium (3H2O). Soil Science Society of America Journal. 41:272-278.

van Genuchten, M. Th.; Wierenga, P. J.; and O'Connor, G. A. 1977. Mass transfer studies in sorbing porous media: III. Experimental evaluation with 2,4,5-T. Soil Science Society of America Journal. 41:278-285.

Vogel, T.; Gerke, H. H.; Zhang, R.; and van Genuchten, M. Th. 2000. Modeling flow and transport in a two-dimensional dual-permeability system with spacially variable hydraulic properties. Journal of Hydrology. 238:78-89.

Waldrop, W. R. 1995. A summary of hydrogeologic studies with the Electromagnetic Borehole Flowmeter. Report QEC T-102, Quantum Engineering Corporation, 112 Tigitsi Lane, Loudon, Tennessee, 37774, 615-458-0506.

Warren, J. E. and Root, P. J. 1963. The behavior of naturally fractured reservoirs. Society of Petroleum Engineers Journal. 3:245-255.

Xiang, J. 1995. The evaluation of the flowmeter test in three-layer aquifers and the influence of disturbed zones. Journal of Hydrology. 166:127-145.

Young, S. C. 1995. Characterization of high-K pathways by borehole flowmeter and tracer tests. Ground Water. 33(2):311-318.

Young, S. C. 1998. Impacts of positive skin effects on borehole flowmeter tests in a heterogeneous granular aquifer. Ground Water. 36(1):67-75.

Young, S. C. and Pearson, H. S. 1995. The electromagnetic borehole flowmeter: Description and application. Ground Water Monitoring & Remediation. 15(4):138-147.

Zhang, Z. and Brussseau, M. L. 1998. Characterizing three-dimensional hydraulic conductivity distributions using qualitative and quantitative geologic borehole data: application to a field site. Ground Water. 36(4):671-678.

Zhang, Z. and Brusseau, M. L. 1999. Nonideal transport of reactive solutes in heterogeneous porous media 5. Simulating regional-scale behavior of a trichloroethene plume during pump-and-treat remediation. Water Resources Research. 35(10):2921-2935.

Zhang, D. and Neuman, S. P. 1996. Effect of local dispersion on solute transport in randomly heterogeneous media. Water Resources Research. 32(9):2715-2723.

Zhang, K.; Woodbury, A. D.; and Dunbar, W. S. 2000. Application of the Lanczos algorithm to the simulation of groundwater flow in dual-porosity media. Advances in Water Resources. 23:579-589.