

Contract No:

This document was prepared in conjunction with work accomplished under Contract No. DE-AC09-08SR22470 with the U.S. Department of Energy (DOE) Office of Environmental Management (EM).

Disclaimer:

This work was prepared under an agreement with and funded by the U.S. Government. Neither the U. S. Government or its employees, nor any of its contractors, subcontractors or their employees, makes any express or implied:

- 1) warranty or assumes any legal liability for the accuracy, completeness, or for the use or results of such use of any information, product, or process disclosed; or
- 2) representation that such use or results of such use would not infringe privately owned rights; or
- 3) endorsement or recommendation of any specifically identified commercial product, process, or service.

Any views and opinions of authors expressed in this work do not necessarily state or reflect those of the United States Government, or its contractors, or subcontractors.

221H-LIB-F-55-025



E. I. DU PONT DE NEMOURS & COMPANY

INCORPORATED

SAVANNAH RIVER LABORATORY

AIKEN, SOUTH CAROLINA 29801

(TWX: 803-824-0018, TEL: 803-824-6331, WU: AUGUSTA, GA.)

CC: J. W. Croach-A. A. Johnson, Wilm.
A. J. Schwertfeger-R. J. Christl
W. P. Bebbington, SRP
J. K. Lower
J. E. Conaway
P. R. Moore
W. J. Mottel
J. J. Urban-F. S. Waters
R. T. Hall
J. H. Hershey
R. I. Martens
D. A. Orth
R. Maher
J. T. Buckner
G. H. Sykes
J. B. Starks 221-F
C. H. Ice-L. H. Meyer, SRL
H. J. Groh
E. L. Albenesius
A. S. Jennings
H. Bull, III
A. N. Parkes-TNX File
TIS File
Vital Records Copy

February 3, 1970

J. A. MONIER, JR., PLANT MANAGER
SAVANNAH RIVER PLANT

ATTENTION: E. B. SHELDON

SILVER NITRATE COATING OF UNGLAZED CERAMIC BERL SADDLES
FOR USE IN IODINE REACTORS--RTA 512-S

SUMMARY

More than 100 cubic feet of unglazed Berl saddles have been successfully coated with silver nitrate for use in spare cartridges for the iodine reactors as requested in RTA 512-S. We understand that the request to improve the coating process to make the coating more resistant to attack has been cancelled.

February 3, 1970

DETAILS

The coating process is being done at TNX on a fill-in basis. Approximately 175 pounds per batch of unglazed ceramic saddles are dipped in AgNO_3 solution in a heated, 55-gallon drum and then dried in electrically heated ovens. An average of two batch runs per week are made.

To date 6,072 pounds (107 cubic feet) of ceramic saddles have been coated with silver nitrate in 36 batch runs. The amount of silver nitrate deposited on the ceramic saddles averages 5.0 weight percent, which is considered acceptable.

The remaining saddles will be processed at the average rate of two batches per week, and it is estimated it will take four to five months to complete the work.

A. N. Parkes
Separations Engineering Division

ANP:mpb