



REPORT NUMBER: 101276459SAT-023
ORIGINAL ISSUE DATE: September 4, 2014
REVISED DATE: N/A

EVALUATION CENTER

16015 Shady Falls Road Elmendorf, TX 78112 (voice) 210-635-8100 (fax) 210-635-8101 www.intertek.com

RENDERED TO

AREVA NP Inc. 4100 International Plaza Fort Worth, TX 76109



PRODUCTS EVALUATED: Dow Corning® Sylgard 170 Silicone Elastomer, Quantum Silicones QSil 5558MC Silicone Elastomer and Dow Corning® 790 Silicone Building Sealant

EVALUATION PROPERTY: Seismic Pressure Resistance (Seismic Pressure Test 9)

Report of Testing pressure resistance capabilities for compliance with the applicable requirements of AREVA NP Inc. Test Plan, Document No. 51-9217475-000

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

1 Table of Contents

| TEM | | | |
|---|-------------|--|--|
| | | | |
| 1 Table of Contents | 2 | | |
| 2 Introduction | 3 | | |
| 3 Test Samples | 3 | | |
| 4 Testing and Evaluation Methods | 4 | | |
| 5 Testing and Evaluation Results | 14 | | |
| 6 Conclusions | | | |
| Appendices | | | |
| Appendix A: Assembly Drawings | 21 | | |
| Appendix B: Test Data | 22 | | |
| Appendix C: Photographs | 142 | | |
| Appendix D: Test Plan | 147 | | |
| Appendix E: Commercial Grade Dedication-Related Dod | cuments 175 | | |
| Appendix F: Quality Documents | 177 | | |
| Revision Summary / Last Page of Report | 189 | | |



2 Introduction

Intertek Testing Services NA (Intertek) has conducted testing for AREVA NP Inc., on the seismic pressure resistance capabilities of Dow Corning® Sylgard 170 Silicone Elastomer, (DC-170), Quantum Silicones QSil 5558MC Silicone Elastomer (QSil 5558MC) and Dow Corning® 790 Silicone Building Sealant (DC-790) through a 12" thick concrete deck for compliance with the applicable requirements of and in accordance with AREVA NP Inc. Document No. 51-9217475-000, *Detailed Test Plan for Conducting MOX Seismic Pressure Test* 9. This test took place on February 12, 2014.

This project was undertaken to evaluate the seismic pressure resistance capabilities of elastomer penetration seals for the sealing of openings in alternate building construction (ABC) walls using alternating pressures at the air pressure increments above atmospheric pressure.

NOTE: The test assembly used in this seismic pressure test was the same test assembly that was constructed and tested in Pressure Test 11 without any changes. Refer to AREVA Doc. 58-9224202-000 or Intertek Test Report No. 101276459SAT-019 for details on Pressure Test 11.

3 Test Samples

3.1. SAMPLE SELECTION

The sealant materials were not independently selected for testing; they were supplied by AREVA NP, Inc., and were received in three shipments from June 21 to January 7, 2014. The samples were received with Certificates of Conformance and are considered traceable. Basic information on sealant material(s) is presented in the table below.

| Sealant Material | Lot /Batch# | Expiration Date |
|------------------|-------------|-----------------|
| DC-170 | 063B02 | 6/30/2014 |
| DC-790 | 0007643997 | 11/29/2014 |
| QSil 5558 MC | 131014 | 11/4/2014 |

Information regarding receiving dates and origin of all the materials in the assembly can be found in Appendix F: Quality Documents of Pressure Test 11 (Intertek Report No. 101276459SAT-019; AREVA document 58-9224202-000). All samples were received in good condition at the Evaluation Center.

3.2. SAMPLE AND ASSEMBLY DESCRIPTION

The test assembly used in this test was the same assembly tested as Pressure Test 11. A detailed description of the concrete deck and penetrations can be found in AREVA NP Inc. Engineering Record 51-9217475-000, *Detailed Test Plan for Conducting Seismic Pressure Test* 9 in Appendix D. For drawings of the concrete deck and penetrations please refer to Appendix A of Pressure Test 11 (Intertek Report No. 101276459SAT-019; AREVA document 58-9224202-000). The concrete slab measured approximately 96" x 96" (8' x 8'). Within this slab



there were two openings into which Structo-Crete material was fastened. The concrete openings were 14" x 20" without beveled edges. The installation and documentation of penetration seal assemblies contained within the test slab was performed by AREVA under AREVA's Quality Assurance Program (Reference 12.4 in the Test Plan found in Appendix D).

4 Testing and Evaluation Methods

The Test Plan in Appendix D defines the test methods, acceptance criteria and test report documentation requirements for Seismic Pressure Test 9. Additionally, this detailed test plan defines the roles and responsibilities of MOX Services, AREVA, the selected testing laboratory, and any other subcontracted entity engaged in support of seismic pressure testing efforts.

The detailed test plan also describes the procurement plan for materials associated with penetration seals in Seismic Pressure Test 9 and identifies the entities responsible for procuring the various components of the test assembly based on the quality level assigned to each component.

The Test Plan also establishes minimum quality requirements for the penetration seal materials used in the test assembly and links quality requirements in the AREVA QA program to customer/project quality requirements.

4.1. TEST APPARATUS

In the absence of any consensus codes or standards related to the pressure testing of penetration seal assemblies for seismic qualification purposes, the MOX Penetration Seal Program has developed a standardized method for conducting seismic pressure testing of MOX penetration seal designs. Specifically, seismic pressure testing will be used to evaluate the seismic inertia of the self-weight of the seal assembly by applying an equivalent pressure to alternating sides of a penetration seal assembly. In support of this effort, Intertek assisted in the design and construction of a pressure test apparatus to be use in the conduct of MOX penetration seal pressure tests.

The pressure chamber apparatus consists of two hemispherical 72" diameter steel pressure vessels, calibrated equipment and a data acquisition system. The apparatus accurately maintains the desired air pressure, using one of two sensitive, manually adjustable pressure regulators; a high (0-15 psi) and a low (0-2 psi) range. The sealed collection chamber feeds any leakage air back to the test device, where it is channeled through one of two calibrated flow meters, once again, a high (0-200 L/min) and a low (0-20 L/min) range. A calibrated electronic pressure transducer (0-5 psi) measures the differential pressure between the two chambers and the data acquisition software determines the net pressure drop across the test seal and the leakage through the seal. The chambers are interchangeable and the direction can be reversed very quickly so both can serve as the pressure or the collection chamber.

The primary components described above include the devices described on the following pages:



Pressure Chamber

2-piece hemispherical 72" diameter steel vessel

3 connection ports per piece

16 flange attachment points per piece

Flange attachment via 3/8" diameter holes @ 22-1/2° spacing



Pressure Cart Stainless steel rolling cart with control equipment and associated Data Acquisition System





Control Air, Inc., Amherst, NH Type 700 0-2 psi Regulator (low)

Regulator (high) Control Air, Inc., Amherst, NH

Type 700 0-15 psi






Mass Flow Meter

Omega Engineering, Inc., Stamford, CT Model No. FMA-872A-V-NIST Serial No. 4270050001001 0-20 lpm



Mass Flow Meter

Omega Engineering, Inc., Stamford, CT Model No. FMA-875A-V-NIST Serial No. 4270050003001 0-200 lpm





Pressure Transducer Omegadyne Inc., Sunbury, OH
Model No. PX409-005 DWUV
Serial No. 406707
Pressure Range: 0-5 psi
Input 0-100mVdc





Power Supply Omega Engineering, Inc., Stamford, CT

Model No. PSS-10 +10V @ 400 mA Input 115 VAC 50/60 Hz

Multifunction DAQ National Instruments,

Model No. NI USB-6210

16 Input, 16-bit, 250 kS/s, Multifunction I/O





Dedicated CPU


HP Compaq Pro-6300 Microtower Serial No. MXL3090LN6 OS Windows 7 Pro





Additionally, during initial system start-up testing and verification, it was discovered that the data acquisition system (DAQ) was so sensitive that "signal noise" resulted in data fluctuations for reported differential pressure even when the system was at equilibrium (i.e., both high side and low side pressure chambers were at atmospheric conditions). After collecting data for 16 hours overnight, the average fluctuation was -0.025 psi.

16-hr Average Electronic Noise (dP = -0.0253 psi)



As seen above, the average data fluctuation due to "signal noise" was -0.025 psi. For this test, the Test Plan required pressure was applied and maintained using the DAQ reported differential pressure without consideration for any "signal noise". Since the "signal noise" always reported some level of negative pressure at the beginning of the test, this method assured that the tests were conducted with additional margin, as the actual differential pressure that the test specimen was subjected to was equal to the DAQ reported differential pressure plus the additional pressure needed to overcome the negative "signal noise" reported at the beginning of the test when both pressure chambers were at atmospheric conditions.



4.2. TEST STANDARD

AREVA NP Inc. Document No. 51-9217475-000

Seismically qualified penetration seals at the MOX facility are required to remain in the opening (penetration) during and after a Design Earthquake seismic event. In order demonstrate that a penetration seal will remain in place, the seal has to be evaluated for two conditions: 1) The seismic inertia of the self-weight of the seal has to be evaluated; and 2) The seismic deflection of the commodities penetrating the seal has to be considered.

Seismic pressure testing was used to evaluate the seismic inertia of the self-weight of the seal assembly. This was accomplished by applying a pressure to alternating sides of the penetration seal to demonstrate that the seal would not become dislodged from the opening due to the seismic inertia of the self-weight of the seal. The seismic deflection of commodities that penetrate the seal will be addressed by a separate analysis.

Ultimately, the overall seismic qualification of MOX penetration seal assemblies will be captured in a penetration seal seismic qualification report that will tie together the results of seismic pressure testing with other analyses performed to address seismic deflection of commodities that penetrate the seal.

The acceptance criterion for evaluating the seismic inertia of the seal self-weight is calculated in MOX Services Calculation "Penetration Seal Seismic Requirements" [Test Plan Reference 12.1] and expressed as an equivalent pressure. Testing at this equivalent pressure qualified that a penetration seal assembly would remain in place (i.e., the penetration seal cannot become dislodged from the opening or otherwise catastrophically fail such that a substantial leakage path is created) during the design earthquake seismic event.

The relative movement of the items penetrating a seal and the movement of the wall / seal during a seismic event were not considered as a part of this test. A separate engineering evaluation is required to evaluate the effect of movement on a seal with penetrating items during a seismic event.

No pressure inducing events are required to be considered concurrently with a seismic event.

The table below identifies the differential pressure levels (stages) for conducting this seismic pressure test, as well as, the acceptance criteria in order for the penetration seal assemblies to meet the seismic pressure testing requirements.

| Test Stage | Differential Pressure (inch w.g.) | Required Hold Time (minutes) | Acceptance Criteria | Basis for the Selected Differential Pressure |
|---------------|---|------------------------------------|---|---|
| 1-4 | 45 (Note 1) | 5 | Penetration Seal Remains in Opening (Does not become dislodged) | Testing at this differential pressure meets the seismic demand expressed as a pressure [Test Plan Reference 12.1] |



Note1: For Seismic Pressure Test 9, a nominal density of 85 pcf was used for the silicone elastomer seal material installed for the purposes of determining the test penetration seal's weight per square foot. 85 pcf bounds the installed seal material with margin. 85 pcf times a seal depth of 8" yields a seal weight of approximately 56.7 psf. Based on Figure B-2.1 of Test Plan Reference 12.1, the corresponding seismic pressure for a seal weight of 56.7 psf is approximately 44.7 inches w.g. Therefore, for Seismic Pressure Test 9 an equivalent seismic pressure of 45 inches w.g. was used.

The test assembly was attached to the seismic pressure test apparatus and subjected to the pressures identified in table as described above.

For Stage 1, the test assembly was attached to the pressure test apparatus and subjected to air pressure at the select pressure level identified in the table. Once this pressure was obtained, the pressure was maintained for the hold time specified in the table. If the penetration seal catastrophically failed during this time, the time of failure was to be noted and the test stopped.

Once the designated hold time for Stage 1 had been achieved, the pressure was vented from the test chamber. Next, the pressure identified in the table for Stage 2 was applied to the opposite side of the penetration seal and held for the designated hold time. If the penetration seal catastrophically failed during this time, the time of failure was to be noted and the test stopped.

Once the designated hold time for Stage 2 had been achieved, the pressure was vented from the test chamber. Next, the pressure identified for Stage 3 was applied to the original side of the penetration seal and held for the designated hold time. If the penetration seal catastrophically failed during this time, the time of failure was to be noted and the test stopped.

Once the designated hold time for Stage 3 had been achieved, the pressure was vented from the test chamber. Finally, the pressure identified in the table for Stage 4 was applied to the opposite side of the penetration seal and held for the designated hold time. If the penetration seal catastrophically failed during this time, the time of failure was to be noted and the test stopped.

Following completion of Stage 4 pressure testing, the pressure was vented from the test chamber. At this point, the test was continued at the discretion of the AREVA test engineer and the testing laboratory manager in charge. Subsequent pressures, and hold times were recorded as directed by the AREVA test engineer.

Note: The pressure used for the testing performed above was based on a seal material depth of 8 inches and a seal material density of 85 pcf. Since the test was successful, subsequent testing pressures were evaluated for a 10 inch depth of material (56 inches w.g.) and a 12 inch depth of material (67 inches w.g.). These tests were designated Stages 1a-4a and 1b-4b, respectively.

If at any pressure level (or test stage) the penetration seal became dislodged from the opening or otherwise catastrophically failed, the pressure test was to be terminated and the time to failure and pressure at which the failure occurred was recorded.



5 Testing and Evaluation Results

5.1. RESULTS AND OBSERVATIONS

The test was initiated at 2:11 p.m. on February 12, 2014. Scott Groesbeck, representing AREVA NP Inc. was present to witness the test. The ambient temperature at the start of the test was 55°F, with a relative humidity of 41%.

The test procedure followed that presented in Section 9.0 of the Test Plan, except that at the completion of Stage 4 the pressure was not vented from the bottom chamber. In lieu of this, the bottom chamber pressure was increased to the Stage 1a level of 56" w.g. and the test continued. This resulted in Stage 4a concluding with the pressure being applied to the top side of the test assembly. A similar process was followed, the top side pressure of 67 w.g. applied, and the test continued for Stages 1b-4b. This minor deviation from the prescribed test method was conducted with the verbal approval of the AREVA Test Engineer and is deemed to have had no adverse impact on the outcome of the test results.

The graphs and table on the following page(s) provide a summary of results and observations for the various pressure stages; any observed leakage, and whether the seal remained in place. Appendix B of this test report contains the raw data for this test.


The graphs are based on data collected throughout the entire test process, including the time periods between stages when the pressure chamber was being vented and refilled. Pressure spikes and leakage rates displayed for time periods between stages should not be misinterpreted, as recorded leakage may have been caused by intentional venting of the pressure chamber though a mass flow meter.

Additionally, it should be noted that when changing between mass flowmeters during a pressure a test, valve lineups and flowpath routes are changed. The time it takes to manipulate the valves, differences in tubing sizes, orifice sizes and mass flowmeter throughput capacity all affect bonnet pressure on the leakage side of the test assembly which can affect recorded leakage values. Generally, the input air on the opposite side of the test assembly remains constant during this time period, since manipulation of the input pressure regulator would require additional operator action. This results in reported differential pressure fluctuations which typically show up as pressure spikes when the raw data is graphed. Within a few minutes of mass flowmeter switchover, the system stabilizes to the new lineup and the data results in a more uniform graph.

Therefore, it is important to analyze the data compiled during the hold times for each pressure stage and not the data before, after or in between pressure stages. The summary table presented after the graphs identifies the approximate start time and stop times for each pressure stage of this test. These times can be correlated to the data under the "Time (min)" heading for the raw data contained in Appendix B of this report. The official start and stop times for each pressure stage were timed using a traceable, calibrated stopwatch.



Stage 1-4
Chamber Differential Pressure and Seal Leakage
Seismic Pressure Test 9
45-in w.g.






Stage 1a-4a

Chamber Differential Pressure and Seal Leakage
Seismic Pressure Test 9


56-in w.g.





Stage 1b-4b

Chamber Differential Pressure and Seal Leakage Seismic Pressure Test 9 67-in w.g.





Test Results and Observations

| Test Stage | Pressurized Side | Differential Pressure (inch w.g.) | Start Time (min) | Required Hold Time (minutes) | Acceptance Criteria | PASS/FAIL |
|---------------|------------------|---|------------------------|------------------------------------|--------------------------|-----------|
| 1 | ТОР | 45 | 20.3 | 5 | Seal Remains In Place | PASS |
| 2 | воттом | 45 | 33 | 5 | Seal Remains In Place | PASS |
| 3 | ТОР | 45 | 50.2 | 5 | Seal Remains In Place | PASS |
| 4 | воттом | 45 | 59.5 | 5 | Seal Remains In Place | PASS |
| 1a | воттом | 56 | 65 | 5 | Seal Remains In Place | PASS |
| 2a | ТОР | 56 | 78.5 | 5 | Seal Remains In Place | PASS |
| 3a | воттом | 56 | 88.4 | 5 | Seal Remains In Place | PASS |
| 4a | ТОР | 56 | 100.3 | 5 | Seal Remains In Place | PASS |
| 1b | ТОР | 67 | 106.1 | 5 | Seal Remains In Place | PASS |
| 2b | воттом | 67 | 120.1 | 5 | Seal Remains In Place | PASS |
| 3b | ТОР | 67 | 130.1 | 5 | Seal Remains In Place | PASS |
| 4b | воттом | 67 | 142.5 | 5 | Seal Remains In Place | PASS |



AREVA NP Inc. September 4, 2014
Report No. 101276459SAT-023 Page 19 of 189

5.2. POST TEST EXAMINATION

Following completion of Seismic Pressure Test 9, the top bonnet was removed and the top side of the test specimen was visually inspected. This inspection revealed the following:

- Integrity of seal and conditions on the exposed side of the penetration
 - No visual changes were observed.
- Location of any penetration seal degradation
 - No visual changes were observed.
- Condition of seal to barrier interface
 - No visual changes were observed.
- Condition of seal to penetrating item interfaces
 - N/A no penetrating items

Following visual inspection of the top side of the test assembly, pressure (~.5 psi) was applied to the bottom chamber and a soapy-water solution was sprayed on the top side of the seal. Leaks were observed at the following locations:

- Pen. 1 Leaks at one screw location (not part of seal assembly). Leaks at two opposite corners of Structo-Crete.
- Pen. 2 Leaks at one screw location (not part of seal assembly). Otherwise no leaks.

Finally, the slab was removed from the bottom bonnet and the bottom side of the test assembly was inspected. No visual changes were noted on the bottom side of the test assembly.

6 Conclusion

Intertek Testing Services NA (Intertek) has conducted testing for AREVA NP Inc., on the seismic pressure resistance capabilities of Dow Corning® Sylgard 170 Silicone Elastomer, (DC-170), Quantum Silicones QSil 5558MC Silicone Elastomer (QSil 5558MC) and Dow Corning® 790 Silicone Building Sealant (DC-790) through a 12" thick concrete deck for compliance with the applicable requirements of and in accordance with AREVA NP Inc. Document No. 51-9217475-000, Detailed *Test Plan for Conducting MOX Seismic Pressure Test* 9. This test took place on February 12, 2014.

The seals in Seismic Pressure Test 9 met the acceptance criteria as defined in the Test Plan.

This project was undertaken to evaluate the seismic pressure resistance capabilities of elastomer penetration seals for the sealing of openings in Structo-Crete walls using alternating pressures at the air pressure increments above atmospheric pressure.

The conclusions of this test report may not be used as part of the requirements for Intertek product certification. Authority to Mark must be issued for a product to become certified.



INTERTEK TESTING SERVICES NA





Engineering Team Lead, Fire Resistance

Reviewed by:

Michael A. Brown Quality Supervisor

AREVA NP Inc. September 4, 2014
Report No. 101276459SAT-023 Page 21 of 189

APPENDIX A Assembly Drawings

The test assembly used in Seismic Pressure Test 9 was the same assembly tested in Pressure Test 11. A detailed description of the assembly is presented in the Test Plan in Appendix D of this report. For drawings of the assembly, please refer to the final test report for Pressure Test 11 (Intertek Report No. 101276459SAT-019; AREVA document 58-9224202-000).



APPENDIX B Test Data



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 0 | 1.447 | 0.0317 | 8.525 | 8.5566 |
| 0.0333 | 1.45 | 0.0305 | 8.5257 | 8.5562 |
| 0.0667 | 1.4418 | 0.0174 | 8.523 | 8.5404 |
| 0.1 | 1.4372 | 0.0174 | 8.5283 | 8.5456 |
| 0.1333 | 1.428 | 0.0174 | 8.5125 | 8.5299 |
| 0.1667 | 1.4257 | 0.0174 | 8.5138 | 8.5312 |
| 0.2 | 1.4198 | 0.0174 | 8.5112 | 8.5286 |
| 0.2333 | 1.4161 | 0.0305 | 8.5125 | 8.543 |
| 0.2667 | 1.4046 | 0.0305 | 8.5086 | 8.5391 |
| 0.3 | 1.404 | 0.0042 | 8.502 | 8.5062 |
| 0.3333 | 1.3954 | 0.0305 | 8.5033 | 8.5338 |
| 0.3667 | 1.3914 | 0.0174 | 8.4967 | 8.5141 |
| 0.4 | 1.3832 | 0.0042 | 8.4902 | 8.4944 |
| 0.4333 | 1.3812 | 0.0042 | 8.4941 | 8.4983 |
| 0.4667 | 1.3773 | 0.0174 | 8.481 | 8.4983 |
| 0.5 | 1.3687 | 0.0174 | 8.4783 | 8.4957 |
| 0.5333 | 1.3648 | 0.0042 | 8.477 | 8.4812 |
| 0.5667 | 1.3608 | 0.0174 | 8.4665 | 8.4838 |
| 0.6 | 1.3549 | 0.0174 | 8.4704 | 8.4878 |
| 0.6333 | 1.3483 | 0.0042 | 8.4573 | 8.4615 |
| 0.6667 | 1.346 | 0.0042 | 8.4494 | 8.4536 |
| 0.7 | 1.3404 | 0.0042 | 8.4468 | 8.451 |
| 0.7333 | 1.3361 | 0.0174 | 8.4376 | 8.4549 |
| 0.7667 | 1.3309 | 0.0042 | 8.4362 | 8.4404 |
| 0.8 | 1.3286 | 0.0174 | 8.4244 | 8.4418 |
| 0.8333 | 1.3246 | 0.0174 | 8.4257 | 8.4431 |
| 0.8667 | 1.318 | 0.0174 | 8.4113 | 8.4286 |
| 0.9 | 1.3128 | 0.0305 | 8.3955 | 8.426 |
| 0.9333 | 1.3092 | 0.0174 | 8.3928 | 8.4102 |
| 0.9667 | 1.3052 | 0.0305 | 8.3889 | 8.4194 |
| 1 | 1.3019 | 0.0042 | 8.381 | 8.3852 |
| 1.0333 | 1.2966 | 0.0042 | 8.3731 | 8.3773 |
| 1.0667 | 1.2907 | 0.0174 | 8.3652 | 8.3826 |
| 1.1 | 1.2841 | 0.0305 | 8.3573 | 8.3878 |
| 1.1333 | 1.2812 | 0.0305 | 8.3442 | 8.3747 |
| 1.1667 | 1.2785 | 0.0042 | 8.3389 | 8.3431 |
| 1.2 | 1.2746 | 0.0174 | 8.3337 | 8.351 |
| 1.2333 | 1.2687 | 0.0305 | 8.3166 | 8.3471 |
| 1.2667 | 1.2621 | 0.0174 | 8.3139 | 8.3313 |
| 1.3 | 1.2614 | 0.0042 | 8.3034 | 8.3076 |
| 1.3333 | 1.2581 | 0.0174 | 8.2982 | 8.3155 |
| 1.3667 | 1.2525 | 0.0042 | 8.2929 | 8.2971 |
| 1.4 | 1.2456 | 0 | 8.2824 | 8.2824 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 1.4333 | 1.2483 | 0.0174 | 8.2758 | 8.2932 |
| 1.4667 | 1.2417 | 0.0042 | 8.2613 | 8.2656 |
| 1.5 | 1.2361 | 0 | 8.2495 | 8.2495 |
| 1.5333 | 1.2344 | 0.0174 | 8.2416 | 8.259 |
| 1.5667 | 1.2298 | 0.0174 | 8.239 | 8.2564 |
| 1.6 | 1.2249 | 0.0174 | 8.2219 | 8.2393 |
| 1.6333 | 1.2216 | 0.0174 | 8.2153 | 8.2327 |
| 1.6667 | 1.2183 | 0.0042 | 8.2074 | 8.2116 |
| 1.7 | 1.2163 | 0.0174 | 8.193 | 8.2103 |
| 1.7333 | 1.2078 | 0.0174 | 8.1877 | 8.2051 |
| 1.7667 | 1.2035 | 0.0042 | 8.1798 | 8.184 |
| 1.8 | 1.2012 | 0.0042 | 8.1667 | 8.1709 |
| 1.8333 | 1.2002 | 0.0042 | 8.1706 | 8.1748 |
| 1.8667 | 1.1982 | 0.0174 | 8.1496 | 8.1669 |
| 1.9 | 1.1916 | 0.0174 | 8.1391 | 8.1564 |
| 1.9333 | 1.1897 | 0.0042 | 8.1272 | 8.1314 |
| 1.9667 | 1.1874 | 0.0174 | 8.118 | 8.1354 |
| 2 | 1.1798 | 0.0174 | 8.1128 | 8.1301 |
| 2.0333 | 1.1785 | 0.0042 | 8.0917 | 8.0959 |
| 2.0667 | 1.1745 | 0 | 8.0891 | 8.0891 |
| 2.1 | 1.1722 | 0.0174 | 8.0733 | 8.0907 |
| 2.1333 | 1.1643 | 0.0042 | 8.068 | 8.0723 |
| 2.1667 | 1.163 | 0.0174 | 8.0536 | 8.0709 |
| 2.2 | 1.1581 | 0.0042 | 8.0378 | 8.042 |
| 2.2333 | 1.1574 | 0.0042 | 8.026 | 8.0302 |
| 2.2667 | 1.1548 | 0.0174 | 8.022 | 8.0394 |
| 2.3 | 1.1521 | 0.0042 | 8.0102 | 8.0144 |
| 2.3333 | 1.1479 | 0.0174 | 8.001 | 8.0183 |
| 2.3667 | 1.1446 | 0.0174 | 7.9865 | 8.0039 |
| 2.4 | 1.138 | 0.0174 | 7.9655 | 7.9828 |
| 2.4333 | 1.1377 | 0.0174 | 7.9628 | 7.9802 |
| 2.4667 | 1.1347 | 0.0174 | 7.9497 | 7.9671 |
| 2.5 | 1.1278 | 0.0174 | 7.9471 | 7.9644 |
| 2.5333 | 1.1275 | 0.0174 | 7.93 | 7.9473 |
| 2.5667 | 1.1235 | 0.0174 | 7.926 | 7.9434 |
| 2.6 | 1.1186 | 0.0174 | 7.905 | 7.9223 |
| 2.6333 | 1.1192 | 0.0174 | 7.884 | 7.9013 |
| 2.6667 | 1.1149 | 0.0042 | 7.884 | 7.8882 |
| 2.7 | 1.111 | 0.0174 | 7.8734 | 7.8908 |
| 2.7333 | 1.1057 | 0.0305 | 7.8642 | 7.8947 |
| 2.7667 | 1.1021 | 0.0042 | 7.8537 | 7.8579 |
| 2.8 | 1.1024 | 0.0042 | 7.8366 | 7.8408 |
| 2.8333 | 1.0968 | 0.0174 | 7.8221 | 7.8395 |



Project No. G101276459SAT-023

| Time | | Ch 2 High Flow | | |
|------------------|------------------|----------------|------------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 2.8667 | 1.0949 | 0.0305 | 7.8129 | 7.8435 |
| 2.9 | 1.0932 | 0.0174 | 7.7985 | 7.8158 |
| 2.9333 | 1.088 | 0.0305 | 7.7919 | 7.8224 |
| 2.9667 | 1.0853 | 0.0174 | 7.7801 | 7.7974 |
| 3 | 1.083 | 0.0174 | 7.7656 | 7.783 |
| 3.0333 | 1.083 | 0.0174 | 7.759 | 7.7764 |
| 3.0667 | 1.0761 | 0.0174 | 7.7393 | 7.7567 |
| 3.1 | 1.0735 | 0.0305 | 7.7275 | 7.758 |
| 3.1333 | 1.0718 | 0.0042 | 7.7209 | 7.7251 |
| 3.1667 | 1.0692 | 0.0174 | 7.713 | 7.7304 |
| 3.2 | 1.0662 | 0.0174 | 7.6972 | 7.7146 |
| 3.2333 | 1.0626 | 0.0174 | 7.688 | 7.7054 |
| 3.2667 | 1.0626 | 0.0174 | 7.6709 | 7.6883 |
| 3.3 | 1.0554 | 0.0042 | 7.6486 | 7.6528 |
| 3.3333 | 1.0527 | 0.0042 | 7.6486 | 7.6528 |
| 3.3667 | 1.0534 | 0.0174 | 7.6302 | 7.6475 |
| 3.4 | 1.0485 | 0.0174 | 7.6183 | 7.6357 |
| 3.4333 | 1.0462 | 0.0174 | 7.6025 | 7.6199 |
| 3.4667 | 1.0432 | 0.0042 | 7.6078 | 7.612 |
| 3.5 | 1.0389 | 0.0174 | 7.5802 | 7.5976 |
| 3.5333 | 1.034 | 0.0174 | 7.571 | 7.5883 |
| 3.5667 | 1.0363 | 0.0042 | 7.5526 | 7.5568 |
| 3.6 | 1.0317 | 0 | 7.5342 | 7.5342 |
| 3.6333 | 1.0284 | 0.0042 | 7.5342 | 7.5384 |
| 3.6667 | 1.0271 | 0.0174 | 7.5197 | 7.5371 |
| 3.7 | 1.0241 | 0.0174 | 7.5026 | 7.52 |
| 3.7333 | 1.0182 | 0 | 7.4881 | 7.4881 |
| 3.7667 | 1.0172 | 0.0174 | 7.4816 | 7.4989 |
| 3.8 | 1.0139 | 0.0042 | 7.4645 | 7.4687 |
| 3.8333 | 1.0136 | 0.0305 | 7.4461 | 7.4766 |
| 3.8667 | 1.0076 | 0.0042 | 7.4382 | 7.4424 |
| 3.9 | 1.0053 | 0.0042 | 7.425 | 7.4292 |
| 3.9333 | 1.0037 | 0.0174 | 7.4185 | 7.4358 |
| 3.9667 | 0.9984 | 0.0042 | 7.4027 | 7.4069 |
| 4 | 0.9981 | 0.0174 | 7.3935 | 7.4108 |
| 4.0333 | 0.9955 | 0.0305 | 7.379 | 7.4095 |
| 4.0667 | 0.9909 | 0.0042 | 7.3724 | 7.3766 |
| 4.1 | 0.9892 | 0.0042 | 7.358 | 7.3622 |
| 4.1333 | 0.9879 | 0.0042 | 7.3461 | 7.3503 |
| 4.1667 | 0.9836 | 0.0174 | 7.329 | 7.3464 |
| 4.2 | 0.983 | 0.0174 | 7.3264 | 7.3438 |
| 4.2333 4.2667 | 0.9757 0.9751 | 0.0305 | 7.3133 7.3001 | 7.3438 7.3043 |
| 4.2007 | 0.9751 | 0.0042 | 7.3001 | 7.3043 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 4.3 | 0.9737 | 0.0437 | 7.2883 | 7.3319 |
| 4.3333 | 0.9711 | 0.0174 | 7.2712 | 7.2885 |
| 4.3667 | 0.9675 | 0.0174 | 7.262 | 7.2793 |
| 4.4 | 0.9645 | 0.0042 | 7.2449 | 7.2491 |
| 4.4333 | 0.9642 | 0.0305 | 7.2344 | 7.2649 |
| 4.4667 | 0.9589 | 0.0042 | 7.2199 | 7.2241 |
| 4.5 | 0.9583 | 0.0174 | 7.2028 | 7.2202 |
| 4.5333 | 0.9553 | 0.0174 | 7.191 | 7.2083 |
| 4.5667 | 0.9497 | 0.0174 | 7.1923 | 7.2096 |
| 4.6 | 0.9477 | 0.0174 | 7.1699 | 7.1873 |
| 4.6333 | 0.9444 | 0.0305 | 7.1541 | 7.1846 |
| 4.6667 | 0.9464 | 0.0305 | 7.1344 | 7.1649 |
| 4.7 | 0.9405 | 0.0305 | 7.1344 | 7.1649 |
| 4.7333 | 0.9402 | 0 | 7.1134 | 7.1134 |
| 4.7667 | 0.9379 | 0.0174 | 7.1002 | 7.1176 |
| 4.8 | 0.9332 | 0.0174 | 7.0884 | 7.1057 |
| 4.8333 | 0.9326 | 0.0042 | 7.0766 | 7.0808 |
| 4.8667 | 0.9316 | 0.0042 | 7.0555 | 7.0597 |
| 4.9 | 0.9257 | 0.0174 | 7.0503 | 7.0676 |
| 4.9333 | 0.9234 | 0.0174 | 7.0318 | 7.0492 |
| 4.9667 | 0.923 | 0.0174 | 7.0292 | 7.0466 |
| 5 | 0.9188 | 0.0174 | 7.0069 | 7.0242 |
| 5.0333 | 0.9168 | 0.0174 | 7.0029 | 7.0203 |
| 5.0667 | 0.9138 | 0.0174 | 6.9832 | 7.0006 |
| 5.1 | 0.9135 | 0.0174 | 6.974 | 6.9913 |
| 5.1333 | 0.9086 | 0.0174 | 6.9635 | 6.9808 |
| 5.1667 | 0.9066 | 0.0042 | 6.9582 | 6.9624 |
| 5.2 | 0.9072 | 0.0305 | 6.9411 | 6.9716 |
| 5.2333 | 0.902 | 0.0174 | 6.9267 | 6.944 |
| 5.2667 | 0.9016 | 0.0174 | 6.9135 | 6.9309 |
| 5.3 | 0.8961 | 0.0305 | 6.8925 | 6.923 |
| 5.3333 | 0.8937 | 0.0042 | 6.8872 | 6.8914 |
| 5.3667 | 0.8914 | 0.0174 | 6.8754 | 6.8927 |
| 5.4 | 0.8911 | 0.0174 | 6.8622 | 6.8796 |
| 5.4333 | 0.8901 | 0.0174 | 6.8543 | 6.8717 |
| 5.4667 | 0.8878 | 0.0174 | 6.8333 | 6.8506 |
| 5.5 | 0.8849 | 0.0042 | 6.8175 | 6.8217 |
| 5.5333 | 0.8806 | 0.0042 | 6.8096 | 6.8138 |
| 5.5667 | 0.8799 | 0.0042 | 6.7952 | 6.7994 |
| 5.6 | 0.8756 | 0.0042 | 6.7794 | 6.7836 |
| 5.6333 | 0.8737 | 0.0042 | 6.7689 | 6.7731 |
| 5.6667 | 0.8704 | 0.0174 | 6.7518 | 6.7691 |
| 5.7 | 0.87 | 0.0174 | 6.7452 | 6.7625 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 5.7333 | 0.8684 | 0.0174 | 6.7373 | 6.7547 |
| 5.7667 | 0.8661 | 0.0305 | 6.7215 | 6.752 |
| 5.8 | 0.8631 | 0.0305 | 6.7097 | 6.7402 |
| 5.8333 | 0.8602 | 0.0174 | 6.6847 | 6.7021 |
| 5.8667 | 0.8589 | 0.0174 | 6.6702 | 6.6876 |
| 5.9 | 0.8566 | 0.0174 | 6.6558 | 6.6731 |
| 5.9333 | 0.8539 | 0.0042 | 6.6531 | 6.6573 |
| 5.9667 | 0.8526 | 0.0305 | 6.6308 | 6.6613 |
| 6 | 0.848 | 0.0042 | 6.6308 | 6.635 |
| 6.0333 | 0.8487 | 0.0042 | 6.6137 | 6.6179 |
| 6.0667 | 0.8463 | 0.0174 | 6.6005 | 6.6179 |
| 6.1 | 0.845 | 0.0174 | 6.594 | 6.6113 |
| 6.1333 | 0.8391 | 0.0174 | 6.569 | 6.5863 |
| 6.1667 | 0.8381 | 0.0042 | 6.5624 | 6.5666 |
| 6.2 | 0.8355 | 0.0174 | 6.5479 | 6.5653 |
| 6.2333 | 0.8325 | 0.0174 | 6.5414 | 6.5587 |
| 6.2667 | 0.8322 | 0.0042 | 6.5269 | 6.5311 |
| 6.3 | 0.8286 | 0.0174 | 6.5085 | 6.5258 |
| 6.3333 | 0.8269 | 0.0042 | 6.4927 | 6.4969 |
| 6.3667 | 0.8259 | 0.0042 | 6.4822 | 6.4864 |
| 6.4 | 0.8194 | 0.0174 | 6.4769 | 6.4943 |
| 6.4333 | 0.8197 | 0.0174 | 6.4572 | 6.4746 |
| 6.4667 | 0.8174 | 0 | 6.4519 | 6.4519 |
| 6.5 | 0.8177 | 0.0174 | 6.4348 | 6.4522 |
| 6.5333 | 0.8144 | 0.0042 | 6.4217 | 6.4259 |
| 6.5667 | 0.8101 | 0.0174 | 6.4138 | 6.4312 |
| 6.6 | 0.8068 | 0.0042 | 6.3928 | 6.397 |
| 6.6333 | 0.8068 | 0 | 6.3875 | 6.3875 |
| 6.6667 | 0.8052 | 0.0174 | 6.377 | 6.3943 |
| 6.7 | 0.8036 | 0.0174 | 6.3665 | 6.3838 |
| 6.7333 | 0.7983 | 0.0305 | 6.352 | 6.3825 |
| 6.7667 | 0.7966 | 0.0174 | 6.3323 | 6.3496 |
| 6.8 | 0.7963 | 0.0305 | 6.3283 | 6.3588 |
| 6.8333 | 0.792 | 0.0042 | 6.3165 | 6.3207 |
| 6.8667 | 0.7917 | 0.0042 | 6.3047 | 6.3089 |
| 6.9 | 0.7917 | 0.0174 | 6.2968 | 6.3141 |
| 6.9333 | 0.7874 | 0.0174 | 6.2784 | 6.2957 |
| 6.9667 | 0.7868 | 0.0042 | 6.2718 | 6.276 |
| 7 7.0333 | 0.7831 0.7795 | 0.0174 0.0042 | 6.256 6.2415 | 6.2734 6.2458 |
| 7.0667 | | | | |
| | 0.7782 | 0.0174 | 6.2284 | 6.2458 |
| 7.1 7.1333 | 0.7746 | 0.0042 0.0174 | 6.2258 | 6.23 |
| 7.1333 | 0.7733 | 0.01/4 | 6.2047 | 6.2221 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 7.1667 | 0.7733 | 0.0042 | 6.1995 | 6.2037 |
| 7.2 | 0.7713 | 0.0042 | 6.1903 | 6.1945 |
| 7.2333 | 0.767 | 0.0305 | 6.1732 | 6.2037 |
| 7.2667 | 0.7664 | 0.0174 | 6.1692 | 6.1866 |
| 7.3 | 0.766 | 0.0174 | 6.1574 | 6.1747 |
| 7.3333 | 0.7618 | 0.0174 | 6.1403 | 6.1577 |
| 7.3667 | 0.7591 | 0.0305 | 6.1285 | 6.159 |
| 7.4 | 0.7555 | 0.0174 | 6.1114 | 6.1287 |
| 7.4333 | 0.7571 | 0.0042 | 6.1074 | 6.1116 |
| 7.4667 | 0.7519 | 0.0174 | 6.0838 | 6.1011 |
| 7.5 | 0.7535 | 0.0174 | 6.0719 | 6.0893 |
| 7.5333 | 0.7509 | 0.0042 | 6.0601 | 6.0643 |
| 7.5667 | 0.7483 | 0.0174 | 6.0522 | 6.0695 |
| 7.6 | 0.746 | 0.0042 | 6.043 | 6.0472 |
| 7.6333 | 0.7453 | 0.0174 | 6.0338 | 6.0511 |
| 7.6667 | 0.7427 | 0.0042 | 6.0219 | 6.0262 |
| 7.7 | 0.74 | 0.0305 | 6.0101 | 6.0406 |
| 7.7333 | 0.7377 | 0.0305 | 5.997 | 6.0275 |
| 7.7667 | 0.7377 | 0.0042 | 5.9838 | 5.988 |
| 7.8 | 0.7351 | 0.0174 | 5.9707 | 5.988 |
| 7.8333 | 0.7318 | 0.0174 | 5.9562 | 5.9736 |
| 7.8667 | 0.7292 | 0.0174 | 5.9417 | 5.9591 |
| 7.9 | 0.7265 | 0.0174 | 5.9299 | 5.9473 |
| 7.9333 | 0.7249 | 0.0174 | 5.922 | 5.9394 |
| 7.9667 | 0.7209 | 0.0174 | 5.9141 | 5.9315 |
| 8 | 0.719 | 0.0042 | 5.9089 | 5.9131 |
| 8.0333 | 0.717 | 0.0174 | 5.8905 | 5.9078 |
| 8.0667 | 0.7176 | 0.0174 | 5.8734 | 5.8907 |
| 8.1 | 0.7176 | 0.0042 | 5.8642 | 5.8684 |
| 8.1333 | 0.714 | 0 | 5.8497 | 5.8497 |
| 8.1667 | 0.7107 | 0.0174 | 5.8484 | 5.8657 |
| 8.2 | 0.7111 | 0.0174 | 5.8352 | 5.8526 |
| 8.2333 | 0.7068 | 0.0042 | 5.8273 | 5.8315 |
| 8.2667 | 0.7091 | 0.0174 | 5.8089 | 5.8263 |
| 8.3 | 0.7018 | 0.0174 | 5.8129 | 5.8302 |
| 8.3333 | 0.7005 | 0.0174 | 5.7905 | 5.8079 |
| 8.3667 | 0.7015 | 0.0174 | 5.7931 | 5.8105 |
| 8.4 | 0.6982 | 0.0174 | 5.7682 | 5.7855 |
| 8.4333 | 0.6953 | 0.0174 | 5.7629 | 5.7803 |
| 8.4667 | 0.6926 | 0.0042 | 5.7471 | 5.7513 |
| 8.5 | 0.691 | 0.0174 | 5.7419 | 5.7592 |
| 8.5333 | 0.6936 | 0.0174 | 5.7261 | 5.7434 |
| 8.5667 | 0.69 | 0.0042 | 5.7156 | 5.7198 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|---------|-------------------------|------------------------|---------------------|
| (min) | (psi) | (LPIVI) | (LPIVI) | (LPIVI) |
| 8.6 | 0.6854 | 0.0305 | 5.709 | 5.7395 |
| 8.6333 | 0.6851 | 0.0174 | 5.6919 | 5.7092 |
| 8.6667 | 0.686 | 0.0174 | 5.6787 | 5.6961 |
| 8.7 | 0.6798 | 0.0174 | 5.6682 | 5.6856 |
| 8.7333 | 0.6758 | 0.0042 | 5.6538 | 5.658 |
| 8.7667 | 0.6772 | 0.0305 | 5.638 | 5.6685 |
| 8.8 | 0.6758 | 0.0305 | 5.6314 | 5.6619 |
| 8.8333 | 0.6748 | 0.0174 | 5.6196 | 5.6369 |
| 8.8667 | 0.6732 | 0.0305 | 5.6077 | 5.6382 |
| 8.9 | 0.6666 | 0.0042 | 5.5985 | 5.6027 |
| 8.9333 | 0.6679 | 0.0174 | 5.588 | 5.6054 |
| 8.9667 | 0.6646 | 0.0042 | 5.5788 | 5.583 |
| 9 | 0.665 | 0.0042 | 5.5617 | 5.5659 |
| 9.0333 | 0.6637 | 0.0174 | 5.5499 | 5.5672 |
| 9.0667 | 0.6597 | 0.0042 | 5.5354 | 5.5396 |
| 9.1 | 0.6581 | 0.0174 | 5.5262 | 5.5436 |
| 9.1333 | 0.6577 | 0.0174 | 5.5144 | 5.5317 |
| 9.1667 | 0.6521 | 0.0174 | 5.5078 | 5.5252 |
| 9.2 | 0.6531 | 0.0174 | 5.4946 | 5.512 |
| 9.2333 | 0.6515 | 0.0042 | 5.4828 | 5.487 |
| 9.2667 | 0.6488 | 0.0174 | 5.471 | 5.4883 |
| 9.3 | 0.6465 | 0.0042 | 5.4578 | 5.462 |
| 9.3333 | 0.6472 | 0.0174 | 5.4526 | 5.4699 |
| 9.3667 | 0.6439 | 0.0305 | 5.4289 | 5.4594 |
| 9.4 | 0.6419 | 0.0042 | 5.4302 | 5.4344 |
| 9.4333 | 0.6432 | 0.0042 | 5.4131 | 5.4173 |
| 9.4667 | 0.639 | 0.0042 | 5.4039 | 5.4081 |
| 9.5 | 0.6373 | 0.0042 | 5.3894 | 5.3937 |
| 9.5333 | 0.6337 | 0.0174 | 5.3776 | 5.395 |
| 9.5667 | 0.6347 | 0.0174 | 5.371 | 5.3884 |
| 9.6 | 0.6344 | 0.0042 | 5.3566 | 5.3608 |
| 9.6333 | 0.6321 | 0.0042 | 5.3461 | 5.3503 |
| 9.6667 | 0.6298 | 0.0174 | 5.3395 | 5.3568 |
| 9.7 | 0.6248 | 0.0042 | 5.3237 | 5.3279 |
| 9.7333 | 0.6238 | 0.0305 | 5.2856 | 5.3161 |
| 9.7667 | 0.6215 | 0.0174 | 5.3027 | 5.32 |
| 9.8 | 0.6222 | 0.0042 | 5.2882 | 5.2924 |
| 9.8333 | 0.6215 | 0.0042 | 5.2842 | 5.2885 |
| 9.8667 | 0.6172 | 0.0174 | 5.275 | 5.2924 |
| 9.9 | 0.6156 | 0.0042 | 5.2632 | 5.2674 |
| 9.9333 | 0.6163 | 0.0305 | 5.2527 | 5.2832 |
| 9.9667 | 0.6136 | 0.0042 | 5.2356 | 5.2398 |
| 10 | 0.6126 | 0.0305 | 5.2264 | 5.2569 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow |
|-----------------|------------------|-------------------------|------------------------|------------------|
| (11111) | (psi) | (LFIVI) | (LFIVI) | (LFIVI) |
| 10.0333 | 0.611 | 0.0042 | 5.2224 | 5.2267 |
| 10.0667 | 0.608 | 0.0174 | 5.2014 | 5.2188 |
| 10.1 | 0.6074 | 0.0174 | 5.2001 | 5.2174 |
| 10.1333 | 0.6037 | 0.0042 | 5.1856 | 5.1898 |
| 10.1667 | 0.6024 | 0.0174 | 5.1738 | 5.1911 |
| 10.2 | 0.6037 | 0.0174 | 5.1672 | 5.1846 |
| 10.2333 | 0.5998 | 0.0305 | 5.1528 | 5.1833 |
| 10.2667 | 0.5985 | 0.0174 | 5.1422 | 5.1596 |
| 10.3 | 0.5932 | 0.0305 | 5.1278 | 5.1583 |
| 10.3333 | 0.5932 | 0.0305 | 5.1251 | 5.1556 |
| 10.3667 | 0.5906 | 0.0174 | 5.1107 | 5.128 |
| 10.4 | 0.5929 | 0.0042 | 5.0962 | 5.1004 |
| 10.4333 | 0.5896 | 0.0305 | 5.0936 | 5.1241 |
| 10.4667 | 0.5893 | 0.0174 | 5.0778 | 5.0952 |
| 10.5 | 0.5853 | 0.0174 | 5.0699 | 5.0873 |
| 10.5333 | 0.584 | 0.0174 | 5.0594 | 5.0767 |
| 10.5667 | 0.585 | 0.0042 | 5.041 | 5.0452 |
| 10.6 | 0.5797 | 0.0174 | 5.0383 | 5.0557 |
| 10.6333 | 0.5797 | 0.0174 | 5.0226 | 5.0399 |
| 10.6667 | 0.5807 | 0.0174 | 5.0107 | 5.0281 |
| 10.7 | 0.5771 | 0.0042 | 5.0042 | 5.0084 |
| 10.7333 | 0.5741 | 0.0174 | 4.991 | 5.0084 |
| 10.7667 | 0.5748 | 0.0174 | 4.9844 | 5.0018 |
| 10.8 | 0.5725 | 0.0174 | 4.9634 | 4.9808 |
| 10.8333 | 0.5708 | 0.0174 | 4.9647 | 4.9821 |
| 10.8667 | 0.5679 | 0.0042 | 4.9516 | 4.9558 |
| 10.9 | 0.5669 | 0.0174 | 4.9253 | 4.9426 |
| 10.9333 | 0.5633 | 0.0042 | 4.9331 | 4.9374 |
| 10.9667 | 0.5639 | 0.0042 | 4.9253 | 4.9295 |
| 11 | 0.5639 | 0.0305 | 4.9147 | 4.9452 |
| 11.0333 | 0.559 | 0.0174 | 4.9055 | 4.9229 |
| 11.0667 11.1 | 0.5619 | 0.0174 | 4.8871 | 4.9045 |
| | 0.5537 | 0.0174 | 4.8845 | 4.9019 |
| 11.1333 | 0.557 | 0.0174 | 4.8713 | 4.8887 |
| 11.1667 11.2 | 0.5534 | 0.0174 0.0305 | 4.8674 4.8543 | 4.8848 4.8848 |
| 11.2333 | 0.5537 | 0.0305 | 4.8343 | 4.8848 |
| 11.2333 | 0.5521 | 0.0174 | 4.8398 | 4.8545 |
| 11.2667 | 0.5475 | 0.0174 | 4.8332 | |
| 11.3 | 0.5458 | 0.0174 | 4.8332 | 4.8506 4.8177 |
| 11.3333 | 0.5438 | 0.0042 | 4.8133 | 4.8177 |
| 11.3667 | 0.5435 | 0.0174 | 4.8043 | 4.8216 |
| 11.4333 | 0.5415 | 0.0174 | 4.7846 | 4.8019 |
| 11.4555 | 0.5419 | 0.0174 | 4.7640 | 4.0019 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 11.4667 | 0.5419 | 0.0174 | 4.7819 | 4.7993 |
| 11.5 | 0.5382 | 0.0305 | 4.7635 | 4.794 |
| 11.5333 | 0.5379 | 0.0174 | 4.7583 | 4.7756 |
| 11.5667 | 0.5392 | 0.0042 | 4.7398 | 4.7441 |
| 11.6 | 0.5346 | 0.0042 | 4.7293 | 4.7335 |
| 11.6333 | 0.5326 | 0.0174 | 4.732 | 4.7493 |
| 11.6667 | 0.529 | 0.0174 | 4.7162 | 4.7335 |
| 11.7 | 0.5336 | 0.0174 | 4.7083 | 4.7256 |
| 11.7333 | 0.5294 | 0.0174 | 4.6951 | 4.7125 |
| 11.7667 | 0.528 | 0.0174 | 4.6872 | 4.7046 |
| 11.8 | 0.5254 | 0.0305 | 4.682 | 4.7125 |
| 11.8333 | 0.5228 | 0.0042 | 4.6623 | 4.6665 |
| 11.8667 | 0.5211 | 0.0174 | 4.6557 | 4.673 |
| 11.9 | 0.5221 | 0.0042 | 4.6412 | 4.6454 |
| 11.9333 | 0.5198 | 0.0174 | 4.6439 | 4.6612 |
| 11.9667 | 0.5178 | 0.0174 | 4.6307 | 4.6481 |
| 12 | 0.5152 | 0.0174 | 4.6202 | 4.6375 |
| 12.0333 | 0.5155 | 0.0042 | 4.611 | 4.6152 |
| 12.0667 | 0.5126 | 0.0174 | 4.5991 | 4.6165 |
| 12.1 | 0.5122 | 0.0042 | 4.5978 | 4.602 |
| 12.1333 | 0.5116 | 0.0174 | 4.5794 | 4.5968 |
| 12.1667 | 0.5103 | 0.0174 | 4.5702 | 4.5876 |
| 12.2 | 0.5073 | 0.0174 | 4.5636 | 4.581 |
| 12.2333 | 0.502 | 0.0042 | 4.5544 | 4.5586 |
| 12.2667 | 0.5047 | 0.0042 | 4.5479 | 4.5521 |
| 12.3 | 0.5057 | 0.0174 | 4.5439 | 4.5613 |
| 12.3333 | 0.504 | 0.0305 | 4.5321 | 4.5626 |
| 12.3667 | 0.5004 | 0 | 4.5176 | 4.5176 |
| 12.4 | 0.4981 | 0.0042 | 4.5097 | 4.5139 |
| 12.4333 | 0.4981 | 0.0305 | 4.4992 | 4.5297 |
| 12.4667 | 0.4955 | 0.0437 | 4.4953 | 4.5389 |
| 12.5 | 0.4945 | 0.0042 | 4.4795 | 4.4837 |
| 12.5333 | 0.4922 | 0.0042 | 4.4663 | 4.4705 |
| 12.5667 | 0.4945 | 0.0042 | 4.4584 | 4.4627 |
| 12.6 | 0.4902 | 0.0305 | 4.4532 | 4.4837 |
| 12.6333 | 0.4925 | 0.0174 | 4.44 | 4.4574 |
| 12.6667 | 0.4846 | 0.0042 | 4.4387 | 4.4429 |
| 12.7 | 0.4839 | 0.0174 | 4.4243 | 4.4416 |
| 12.7333 | 0.4836 | 0.0174 | 4.4137 | 4.4311 |
| 12.7667 | 0.4829 | 0.0174 | 4.4072 | 4.4245 |
| 12.8 | 0.4852 | 0.0174 | 4.3966 | 4.414 |
| 12.8333 | 0.4793 | 0.0042 | 4.3901 | 4.3943 |
| 12.8667 | 0.4793 | 0.0305 | 4.3822 | 4.4127 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 12.9 | 0.4741 | 0.0174 | 4.3769 | 4.3943 |
| 12.9333 | 0.4783 | 0.0305 | 4.3572 | 4.3877 |
| 12.9667 | 0.4767 | 0.0174 | 4.3559 | 4.3732 |
| 13 | 0.4731 | 0.0174 | 4.348 | 4.3653 |
| 13.0333 | 0.4734 | 0.0174 | 4.3322 | 4.3496 |
| 13.0667 | 0.4721 | 0.0174 | 4.3335 | 4.3509 |
| 13.1 | 0.4721 | 0.0174 | 4.3112 | 4.3285 |
| 13.1333 | 0.4698 | 0.0305 | 4.3138 | 4.3443 |
| 13.1667 | 0.4662 | 0.0174 | 4.2941 | 4.3114 |
| 13.2 | 0.4671 | 0.0174 | 4.2941 | 4.3114 |
| 13.2333 | 0.4622 | 0.0305 | 4.2757 | 4.3062 |
| 13.2667 | 0.4645 | 0.0305 | 4.2665 | 4.297 |
| 13.3 | 0.4592 | 0.0174 | 4.2546 | 4.272 |
| 13.3333 | 0.4602 | 0.0042 | 4.2454 | 4.2496 |
| 13.3667 | 0.4589 | 0.0174 | 4.2349 | 4.2523 |
| 13.4 | 0.4583 | 0.0174 | 4.2323 | 4.2496 |
| 13.4333 | 0.4569 | 0.0174 | 4.2139 | 4.2312 |
| 13.4667 | 0.455 | 0.0042 | 4.2086 | 4.2128 |
| 13.5 | 0.4523 | 0.0174 | 4.1915 | 4.2089 |
| 13.5333 | 0.4536 | 0.0042 | 4.1797 | 4.1839 |
| 13.5667 | 0.4523 | 0.0174 | 4.1678 | 4.1852 |
| 13.6 | 0.4517 | 0.0042 | 4.1586 | 4.1628 |
| 13.6333 | 0.4513 | 0.0174 | 4.1442 | 4.1615 |
| 13.6667 | 0.4517 | 0.0174 | 4.1363 | 4.1536 |
| 13.7 | 0.4484 | 0.0042 | 4.131 | 4.1352 |
| 13.7333 | 0.4467 | 0.0174 | 4.1166 | 4.1339 |
| 13.7667 | 0.4415 | 0.0174 | 4.1047 | 4.1221 |
| 13.8 | 0.4464 | 0.0042 | 4.0942 | 4.0984 |
| 13.8333 | 0.4415 | 0.0174 | 4.0876 | 4.105 |
| 13.8667 | 0.4408 | 0.0174 | 4.0745 | 4.0918 |
| 13.9 | 0.4388 | 0.0174 | 4.0666 | 4.0839 |
| 13.9333 | 0.4365 | 0.0174 | 4.0561 | 4.0734 |
| 13.9667 | 0.4349 | 0.0042 | 4.0495 | 4.0537 |
| 14 | 0.4346 | 0.0042 | 4.0403 | 4.0445 |
| 14.0333 | 0.4336 | 0.0174 | 4.0284 | 4.0458 |
| 14.0667 | 0.4326 | 0.0174 | 4.0219 | 4.0392 |
| 14.1 | 0.429 | 0.0437 | 4.0074 | 4.0511 |
| 14.1333 | 0.4306 | 0 | 3.9995 | 3.9995 |
| 14.1667 | 0.4323 | 0.0174 | 3.9877 | 4.005 |
| 14.2 | 0.427 | 0.0042 | 3.9785 | 3.9827 |
| 14.2333 | 0.4267 | 0.0305 | 3.9706 | 4.0011 |
| 14.2667 | 0.4247 | 0.0305 | 3.9627 | 3.9932 |
| 14.3 | 0.4273 | 0.0042 | 3.9548 | 3.959 |



Project No. G101276459SAT-023

| Time | | Ch 2 High Flow | | |
|--------------------|--------|------------------|-----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 14 2222 | 0.4217 | 0.0205 | 2.0456 | 2.0761 |
| 14.3333 14.3667 | 0.4217 | 0.0305 0.0174 | 3.9456 3.943 | 3.9761 3.9603 |
| 14.3667 | | 0.0174 | | |
| | 0.4194 | | 3.9311 | 3.9616 |
| 14.4333 | 0.4181 | 0.0042 | 3.9272 | 3.9314 |
| 14.4667 | 0.4171 | 0.0174 | 3.914 | 3.9314 |
| 14.5 | 0.4174 | 0.0174 | 3.9127 | 3.9301 |
| 14.5333 14.5667 | 0.4141 | 0.0042 | 3.9075 | 3.9117 |
| | 0.4141 | 0.0174 | 3.897 | 3.9143 |
| 14.6 | 0.4118 | 0.0042 | 3.8785 | 3.8827 |
| 14.6333 | 0.4118 | 0.0174 | 3.8693 | 3.8867 |
| 14.6667 | 0.4128 | 0.0305 | 3.8628 | 3.8933 |
| 14.7 | 0.4086 | 0.0174 | 3.8575 | 3.8749 |
| 14.7333 | 0.4082 | 0.0305 | 3.847 | 3.8775 |
| 14.7667 | 0.4039 | 0.0042 | 3.8444 | 3.8486 |
| 14.8 | 0.4039 | 0.0174 | 3.8391 | 3.8564 |
| 14.8333 | 0.4039 | 0.0174 | 3.822 | 3.8394 |
| 14.8667 | 0.4062 | 0.0174 | 3.8141 | 3.8315 |
| 14.9 | 0.402 | 0.0174 | 3.8102 | 3.8275 |
| 14.9333 | 0.3987 | 0.0174 | 3.8049 | 3.8223 |
| 14.9667 | 0.4013 | 0.0042 | 3.7957 | 3.7999 |
| 15 | 0.3964 | 0.0174 | 3.7918 | 3.8091 |
| 15.0333 | 0.3964 | 0.0042 | 3.7825 | 3.7868 |
| 15.0667 | 0.3954 | 0.0174 | 3.772 | 3.7894 |
| 15.1 | 0.3951 | 0.0174 | 3.7655 | 3.7828 |
| 15.1333 | 0.3947 | 0.0174 | 3.7628 | 3.7802 |
| 15.1667 | 0.3947 | 0.0174 | 3.7497 | 3.767 |
| 15.2 | 0.3937 | 0.0174 | 3.7431 | 3.7605 |
| 15.2333 | 0.3898 | 0.0305 | 3.7444 | 3.7749 |
| 15.2667 | 0.3911 | 0.0042 | 3.7339 | 3.7381 |
| 15.3 | 0.3875 | 0.0174 | 3.726 | 3.7434 |
| 15.3333 | 0.3872 | 0.0174 | 3.7168 | 3.7342 |
| 15.3667 | 0.3865 | 0.0174 | 3.7076 | 3.725 |
| 15.4 | 0.3825 | 0.0305 | 3.6944 | 3.725 |
| 15.4333 | 0.3812 | 0.0174 | 3.6866 | 3.7039 |
| 15.4667 | 0.3829 | 0 | 3.6813 | 3.6813 |
| 15.5 | 0.3806 | 0.0174 | 3.6603 | 3.6776 |
| 15.5333 | 0.3786 | 0.0174 | 3.6537 | 3.671 |
| 15.5667 | 0.3793 | 0.0174 | 3.6418 | 3.6592 |
| 15.6 | 0.3786 | 0.0174 | 3.6366 | 3.6539 |
| 15.6333 | 0.3746 | 0.0174 | 3.6208 | 3.6382 |
| 15.6667 | 0.3786 | 0.0042 | 3.6142 | 3.6184 |
| 15.7 | 0.3737 | 0.0305 | 3.6103 | 3.6408 |
| 15.7333 | 0.373 | 0.0305 | 3.5945 | 3.625 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|---------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 15.7667 | 0.373 | 0.0174 | 3.584 | 3.6013 |
| 15.8 | 0.3694 | 0.0174 | 3.5814 | 3.5987 |
| 15.8333 | 0.3697 | 0.0305 | 3.5695 | 3.6 |
| 15.8667 | 0.3691 | 0.0305 | 3.5537 | 3.5842 |
| 15.9 | 0.3671 | 0.0174 | 3.5511 | 3.5685 |
| 15.9333 | 0.3671 | 0.0305 | 3.5432 | 3.5737 |
| 15.9667 | 0.3641 | 0.0042 | 3.5301 | 3.5343 |
| 16 | 0.3625 | 0.0042 | 3.5222 | 3.5264 |
| 16.0333 | 0.3612 | 0.0174 | 3.5169 | 3.5343 |
| 16.0667 | 0.3644 | 0.0042 | 3.5051 | 3.5093 |
| 16.1 | 0.3615 | 0.0042 | 3.4919 | 3.4961 |
| 16.1333 | 0.3605 | 0.0042 | 3.484 | 3.4883 |
| 16.1667 | 0.3585 | 0.0042 | 3.4775 | 3.4817 |
| 16.2 | 0.3565 | 0.0042 | 3.4722 | 3.4764 |
| 16.2333 | 0.3559 | 0.0174 | 3.4656 | 3.483 |
| 16.2667 | 0.3559 | 0.0042 | 3.4577 | 3.462 |
| 16.3 | 0.3539 | 0.0305 | 3.4538 | 3.4843 |
| 16.3333 | 0.3523 | 0.0042 | 3.4459 | 3.4501 |
| 16.3667 | 0.3493 | 0.0042 | 3.4301 | 3.4343 |
| 16.4 | 0.3526 | 0.0305 | 3.4301 | 3.4606 |
| 16.4333 | 0.3536 | 0.0042 | 3.4209 | 3.4251 |
| 16.4667 | 0.349 | 0.0042 | 3.413 | 3.4172 |
| 16.5 | 0.3493 | 0.0042 | 3.4012 | 3.4054 |
| 16.5333 | 0.3454 | 0.0042 | 3.392 | 3.3962 |
| 16.5667 | 0.3434 | 0.0174 | 3.3841 | 3.4015 |
| 16.6 | 0.3467 | 0.0305 | 3.3802 | 3.4107 |
| 16.6333 | 0.3444 | 0.0042 | 3.371 | 3.3752 |
| 16.6667 | 0.3407 | 0.0174 | 3.367 | 3.3844 |
| 16.7 | 0.3427 | 0.0042 | 3.3618 | 3.366 |
| 16.7333 | 0.3388 | 0.0174 | 3.3512 | 3.3686 |
| 16.7667 | 0.3398 | 0.0042 | 3.3368 | 3.341 |
| 16.8 | 0.3394 | 0.0305 | 3.3355 | 3.366 |
| 16.8333 | 0.3371 | 0.0042 | 3.3263 | 3.3305 |
| 16.8667 | 0.3381 | 0.0174 | 3.3144 | 3.3318 |
| 16.9 | 0.3365 | 0.0305 | 3.3078 | 3.3383 |
| 16.9333 | 0.3319 | 0.0305 | 3.2986 | 3.3291 |
| 16.9667 | 0.3292 | 0.0174 | 3.2907 | 3.3081 |
| 17 | 0.3325 | 0.0174 | 3.2842 | 3.3015 |
| 17.0333 | 0.3335 | 0.0305 | 3.2763 | 3.3068 |
| 17.0667 | 0.3269 | 0.0174 | 3.2644 | 3.2818 |
| 17.1 | 0.3276 | 0.0042 | 3.2579 | 3.2621 |
| 17.1333 | 0.3269 | 0.0042 | 3.2526 | 3.2568 |
| 17.1667 | 0.3276 | 0.0042 | 3.2487 | 3.2529 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 17.2 | 0.3266 | 0.0305 | 3.2408 | 3.2713 |
| 17.2333 | 0.3263 | 0.0437 | 3.2289 | 3.2726 |
| 17.2667 | 0.3226 | 0.0305 | 3.2237 | 3.2542 |
| 17.3 | 0.324 | 0.0174 | 3.2184 | 3.2358 |
| 17.3333 | 0.3226 | 0.0042 | 3.2105 | 3.2147 |
| 17.3667 | 0.3213 | 0.0042 | 3.2013 | 3.2055 |
| 17.4 | 0.323 | 0.0174 | 3.1934 | 3.2108 |
| 17.4333 | 0.3213 | 0.0437 | 3.1869 | 3.2305 |
| 17.4667 | 0.3161 | 0.0305 | 3.1711 | 3.2016 |
| 17.5 | 0.3157 | 0.0042 | 3.1632 | 3.1674 |
| 17.5333 | 0.3151 | 0.0174 | 3.1566 | 3.174 |
| 17.5667 | 0.3072 | 0.0174 | 3.1395 | 3.1569 |
| 17.6 | 0.2933 | 0.0042 | 3.1395 | 3.1437 |
| 17.6333 | 0.2841 | 0.0305 | 3.1277 | 3.1582 |
| 17.6667 | 0.2966 | 0.0042 | 3.1106 | 3.1148 |
| 17.7 | 0.3328 | 0.0042 | 3.1106 | 3.1148 |
| 17.7333 | 0.3694 | 0.0174 | 3.104 | 3.1214 |
| 17.7667 | 0.4151 | 0.0042 | 3.1119 | 3.1161 |
| 17.8 | 0.4494 | 0.0174 | 3.1159 | 3.1332 |
| 17.8333 | 0.4767 | 0 | 3.1224 | 3.1224 |
| 17.8667 | 0.4991 | 0.0174 | 3.1369 | 3.1543 |
| 17.9 | 0.5113 | 0.0174 | 3.1527 | 3.17 |
| 17.9333 | 0.5195 | 0.0174 | 3.1685 | 3.1858 |
| 17.9667 | 0.5172 | 0.0042 | 3.1855 | 3.1898 |
| 18 | 0.4994 | 0.0174 | 3.2053 | 3.2226 |
| 18.0333 | 0.4787 | 0.0042 | 3.2053 | 3.2095 |
| 18.0667 | 0.4599 | 0.0305 | 3.2224 | 3.2529 |
| 18.1 | 0.4448 | 0.0042 | 3.2224 | 3.2266 |
| 18.1333 | 0.4227 | 0.0174 | 3.2224 | 3.2397 |
| 18.1667 | 0.4079 | 0.0174 | 3.2263 | 3.2437 |
| 18.2 | 0.3895 | 0.0042 | 3.2171 | 3.2213 |
| 18.2333 | 0.3779 | 0.0305 | 3.225 | 3.2555 |
| 18.2667 | 0.3615 | 0.0174 | 3.2158 | 3.2332 |
| 18.3 | 0.3404 | 0.0042 | 3.2026 | 3.2069 |
| 18.3333 | 0.3315 | 0.0305 | 3.2 | 3.2305 |
| 18.3667 | 0.3144 | 0.0174 | 3.1895 | 3.2069 |
| 18.4 | 0.3042 | 0.0174 | 3.179 | 3.1963 |
| 18.4333 | 0.2933 | 0.0305 | 3.1737 | 3.2042 |
| 18.4667 | 0.2812 | 0.0042 | 3.1579 | 3.1621 |
| 18.5 | 0.269 | 0.0174 | 3.1422 | 3.1595 |
| 18.5333 | 0.2608 | 0.0042 | 3.1264 | 3.1306 |
| 18.5667 | 0.2492 | 0.0042 | 3.1053 | 3.1095 |
| 18.6 | 0.2525 | 0.0174 | 3.0922 | 3.1095 |
| | | | | |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 18.6333 | 0.2779 | 0.0174 | 3.0777 | 3.0951 |
| 18.6667 | 0.3029 | 0.0042 | 3.0698 | 3.074 |
| 18.7 | 0.3375 | 0.0042 | 3.0606 | 3.0648 |
| 18.7333 | 0.3753 | 0.0174 | 3.0659 | 3.0832 |
| 18.7667 | 0.4128 | 0.0174 | 3.0659 | 3.0832 |
| 18.8 | 0.4484 | 0.0174 | 3.0738 | 3.0911 |
| 18.8333 | 0.4859 | 0.0042 | 3.0843 | 3.0885 |
| 18.8667 | 0.5228 | 0.0042 | 3.1014 | 3.1056 |
| 18.9 | 0.5544 | 0.0174 | 3.1237 | 3.1411 |
| 18.9333 | 0.5906 | 0.0174 | 3.1382 | 3.1556 |
| 18.9667 | 0.6219 | 0.0042 | 3.1698 | 3.174 |
| 19 | 0.6656 | 0.0042 | 3.1921 | 3.1963 |
| 19.0333 | 0.7068 | 0.0305 | 3.2237 | 3.2542 |
| 19.0667 | 0.7466 | 0.0305 | 3.2592 | 3.2897 |
| 19.1 | 0.7907 | 0 | 3.2934 | 3.2934 |
| 19.1333 | 0.8259 | 0.0174 | 3.3341 | 3.3515 |
| 19.1667 | 0.8615 | 0.0305 | 3.3736 | 3.4041 |
| 19.2 | 0.9007 | 0.0042 | 3.417 | 3.4212 |
| 19.2333 | 0.9375 | 0.0174 | 3.4577 | 3.4751 |
| 19.2667 | 0.9737 | 0.0174 | 3.5077 | 3.5251 |
| 19.3 | 1.0053 | 0.0042 | 3.5551 | 3.5593 |
| 19.3333 | 1.0396 | 0.0305 | 3.5985 | 3.629 |
| 19.3667 | 1.0685 | 0.0174 | 3.651 | 3.6684 |
| 19.4 | 1.1034 | 0.0174 | 3.7063 | 3.7236 |
| 19.4333 | 1.1311 | 0.0042 | 3.7536 | 3.7578 |
| 19.4667 | 1.1676 | 0.0174 | 3.8115 | 3.8288 |
| 19.5 | 1.2032 | 0.0174 | 3.8693 | 3.8867 |
| 19.5333 | 1.2506 | 0.0174 | 3.9154 | 3.9327 |
| 19.5667 | 1.2891 | 0.0174 | 3.9824 | 3.9998 |
| 19.6 | 1.3421 | 0.0174 | 4.0363 | 4.0537 |
| 19.6333 | 1.3641 | 0.0174 | 4.0968 | 4.1142 |
| 19.6667 | 1.3852 | 0.0174 | 4.1639 | 4.1812 |
| 19.7 | 1.397 | 0.0174 | 4.2244 | 4.2417 |
| 19.7333 | 1.3961 | 0.0174 | 4.2796 | 4.297 |
| 19.7667 | 1.3845 | 0.0174 | 4.3348 | 4.3522 |
| 19.8 | 1.3868 | 0.0174 | 4.3874 | 4.4048 |
| 19.8333 | 1.4079 | 0.0042 | 4.4506 | 4.4548 |
| 19.8667 | 1.4431 | 0.0174 | 4.5005 | 4.5179 |
| 19.9 | 1.4612 | 0.0042 | 4.5584 | 4.5626 |
| 19.9333 | 1.476 | 0.0305 | 4.6162 | 4.6467 |
| 19.9667 | 1.4905 | 0.0174 | 4.678 | 4.6954 |
| 20 | 1.5053 | 0 | 4.7333 | 4.7333 |
| 20.0333 | 1.5218 | 0.0042 | 4.7938 | 4.798 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 20.0667 | 1.5356 | 0.0042 | 4.849 | 4.8532 |
| 20.1 | 1.5481 | 0.0174 | 4.9003 | 4.9176 |
| 20.1333 | 1.5672 | 0.0174 | 4.9476 | 4.965 |
| 20.1667 | 1.5774 | 0.0437 | 5.0147 | 5.0583 |
| 20.2 | 1.5932 | 0.0174 | 5.062 | 5.0794 |
| 20.2333 | 1.6054 | 0.0042 | 5.1172 | 5.1215 |
| 20.2667 | 1.6163 | 0.0042 | 5.1777 | 5.1819 |
| 20.3 | 1.6308 | 0.0305 | 5.2277 | 5.2582 |
| 20.3333 | 1.6406 | 0.0042 | 5.2948 | 5.299 |
| 20.3667 | 1.6521 | 0.0174 | 5.3434 | 5.3608 |
| 20.4 | 1.662 | 0.0042 | 5.3987 | 5.4029 |
| 20.4333 | 1.6673 | 0.0042 | 5.4565 | 5.4607 |
| 20.4667 | 1.666 | 0.0174 | 5.5091 | 5.5265 |
| 20.5 | 1.6676 | 0.0174 | 5.567 | 5.5843 |
| 20.5333 | 1.6689 | 0.0042 | 5.6183 | 5.6225 |
| 20.5667 | 1.6749 | 0.0042 | 5.6708 | 5.6751 |
| 20.6 | 1.6755 | 0.0042 | 5.7195 | 5.7237 |
| 20.6333 | 1.6749 | 0.0042 | 5.7576 | 5.7618 |
| 20.6667 | 1.6791 | 0.0042 | 5.8063 | 5.8105 |
| 20.7 | 1.6788 | 0.0174 | 5.8471 | 5.8644 |
| 20.7333 | 1.6735 | 0.0042 | 5.8931 | 5.8973 |
| 20.7667 | 1.665 | 0.0174 | 5.9325 | 5.9499 |
| 20.8 | 1.6591 | 0.0042 | 5.9693 | 5.9736 |
| 20.8333 | 1.6515 | 0.0174 | 6.0088 | 6.0262 |
| 20.8667 | 1.6436 | 0.0305 | 6.0496 | 6.0801 |
| 20.9 | 1.641 | 0.0174 | 6.0903 | 6.1077 |
| 20.9333 | 1.636 | 0.0042 | 6.1245 | 6.1287 |
| 20.9667 | 1.6301 | 0.0174 | 6.1745 | 6.1918 |
| 21 | 1.6232 | 0.0042 | 6.1968 | 6.201 |
| 21.0333 | 1.6186 | 0.0042 | 6.2389 | 6.2431 |
| 21.0667 | 1.6123 | 0.0042 | 6.2652 | 6.2694 |
| 21.1 | 1.6153 | 0.0174 | 6.2928 | 6.3102 |
| 21.1333 | 1.6248 | 0.0042 | 6.3323 | 6.3365 |
| 21.1667 | 1.6255 | 0.0174 | 6.3612 | 6.3786 |
| 21.2 | 1.6321 | 0.0042 | 6.3941 | 6.3983 |
| 21.2333 | 1.6383 | 0.0174 | 6.4243 | 6.4417 |
| 21.2667 | 1.6446 | 0.0174 | 6.4519 | 6.4693 |
| 21.3 | 1.6489 | 0.0174 | 6.4927 | 6.5101 |
| 21.3333 | 1.6512 | 0.0174 | 6.5256 | 6.5429 |
| 21.3667 | 1.6548 | 0.0042 | 6.5585 | 6.5627 |
| 21.4 | 1.662 | 0.0174 | 6.5966 | 6.6139 |
| 21.4333 | 1.6637 | 0.0174 | 6.6282 | 6.6455 |
| 21.4667 | 1.6679 | 0.0437 | 6.6676 | 6.7113 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 21.5 | 1.6693 | 0.0305 | 6.6978 | 6.7284 |
| 21.5333 | 1.6683 | 0.0174 | 6.7347 | 6.752 |
| 21.5667 | 1.6633 | 0.0305 | 6.7623 | 6.7928 |
| 21.6 | 1.6617 | 0.0174 | 6.7938 | 6.8112 |
| 21.6333 | 1.6581 | 0.0174 | 6.8188 | 6.8362 |
| 21.6667 | 1.6568 | 0.0305 | 6.857 | 6.8875 |
| 21.7 | 1.6518 | 0.0174 | 6.878 | 6.8954 |
| 21.7333 | 1.6489 | 0.0174 | 6.9096 | 6.9269 |
| 21.7667 | 1.6475 | 0.0174 | 6.9293 | 6.9466 |
| 21.8 | 1.6419 | 0 | 6.9661 | 6.9661 |
| 21.8333 | 1.6436 | 0.0042 | 6.9819 | 6.9861 |
| 21.8667 | 1.6387 | 0.0042 | 7.0161 | 7.0203 |
| 21.9 | 1.6373 | 0.0042 | 7.0345 | 7.0387 |
| 21.9333 | 1.6387 | 0.0042 | 7.0581 | 7.0624 |
| 21.9667 | 1.6367 | 0.0042 | 7.0844 | 7.0887 |
| 22 | 1.6363 | 0.0042 | 7.1029 | 7.1071 |
| 22.0333 | 1.6436 | 0.0305 | 7.137 | 7.1676 |
| 22.0667 | 1.6466 | 0.0305 | 7.1581 | 7.1886 |
| 22.1 | 1.6485 | 0.0042 | 7.1752 | 7.1794 |
| 22.1333 | 1.6485 | 0.0042 | 7.2015 | 7.2057 |
| 22.1667 | 1.6538 | 0.0174 | 7.2238 | 7.2412 |
| 22.2 | 1.6577 | 0.0305 | 7.2396 | 7.2701 |
| 22.2333 | 1.6581 | 0.0174 | 7.2672 | 7.2846 |
| 22.2667 | 1.6614 | 0.0305 | 7.287 | 7.3175 |
| 22.3 | 1.6584 | 0.0042 | 7.3001 | 7.3043 |
| 22.3333 | 1.6627 | 0.0042 | 7.3356 | 7.3398 |
| 22.3667 | 1.6647 | 0.0174 | 7.3527 | 7.3701 |
| 22.4 | 1.6663 | 0.0174 | 7.3764 | 7.3937 |
| 22.4333 | 1.6683 | 0.0174 | 7.3935 | 7.4108 |
| 22.4667 | 1.6703 | 0.0174 | 7.4119 | 7.4292 |
| 22.5 | 1.6699 | 0.0174 | 7.4448 | 7.4621 |
| 22.5333 | 1.6716 | 0.0042 | 7.4697 | 7.4739 |
| 22.5667 | 1.6755 | 0.0042 | 7.4895 | 7.4937 |
| 22.6 | 1.6729 | 0.0042 | 7.5052 | 7.5094 |
| 22.6333 | 1.6653 | 0.0042 | 7.5276 | 7.5318 |
| 22.6667 | 1.663 | 0.0174 | 7.5473 | 7.5647 |
| 22.7 | 1.6577 | 0.0042 | 7.5539 | 7.5581 |
| 22.7333 | 1.6528 | 0.0174 | 7.5815 | 7.5989 |
| 22.7667 | 1.6515 | 0.0042 | 7.6039 | 7.6081 |
| 22.8 | 1.6492 | 0.0174 | 7.6275 | 7.6449 |
| 22.8333 | 1.6413 | 0.0042 | 7.6328 | 7.637 |
| 22.8667 | 1.639 | 0.0174 | 7.6499 | 7.6672 |
| 22.9 | 1.638 | 0.0042 | 7.6683 | 7.6725 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 22.9333 | 1.6337 | 0.0174 | 7.6788 | 7.6962 |
| 22.9667 | 1.6301 | 0.0174 | 7.692 | 7.7093 |
| 23 | 1.6308 | 0.0174 | 7.7183 | 7.7356 |
| 23.0333 | 1.6245 | 0.0305 | 7.734 | 7.7646 |
| 23.0667 | 1.6215 | 0.0174 | 7.7446 | 7.7619 |
| 23.1 | 1.6205 | 0.0174 | 7.763 | 7.7803 |
| 23.1333 | 1.6229 | 0.0174 | 7.7761 | 7.7935 |
| 23.1667 | 1.6196 | 0.0174 | 7.7919 | 7.8093 |
| 23.2 | 1.6173 | 0.0174 | 7.8077 | 7.825 |
| 23.2333 | 1.6146 | 0 | 7.8143 | 7.8143 |
| 23.2667 | 1.6117 | 0.0042 | 7.8248 | 7.829 |
| 23.3 | 1.608 | 0.0174 | 7.8392 | 7.8566 |
| 23.3333 | 1.6071 | 0.0042 | 7.8537 | 7.8579 |
| 23.3667 | 1.6064 | 0.0174 | 7.8669 | 7.8842 |
| 23.4 | 1.6044 | 0.0174 | 7.8787 | 7.896 |
| 23.4333 | 1.609 | 0.0305 | 7.8932 | 7.9237 |
| 23.4667 | 1.613 | 0.0042 | 7.9024 | 7.9066 |
| 23.5 | 1.6163 | 0.0174 | 7.9076 | 7.925 |
| 23.5333 | 1.6202 | 0.0174 | 7.9234 | 7.9408 |
| 23.5667 | 1.6235 | 0.0174 | 7.9379 | 7.9552 |
| 23.6 | 1.6261 | 0.0174 | 7.9497 | 7.9671 |
| 23.6333 | 1.6281 | 0.0174 | 7.9668 | 7.9842 |
| 23.6667 | 1.6344 | 0.0174 | 7.9773 | 7.9947 |
| 23.7 | 1.637 | 0.0174 | 7.9891 | 8.0065 |
| 23.7333 | 1.6396 | 0.0174 | 8.0076 | 8.0249 |
| 23.7667 | 1.6406 | 0.0042 | 8.0233 | 8.0275 |
| 23.8 | 1.6466 | 0.0174 | 8.0312 | 8.0486 |
| 23.8333 | 1.6472 | 0.0174 | 8.0523 | 8.0696 |
| 23.8667 | 1.6469 | 0.0042 | 8.0536 | 8.0578 |
| 23.9 | 1.6502 | 0.0174 | 8.0746 | 8.092 |
| 23.9333 | 1.6505 | 0.0042 | 8.0838 | 8.088 |
| 23.9667 | 1.6554 | 0.0042 | 8.1075 | 8.1117 |
| 24 | 1.6571 | 0.0042 | 8.1075 | 8.1117 |
| 24.0333 | 1.6571 | 0.0305 | 8.1272 | 8.1577 |
| 24.0667 | 1.6597 | 0.0174 | 8.1364 | 8.1538 |
| 24.1 | 1.6633 | 0.0042 | 8.1575 | 8.1617 |
| 24.1333 | 1.663 | 0.0042 | 8.1772 | 8.1814 |
| 24.1667 | 1.6643 | 0.0042 | 8.1825 | 8.1867 |
| 24.2 | 1.6633 | 0.0305 | 8.1982 | 8.2287 |
| 24.2333 | 1.6653 | 0.0042 | 8.214 | 8.2182 |
| 24.2667 | 1.6653 | 0.0174 | 8.2245 | 8.2419 |
| 24.3 | 1.667 | 0.0174 | 8.2416 | 8.259 |
| 24.3333 | 1.6689 | 0.0174 | 8.2416 | 8.259 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 24.3667 | 1.6719 | 0.0174 | 8.2574 | 8.2748 |
| 24.4 | 1.6709 | 0.0174 | 8.2679 | 8.2853 |
| 24.4333 | 1.6716 | 0.0174 | 8.2824 | 8.2997 |
| 24.4667 | 1.6739 | 0.0174 | 8.2955 | 8.3129 |
| 24.5 | 1.6742 | 0.0042 | 8.3021 | 8.3063 |
| 24.5333 | 1.6683 | 0.0174 | 8.3139 | 8.3313 |
| 24.5667 | 1.6614 | 0.0042 | 8.3258 | 8.33 |
| 24.6 | 1.6597 | 0.0042 | 8.3442 | 8.3484 |
| 24.6333 | 1.6525 | 0.0174 | 8.3468 | 8.3642 |
| 24.6667 | 1.6459 | 0.0305 | 8.3573 | 8.3878 |
| 24.7 | 1.6416 | 0.0174 | 8.3705 | 8.3878 |
| 24.7333 | 1.6393 | 0.0174 | 8.381 | 8.3984 |
| 24.7667 | 1.637 | 0.0305 | 8.3915 | 8.422 |
| 24.8 | 1.6327 | 0.0305 | 8.3955 | 8.426 |
| 24.8333 | 1.6278 | 0.0174 | 8.3994 | 8.4168 |
| 24.8667 | 1.6252 | 0.0305 | 8.4073 | 8.4378 |
| 24.9 | 1.6212 | 0.0174 | 8.4218 | 8.4391 |
| 24.9333 | 1.6179 | 0.0174 | 8.431 | 8.4483 |
| 24.9667 | 1.6215 | 0.0174 | 8.4336 | 8.451 |
| 25 | 1.6209 | 0.0042 | 8.4454 | 8.4497 |
| 25.0333 | 1.6209 | 0.0174 | 8.452 | 8.4694 |
| 25.0667 | 1.6268 | 0.0174 | 8.4625 | 8.4799 |
| 25.1 | 1.6245 | 0.0174 | 8.4665 | 8.4838 |
| 25.1333 | 1.6284 | 0.0174 | 8.4744 | 8.4917 |
| 25.1667 | 1.6291 | 0.0174 | 8.4823 | 8.4996 |
| 25.2 | 1.6304 | 0.0042 | 8.4875 | 8.4917 |
| 25.2333 | 1.6344 | 0.0174 | 8.498 | 8.5154 |
| 25.2667 | 1.641 | 0.0042 | 8.5125 | 8.5167 |
| 25.3 | 1.6393 | 0.0174 | 8.5099 | 8.5272 |
| 25.3333 | 1.6462 | 0.0174 | 8.5243 | 8.5417 |
| 25.3667 | 1.6489 | 0.0042 | 8.5257 | 8.5299 |
| 25.4 | 1.6521 | 0.0174 | 8.5414 | 8.5588 |
| 25.4333 | 1.6535 | 0.0174 | 8.5414 | 8.5588 |
| 25.4667 | 1.6571 | 0.0305 | 8.552 | 8.5825 |
| 25.5 | 1.6604 | 0.0174 | 8.5625 | 8.5798 |
| 25.5333 | 1.661 | 0.0174 | 8.5717 | 8.589 |
| 25.5667 | 1.6535 | 0.0174 | 8.5875 | 8.6048 |
| 25.6 | 1.6413 | 0.0174 | 8.5875 | 8.6048 |
| 25.6333 | 1.6387 | 0.0174 | 8.598 | 8.6153 |
| 25.6667 | 1.6275 | 0.0305 | 8.6019 | 8.6324 |
| 25.7 | 1.6196 | 0.0174 | 8.6124 | 8.6298 |
| 25.7333 | 1.6136 | 0.0042 | 8.6151 | 8.6193 |
| 25.7667 | 1.608 | 0.0174 | 8.623 | 8.6403 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 25.8 | 1.5995 | 0.0174 | 8.6322 | 8.6495 |
| 25.8333 | 1.5939 | 0.0174 | 8.6269 | 8.6443 |
| 25.8667 | 1.5853 | 0.0174 | 8.6243 | 8.6416 |
| 25.9 | 1.5274 | 0.0174 | 8.6348 | 8.6522 |
| 25.9333 | 1.4711 | 0.0042 | 8.6269 | 8.6311 |
| 25.9667 | 1.4135 | 0.0174 | 8.6072 | 8.6245 |
| 26 | 1.3569 | 0.0042 | 8.6111 | 8.6153 |
| 26.0333 | 1.3016 | 0.0174 | 8.5888 | 8.6061 |
| 26.0667 | 1.2519 | 0.0305 | 8.5848 | 8.6153 |
| 26.1 | 1.2048 | 0.0305 | 8.5612 | 8.5917 |
| 26.1333 | 1.1689 | 0.0042 | 8.1312 | 8.1354 |
| 26.1667 | 1.1373 | 0.0174 | 7.6617 | 7.6791 |
| 26.2 | 1.1103 | 0 | 7.2593 | 7.2593 |
| 26.2333 | 1.0906 | 0.0174 | 6.5769 | 6.5942 |
| 26.2667 | 1.0659 | 0.0042 | 5.9917 | 5.9959 |
| 26.3 | 1.0448 | 0.0305 | 5.4486 | 5.4791 |
| 26.3333 | 1.0208 | 0.0042 | 4.9476 | 4.9518 |
| 26.3667 | 0.9978 | 0.0042 | 4.4782 | 4.4824 |
| 26.4 | 0.9774 | 0.0174 | 4.014 | 4.0313 |
| 26.4333 | 0.9537 | 0.0174 | 3.605 | 3.6224 |
| 26.4667 | 0.9296 | 0.0174 | 3.2263 | 3.2437 |
| 26.5 | 0.9043 | 0.0174 | 2.9291 | 2.9465 |
| 26.5333 | 0.8796 | 0.0174 | 2.5899 | 2.6072 |
| 26.5667 | 0.8615 | 0.0174 | 2.2901 | 2.3074 |
| 26.6 | 0.8355 | 0.0174 | 2.0126 | 2.03 |
| 26.6333 | 0.8101 | 0.0174 | 1.7627 | 1.7801 |
| 26.6667 | 0.7848 | 0.0042 | 1.5563 | 1.5605 |
| 26.7 | 0.7614 | 0.0305 | 1.3801 | 1.4106 |
| 26.7333 | 0.7292 | 0.0042 | 1.4892 | 1.4934 |
| 26.7667 | 0.6962 | 0.0174 | 1.6996 | 1.717 |
| 26.8 | 0.6673 | 0.0174 | 1.8706 | 1.8879 |
| 26.8333 | 0.6324 | 0.0174 | 2.01 | 2.0273 |
| 26.8667 | 0.6077 | 0.0305 | 2.1336 | 2.1641 |
| 26.9 | 0.5784 | 0.0042 | 2.248 | 2.2522 |
| 26.9333 | 0.5504 | 0 | 2.3466 | 2.3466 |
| 26.9667 | 0.5241 | 0.0305 | 2.4281 | 2.4586 |
| 27 | 0.503 | 0.0174 | 2.511 | 2.5283 |
| 27.0333 | 0.4741 | 0 | 2.5754 | 2.5754 |
| 27.0667 | 0.454 | 0.0174 | 2.6398 | 2.6572 |
| 27.1 | 0.4313 | 0.0174 | 2.6885 | 2.7058 |
| 27.1333 | 0.4062 | 0.0174 | 2.7477 | 2.765 |
| 27.1667 | 0.3911 | 0.0174 | 2.7911 | 2.8084 |
| 27.2 | 0.3694 | 0.0174 | 2.8331 | 2.8505 |



Project No. G101276459SAT-023

| Time | | Ch 2 High Flow | | |
|-----------------|---------|------------------|--------|-----------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 27.2333 | 0.3519 | 0.0042 | 2.8686 | 2.8728 |
| 27.2667 | 0.3338 | 0.0042 | 2.9002 | 2.9044 |
| 27.2007 | 0.317 | 0.0174 | 2.9291 | 2.9465 |
| 27.3333 | 0.2963 | 0.0174 | 2.9475 | 2.9475 |
| 27.3667 | 0.298 | 0.0174 | 2.7477 | 2.765 |
| 27.4 | 0.3197 | 0.0174 | 2.2598 | 2.2772 |
| 27.4333 | 0.3391 | 0.0174 | 1.8416 | 1.859 |
| 27.4667 | -0.0483 | 0.0174 | 1.4998 | 1.5171 |
| 27.5 | -0.0408 | 0.0305 | 1.2197 | 1.2502 |
| 27.5333 | -0.0355 | 0.0174 | 0.9856 | 1.003 |
| 27.5667 | -0.0243 | 0.0042 | 0.7923 | 0.7965 |
| 27.6 | -0.0227 | 0.0042 | 0.6463 | 0.6505 |
| 27.6333 | -0.0194 | 0.0174 | 0.5635 | 0.5808 |
| 27.6667 | -0.0197 | 0.0042 | 0.4872 | 0.4914 |
| 27.7 | -0.0174 | 0.0042 | 0.4622 | 0.4664 |
| 27.7333 | -0.021 | 0.0042 | 0.5267 | 0.5309 |
| 27.7667 | -0.0184 | 0.0174 | 0.002 | 0.0194 |
| 27.8 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 27.8333 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 27.8667 | -0.0059 | 0.0174 | 0.0033 | 0.0207 |
| 27.9 | -0.0055 | 0.0437 | 0.002 | 0.0457 |
| 27.9333 | -0.0088 | 0.0305 | 0.002 | 0.0325 |
| 27.9667 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 28 | -0.0032 | 0.0305 | 0.002 | 0.0325 |
| 28.0333 | -0.0026 | 0.0042 | 0.0007 | 0.0049 |
| 28.0667 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 28.1 | -0.0036 | 0.0042 | 0.0033 | 0.0075 |
| 28.1333 | -0.0009 | 0.0174 | 0.002 | 0.0194 |
| 28.1667 | -0.0026 | 0.0042 | 0.002 | 0.0062 |
| 28.2 | -0.0003 | 0.0174 | 0.0007 | 0.018 |
| 28.2333 | -0.0003 | 0.0042 | 0.0007 | 0.0049 |
| 28.2667 | 0.002 | 0.0042 | 0.0033 | 0.0075 |
| 28.3 | -0.0003 | 0.0437 | 0.0007 | 0.0443 |
| 28.3333 | -0.0009 | 0.0305 | 0.002 | 0.0325 |
| 28.3667 | -0.0009 | 0.0305 | 0.0033 | 0.0338 |
| 28.4 | 0.001 | 0.0042 | 0.002 | 0.0062 |
| 28.4333 | -0.0009 | 0.0305 | 0.0033 | 0.0338 |
| 28.4667 | 0.001 | 0.0042 | 0 | 0.0042 |
| 28.5 | 0.0017 | 0.0174 | 0.0033 | 0.0207 |
| 28.5333 | -0.0009 | 0.0174 | 0.0007 | 0.018 |
| 28.5667 | -0.0006 | 0.0305 | 0.002 | 0.0325 |
| 28.6 28.6333 | 0.0007 | 0.0174 0.0042 | 0.0007 | 0.018 0.0042 |
| 28.0333 | -0.0003 | 0.0042 | 0 | 0.0042 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 28.6667 | -0.0006 | 0.0174 | 0.0033 | 0.0207 |
| 28.7 | 0.0004 | 0.0437 | 0.002 | 0.0457 |
| 28.7333 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 28.7667 | 0.0001 | 0.0174 | 0.0033 | 0.0207 |
| 28.8 | -0.0013 | 0.0042 | 0 | 0.0042 |
| 28.8333 | 0.0001 | 0.0042 | 0 | 0.0042 |
| 28.8667 | -0.0009 | 0.0305 | 0.002 | 0.0325 |
| 28.9 | -0.0029 | 0 | 0.0007 | 0.0007 |
| 28.9333 | -0.0032 | 0.0042 | 0.0007 | 0.0049 |
| 28.9667 | -0.0022 | 0.0042 | 0.0007 | 0.0049 |
| 29 | -0.0026 | 0.0174 | 0.0007 | 0.018 |
| 29.0333 | -0.0029 | 0.0174 | 0.002 | 0.0194 |
| 29.0667 | -0.0006 | 0.0174 | 0.0007 | 0.018 |
| 29.1 | -0.0006 | 0.0042 | 0.002 | 0.0062 |
| 29.1333 | 0.0014 | 0.0174 | 0.8791 | 0.8964 |
| 29.1667 | -0.0299 | 0.0042 | 1.3512 | 1.3554 |
| 29.2 | -0.0371 | 0.0042 | 1.388 | 1.3922 |
| 29.2333 | -0.0427 | 0.0305 | 1.4222 | 1.4527 |
| 29.2667 | -0.0414 | 0.0042 | 1.4748 | 1.479 |
| 29.3 | -0.0437 | 0.0174 | 1.5076 | 1.525 |
| 29.3333 | -0.0457 | 0.0042 | 1.5524 | 1.5566 |
| 29.3667 | -0.0503 | 0.0174 | 1.5971 | 1.6144 |
| 29.4 | -0.047 | 0.0042 | 0.0033 | 0.0075 |
| 29.4333 | -0.0467 | 0.0174 | 0.002 | 0.0194 |
| 29.4667 | -0.0385 | 0.0174 | 0.0033 | 0.0207 |
| 29.5 | -0.0309 | 0.0042 | 0.002 | 0.0062 |
| 29.5333 | -0.0269 | 0.0042 | 0 | 0.0042 |
| 29.5667 | -0.019 | 0.0042 | 0.002 | 0.0062 |
| 29.6 | -0.0134 | 0.0174 | 0.0033 | 0.0207 |
| 29.6333 | -0.0111 | 0.0174 | 0.0033 | 0.0207 |
| 29.6667 | -0.0088 | 0.0174 | 0 | 0.0174 |
| 29.7 | -0.0088 | 0.0174 | 0.002 | 0.0194 |
| 29.7333 | -0.0085 | 0.0174 | 0.002 | 0.0194 |
| 29.7667 | -0.0118 | 0.0042 | 0.002 | 0.0062 |
| 29.8 | -0.0128 | 0.0174 | 0.0007 | 0.018 |
| 29.8333 | -0.0151 | 0.0174 | 0.002 | 0.0194 |
| 29.8667 | -0.0151 | 0.0174 | 0.002 | 0.0194 |
| 29.9 | -0.0151 | 0.0174 | 0.0007 | 0.018 |
| 29.9333 | -0.019 | 0.0174 | 0.0046 | 0.022 |
| 29.9667 | -0.0204 | 0.0305 | 0.0007 | 0.0312 |
| 30 | -0.0204 | 0.0174 | 0.0007 | 0.018 |
| 30.0333 | -0.0223 | 0.0042 | 0.002 | 0.0062 |
| 30.0667 | -0.0236 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| () | (1) | (=::::, | | (|
| 30.1 | 0.0057 | 0 | 0.002 | 0.002 |
| 30.1333 | 0.057 | 0.0174 | 0.8265 | 0.8438 |
| 30.1667 | 0.107 | 0.0174 | 0.8278 | 0.8452 |
| 30.2 | 0.1551 | 0.0174 | 0.8436 | 0.8609 |
| 30.2333 | 0.2032 | 0.0174 | 0.9225 | 0.9398 |
| 30.2667 | 0.2469 | 0.0042 | 1.0014 | 1.0056 |
| 30.3 | 0.2894 | 0.0174 | 1.0816 | 1.0989 |
| 30.3333 | 0.3292 | 0 | 1.1618 | 1.1618 |
| 30.3667 | 0.371 | 0.0042 | 1.246 | 1.2502 |
| 30.4 | 0.4112 | 0.0174 | 1.3249 | 1.3422 |
| 30.4333 | 0.4451 | 0.0042 | 1.4051 | 1.4093 |
| 30.4667 | 0.4803 | 0.0174 | 1.4905 | 1.5079 |
| 30.5 | 0.5172 | 0.0174 | 1.5773 | 1.5947 |
| 30.5333 | 0.5517 | 0.0174 | 1.6536 | 1.671 |
| 30.5667 | 0.5833 | 0.0042 | 1.7364 | 1.7407 |
| 30.6 | 0.6153 | 0.0174 | 1.8193 | 1.8366 |
| 30.6333 | 0.6495 | 0.0174 | 1.9048 | 1.9221 |
| 30.6667 | 0.6781 | 0.0042 | 1.9837 | 1.9879 |
| 30.7 | 0.7078 | 0.0042 | 2.0665 | 2.0707 |
| 30.7333 | 0.739 | 0.0042 | 2.152 | 2.1562 |
| 30.7667 | 0.7654 | 0.0174 | 2.2282 | 2.2456 |
| 30.8 | 0.7914 | 0.0042 | 2.3071 | 2.3114 |
| 30.8333 | 0.8194 | 0.0174 | 2.3808 | 2.3981 |
| 30.8667 | 0.846 | 0.0174 | 2.4715 | 2.4889 |
| 30.9 | 0.8704 | 0.0174 | 2.5438 | 2.5612 |
| 30.9333 | 0.898 | 0.0042 | 2.6241 | 2.6283 |
| 30.9667 | 0.9184 | 0.0174 | 2.6951 | 2.7124 |
| 31 | 0.9408 | 0.0174 | 2.7726 | 2.79 |
| 31.0333 | 0.9625 | 0.0174 | 2.8476 | 2.865 |
| 31.0667 | 0.9853 | 0.0042 | 2.9226 | 2.9268 |
| 31.1 | 1.0073 | 0.0042 | 2.9962 | 3.0004 |
| 31.1333 | 1.03 | 0.0305 | 3.0633 | 3.0938 |
| 31.1667 | 1.0498 | 0.0174 | 3.1422 | 3.1595 |
| 31.2 | 1.0702 | 0.0174 | 3.2132 | 3.2305 |
| 31.2333 | 1.0889 | 0.0174 | 3.2815 | 3.2989 |
| 31.2667 | 1.1094 | 0.0042 | 3.3473 | 3.3515 |
| 31.3 | 1.1271 | 0.0305 | 3.417 | 3.4475 |
| 31.3333 | 1.1419 | 0.0174 | 3.4827 | 3.5001 |
| 31.3667 | 1.1643 | 0.0174 | 3.5498 | 3.5672 |
| 31.4 | 1.1814 | 0.0437 | 3.6142 | 3.6579 |
| 31.4333 | 1.1982 | 0.0174 | 3.6747 | 3.6921 |
| 31.4667 | 1.2117 | 0.0305 | 3.7418 | 3.7723 |
| 31.5 | 1.2305 | 0.0042 | 3.8036 | 3.8078 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 31.5333 | 1.2489 | 0.0042 | 3.8601 | 3.8643 |
| 31.5667 | 1.2595 | 0.0174 | 3.9246 | 3.9419 |
| 31.6 | 1.2762 | 0.0042 | 3.9798 | 3.984 |
| 31.6333 | 1.2881 | 0.0042 | 4.0377 | 4.0419 |
| 31.6667 | 1.3013 | 0.0042 | 4.106 | 4.1102 |
| 31.7 | 1.3194 | 0.0174 | 4.1626 | 4.1799 |
| 31.7333 | 1.3302 | 0.0042 | 4.2231 | 4.2273 |
| 31.7667 | 1.3457 | 0.0174 | 4.2757 | 4.293 |
| 31.8 | 1.3582 | 0.0174 | 4.3348 | 4.3522 |
| 31.8333 | 1.3694 | 0.0174 | 4.4072 | 4.4245 |
| 31.8667 | 1.3819 | 0.0042 | 4.4703 | 4.4745 |
| 31.9 | 1.3924 | 0.0305 | 4.5426 | 4.5731 |
| 31.9333 | 1.4013 | 0.0174 | 4.6084 | 4.6257 |
| 31.9667 | 1.4145 | 0.0174 | 4.6794 | 4.6967 |
| 32 | 1.4224 | 0.0042 | 4.7412 | 4.7454 |
| 32.0333 | 1.4309 | 0.0042 | 4.8082 | 4.8124 |
| 32.0667 | 1.4418 | 0.0174 | 4.8674 | 4.8848 |
| 32.1 | 1.4504 | 0.0042 | 4.9292 | 4.9334 |
| 32.1333 | 1.4586 | 0.0305 | 4.9936 | 5.0241 |
| 32.1667 | 1.4688 | 0.0174 | 5.0581 | 5.0754 |
| 32.2 | 1.479 | 0.0174 | 5.1278 | 5.1451 |
| 32.2333 | 1.4846 | 0.0174 | 5.1883 | 5.2056 |
| 32.2667 | 1.4945 | 0.0174 | 5.2474 | 5.2648 |
| 32.3 | 1.5027 | 0.0174 | 5.3092 | 5.3266 |
| 32.3333 | 1.5099 | 0.0174 | 5.3724 | 5.3897 |
| 32.3667 | 1.5169 | 0.0174 | 5.4263 | 5.4436 |
| 32.4 | 1.5254 | 0.0174 | 5.492 | 5.5094 |
| 32.4333 | 1.5327 | 0.0174 | 5.5446 | 5.562 |
| 32.4667 | 1.5356 | 0.0174 | 5.5985 | 5.6159 |
| 32.5 | 1.5448 | 0.0305 | 5.6524 | 5.6829 |
| 32.5333 | 1.5531 | 0.0174 | 5.6998 | 5.7171 |
| 32.5667 | 1.5606 | 0.0174 | 5.7524 | 5.7697 |
| 32.6 | 1.5616 | 0.0305 | 5.801 | 5.8315 |
| 32.6333 | 1.5685 | 0.0305 | 5.8563 | 5.8868 |
| 32.6667 | 1.5745 | 0.0174 | 5.9036 | 5.921 |
| 32.7 | 1.5814 | 0.0174 | 5.9509 | 5.9683 |
| 32.7333 | 1.585 | 0.0305 | 5.9996 | 6.0301 |
| 32.7667 | 1.5909 | 0.0174 | 6.043 | 6.0603 |
| 32.8 | 1.5942 | 0.0042 | 6.093 | 6.0972 |
| 32.8333 | 1.5992 | 0.0174 | 6.1403 | 6.1577 |
| 32.8667 | 1.6061 | 0.0305 | 6.1929 | 6.2234 |
| 32.9 | 1.61 | 0.0305 | 6.2429 | 6.2734 |
| 32.9333 | 1.612 | 0.0174 | 6.2797 | 6.297 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 32.9667 | 1.6186 | 0.0174 | 6.3204 | 6.3378 |
| 33 | 1.6258 | 0.0305 | 6.3638 | 6.3943 |
| 33.0333 | 1.6242 | 0.0174 | 6.4164 | 6.4338 |
| 33.0667 | 1.6301 | 0.0305 | 6.4493 | 6.4798 |
| 33.1 | 1.6337 | 0.0305 | 6.5006 | 6.5311 |
| 33.1333 | 1.6396 | 0.0174 | 6.5374 | 6.5548 |
| 33.1667 | 1.6429 | 0.0042 | 6.5834 | 6.5876 |
| 33.2 | 1.6452 | 0.0174 | 6.6216 | 6.6389 |
| 33.2333 | 1.6495 | 0.0042 | 6.6715 | 6.6758 |
| 33.2667 | 1.6512 | 0 | 6.7123 | 6.7123 |
| 33.3 | 1.6525 | 0.0174 | 6.7544 | 6.7717 |
| 33.3333 | 1.6515 | 0.0305 | 6.7925 | 6.823 |
| 33.3667 | 1.6396 | 0 | 6.8385 | 6.8385 |
| 33.4 | 1.6258 | 0.0174 | 6.8793 | 6.8967 |
| 33.4333 | 1.612 | 0.0042 | 6.9096 | 6.9138 |
| 33.4667 | 1.6015 | 0.0174 | 6.9477 | 6.965 |
| 33.5 | 1.588 | 0.0174 | 6.9792 | 6.9966 |
| 33.5333 | 1.5751 | 0.0305 | 7.0108 | 7.0413 |
| 33.5667 | 1.5643 | 0.0042 | 7.0424 | 7.0466 |
| 33.6 | 1.5527 | 0.0042 | 7.0739 | 7.0781 |
| 33.6333 | 1.5445 | 0.0042 | 7.1042 | 7.1084 |
| 33.6667 | 1.5439 | 0.0042 | 7.1357 | 7.1399 |
| 33.7 | 1.5442 | 0.0042 | 7.1568 | 7.161 |
| 33.7333 | 1.5448 | 0.0042 | 7.1844 | 7.1886 |
| 33.7667 | 1.5455 | 0.0174 | 7.2107 | 7.228 |
| 33.8 | 1.5541 | 0.0174 | 7.2462 | 7.2635 |
| 33.8333 | 1.5564 | 0.0042 | 7.2725 | 7.2767 |
| 33.8667 | 1.5636 | 0.0174 | 7.3027 | 7.3201 |
| 33.9 | 1.5682 | 0.0174 | 7.3264 | 7.3438 |
| 33.9333 | 1.5778 | 0.0042 | 7.3566 | 7.3609 |
| 33.9667 | 1.5837 | 0 | 7.3764 | 7.3764 |
| 34 | 1.5889 | 0.0174 | 7.3974 | 7.4148 |
| 34.0333 | 1.5995 | 0.0305 | 7.4395 | 7.47 |
| 34.0667 | 1.608 | 0.0174 | 7.4605 | 7.4779 |
| 34.1 | 1.6113 | 0.0174 | 7.4895 | 7.5068 |
| 34.1333 | 1.6202 | 0.0174 | 7.5223 | 7.5397 |
| 34.1667 | 1.6245 | 0.0042 | 7.5486 | 7.5528 |
| 34.2 | 1.6288 | 0.0174 | 7.571 | 7.5883 |
| 34.2333 | 1.636 | 0.0042 | 7.6025 | 7.6068 |
| 34.2667 | 1.6252 | 0.0042 | 7.6328 | 7.637 |
| 34.3 | 1.6202 | 0.0305 | 7.6473 | 7.6778 |
| 34.3333 | 1.6225 | 0.0042 | 7.6867 | 7.6909 |
| 34.3667 | 1.6252 | 0.0305 | 7.7091 | 7.7396 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|---------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 34.4 | 1.6258 | 0.0042 | 7.7275 | 7.7317 |
| 34.4333 | 1.6268 | 0.0305 | 7.7577 | 7.7882 |
| 34.4667 | 1.6308 | 0.0174 | 7.7866 | 7.804 |
| 34.5 | 1.6301 | 0.0042 | 7.8116 | 7.8158 |
| 34.5333 | 1.6327 | 0.0042 | 7.8353 | 7.8395 |
| 34.5667 | 1.638 | 0.0437 | 7.8537 | 7.8974 |
| 34.6 | 1.6347 | 0.0042 | 7.8774 | 7.8816 |
| 34.6333 | 1.636 | 0.0042 | 7.9063 | 7.9105 |
| 34.6667 | 1.6383 | 0.0174 | 7.9352 | 7.9526 |
| 34.7 | 1.6393 | 0.0305 | 7.9615 | 7.992 |
| 34.7333 | 1.6449 | 0.0174 | 7.9734 | 7.9907 |
| 34.7667 | 1.6446 | 0.0042 | 8.0049 | 8.0091 |
| 34.8 | 1.6406 | 0.0174 | 8.022 | 8.0394 |
| 34.8333 | 1.636 | 0.0174 | 8.0431 | 8.0604 |
| 34.8667 | 1.6304 | 0.0174 | 8.0746 | 8.092 |
| 34.9 | 1.6278 | 0.0174 | 8.093 | 8.1104 |
| 34.9333 | 1.6215 | 0.0174 | 8.1088 | 8.1262 |
| 34.9667 | 1.615 | 0.0042 | 8.1259 | 8.1301 |
| 35 | 1.61 | 0.0042 | 8.1535 | 8.1577 |
| 35.0333 | 1.6103 | 0.0174 | 8.1693 | 8.1867 |
| 35.0667 | 1.6074 | 0.0174 | 8.1917 | 8.209 |
| 35.1 | 1.6028 | 0.0042 | 8.2035 | 8.2077 |
| 35.1333 | 1.5998 | 0.0042 | 8.235 | 8.2393 |
| 35.1667 | 1.6011 | 0.0174 | 8.239 | 8.2564 |
| 35.2 | 1.5998 | 0.0042 | 8.2679 | 8.2721 |
| 35.2333 | 1.5988 | 0.0174 | 8.2811 | 8.2984 |
| 35.2667 | 1.5995 | 0.0174 | 8.3074 | 8.3247 |
| 35.3 | 1.6024 | 0.0174 | 8.3087 | 8.326 |
| 35.3333 | 1.6011 | 0.0305 | 8.3416 | 8.3721 |
| 35.3667 | 1.6028 | 0.0042 | 8.36 | 8.3642 |
| 35.4 | 1.6038 | 0 | 8.3521 | 8.3521 |
| 35.4333 | 1.6047 | 0.0174 | 8.3784 | 8.3957 |
| 35.4667 | 1.6057 | 0.0174 | 8.3942 | 8.4115 |
| 35.5 | 1.6084 | 0.0042 | 8.4099 | 8.4141 |
| 35.5333 | 1.6074 | 0.0174 | 8.4284 | 8.4457 |
| 35.5667 | 1.6094 | 0 | 8.4481 | 8.4481 |
| 35.6 | 1.61 | 0.0042 | 8.4625 | 8.4667 |
| 35.6333 | 1.6136 | 0.0437 | 8.4691 | 8.5128 |
| 35.6667 | 1.6176 | 0.0305 | 8.4888 | 8.5193 |
| 35.7 | 1.6173 | 0.0042 | 8.5125 | 8.5167 |
| 35.7333 | 1.6222 | 0.0174 | 8.5349 | 8.5522 |
| 35.7667 | 1.6235 | 0.0174 | 8.5454 | 8.5627 |
| 35.8 | 1.6291 | 0.0305 | 8.5585 | 8.589 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|------------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | W W 10 1000 | that programming | |
| 35.8333 | 1.6327 | 0.0305 | 8.5783 | 8.6088 |
| 35.8667 | 1.6311 | 0.0042 | 8.5967 | 8.6009 |
| 35.9 | 1.635 | 0.0042 | 8.6072 | 8.6114 |
| 35.9333 | 1.6393 | 0.0174 | 8.6282 | 8.6456 |
| 35.9667 | 1.6383 | 0.0174 | 8.6387 | 8.6561 |
| 36 | 1.6439 | 0.0042 | 8.6545 | 8.6587 |
| 36.0333 | 1.6426 | 0.0174 | 8.6782 | 8.6956 |
| 36.0667 | 1.6452 | 0.0174 | 8.6861 | 8.7034 |
| 36.1 | 1.6469 | 0.0042 | 8.7006 | 8.7048 |
| 36.1333 | 1.6433 | 0.0042 | 8.719 | 8.7232 |
| 36.1667 | 1.6429 | 0.0174 | 8.7282 | 8.7455 |
| 36.2 | 1.6413 | 0.0042 | 8.7545 | 8.7587 |
| 36.2333 | 1.6387 | 0.0174 | 8.7729 | 8.7902 |
| 36.2667 | 1.6373 | 0.0042 | 8.7768 | 8.781 |
| 36.3 | 1.6396 | 0.0174 | 8.7979 | 8.8152 |
| 36.3333 | 1.6373 | 0.0042 | 8.8084 | 8.8126 |
| 36.3667 | 1.634 | 0 | 8.8176 | 8.8176 |
| 36.4 | 1.6331 | 0.0174 | 8.836 | 8.8534 |
| 36.4333 | 1.6334 | 0.0174 | 8.8439 | 8.8612 |
| 36.4667 | 1.6311 | 0.0042 | 8.8623 | 8.8665 |
| 36.5 | 1.6281 | 0.0174 | 8.8833 | 8.9007 |
| 36.5333 | 1.6275 | 0 | 8.8912 | 8.8912 |
| 36.5667 | 1.6278 | 0.0042 | 8.9017 | 8.9059 |
| 36.6 | 1.6294 | 0.0174 | 8.907 | 8.9244 |
| 36.6333 | 1.6311 | 0.0174 | 8.9267 | 8.9441 |
| 36.6667 | 1.6281 | 0.0305 | 8.9359 | 8.9664 |
| 36.7 | 1.6265 | 0.0174 | 8.9465 | 8.9638 |
| 36.7333 | 1.6265 | 0.0174 | 8.953 | 8.9704 |
| 36.7667 | 1.6252 | 0.0305 | 8.9662 | 8.9967 |
| 36.8 | 1.6245 | 0.0042 | 8.9885 | 8.9927 |
| 36.8333 | 1.6202 | 0.0042 | 8.9977 | 9.0019 |
| 36.8667 | 1.6235 | 0.0174 | 9.0043 | 9.0217 |
| 36.9 | 1.6209 | 0.0305 | 9.0122 | 9.0427 |
| 36.9333 | 1.6225 | 0.0042 | 9.028 | 9.0322 |
| 36.9667 | 1.6222 | 0 | 9.0372 | 9.0372 |
| 37 | 1.6225 | 0.0174 | 9.0516 | 9.069 |
| 37.0333 | 1.6202 | 0.0437 | 9.0648 | 9.1085 |
| 37.0667 | 1.6212 | 0.0174 | 9.0766 | 9.094 |
| 37.1 | 1.6196 | 0 | 9.0819 | 9.0819 |
| 37.1333 | 1.6169 | 0.0174 | 9.0858 | 9.1032 |
| 37.1667 | 1.6199 | 0.0042 | 9.0964 | 9.1006 |
| 37.2 | 1.6196 | 0.0174 | 9.1029 | 9.1203 |
| 37.2333 | 1.6173 | 0.0042 | 9.1253 | 9.1295 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 37.2667 | 1.6173 | 0.0174 | 9.1279 | 9.1453 |
| 37.3 | 1.6146 | 0.0305 | 9.1292 | 9.1597 |
| 37.3333 | 1.6153 | 0.0174 | 9.1384 | 9.1558 |
| 37.3667 | 1.6153 | 0.0042 | 9.1476 | 9.1519 |
| 37.4 | 1.615 | 0.0042 | 9.1595 | 9.1637 |
| 37.4333 | 1.6136 | 0.0174 | 9.1674 | 9.1847 |
| 37.4667 | 1.6163 | 0.0042 | 9.1805 | 9.1847 |
| 37.5 | 1.613 | 0.0305 | 9.191 | 9.2215 |
| 37.5333 | 1.6143 | 0.0437 | 9.2002 | 9.2439 |
| 37.5667 | 1.6173 | 0.0042 | 9.1963 | 9.2005 |
| 37.6 | 1.6143 | 0.0174 | 9.2081 | 9.2255 |
| 37.6333 | 1.6123 | 0.0174 | 9.2318 | 9.2492 |
| 37.6667 | 1.6153 | 0.0042 | 9.2384 | 9.2426 |
| 37.7 | 1.6163 | 0.0042 | 9.2226 | 9.2268 |
| 37.7333 | 1.6182 | 0 | 9.2397 | 9.2397 |
| 37.7667 | 1.6156 | 0.0174 | 9.2384 | 9.2557 |
| 37.8 | 1.6186 | 0.0042 | 9.2476 | 9.2518 |
| 37.8333 | 1.6215 | 0 | 9.2542 | 9.2542 |
| 37.8667 | 1.6199 | 0.0174 | 9.2778 | 9.2952 |
| 37.9 | 1.6199 | 0.0042 | 9.2831 | 9.2873 |
| 37.9333 | 1.6219 | 0.0042 | 9.2857 | 9.2899 |
| 37.9667 | 1.6242 | 0.0174 | 9.2936 | 9.311 |
| 38 | 1.6238 | 0.0042 | 9.2989 | 9.3031 |
| 38.0333 | 1.6242 | 0.0042 | 9.3054 | 9.3096 |
| 38.0667 | 1.6248 | 0.0042 | 9.3199 | 9.3241 |
| 38.1 | 1.6248 | 0.0174 | 9.3291 | 9.3465 |
| 38.1333 | 1.6261 | 0.0174 | 9.3317 | 9.3491 |
| 38.1667 | 1.6255 | 0.0305 | 9.3396 | 9.3701 |
| 38.2 | 1.6284 | 0.0174 | 9.3594 | 9.3767 |
| 38.2333 | 1.6298 | 0.0042 | 9.3567 | 9.3609 |
| 38.2667 | 1.6311 | 0.0042 | 9.3672 | 9.3715 |
| 38.3 | 1.6284 | 0.0174 | 9.362 | 9.3793 |
| 38.3333 | 1.6324 | 0.0042 | 9.3686 | 9.3728 |
| 38.3667 | 1.6321 | 0.0174 | 9.3791 | 9.3964 |
| 38.4 | 1.5978 | 0.0042 | 9.3857 | 9.3899 |
| 38.4333 | 1.5363 | 0.0042 | 9.3922 | 9.3964 |
| 38.4667 | 1.4751 | 0.0042 | 9.387 | 9.3912 |
| 38.5 | 1.4165 | 0.0042 | 9.3699 | 9.3741 |
| 38.5333 | 1.3625 | 0.0042 | 9.3751 | 9.3793 |
| 38.5667 | 1.3095 | 0.0174 | 9.3515 | 9.3688 |
| 38.6 | 1.2578 | 0.0174 | 9.3396 | 9.357 |
| 38.6333 | 1.2173 | 0.0042 | 9.1437 | 9.1479 |
| 38.6667 | 1.1874 | 0.0174 | 8.6072 | 8.6245 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| () | (100.7) | (=:, | (=:, | (=:, |
| 38.7 | 1.1597 | 0.0042 | 8.122 | 8.1262 |
| 38.7333 | 1.1288 | 0.0174 | 7.6617 | 7.6791 |
| 38.7667 | 1.1024 | 0.0174 | 7.2344 | 7.2517 |
| 38.8 | 1.0751 | 0.0174 | 6.7886 | 6.8059 |
| 38.8333 | 1.0468 | 0.0042 | 6.3823 | 6.3865 |
| 38.8667 | 1.0231 | 0.0174 | 5.9956 | 6.013 |
| 38.9 | 0.9925 | 0.0042 | 5.7077 | 5.7119 |
| 38.9333 | 0.9695 | 0.0042 | 5.3894 | 5.3937 |
| 38.9667 | 0.9395 | 0.0042 | 5.1698 | 5.1741 |
| 39 | 0.9178 | 0.0305 | 4.8003 | 4.8308 |
| 39.0333 | 0.8974 | 0.0174 | 4.4085 | 4.4258 |
| 39.0667 | 0.876 | 0.0305 | 4.0824 | 4.1129 |
| 39.1 | 0.844 | 0.0042 | 3.9246 | 3.9288 |
| 39.1333 | 0.819 | 0.0305 | 3.8733 | 3.9038 |
| 39.1667 | 0.7907 | 0.0042 | 3.8273 | 3.8315 |
| 39.2 | 0.7614 | 0.0174 | 3.7615 | 3.7789 |
| 39.2333 | 0.7328 | 0.0174 | 3.7115 | 3.7289 |
| 39.2667 | 0.7071 | 0.0305 | 3.6708 | 3.7013 |
| 39.3 | 0.6808 | 0.0042 | 3.6484 | 3.6526 |
| 39.3333 | 0.6535 | 0.0174 | 3.6313 | 3.6487 |
| 39.3667 | 0.6301 | 0.0042 | 3.5235 | 3.5277 |
| 39.4 | 0.6156 | 0.0042 | 3.25 | 3.2542 |
| 39.4333 | 0.6057 | 0.0042 | 2.8108 | 2.815 |
| 39.4667 | 0.5899 | 0.0042 | 2.4242 | 2.4284 |
| 39.5 | 0.5748 | 0.0174 | 2.102 | 2.1194 |
| 39.5333 | 0.5636 | 0.0174 | 1.8259 | 1.8432 |
| 39.5667 | 0.5445 | 0.0174 | 1.7101 | 1.7275 |
| 39.6 | 0.5271 | 0.0305 | 1.5681 | 1.5986 |
| 39.6333 | 0.5109 | 0.0042 | 1.4209 | 1.4251 |
| 39.6667 | 0.4931 | 0.0174 | 1.3328 | 1.3501 |
| 39.7 | 0.4764 | 0.0174 | 1.292 | 1.3093 |
| 39.7333 | 0.456 | 0.0042 | 1.3709 | 1.3751 |
| 39.7667 | 0.4332 | 0.0174 | 1.5076 | 1.525 |
| 39.8 | 0.4099 | 0.0042 | 1.6181 | 1.6223 |
| 39.8333 | 0.3881 | 0.0042 | 1.722 | 1.7262 |
| 39.8667 | 0.373 | 0.0174 | 1.8075 | 1.8248 |
| 39.9 | 0.3516 | 0.0042 | 1.8811 | 1.8853 |
| 39.9333 | 0.3371 | 0.0042 | 1.9482 | 1.9524 |
| 39.9667 | 0.3151 | 0.0174 | 2.0126 | 2.03 |
| 40 | 0.3006 | 0.0174 | 2.0718 | 2.0891 |
| 40.0333 | 0.2848 | 0.0174 | 2.1204 | 2.1378 |
| 40.0667 | 0.2687 | 0.0174 | 2.1691 | 2.1864 |
| 40.1 | 0.2538 | 0.0174 | 2.2125 | 2.2298 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | | Ch 3 Low Flow | |
|--------------------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 40.1333 | 0.2387 | 0.0305 | 2.248 | 2.2785 |
| 40.1333 | 0.2249 | 0.0303 | 2.248 | 2.2783 |
| 40.1667 | 0.2114 | 0.0042 | 2.3124 | 2.3166 |
| 40.2333 | 0.2114 | 0.0042 | 2.1231 | 2.1273 |
| 40.2667 | 0.2018 | 0.0042 | 1.9166 | 1.934 |
| 40.2667 | 0.1989 | 0.0042 | 1.7364 | 1.7407 |
| 40.3333 | 0.1903 | 0.0042 | 1.6234 | 1.6276 |
| 40.3667 | 0.1729 | 0.0042 | 1.6746 | 1.6789 |
| 40.3667 | 0.1729 | 0.0174 | 1.7312 | 1.7485 |
| | | | | |
| 40.4333 40.4667 | 0.1498 | 0.0042 | 1.7798 | 1.7841 |
| | 0.1429 | 0.0042 | 1.818 | 1.8222 |
| 40.5 | 0.1403 | 0.0042 | 1.4117 | 1.4159 |
| 40.5333 | 0.1465 | 0.0174 | 1.0264 | 1.0437 |
| 40.5667 | 0.1432 | 0.0174 | 0.716 | 0.7334 |
| 40.6 | 0.1409 | 0.0305 | 0.482 | 0.5125 |
| 40.6333 | 0.1413 | 0.0174 | 0.3189 | 0.3363 |
| 40.6667 | 0.134 | 0.0174 | 0.002 | 0.0194 |
| 40.7 | 0.1261 | 0.0042 | 0 | 0.0042 |
| 40.7333 | 0.1238 | 0.0174 | 0.0007 | 0.018 |
| 40.7667 | 0.1156 | 0.0174 | 0.002 | 0.0194 |
| 40.8 | 0.1136 | 0.0174 | 0.0007 | 0.018 |
| 40.8333 | 0.1037 | 0.0042 | 0.0033 | 0.0075 |
| 40.8667 | 0.0998 | 0.0042 | 0.0033 | 0.0075 |
| 40.9 | 0.0945 | 0.0042 | 0.002 | 0.0062 |
| 40.9333 | 0.0909 | 0.0174 | 0.0007 | 0.018 |
| 40.9667 | 0.086 | 0.0305 | 0.002 | 0.0325 |
| 41 | 0.0777 | 0.0042 | 0.0007 | 0.0049 |
| 41.0333 | 0.0748 | 0.0042 | 0 | 0.0042 |
| 41.0667 | 0.0705 | 0.0174 | 0.0033 | 0.0207 |
| 41.1 | 0.0652 | 0.0042 | 0.002 | 0.0062 |
| 41.1333 | 0.0596 | 0.0042 | 0.0007 | 0.0049 |
| 41.1667 | 0.0563 | 0.0305 | 0.0033 | 0.0338 |
| 41.2 | 0.0563 | 0.0042 | 0.0033 | 0.0075 |
| 41.2333 | 0.0507 | 0.0174 | 0.002 | 0.0194 |
| 41.2667 | 0.0468 | 0.0042 | 0.0033 | 0.0075 |
| 41.3 | 0.0448 | 0.0174 | 0.0033 | 0.0207 |
| 41.3333 | 0.0405 | 0.0042 | 0 | 0.0042 |
| 41.3667 | 0.0399 | 0.0174 | 0.0007 | 0.018 |
| 41.4 | 0.0356 | 0.0305 | 0.002 | 0.0325 |
| 41.4333 | 0.0333 | 0.0042 | 0.002 | 0.0062 |
| 41.4667 | 0.0303 | 0.0305 | 0.002 | 0.0325 |
| 41.5 | 0.031 | 0.0174 | 0.0033 | 0.0207 |
| 41.5333 | 0.028 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | | Ch 2 High Flow | | |
|--------------------|---------|----------------|------------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 41.5667 | 0.0234 | 0.0174 | 0.0007 | 0.018 |
| 41.6 | 0.0241 | 0.0174 | 0.0007 | 0.018 |
| 41.6333 | 0.0231 | 0.0042 | 0.002 | 0.0062 |
| 41.6667 | 0.0205 | 0.0042 | 0.002 | 0.0062 |
| 41.7 | 0.0201 | 0.0174 | 0.0007 | 0.018 |
| 41.7333 | 0.0185 | 0.0042 | 0.002 | 0.0062 |
| 41.7667 | 0.0185 | 0.0174 | 0.002 | 0.0194 |
| 41.8 | 0.0155 | 0.0174 | 0.0007 | 0.018 |
| 41.8333 | 0.0116 | 0.0042 | 0.002 | 0.0062 |
| 41.8667 | 0.0132 | 0.0042 | 0.0046 | 0.0088 |
| 41.9 | 0.0103 | 0.0174 | 0.0007 | 0.018 |
| 41.9333 | 0.0099 | 0.0174 | 0.002 | 0.0194 |
| 41.9667 | 0.0116 | 0.0042 | 0.0007 | 0.0049 |
| 42 | 0.0083 | 0.0174 | 0.0007 | 0.018 |
| 42.0333 | 0.0083 | 0.0174 | 0.002 | 0.0194 |
| 42.0667 | 0.0116 | 0.0042 | 0.002 | 0.0062 |
| 42.1 | 0.007 | 0.0174 | 0.002 | 0.0194 |
| 42.1333 | 0.0106 | 0.0042 | 0.0007 | 0.0049 |
| 42.1667 | 0.007 | 0.0174 | 0 | 0.0174 |
| 42.2 | 0.008 | 0.0305 | 0.0007 | 0.0312 |
| 42.2333 | 0.007 | 0.0174 | 0.002 | 0.0194 |
| 42.2667 | 0.0076 | 0.0174 | 0.002 | 0.0194 |
| 42.3 | 0.002 | 0 | 0.0033 | 0.0033 |
| 42.3333 | 0.0057 | 0.0042 | 0.002 | 0.0062 |
| 42.3667 | 0.0047 | 0.0174 | 0.0007 | 0.018 |
| 42.4 | 0.0024 | 0.0174 | 0.002 | 0.0194 |
| 42.4333 | 0.002 | 0.0042 | 0.002 | 0.0062 |
| 42.4667 | 0.0027 | 0.0174 | 0.002 | 0.0194 |
| 42.5 | 0.0004 | 0.0174 | 0.002 | 0.0194 |
| 42.5333 | -0.0003 | 0.0174 | 0.002 | 0.0194 |
| 42.5667 | -0.0009 | 0.0042 | 0.002 | 0.0062 |
| 42.6 | -0.0013 | 0.0042 | 0.002 | 0.0062 |
| 42.6333 | 0.0004 | 0.0174 | 0.0007 | 0.018 |
| 42.6667 | 0.0001 | 0.0174 | 0.002 | 0.0194 |
| 42.7 | 0.0001 | 0.0174 | 0.0007 | 0.018 |
| 42.7333 42.7667 | -0.0013 | 0.0042 | 0.002 | 0.0062 |
| | 0.0027 | 0.0305 | 0.0033 | 0.0338 |
| 42.8 42.8333 | -0.0026 | 0.0174 | 0.0033 | 0.0207 |
| 42.8333 | 0.0004 | 0.0042 | 0.0007 0.0007 | 0.0049 0.0049 |
| 42.8667 | 0.001 | 0.0042 | 0.0007 | 0.0049 |
| 42.9 | -0.0003 | 0.0042 | 0.0007 | 0.0049 |
| 42.9333 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 42.3007 | 0.0030 | 0.0174 | 0.0007 | 0.010 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | |
|-----------------|--------------------|------------------|----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 42 | 0.0001 | 0.0042 | 5000 | 0.0040 |
| 43 43.0333 | 0.0001 | 0.0042 | 0.0007 | 0.0049 |
| 43.0667 | -0.0003 | 0.0174 | 0.002 | 0.0062 |
| | | | | |
| 43.1 43.1333 | -0.0009 | 0.0174 | 0.0007 | 0.018 |
| | 0.0001 | 0.0042 | 0.002 | 0.0062 |
| 43.1667 | -0.0032 -0.0016 | 0.0305 0.0174 | 0.002 | 0.0325 0.0207 |
| 43.2 43.2333 | | | 0.0033 | |
| | -0.0016 | 0.0174 | 0.002 | 0.0194 |
| 43.2667 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 43.3 | -0.0019 | 0.0174 | 0.0033 | 0.0207 |
| 43.3333 | -0.0029 | 0.0305 | 0.002 | 0.0325 |
| 43.3667 43.4 | -0.0049 | 0.0305 | 0.002 | 0.0325 |
| 43.4333 | -0.0022 -0.0003 | 0.0174 0.0042 | 0.002 | 0.0194 0.0062 |
| 43.4667 | -0.0003 | 0.0042 | 0.002 | 0.0062 |
| | -0.0026 | | | 0.0075 |
| 43.5 43.5333 | | 0.0305 | 0.002 | |
| | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 43.5667 | -0.0029 | 0.0174 | 0.0007 | 0.018 |
| 43.6 43.6333 | -0.0039 -0.0026 | 0.0174 | 0.002 0.002 | 0.0194 |
| | | 0.0174 | | 0.0194 |
| 43.6667 43.7 | -0.0029 | 0.0305 | 0.0007 | 0.0312 |
| 43.7 | -0.0013 -0.0009 | 0.0305 0.0305 | 0.0033 | 0.0338 0.0325 |
| 43.7667 | -0.0009 | 0.0303 | 0.002 | 0.0323 |
| 43.7667 | -0.0039 | 0.0174 | 0.0033 | 0.0207 |
| 43.8333 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 43.8667 | -0.0029 | 0.0174 | 0.002 | 0.0194 |
| 43.8667 | -0.0013 | 0.0303 | 0.002 | 0.0323 |
| 43.9333 | 0.0036 | 0.0174 | 0.002 | 0.0194 |
| 43.9667 | -0.0065 | 0.0303 | 0.002 | 0.0323 |
| 43.9667 | -0.0065 | 0.0174 | 0.0007 | 0.018 |
| 44.0333 | -0.0028 | 0.0174 | 0.002 | 0.0134 |
| 44.0553 | -0.0032 | 0.0042 | 0.0007 | 0.018 |
| 44.0667 | -0.0032 | 0.0042 | 0.0033 | 0.0073 |
| 44.1333 | -0.0018 | 0.0174 | 0.0033 | 0.0049 |
| 44.1667 | -0.0022 | 0.0174 | 0.0033 | 0.0207 |
| 44.1667 | -0.0032 | 0.0174 | 0.0033 | 0.0207 |
| 44.2333 | -0.0049 | 0.0174 | 0.002 | 0.0002 |
| 44.2555 | -0.0049 | 0.0042 | 0.002 | 0.0194 |
| 44.2667 | -0.0062 | 0.0305 | 0.0033 | 0.0042 |
| 44.3 | -0.0069 | 0.0303 | 0.0033 | 0.0338 |
| 44.3667 | -0.0144 | 0.0174 | 0.0007 | 0.018 |
| 44.3667 | -0.0131 | 0.0174 | 0.002 | 0.0194 |
| 44.4 | 0.0128 | 0.0174 | 0.002 | 0.0134 |



Project No. G101276459SAT-023

| Time | | Ch 2 High Flow | | |
|-----------------|------------------|------------------|----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 44.4333 | -0.0141 | 0.0174 | 0.002 | 0.0194 |
| 44.4667 | -0.0131 | 0.0174 | 0 | 0.0174 |
| 44.5 | -0.0151 | 0.0174 | 0.0033 | 0.0207 |
| 44.5333 | -0.0164 | 0.0305 | 0.002 | 0.0325 |
| 44.5667 | -0.018 | 0.0305 | 0.002 | 0.0325 |
| 44.6 | -0.0148 | 0.0305 | 0.002 | 0.0325 |
| 44.6333 | -0.0177 | 0.0437 | 0.002 | 0.0457 |
| 44.6667 | -0.0171 | 0.0042 | 0.0007 | 0.0049 |
| 44.7 | -0.0144 | 0.0042 | 0.002 | 0.0062 |
| 44.7333 | -0.0164 | 0.0437 | 0.0033 | 0.047 |
| 44.7667 | -0.0154 | 0.0042 | 0.002 | 0.0062 |
| 44.8 | -0.0187 | 0.0174 | 0.0007 | 0.018 |
| 44.8333 | -0.0171 | 0.0174 | 0.0007 | 0.018 |
| 44.8667 | -0.0184 | 0.0174 | 0.0033 | 0.0207 |
| 44.9 | -0.0194 | 0.0174 | 0.002 | 0.0194 |
| 44.9333 | -0.0174 | 0.0174 | 0.0033 | 0.0207 |
| 44.9667 | -0.0171 | 0.0174 | 0.002 | 0.0194 |
| 45 | -0.0161 | 0.0042 | 0.0033 | 0.0075 |
| 45.0333 | -0.0171 | 0.0174 | 0.002 | 0.0194 |
| 45.0667 | -0.0157 | 0.0174 | 0.0033 | 0.0207 |
| 45.1 | -0.0111 | 0.0042 | 0.0007 | 0.0049 |
| 45.1333 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 45.1667 | 0.0007 | 0.0305 | 0.0033 | 0.0338 |
| 45.2 | 0.0356 | 0.0174 | 0.002 | 0.0194 |
| 45.2333 | 0.0847 | 0.0305 | 0.002 | 0.0325 |
| 45.2667 | 0.135 | 0.0174 | 0.002 | 0.0194 |
| 45.3 | 0.1791 | 0.0174 | 0.0007 | 0.018 |
| 45.3333 | 0.2239 | 0.0042 | 0.002 | 0.0062 |
| 45.3667 | 0.27 | 0.0174 | 0.0007 | 0.018 |
| 45.4 | 0.3095 | 0.0042 | 0.002 | 0.0062 |
| 45.4333 | 0.3523 | 0.0174 | 0.002 | 0.0194 |
| 45.4667 | 0.3904 | 0.0174 | 0.002 | 0.0194 |
| 45.5 | 0.4267 | 0.0174 | 0.002 | 0.0194 |
| 45.5333 | 0.4652 | 0.0174 | 0.002 | 0.0194 |
| 45.5667 | 0.503 | 0.0174 | 0.002 | 0.0194 |
| 45.6 | 0.5396 | 0 | 0.002 | 0.002 |
| 45.6333 | 0.5745 | 0.0305 | 0.002 | 0.0325 |
| 45.6667 | 0.6051 | 0.0042 | 0.0007 | 0.0049 |
| 45.7 | 0.6386 | 0.0305 | 0.002 | 0.0325 |
| 45.7333 | 0.6683 | 0.0042 | 0.002 | 0.0062 |
| 45.7667 | 0.7022 | 0.0174 | 0.0007 | 0.018 |
| 45.8 45.8333 | 0.7302 0.7555 | 0.0042 0.0437 | 0.002 0.002 | 0.0062 0.0457 |
| 45.8333 | 0./555 | 0.0437 | 0.002 | 0.0457 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|---------|---------|----------------|--------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 45.8667 | 0.7868 | 0.0305 | 0.002 | 0.0325 |
| 45.9 | 0.8128 | 0.0174 | 0.002 | 0.0194 |
| 45.9333 | 0.8381 | 0.0174 | 0.002 | 0.0194 |
| 45.9667 | 0.8618 | 0.0305 | 0.0007 | 0.0312 |
| 46 | 0.8882 | 0.0174 | 0.002 | 0.0194 |
| 46.0333 | 0.9112 | 0.0042 | 0.002 | 0.0062 |
| 46.0667 | 0.9375 | 0.0042 | 0.0033 | 0.0075 |
| 46.1 | 0.9569 | 0.0042 | 0.002 | 0.0062 |
| 46.1333 | 0.9846 | 0.0042 | 0.0007 | 0.0049 |
| 46.1667 | 1.0011 | 0.0042 | 0.0033 | 0.0075 |
| 46.2 | 1.0205 | 0.0174 | 0.0007 | 0.018 |
| 46.2333 | 1.0458 | 0.0174 | 0.002 | 0.0194 |
| 46.2667 | 1.0646 | 0.0042 | 0.002 | 0.0062 |
| 46.3 | 1.0804 | 0.0174 | 0.002 | 0.0194 |
| 46.3333 | 1.1015 | 0.0174 | 0.002 | 0.0194 |
| 46.3667 | 1.1166 | 0.0042 | 0.0033 | 0.0075 |
| 46.4 | 1.134 | 0.0042 | 0.002 | 0.0062 |
| 46.4333 | 1.1505 | 0.0174 | 0.0033 | 0.0207 |
| 46.4667 | 1.167 | 0.0174 | 0.002 | 0.0194 |
| 46.5 | 1.1824 | 0.0174 | 0.002 | 0.0194 |
| 46.5333 | 1.1979 | 0.0042 | 0.0007 | 0.0049 |
| 46.5667 | 1.2127 | 0.0042 | 0.0033 | 0.0075 |
| 46.6 | 1.2275 | 0.0042 | 0.0033 | 0.0075 |
| 46.6333 | 1.2413 | 0.0174 | 0.002 | 0.0194 |
| 46.6667 | 1.2552 | 0.0174 | 0.002 | 0.0194 |
| 46.7 | 1.2654 | 0.0042 | 0.002 | 0.0062 |
| 46.7333 | 1.2799 | 0.0174 | 0.0007 | 0.018 |
| 46.7667 | 1.2937 | 0.0174 | 0.0033 | 0.0207 |
| 46.8 | 1.3062 | 0.0305 | 0.002 | 0.0325 |
| 46.8333 | 1.3164 | 0.0042 | 0.0007 | 0.0049 |
| 46.8667 | 1.3263 | 0.0042 | 0.002 | 0.0062 |
| 46.9 | 1.3388 | 0.0174 | 0.002 | 0.0194 |
| 46.9333 | 1.3473 | 0.0174 | 0.002 | 0.0194 |
| 46.9667 | 1.3582 | 0.0174 | 0.002 | 0.0194 |
| 47 | 1.3674 | 0.0042 | 0.0033 | 0.0075 |
| 47.0333 | 1.3786 | 0.0174 | 0.002 | 0.0194 |
| 47.0667 | 1.3862 | 0.0042 | 0.002 | 0.0062 |
| 47.1 | 1.3901 | 0.0174 | 0.002 | 0.0194 |
| 47.1333 | 1.4023 | 0.0042 | 0.002 | 0.0062 |
| 47.1667 | 1.4079 | 0.0174 | 0.0007 | 0.018 |
| 47.2 | 1.4194 | 0.0305 | 0.002 | 0.0325 |
| 47.2333 | 1.425 | 0.0042 | 0.0007 | 0.0049 |
| 47.2667 | 1.4339 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|------------------|------------------|------------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 47.3 | 1.4369 | 0.0305 | 0.0033 | 0.0338 |
| 47.3333 | 1.4474 | 0.0174 | 0.002 | 0.0194 |
| 47.3667 | 1.4494 | 0.0305 | 0.002 | 0.0325 |
| 47.4 | 1.4556 | 0.0174 | 0.0007 | 0.018 |
| 47.4333 | 1.4635 | 0.0174 | 0.002 | 0.0194 |
| 47.4667 | 1.4675 | 0.0305 | 0.0007 | 0.0312 |
| 47.5 | 1.4751 | 0.0305 | 0.002 | 0.0325 |
| 47.5333 | 1.482 | 0.0174 | 0.0007 | 0.018 |
| 47.5667 | 1.4849 | 0.0174 | 0.0033 | 0.0207 |
| 47.6 | 1.4895 | 0.0042 | 0.002 | 0.0062 |
| 47.6333 | 1.4951 | 0.0174 | 0 | 0.0174 |
| 47.6667 | 1.4994 | 0.0305 | 0.002 | 0.0325 |
| 47.7 | 1.5067 | 0.0174 | 9.0069 | 9.0243 |
| 47.7333 | 1.5162 | 0.0042 | 8.6835 | 8.6877 |
| 47.7667 | 1.5254 | 0.0305 | 8.3928 | 8.4234 |
| 47.8 | 1.534 | 0.0174 | 8.1903 | 8.2077 |
| 47.8333 | 1.5402 | 0.0174 | 8.051 | 8.0683 |
| 47.8667 | 1.5471 | 0.0042 | 7.9615 | 7.9657 |
| 47.9 | 1.5567 | 0.0042 | 7.8971 | 7.9013 |
| 47.9333 | 1.562 | 0.0042 | 7.8537 | 7.8579 |
| 47.9667 | 1.5692 | 0.0042 | 7.8366 | 7.8408 |
| 48 | 1.5758 | 0.0042 | 7.8195 | 7.8237 |
| 48.0333 | 1.5847 | 0.0042 | 7.8116 | 7.8158 |
| 48.0667 | 1.5853 | 0.0174 | 7.8037 | 7.8211 |
| 48.1 | 1.5945 | 0.0174 | 7.7985 | 7.8158 |
| 48.1333 | 1.5962 | 0.0174 | 7.7932 | 7.8106 |
| 48.1667 | 1.6061 | 0.0042 | 7.7998 | 7.804 |
| 48.2 | 1.6084 | 0.0174 | 7.8011 | 7.8185 |
| 48.2333 | 1.6126 | 0.0174 | 7.7972 | 7.8145 |
| 48.2667 | 1.6202 | 0.0174 | 7.8037 | 7.8211 |
| 48.3 | 1.6245 | 0.0305 | 7.8064 | 7.8369 |
| 48.3333 | 1.6291 | 0.0174 | 7.8077 | 7.825 |
| 48.3667 | 1.6337 | 0.0042 | 7.8143 | 7.8185 |
| 48.4 | 1.6347 | 0.0305 | 7.8169 | 7.8474 |
| 48.4333 | 1.6416 | 0.0174 | 7.8353 | 7.8527 |
| 48.4667 48.5 | 1.6459 1.6311 | 0.0042 0.0174 | 7.8314 7.8432 | 7.8356 7.8605 |
| | | | | |
| 48.5333 48.5667 | 1.6209 | 0.0042 | 7.8471 | 7.8513 |
| 48.5667 | 1.6087 1.6021 | 0.0174 0.0174 | 7.8563 7.8537 | 7.8737 7.8711 |
| 48.6333 | 1.5893 | 0.0174 | 7.8682 | 7.8855 |
| 48.6667 | | 0.0174 | | |
| | 1.583 1.5702 | 0.0042 | 7.8708 7.8761 | 7.875 7.8803 |
| 48.7 | 1.5/02 | 0.0042 | 7.8/61 | 7.8803 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 48.7333 | 1.5623 | 0.0174 | 7.88 | 7.8974 |
| 48.7667 | 1.5534 | 0.0305 | 7.8787 | 7.9092 |
| 48.8 | 1.5475 | 0.0174 | 7.8879 | 7.9053 |
| 48.8333 | 1.5343 | 0.0174 | 7.8826 | 7.9 |
| 48.8667 | 1.5267 | 0.0174 | 7.8971 | 7.9145 |
| 48.9 | 1.5205 | 0.0042 | 7.8945 | 7.8987 |
| 48.9333 | 1.5103 | 0.0042 | 7.901 | 7.9053 |
| 48.9667 | 1.5053 | 0.0174 | 7.8866 | 7.9039 |
| 49 | 1.4965 | 0.0174 | 7.8971 | 7.9145 |
| 49.0333 | 1.4869 | 0.0174 | 7.905 | 7.9223 |
| 49.0667 | 1.4816 | 0.0174 | 7.8971 | 7.9145 |
| 49.1 | 1.4751 | 0.0305 | 7.901 | 7.9316 |
| 49.1333 | 1.4658 | 0.0042 | 7.8958 | 7.9 |
| 49.1667 | 1.4596 | 0.0174 | 7.9024 | 7.9197 |
| 49.2 | 1.4527 | 0.0174 | 7.8997 | 7.9171 |
| 49.2333 | 1.4458 | 0.0174 | 7.9089 | 7.9263 |
| 49.2667 | 1.4365 | 0.0042 | 7.8971 | 7.9013 |
| 49.3 | 1.4319 | 0.0042 | 7.8971 | 7.9013 |
| 49.3333 | 1.43 | 0.0174 | 7.8945 | 7.9118 |
| 49.3667 | 1.4319 | 0.0174 | 7.8997 | 7.9171 |
| 49.4 | 1.4379 | 0.0305 | 7.9037 | 7.9342 |
| 49.4333 | 1.4405 | 0.0042 | 7.9063 | 7.9105 |
| 49.4667 | 1.4491 | 0.0174 | 7.9089 | 7.9263 |
| 49.5 | 1.4573 | 0.0174 | 7.9116 | 7.9289 |
| 49.5333 | 1.4632 | 0.0042 | 7.9168 | 7.921 |
| 49.5667 | 1.4737 | 0.0174 | 7.9089 | 7.9263 |
| 49.6 | 1.4833 | 0.0174 | 7.9129 | 7.9302 |
| 49.6333 | 1.4922 | 0.0042 | 7.9234 | 7.9276 |
| 49.6667 | 1.4991 | 0.0174 | 7.9287 | 7.946 |
| 49.7 | 1.508 | 0.0174 | 7.9392 | 7.9565 |
| 49.7333 | 1.5172 | 0.0305 | 7.951 | 7.9815 |
| 49.7667 | 1.5241 | 0.0174 | 7.9484 | 7.9657 |
| 49.8 | 1.5307 | 0.0174 | 7.9589 | 7.9763 |
| 49.8333 | 1.5399 | 0.0305 | 7.976 | 8.0065 |
| 49.8667 | 1.5439 | 0.0174 | 7.9839 | 8.0012 |
| 49.9 | 1.5494 | 0.0305 | 8.001 | 8.0315 |
| 49.9333 | 1.5583 | 0.0174 | 8.0089 | 8.0262 |
| 49.9667 | 1.5662 | 0.0305 | 8.0141 | 8.0446 |
| 50 | 1.5761 | 0.0174 | 8.022 | 8.0394 |
| 50.0333 | 1.5827 | 0.0042 | 8.0339 | 8.0381 |
| 50.0667 | 1.5903 | 0.0305 | 8.0496 | 8.0801 |
| 50.1 | 1.6038 | 0.0174 | 8.0654 | 8.0828 |
| 50.1333 | 1.611 | 0.0042 | 8.0707 | 8.0749 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|---------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 50.1667 | 1.6248 | 0.0437 | 8.0917 | 8.1354 |
| 50.2 | 1.6337 | 0.0305 | 8.097 | 8.1275 |
| 50.2333 | 1.6459 | 0.0174 | 8.1233 | 8.1406 |
| 50.2667 | 1.6505 | 0.0174 | 8.1299 | 8.1472 |
| 50.2 | 1.6528 | 0.0174 | 8.1548 | 8.1722 |
| 50.3333 | 1.6466 | 0.0174 | 8.1706 | 8.188 |
| 50.3667 | 1.6423 | 0.0174 | 8.1877 | 8.2051 |
| 50.4 | 1.634 | 0.0174 | 8.1864 | 8.2038 |
| 50.4333 | 1.6281 | 0.0174 | 8.2035 | 8.2208 |
| 50.4667 | 1.6278 | 0.0174 | 8.2153 | 8.2327 |
| 50.5 | 1.6271 | 0.0174 | 8.2337 | 8.2511 |
| 50.5333 | 1.6261 | 0.0305 | 8.239 | 8.2695 |
| 50.5667 | 1.6284 | 0.0174 | 8.26 | 8.2774 |
| 50.6 | 1.6327 | 0.0174 | 8.2627 | 8.2627 |
| 50.6333 | 1.6354 | 0.0042 | 8.2732 | 8.2774 |
| 50.6667 | 1.6357 | 0.0174 | 8.2916 | 8.309 |
| 50.7 | 1.6383 | 0.0042 | 8.2916 | 8.2958 |
| 50.7333 | 1.6387 | 0.0174 | 8.3166 | 8.3339 |
| 50.7667 | 1.6387 | 0.0042 | 8.3232 | 8.3274 |
| 50.8 | 1.6406 | 0.0174 | 8.3376 | 8.355 |
| 50.8333 | 1.6429 | 0.0174 | 8.3442 | 8.3616 |
| 50.8667 | 1.6449 | 0.0042 | 8.3573 | 8.3616 |
| 50.9 | 1.6498 | 0.0174 | 8.3718 | 8.3892 |
| 50.9333 | 1.6492 | 0.0174 | 8.3758 | 8.3931 |
| 50.9667 | 1.6479 | 0.0042 | 8.385 | 8.3892 |
| 51 | 1.6449 | 0.0174 | 8.4021 | 8.4194 |
| 51.0333 | 1.6472 | 0.0305 | 8.4152 | 8.4457 |
| 51.0667 | 1.6429 | 0.0174 | 8.4284 | 8.4457 |
| 51.1 | 1.639 | 0.0174 | 8,4297 | 8.447 |
| 51.1333 | 1.638 | 0.0174 | 8.4415 | 8.4589 |
| 51.1667 | 1.6387 | 0.0174 | 8.4494 | 8.4667 |
| 51.2 | 1.6291 | 0.0305 | 8.456 | 8.4865 |
| 51.2333 | 1.6304 | 0.0174 | 8.4678 | 8.4852 |
| 51.2667 | 1.6271 | 0.0174 | 8.4717 | 8.4891 |
| 51.3 | 1.6258 | 0 | 8.481 | 8.481 |
| 51.3333 | 1.6275 | 0.0174 | 8.4967 | 8.5141 |
| 51.3667 | 1.6245 | 0.0042 | 8.5125 | 8.5167 |
| 51.4 | 1.6176 | 0.0042 | 8.5125 | 8.5167 |
| 51.4333 | 1.6173 | 0.0174 | 8.5099 | 8.5272 |
| 51.4667 | 1.6196 | 0.0174 | 8.5151 | 8.5325 |
| 51.5 | 1.6173 | 0.0042 | 8.5296 | 8.5338 |
| 51.5333 | 1.6202 | 0.0174 | 8.5309 | 8.5483 |
| 51.5667 | 1.6199 | 0.0174 | 8.5388 | 8.5562 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 51.6 | 1.6169 | 0 | 8.5546 | 8.5546 |
| 51.6333 | 1.6196 | 0.0305 | 8.5598 | 8.5904 |
| 51.6667 | 1.6196 | 0.0174 | 8.5691 | 8.5864 |
| 51.7 | 1.6182 | 0.0042 | 8.5664 | 8.5706 |
| 51.7333 | 1.6229 | 0.0305 | 8.573 | 8.6035 |
| 51.7667 | 1.6245 | 0.0305 | 8.5914 | 8.6219 |
| 51.8 | 1.6212 | 0.0042 | 8.598 | 8.6022 |
| 51.8333 | 1.6252 | 0.0042 | 8.6124 | 8.6167 |
| 51.8667 | 1.6245 | 0.0042 | 8.5967 | 8.6009 |
| 51.9 | 1.6314 | 0.0042 | 8.6072 | 8.6114 |
| 51.9333 | 1.6301 | 0.0042 | 8.6322 | 8.6364 |
| 51.9667 | 1.6324 | 0.0305 | 8.6282 | 8.6587 |
| 52 | 1.6317 | 0.0174 | 8.6401 | 8.6574 |
| 52.0333 | 1.6308 | 0.0174 | 8.6453 | 8.6627 |
| 52.0667 | 1.6304 | 0.0042 | 8.6506 | 8.6548 |
| 52.1 | 1.6291 | 0.0174 | 8.6598 | 8.6771 |
| 52.1333 | 1.6284 | 0.0174 | 8.6677 | 8.685 |
| 52.1667 | 1.6294 | 0.0305 | 8.6703 | 8.7008 |
| 52.2 | 1.6255 | 0.0174 | 8.6769 | 8.6942 |
| 52.2333 | 1.6271 | 0.0042 | 8.6874 | 8.6916 |
| 52.2667 | 1.6222 | 0.0174 | 8.6979 | 8.7153 |
| 52.3 | 1.6229 | 0.0174 | 8.6953 | 8.7126 |
| 52.3333 | 1.6248 | 0.0305 | 8.7124 | 8.7429 |
| 52.3667 | 1.6265 | 0.0042 | 8.7098 | 8.714 |
| 52.4 | 1.6209 | 0.0174 | 8.715 | 8.7324 |
| 52.4333 | 1.6222 | 0.0042 | 8.7269 | 8.7311 |
| 52.4667 | 1.6229 | 0.0042 | 8.7282 | 8.7324 |
| 52.5 | 1.6229 | 0.0174 | 8.7334 | 8.7508 |
| 52.5333 | 1.6196 | 0.0174 | 8.74 | 8.7574 |
| 52.5667 | 1.6229 | 0.0174 | 8.7466 | 8.7639 |
| 52.6 | 1.6222 | 0.0437 | 8.7571 | 8.8008 |
| 52.6333 | 1.6275 | 0.0174 | 8.7545 | 8.7718 |
| 52.6667 | 1.6275 | 0.0174 | 8.7676 | 8.785 |
| 52.7 | 1.6284 | 0.0305 | 8.7729 | 8.8034 |
| 52.7333 | 1.6298 | 0.0174 | 8.7834 | 8.8008 |
| 52.7667 | 1.6298 | 0.0042 | 8.7755 | 8.7797 |
| 52.8 | 1.6337 | 0.0042 | 8.7742 | 8.7784 |
| 52.8333 | 1.6327 | 0.0174 | 8.7952 | 8.8126 |
| 52.8667 | 1.6337 | 0.0042 | 8.7965 | 8.8008 |
| 52.9 | 1.6347 | 0.0174 | 8.8097 | 8.8271 |
| 52.9333 | 1.6344 | 0.0174 | 8.8057 | 8.8231 |
| 52.9667 | 1.6337 | 0.0174 | 8.8176 | 8.8349 |
| 53 | 1.6387 | 0.0174 | 8.8202 | 8.8376 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 53.0333 | 1.6387 | 0.0305 | 8.8268 | 8.8573 |
| 53.0667 | 1.637 | 0.0305 | 8.8334 | 8.8639 |
| 53.1 | 1.6387 | 0 | 8.8307 | 8.8307 |
| 53.1333 | 1.6413 | 0.0042 | 8.8465 | 8.8507 |
| 53.1667 | 1.6396 | 0.0042 | 8.8452 | 8.8494 |
| 53.2 | 1.6416 | 0.0174 | 8.8505 | 8.8678 |
| 53.2333 | 1.639 | 0.0174 | 8.8649 | 8.8823 |
| 53.2667 | 1.6426 | 0.0174 | 8.8583 | 8.8757 |
| 53.3 | 1.6433 | 0.0042 | 8.8689 | 8.8731 |
| 53.3333 | 1.639 | 0.0174 | 8.8833 | 8.9007 |
| 53.3667 | 1.6436 | 0.0042 | 8.8899 | 8.8941 |
| 53.4 | 1.64 | 0.0174 | 8.8965 | 8.9138 |
| 53.4333 | 1.6452 | 0.0174 | 8.8952 | 8.9125 |
| 53.4667 | 1.6423 | 0.0174 | 8.8991 | 8.9165 |
| 53.5 | 1.6433 | 0.0042 | 8.9057 | 8.9099 |
| 53.5333 | 1.6442 | 0.0305 | 8.9162 | 8.9467 |
| 53.5667 | 1.6436 | 0.0174 | 8.9096 | 8.927 |
| 53.6 | 1.6433 | 0.0042 | 8.9241 | 8.9283 |
| 53.6333 | 1.6469 | 0.0174 | 8.9307 | 8.948 |
| 53.6667 | 1.634 | 0.0042 | 8.9346 | 8.9388 |
| 53.7 | 1.5722 | 0.0174 | 8.932 | 8.9493 |
| 53.7333 | 1.5096 | 0.0174 | 8.9372 | 8.9546 |
| 53.7667 | 1.455 | 0.0042 | 8.9267 | 8.9309 |
| 53.8 | 1.3974 | 0.0174 | 8.9136 | 8.9309 |
| 53.8333 | 1.3454 | 0.0174 | 8.8978 | 8.9152 |
| 53.8667 | 1.2983 | 0.0042 | 8.765 | 8.7692 |
| 53.9 | 1.2851 | 0.0042 | 7.7262 | 7.7304 |
| 53.9333 | 1.271 | 0.0042 | 6.7215 | 6.7257 |
| 53.9667 | 1.2509 | 0.0042 | 5.8497 | 5.8539 |
| 54 | 1.2318 | 0.0305 | 5.1054 | 5.1359 |
| 54.0333 | 1.2134 | 0 | 4.4256 | 4.4256 |
| 54.0667 | 1.189 | 0.0174 | 3.8312 | 3.8486 |
| 54.1 | 1.1627 | 0.0305 | 3.3065 | 3.337 |
| 54.1333 | 1.135 | 0.0174 | 2.8318 | 2.8492 |
| 54.1667 | 1.111 | 0.0174 | 2.4058 | 2.4231 |
| 54.2 | 1.0791 | 0.0042 | 2.0415 | 2.0457 |
| 54.2333 | 1.0498 | 0.0042 | 1.7259 | 1.7301 |
| 54.2667 | 1.0234 | 0.0174 | 1.4682 | 1.4856 |
| 54.3 | 0.9922 | 0.0042 | 1.2328 | 1.237 |
| 54.3333 | 0.9652 | 0.0174 | 1.0382 | 1.0556 |
| 54.3667 | 0.9316 | 0.0042 | 0.8896 | 0.8938 |
| 54.4 | 0.9013 | 0.0042 | 0.7686 | 0.7728 |
| 54.4333 | 0.8737 | 0.0174 | 0.6713 | 0.6887 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|--------------------|------------------|-----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 54.4667 | 0.8401 | 0.0305 | 0.5937 | 0.6242 |
| 54.5 | 0.8147 | 0.0174 | 0.5267 | 0.544 |
| 54.5333 | 0.7838 | 0.0042 | 0.4767 | 0.4809 |
| 54.5667 | 0.7575 | 0.0174 | 0.4346 | 0.452 |
| 54.6 | 0.7298 | 0.0305 | 0.4057 | 0.4362 |
| 54.6333 | 0.7022 | 0.0305 | 0.3741 | 0.4046 |
| 54.6667 | 0.6781 | 0.0042 | 0.3531 | 0.3573 |
| 54.7 | 0.6531 | 0.0042 | 0.3281 | 0.3323 |
| 54.7333 | 0.6298 | 0.0174 | 0.3084 | 0.3257 |
| 54.7667 | 0.6074 | 0.0305 | 0.002 | 0.0325 |
| 54.8 | 0.5824 | 0.0174 | 0.0007 | 0.018 |
| 54.8333 | 0.5616 | 0.0042 | 0.0007 | 0.0049 |
| 54.8667 | 0.5392 | 0.0437 | 0.002 | 0.0457 |
| 54.9 | 0.5175 | 0.0174 | 0.0007 | 0.018 |
| 54.9333 | 0.4994 | 0.0174 | 0.0033 | 0.0207 |
| 54.9667 55 | 0.4806 0.4615 | 0.0042 | 0.0033 | 0.0042 0.0075 |
| | 0.4431 | 0.0042 | | |
| 55.0333 | | | 0 | 0.0174 |
| 55.0667 55.1 | -0.0098 | 0.0174 0.0174 | 0.002 0.0007 | 0.0194 |
| | -0.0072 | | | 0.018 |
| 55.1333 55.1667 | -0.0088 -0.0085 | 0.0042 0.0042 | 0.002 | 0.0062 |
| 55.2 | -0.0085 | 0.0042 | 0.002 | 0.0062 |
| 55.2333 | -0.0088 | 0.0174 | 0.0007 | 0.0007 |
| 55.2667 | -0.0088 | 0.0174 | 0.0007 | 0.018 |
| 55.3 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 55.3333 | -0.0065 | 0.0174 | 0.0007 | 0.0134 |
| 55.3667 | -0.0049 | 0.0174 | 0.0007 | 0.018 |
| 55.4 | -0.0092 | 0.0174 | 0.0007 | 0.0194 |
| 55.4333 | -0.0101 | 0.0042 | 0.002 | 0.0062 |
| 55.4667 | -0.0078 | 0.0042 | 0.002 | 0.0062 |
| 55.5 | -0.0049 | 0.0305 | 0.0033 | 0.0338 |
| 55.5333 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 55.5667 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 55.6 | -0.0059 | 0.0305 | 0.002 | 0.0325 |
| 55.6333 | -0.0022 | 0.0305 | 0.0007 | 0.0312 |
| 55.6667 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 55.7 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 55.7333 | -0.0052 | 0.0305 | 0 | 0.0305 |
| 55.7667 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 55.8 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 55.8333 | -0.0036 | 0 | 0.002 | 0.002 |
| 55.8667 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| | | | | |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 55.9 | -0.0049 | 0.0042 | 0.0007 | 0.0049 |
| 55.9333 | -0.0059 | 0.0042 | 0.002 | 0.0062 |
| 55.9667 | -0.0059 | 0.0042 | 0.0033 | 0.0075 |
| 56 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 56.0333 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 56.0667 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 56.1 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 56.1333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 56.1667 | -0.0072 | 0.0042 | 0.002 | 0.0062 |
| 56.2 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 56.2333 | -0.0022 | 0.0174 | 0.002 | 0.0194 |
| 56.2667 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 56.3 | -0.0036 | 0.0174 | 0.0033 | 0.0207 |
| 56.3333 | -0.0049 | 0.0305 | 0.0007 | 0.0312 |
| 56.3667 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 56.4 | -0.0062 | 0.0042 | 0.002 | 0.0062 |
| 56.4333 | -0.0049 | 0.0042 | 0.002 | 0.0062 |
| 56.4667 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 56.5 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 56.5333 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 56.5667 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 56.6 | -0.0049 | 0.0042 | 0.002 | 0.0062 |
| 56.6333 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 56.6667 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 56.7 | -0.0046 | 0.0305 | 0.002 | 0.0325 |
| 56.7333 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 56.7667 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 56.8 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 56.8333 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 56.8667 | -0.0072 | 0.0174 | 0.0033 | 0.0207 |
| 56.9 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 56.9333 | -0.0088 | 0.0042 | 0.002 | 0.0062 |
| 56.9667 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 57 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 57.0333 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 57.0667 | -0.0055 | 0.0305 | 0.0007 | 0.0312 |
| 57.1 | -0.0036 | 0 | 0.002 | 0.002 |
| 57.1333 | -0.0016 | 0.0174 | 0.0007 | 0.018 |
| 57.1667 | -0.0029 | 0.0042 | 0.002 | 0.0062 |
| 57.2 | -0.0069 | 0.0042 | 0.0033 | 0.0075 |
| 57.2333 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 57.2667 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 57.3 | -0.0078 | 0.0305 | 0.0033 | 0.0338 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|---------|------------------|------------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 57.3333 | -0.0032 | 0.0042 | 0.0007 | 0.0049 |
| 57.3667 | -0.0062 | 0.0042 | 0.0033 | 0.0075 |
| 57.4 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 57.4333 | -0.0026 | 0.0042 | 0.002 | 0.0062 |
| 57.4667 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 57.5 | -0.0055 | 0.0042 | 0.0007 | 0.0049 |
| 57.5333 | -0.0078 | 0.0174 | 0.0007 | 0.018 |
| 57.5667 | -0.0062 | 0 | 0 | 0 |
| 57.6 | -0.0065 | 0.0174 | 0.0007 | 0.018 |
| 57.6333 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 57.6667 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 57.7 | -0.0022 | 0.0305 | 0.0007 | 0.0312 |
| 57.7333 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 57.7667 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 57.8 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 57.8333 | -0.0075 | 0.0042 | 0.002 | 0.0062 |
| 57.8667 | -0.0092 | 0.0042 | 0.002 | 0.0062 |
| 57.9 | -0.0082 | 0.0042 | 0.002 | 0.0062 |
| 57.9333 | 0.0129 | 0.0042 | 0.002 | 0.0062 |
| 57.9667 | 0.0639 | 0.0042 | 0.002 | 0.0062 |
| 58 | 0.11 | 0.0174 | 0.002 | 0.0194 |
| 58.0333 | 0.1597 | 0.0174 | 0.0033 | 0.0207 |
| 58.0667 | 0.2032 | 0.0174 | 0.002 | 0.0194 |
| 58.1 | 0.2473 | 0.0174 | 0.0007 | 0.018 |
| 58.1333 | 0.2983 | 0.0174 | 0.0007 | 0.018 |
| 58.1667 | 0.3542 | 0.0305 | 0.816 | 0.8465 |
| 58.2 | 0.4076 | 0.0305 | 0.912 | 0.9425 |
| 58.2333 | 0.4632 | 0.0174 | 1.0066 | 1.024 |
| 58.2667 | 0.5162 | 0.0174 | 1.0961 | 1.1134 |
| 58.3 | 0.5698 | 0.0042 | 1.2013 1.3012 | 1.2055 1.3054 |
| 58.3333 58.3667 | 0.6238 | 0.0042 0.0174 | 1.4064 | 1.4237 |
| 58.4 | 0.6788 | 0.0174 | 1.5129 | 1.5303 |
| 58.4333 | 0.7845 | 0.0174 | 1.626 | 1.6433 |
| 58.4667 | 0.7843 | 0.0174 | 1.7338 | 1.7643 |
| 58.5 | 0.8855 | 0.0305 | 1.8246 | 1.8551 |
| 58.5333 | 0.8833 | 0.0305 | 1.9205 | 1.9511 |
| 58.5667 | 0.9293 | 0.0305 | 2.0231 | 2.0536 |
| 58.6 | 1.0271 | 0.0303 | 2.1323 | 2.1496 |
| 58.6333 | 1.0715 | 0.0174 | 2.2309 | 2.2482 |
| 58.6667 | 1.1199 | 0.0174 | 2.3308 | 2.3482 |
| 58.7 | 1.1199 | 0.0174 | 2.4347 | 2.4389 |
| 58.7333 | 1.2134 | 0.0042 | 2.5452 | 2.5494 |
| 30.7333 | 1.2154 | 0.0042 | 2.5432 | 2.5454 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 58.7667 | 1.2588 | 0 | 2.6517 | 2.6517 |
| 58.8 | 1.2999 | 0.0174 | 2.7529 | 2.7703 |
| 58.8333 | 1.3424 | 0.0174 | 2.8608 | 2.8781 |
| 58.8667 | 1.3812 | 0.0174 | 2.9646 | 2.982 |
| 58.9 | 1.4227 | 0.0174 | 3.0738 | 3.0911 |
| 58.9333 | 1.4612 | 0.0174 | 3.1895 | 3.2069 |
| 58.9667 | 1.5004 | 0.0305 | 3.2947 | 3.3252 |
| 59 | 1.5429 | 0.0437 | 3.3999 | 3.4435 |
| 59.0333 | 1.5801 | 0.0042 | 3.5103 | 3.5146 |
| 59.0667 | 1.6097 | 0.0305 | 3.6169 | 3.6474 |
| 59.1 | 1.6354 | 0.0174 | 3.7181 | 3.7355 |
| 59.1333 | 1.638 | 0.0042 | 3.8233 | 3.8275 |
| 59.1667 | 1.6278 | 0.0174 | 3.918 | 3.9353 |
| 59.2 | 1.613 | 0.0174 | 4.0048 | 4.0221 |
| 59.2333 | 1.6064 | 0.0174 | 4.0863 | 4.1037 |
| 59.2667 | 1.5968 | 0.0174 | 4.1731 | 4.1905 |
| 59.3 | 1.5922 | 0.0174 | 4.2612 | 4.2786 |
| 59.3333 | 1.5965 | 0.0042 | 4.3388 | 4.343 |
| 59.3667 | 1.6064 | 0.0174 | 4.4164 | 4.4337 |
| 59.4 | 1.6163 | 0.0042 | 4.5005 | 4.5047 |
| 59.4333 | 1.6202 | 0.0174 | 4.5702 | 4.5876 |
| 59.4667 | 1.6294 | 0.0174 | 4.6465 | 4.6638 |
| 59.5 | 1.6314 | 0.0174 | 4.7228 | 4.7401 |
| 59.5333 | 1.6357 | 0.0174 | 4.7964 | 4.8137 |
| 59.5667 | 1.641 | 0.0305 | 4.8674 | 4.8979 |
| 59.6 | 1.6479 | 0.0042 | 4.9384 | 4.9426 |
| 59.6333 | 1.6525 | 0.0174 | 5.0147 | 5.032 |
| 59.6667 | 1.6581 | 0.0174 | 5.0778 | 5.0952 |
| 59.7 | 1.6633 | 0.0174 | 5.1514 | 5.1688 |
| 59.7333 | 1.6614 | 0.0437 | 5.2251 | 5.2687 |
| 59.7667 | 1.662 | 0.0174 | 5.2803 | 5.2977 |
| 59.8 | 1.664 | 0.0174 | 5.3566 | 5.3739 |
| 59.8333 | 1.6663 | 0.0174 | 5.4079 | 5.4252 |
| 59.8667 | 1.6683 | 0.0305 | 5.4723 | 5.5028 |
| 59.9 | 1.6663 | 0.0305 | 5.5223 | 5.5528 |
| 59.9333 | 1.6663 | 0.0174 | 5.5841 | 5.6014 |
| 59.9667 | 1.6643 | 0.0174 | 5.6419 | 5.6593 |
| 60 | 1.6637 | 0.0042 | 5.6879 | 5.6922 |
| 60.0333 | 1.6627 | 0.0174 | 5.7497 | 5.7671 |
| 60.0667 | 1.6581 | 0.0174 | 5.7997 | 5.8171 |
| 60.1 | 1.6597 | 0.0042 | 5.8431 | 5.8473 |
| 60.1333 | 1.6591 | 0.0174 | 5.8983 | 5.9157 |
| 60.1667 | 1.6604 | 0.0174 | 5.9483 | 5.9657 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 60.2 | 1.6604 | 0.0174 | 5.993 | 6.0104 |
| 60.2333 | 1.6607 | 0.0042 | 6.039 | 6.0433 |
| 60.2667 | 1.6607 | 0.0042 | 6.0745 | 6.0788 |
| 60.3 | 1.661 | 0 | 6.1271 | 6.1271 |
| 60.3333 | 1.6597 | 0.0174 | 6.1679 | 6.1853 |
| 60.3667 | 1.6587 | 0.0305 | 6.2192 | 6.2497 |
| 60.4 | 1.6597 | 0.0437 | 6.2678 | 6.3115 |
| 60.4333 | 1.6597 | 0.0042 | 6.2994 | 6.3036 |
| 60.4667 | 1.661 | 0.0174 | 6.3375 | 6.3549 |
| 60.5 | 1.6521 | 0.0174 | 6.3783 | 6.3957 |
| 60.5333 | 1.6387 | 0.0042 | 6.4217 | 6.4259 |
| 60.5667 | 1.6268 | 0.0174 | 6.4533 | 6.4706 |
| 60.6 | 1.6143 | 0.0305 | 6.4993 | 6.5298 |
| 60.6333 | 1.6024 | 0.0174 | 6.5308 | 6.5482 |
| 60.6667 | 1.5886 | 0.0174 | 6.5703 | 6.5876 |
| 60.7 | 1.5804 | 0.0305 | 6.5992 | 6.6297 |
| 60.7333 | 1.5712 | 0.0042 | 6.6347 | 6.6389 |
| 60.7667 | 1.5606 | 0.0174 | 6.661 | 6.6784 |
| 60.8 | 1.5541 | 0.0042 | 6.69 | 6.6942 |
| 60.8333 | 1.5445 | 0.0042 | 6.7189 | 6.7231 |
| 60.8667 | 1.5356 | 0.0305 | 6.7478 | 6.7783 |
| 60.9 | 1.5323 | 0.0174 | 6.7794 | 6.7967 |
| 60.9333 | 1.5231 | 0.0305 | 6.807 | 6.8375 |
| 60.9667 | 1.5356 | 0.0042 | 6.8307 | 6.8349 |
| 61 | 1.5429 | 0.0042 | 6.8622 | 6.8664 |
| 61.0333 | 1.5573 | 0.0174 | 6.8872 | 6.9046 |
| 61.0667 | 1.5656 | 0.0174 | 6.9135 | 6.9309 |
| 61.1 | 1.5705 | 0.0174 | 6.9451 | 6.9624 |
| 61.1333 | 1.5834 | 0.0174 | 6.9714 | 6.9887 |
| 61.1667 | 1.5919 | 0.0042 | 6.9977 | 7.0019 |
| 61.2 | 1.5985 | 0.0042 | 7.0266 | 7.0308 |
| 61.2333 | 1.6087 | 0.0042 | 7.0529 | 7.0571 |
| 61.2667 | 1.6123 | 0.0305 | 7.0871 | 7.1176 |
| 61.3 | 1.6196 | 0.0174 | 7.1239 | 7.1413 |
| 61.3333 | 1.6261 | 0.0042 | 7.1397 | 7.1439 |
| 61.3667 | 1.6337 | 0.0305 | 7.1739 | 7.2044 |
| 61.4 | 1.6413 | 0.0042 | 7.2107 | 7.2149 |
| 61.4333 | 1.6475 | 0.0305 | 7.2317 | 7.2622 |
| 61.4667 | 1.6525 | 0.0174 | 7.2672 | 7.2846 |
| 61.5 | 1.6531 | 0.0174 | 7.2948 | 7.3122 |
| 61.5333 | 1.6541 | 0.0042 | 7.3133 | 7.3175 |
| 61.5667 | 1.6535 | 0.0174 | 7.3422 | 7.3595 |
| 61.6 | 1.6538 | 0.0174 | 7.3777 | 7.395 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 61.6333 | 1.6568 | 0.0174 | 7.3987 | 7.4161 |
| 61.6667 | 1.6571 | 0.0174 | 7.4329 | 7.4503 |
| 61.7 | 1.66 | 0.0174 | 7.4645 | 7.4818 |
| 61.7333 | 1.6591 | 0.0174 | 7.4895 | 7.5068 |
| 61.7667 | 1.664 | 0.0174 | 7.5158 | 7.5331 |
| 61.8 | 1.663 | 0.0174 | 7.5447 | 7.562 |
| 61.8333 | 1.663 | 0.0174 | 7.5499 | 7.5673 |
| 61.8667 | 1.6624 | 0.0042 | 7.5841 | 7.5883 |
| 61.9 | 1.6581 | 0.0174 | 7.6039 | 7.6212 |
| 61.9333 | 1.6548 | 0.0174 | 7.6288 | 7.6462 |
| 61.9667 | 1.6531 | 0.0042 | 7.6459 | 7.6501 |
| 62 | 1.6495 | 0.0042 | 7.6749 | 7.6791 |
| 62.0333 | 1.6466 | 0.0174 | 7.7025 | 7.7198 |
| 62.0667 | 1.6423 | 0.0305 | 7.7169 | 7.7475 |
| 62.1 | 1.6393 | 0.0174 | 7.7459 | 7.7632 |
| 62.1333 | 1.6334 | 0.0174 | 7.763 | 7.7803 |
| 62.1667 | 1.6321 | 0.0174 | 7.7827 | 7.8001 |
| 62.2 | 1.6284 | 0.0174 | 7.8011 | 7.8185 |
| 62.2333 | 1.6242 | 0.0174 | 7.8235 | 7.8408 |
| 62.2667 | 1.6235 | 0.0042 | 7.834 | 7.8382 |
| 62.3 | 1.6215 | 0.0042 | 7.8524 | 7.8566 |
| 62.3333 | 1.6146 | 0.0174 | 7.8787 | 7.896 |
| 62.3667 | 1.6163 | 0.0042 | 7.8879 | 7.8921 |
| 62.4 | 1.6126 | 0.0042 | 7.905 | 7.9092 |
| 62.4333 | 1.6097 | 0.0042 | 7.9287 | 7.9329 |
| 62.4667 | 1.6064 | 0.0174 | 7.9431 | 7.9605 |
| 62.5 | 1.6047 | 0.0305 | 7.9615 | 7.992 |
| 62.5333 | 1.6041 | 0.0174 | 7.9786 | 7.996 |
| 62.5667 | 1.6031 | 0.0042 | 7.9984 | 8.0026 |
| 62.6 | 1.6024 | 0.0042 | 8.0062 | 8.0105 |
| 62.6333 | 1.5972 | 0.0174 | 8.0286 | 8.046 |
| 62.6667 | 1.6028 | 0.0174 | 8.0339 | 8.0512 |
| 62.7 | 1.5965 | 0.0042 | 8.0549 | 8.0591 |
| 62.7333 | 1.5982 | 0.0305 | 8.0746 | 8.1051 |
| 62.7667 | 1.5992 | 0.0174 | 8.0812 | 8.0986 |
| 62.8 | 1.6011 | 0.0174 | 8.1049 | 8.1222 |
| 62.8333 | 1.6031 | 0.0042 | 8.1193 | 8.1235 |
| 62.8667 | 1.6067 | 0.0042 | 8.1272 | 8.1314 |
| 62.9 | 1.608 | 0.0305 | 8.1338 | 8.1643 |
| 62.9333 | 1.6103 | 0.0305 | 8.1548 | 8.1853 |
| 62.9667 | 1.612 | 0.0174 | 8.1746 | 8.1919 |
| 63 | 1.613 | 0.0174 | 8.1798 | 8.1972 |
| 63.0333 | 1.6159 | 0.0042 | 8.2022 | 8.2064 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 63.0667 | 1.6196 | 0.0174 | 8.2219 | 8.2393 |
| 63.1 | 1.6202 | 0.0174 | 8.2285 | 8.2458 |
| 63.1333 | 1.6219 | 0.0042 | 8.2495 | 8.2537 |
| 63.1667 | 1.6229 | 0.0042 | 8.2587 | 8.2629 |
| 63.2 | 1.6242 | 0.0174 | 8.2771 | 8.2945 |
| 63.2333 | 1.6235 | 0.0174 | 8.2863 | 8.3037 |
| 63.2667 | 1.6275 | 0.0305 | 8.2942 | 8.3247 |
| 63.3 | 1.6281 | 0.0042 | 8.3205 | 8.3247 |
| 63.3333 | 1.6275 | 0 | 8.3389 | 8.3389 |
| 63.3667 | 1.6275 | 0.0042 | 8.3416 | 8.3458 |
| 63.4 | 1.6314 | 0.0174 | 8.3587 | 8.376 |
| 63.4333 | 1.6317 | 0.0042 | 8.381 | 8.3852 |
| 63.4667 | 1.6331 | 0.0174 | 8.3863 | 8.4036 |
| 63.5 | 1.634 | 0.0042 | 8.4007 | 8.4049 |
| 63.5333 | 1.6357 | 0.0174 | 8.4231 | 8.4404 |
| 63.5667 | 1.6363 | 0.0174 | 8.4336 | 8.451 |
| 63.6 | 1.6334 | 0.0174 | 8.4547 | 8.472 |
| 63.6333 | 1.6377 | 0.0042 | 8.4612 | 8.4654 |
| 63.6667 | 1.6363 | 0.0174 | 8.4757 | 8.493 |
| 63.7 | 1.6393 | 0.0174 | 8.4862 | 8.5036 |
| 63.7333 | 1.6377 | 0.0174 | 8.502 | 8.5193 |
| 63.7667 | 1.6396 | 0.0174 | 8.5099 | 8.5272 |
| 63.8 | 1.6387 | 0.0042 | 8.5257 | 8.5299 |
| 63.8333 | 1.6387 | 0.0174 | 8.5428 | 8.5601 |
| 63.8667 | 1.6429 | 0.0305 | 8.5467 | 8.5772 |
| 63.9 | 1.6423 | 0.0042 | 8.5612 | 8.5654 |
| 63.9333 | 1.6429 | 0.0042 | 8.5717 | 8.5759 |
| 63.9667 | 1.6446 | 0.0174 | 8.5888 | 8.6061 |
| 64 | 1.6393 | 0.0305 | 8.5888 | 8.6193 |
| 64.0333 | 1.6403 | 0.0174 | 8.6019 | 8.6193 |
| 64.0667 | 1.6413 | 0.0174 | 8.6177 | 8.6351 |
| 64.1 | 1.64 | 0.0174 | 8.6295 | 8.6469 |
| 64.1333 | 1.6433 | 0.0174 | 8.6361 | 8.6535 |
| 64.1667 | 1.6433 | 0.0174 | 8.6453 | 8.6627 |
| 64.2 | 1.6442 | 0.0305 | 8.6506 | 8.6811 |
| 64.2333 | 1.6442 | 0.0174 | 8.669 | 8.6863 |
| 64.2667 | 1.641 | 0 | 8.6887 | 8.6887 |
| 64.3 | 1.6406 | 0.0305 | 8.6927 | 8.7232 |
| 64.3333 | 1.6436 | 0.0174 | 8.6966 | 8.714 |
| 64.3667 | 1.6433 | 0.0042 | 8.7098 | 8.714 |
| 64.4 | 1.639 | 0.0042 | 8.7176 | 8.7219 |
| 64.4333 | 1.6439 | 0.0174 | 8.7387 | 8.756 |
| 64.4667 | 1.6426 | 0.0042 | 8.7518 | 8.756 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|---------|------------------|------------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 64.5 | 1.6492 | 0.0174 | 8.7597 | 8.7771 |
| 64.5333 | 1.6778 | 0.0042 | 8.7716 | 8.7758 |
| 64.5667 | 1.7101 | 0.0174 | 8.7913 | 8.8086 |
| 64.6 | 1.7427 | 0.0042 | 8.8097 | 8.8139 |
| 64.6333 | 1.7779 | 0.0042 | 8.8294 | 8.8336 |
| 64.6667 | 1.8098 | 0.0042 | 8.857 | 8.8612 |
| 64.7 | 1.8424 | 0.0174 | 8.8715 | 8.8889 |
| 64.7333 | 1.8714 | 0.0042 | 8.8978 | 8.902 |
| 64.7667 | 1.903 | 0.0042 | 8.9215 | 8.9257 |
| 64.8 | 1.9342 | 0.0174 | 8.9491 | 8.9664 |
| 64.8333 | 1.9612 | 0.0305 | 8.9741 | 9.0046 |
| 64.8667 | 1.982 | 0.0305 | 9.0043 | 9.0348 |
| 64.9 | 1.9932 | 0.0042 | 9.0332 | 9.0374 |
| 64.9333 | 1.9961 | 0.0042 | 9.0635 | 9.0677 |
| 64.9667 | 2.0044 | 0.0174 | 9.0924 | 9.1098 |
| 65 | 2.0076 | 0.0042 | 9.1279 | 9.1321 |
| 65.0333 | 2.0132 | 0.0042 | 9.1476 | 9.1519 |
| 65.0667 | 2.0215 | 0.0305 | 9.1805 | 9.211 |
| 65.1 | 2.0281 | 0.0042 | 9.2016 | 9.2058 |
| 65.1333 | 2.0327 | 0.0174 | 9.2279 | 9.2452 |
| 65.1667 | 2.035 | 0.0305 | 9.2673 | 9.2978 |
| 65.2 | 2.0429 | 0.0174 | 9.2949 | 9.3123 |
| 65.2333 | 2.0439 | 0.0042 | 9.3225 | 9.3267 |
| 65.2667 | 2.0488 | 0.0042 | 9.3488 | 9.353 |
| 65.3 | 2.056 | 0.0042 | 9.3738 | 9.378 |
| 65.3333 | 2.06 | 0.0174 | 9.3949 | 9.4122 |
| 65.3667 | 2.0606 | 0.0174 | 9.4343 | 9.4517 |
| 65.4 | 2.0666 | 0.0305 | 9.4553 | 9.4859 |
| 65.4333 65.4667 | 2.0656 | 0.0305 0.0568 | 9.4764 | 9.5069 9.5555 |
| 65.5 | 2.0685 | 0.0568 | 9.4987 9.5237 | 9.5555 |
| 65.5333 | 2.0676 | 0.0305 | 9.5461 | 9.5766 |
| 65.5667 | 2.0676 | 0.0042 | 9.5619 | 9.5661 |
| 65.6 | 2.0692 | 0.0042 | 9.6026 | 9.6026 |
| 65.6333 | 2.0639 | 0.0174 | 9.6079 | 9.6252 |
| 65.6667 | 2.0656 | 0.0174 | 9.6342 | 9.6515 |
| 65.7 | 2.0666 | 0.0042 | 9.6592 | 9.6634 |
| 65.7333 | 2.0626 | 0.0174 | 9.6749 | 9.6923 |
| 65.7667 | 2.0623 | 0.0042 | 9.7078 | 9.712 |
| 65.8 | 2.0606 | 0.0174 | 9.7262 | 9.7436 |
| 65.8333 | 2.061 | 0.0174 | 9.7486 | 9.7659 |
| 65.8667 | 2.0593 | 0.0042 | 9.7604 | 9.7646 |
| 65.9 | 2.0603 | 0.0042 | 9.7854 | 9.7896 |
| 05.5 | 2.0003 | 0.0042 | 5.7054 | 5.7050 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 65.9333 | 2.0534 | 0 | 9.8117 | 9.8117 |
| 65.9667 | 2.0557 | 0.0174 | 9.8235 | 9.8409 |
| 66 | 2.0544 | 0.0174 | 9.8367 | 9.854 |
| 66.0333 | 2.0527 | 0.0042 | 9.8643 | 9.8685 |
| 66.0667 | 2.0531 | 0.0305 | 9.8867 | 9.9172 |
| 66.1 | 2.0527 | 0.0174 | 9.9116 | 9.929 |
| 66.1333 | 2.0435 | 0.0174 | 9.9301 | 9.9474 |
| 66.1667 | 2.0389 | 0 | 9.9511 | 9.9511 |
| 66.2 | 2.036 | 0.0174 | 9.959 | 9.9763 |
| 66.2333 | 2.032 | 0.0042 | 9.9827 | 9.9869 |
| 66.2667 | 2.0251 | 0.0174 | 9.9919 | 10.0092 |
| 66.3 | 2.0218 | 0.0042 | 10.0063 | 10.0105 |
| 66.3333 | 2.0155 | 0.0174 | 10.0366 | 10.0539 |
| 66.3667 | 2.0139 | 0.0042 | 10.0431 | 10.0473 |
| 66.4 | 2.009 | 0 | 10.0576 | 10.0576 |
| 66.4333 | 2.0034 | 0.0042 | 10.0813 | 10.0855 |
| 66.4667 | 2.0044 | 0.0174 | 10.0892 | 10.1065 |
| 66.5 | 2.0007 | 0.0042 | 10.1049 | 10.1092 |
| 66.5333 | 2.0011 | 0.0042 | 10.1194 | 10.1236 |
| 66.5667 | 1.9984 | 0.0174 | 10.126 | 10.1433 |
| 66.6 | 1.9978 | 0.0174 | 10.1418 | 10.1591 |
| 66.6333 | 1.9994 | 0.0174 | 10.1602 | 10.1775 |
| 66.6667 | 1.9984 | 0.0174 | 10.1667 | 10.1841 |
| 66.7 | 2.004 | 0.0042 | 10.1825 | 10.1867 |
| 66.7333 | 2.0014 | 0.0174 | 10.1983 | 10.2157 |
| 66.7667 | 2.0047 | 0.0042 | 10.2154 | 10.2196 |
| 66.8 | 2.007 | 0.0042 | 10.2325 | 10.2367 |
| 66.8333 | 2.005 | 0.0174 | 10.2325 | 10.2499 |
| 66.8667 | 2.008 | 0 | 10.2614 | 10.2614 |
| 66.9 | 2.0073 | 0.0174 | 10.2627 | 10.2801 |
| 66.9333 | 2.0083 | 0.0174 | 10.2759 | 10.2932 |
| 66.9667 | 2.0086 | 0.0174 | 10.2969 | 10.3143 |
| 67 | 2.0142 | 0.0042 | 10.3061 | 10.3103 |
| 67.0333 | 2.0106 | 0.0174 | 10.3153 | 10.3327 |
| 67.0667 | 2.0139 | 0.0305 | 10.3311 | 10.3616 |
| 67.1 | 2.0155 | 0 | 10.3403 | 10.3403 |
| 67.1333 | 2.0152 | 0.0174 | 10.3548 | 10.3721 |
| 67.1667 | 2.0185 | 0.0174 | 10.3587 | 10.3761 |
| 67.2 | 2.0162 | 0.0305 | 10.3706 | 10.4011 |
| 67.2333 | 2.0188 | 0.0174 | 10.3758 | 10.3932 |
| 67.2667 | 2.0139 | 0.0042 | 10.3916 | 10.3958 |
| 67.3 | 2.0179 | 0.0174 | 10.41 | 10.4274 |
| 67.3333 | 2.0169 | 0.0305 | 10.4153 | 10.4458 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 67.3667 | 2.0198 | 0.0042 | 10.4284 | 10.4326 |
| 67.4 | 2.0192 | 0.0042 | 10.4416 | 10.4458 |
| 67.4333 | 2.0215 | 0.0305 | 10.4587 | 10.4892 |
| 67.4667 | 2.0195 | 0.0174 | 10.4705 | 10.4879 |
| 67.5 | 2.0188 | 0.0174 | 10.4863 | 10.5036 |
| 67.5333 | 2.0218 | 0.0042 | 10.5047 | 10.5089 |
| 67.5667 | 2.0231 | 0.0174 | 10.5139 | 10.5313 |
| 67.6 | 2.0192 | 0.0042 | 10.5139 | 10.5181 |
| 67.6333 | 2.0228 | 0.0174 | 10.5336 | 10.551 |
| 67.6667 | 2.0251 | 0.0174 | 10.5455 | 10.5628 |
| 67.7 | 2.0241 | 0.0042 | 10.5494 | 10.5536 |
| 67.7333 | 2.0251 | 0.0042 | 10.5718 | 10.576 |
| 67.7667 | 2.0208 | 0.0174 | 10.5783 | 10.5957 |
| 67.8 | 2.0241 | 0 | 10.5954 | 10.5954 |
| 67.8333 | 2.0228 | 0.0305 | 10.6059 | 10.6365 |
| 67.8667 | 2.0244 | 0.0042 | 10.6086 | 10.6128 |
| 67.9 | 2.0225 | 0.0042 | 10.6309 | 10.6351 |
| 67.9333 | 2.0241 | 0.0174 | 10.6362 | 10.6536 |
| 67.9667 | 2.0238 | 0.0174 | 10.6375 | 10.6549 |
| 68 | 2.0225 | 0.0174 | 10.6533 | 10.6706 |
| 68.0333 | 2.0277 | 0.0042 | 10.6546 | 10.6588 |
| 68.0667 | 2.0241 | 0.0174 | 10.6743 | 10.6917 |
| 68.1 | 2.0225 | 0.0174 | 10.6809 | 10.6983 |
| 68.1333 | 2.0264 | 0.0042 | 10.6914 | 10.6956 |
| 68.1667 | 2.0234 | 0.0305 | 10.7072 | 10.7377 |
| 68.2 | 2.0248 | 0.0042 | 10.7125 | 10.7167 |
| 68.2333 | 2.0254 | 0.0174 | 10.7138 | 10.7311 |
| 68.2667 | 2.0264 | 0.0174 | 10.7322 | 10.7495 |
| 68.3 | 2.0228 | 0.0042 | 10.7401 | 10.7443 |
| 68.3333 | 2.0261 | 0.0174 | 10.744 | 10.7614 |
| 68.3667 | 2.0261 | 0.0042 | 10.7572 | 10.7614 |
| 68.4 | 2.0225 | 0.0042 | 10.7637 | 10.768 |
| 68.4333 | 2.0258 | 0.0174 | 10.7782 | 10.7956 |
| 68.4667 | 2.0264 | 0.0042 | 10.7848 | 10.789 |
| 68.5 | 2.0261 | 0.0042 | 10.7927 | 10.7969 |
| 68.5333 | 2.0251 | 0.0174 | 10.8071 | 10.8245 |
| 68.5667 | 2.0264 | 0.0174 | 10.7966 | 10.814 |
| 68.6 | 2.0251 | 0.0174 | 10.8163 | 10.8337 |
| 68.6333 | 2.0274 | 0.0174 | 10.8229 | 10.8403 |
| 68.6667 | 2.0241 | 0.0174 | 10.8348 | 10.8521 |
| 68.7 | 2.0225 | 0.0174 | 10.8321 | 10.8495 |
| 68.7333 | 2.0248 | 0.0174 | 10.8466 | 10.8639 |
| 68.7667 | 2.0228 | 0.0174 | 10.8558 | 10.8732 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 68.8 | 2.0251 | 0.0305 | 10.8532 | 10.8837 |
| 68.8333 | 2.0241 | 0.0174 | 10.8689 | 10.8863 |
| 68.8667 | 2.0231 | 0.0174 | 10.8821 | 10.8995 |
| 68.9 | 2.0248 | 0.0174 | 10.8808 | 10.8981 |
| 68.9333 | 2.0215 | 0.0174 | 10.9044 | 10.9218 |
| 68.9667 | 2.0251 | 0.0042 | 10.9031 | 10.9073 |
| 69 | 2.0238 | 0.0042 | 10.9044 | 10.9087 |
| 69.0333 | 2.0261 | 0.0305 | 10.9137 | 10.9442 |
| 69.0667 | 2.0271 | 0.0174 | 10.9255 | 10.9428 |
| 69.1 | 2.0251 | 0.0174 | 10.9229 | 10.9402 |
| 69.1333 | 2.0261 | 0.0174 | 10.9518 | 10.9691 |
| 69.1667 | 2.0254 | 0.0174 | 10.9557 | 10.9731 |
| 69.2 | 2.0238 | 0.0042 | 10.9623 | 10.9665 |
| 69.2333 | 2.0264 | 0.0042 | 10.9584 | 10.9626 |
| 69.2667 | 2.0228 | 0.0174 | 10.961 | 10.9784 |
| 69.3 | 2.0215 | 0.0174 | 10.9689 | 10.9862 |
| 69.3333 | 2.0251 | 0.0042 | 10.982 | 10.9862 |
| 69.3667 | 2.0228 | 0.0174 | 10.9847 | 11.002 |
| 69.4 | 2.0241 | 0.0305 | 10.9978 | 11.0283 |
| 69.4333 | 2.0228 | 0.0042 | 11.007 | 11.0112 |
| 69.4667 | 2.0231 | 0.0042 | 11.0189 | 11.0231 |
| 69.5 | 2.0248 | 0.0174 | 11.0215 | 11.0388 |
| 69.5333 | 2.0231 | 0.0042 | 11.0215 | 11.0257 |
| 69.5667 | 2.0238 | 0.0042 | 11.0307 | 11.0349 |
| 69.6 | 2.0258 | 0.0174 | 11.0438 | 11.0612 |
| 69.6333 | 2.0248 | 0.0174 | 11.0557 | 11.073 |
| 69.6667 | 2.0211 | 0.0174 | 11.0478 | 11.0651 |
| 69.7 | 2.0234 | 0.0042 | 11.053 | 11.0572 |
| 69.7333 | 2.0202 | 0.0305 | 11.0609 | 11.0914 |
| 69.7667 | 2.0215 | 0 | 11.0662 | 11.0662 |
| 69.8 | 2.0225 | 0.0305 | 11.0833 | 11.1138 |
| 69.8333 | 2.0231 | 0.0042 | 11.0885 | 11.0928 |
| 69.8667 | 2.0241 | 0.0174 | 11.0978 | 11.1151 |
| 69.9 | 2.0238 | 0.0042 | 11.1017 | 11.1059 |
| 69.9333 | 2.0211 | 0.0174 | 11.0912 | 11.1085 |
| 69.9667 | 2.0198 | 0 | 11.1004 | 11.1004 |
| 70 | 2.0202 | 0.0042 | 11.128 | 11.1322 |
| 70.0333 | 2.0221 | 0.0305 | 11.1162 | 11.1467 |
| 70.0667 | 2.0211 | 0.0042 | 11.1267 | 11.1309 |
| 70.1 | 2.0234 | 0.0174 | 11.1306 | 11.148 |
| 70.1333 | 2.0211 | 0.0174 | 11.1451 | 11.1624 |
| 70.1667 | 2.0211 | 0.0174 | 11.1411 | 11.1585 |
| 70.2 | 2.0211 | 0.0042 | 11.1543 | 11.1585 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 70.2333 | 2.0165 | 0.0042 | 11.1582 | 11.1624 |
| 70.2667 | 2.0208 | 0.0174 | 11.1635 | 11.1809 |
| 70.3 | 2.01 | 0.0174 | 11.1714 | 11.1887 |
| 70.3333 | 1.9421 | 0.0174 | 11.178 | 11.1953 |
| 70.3667 | 1.8747 | 0.0174 | 11.1609 | 11.1782 |
| 70.4 | 1.8059 | 0.0174 | 11.1582 | 11.1756 |
| 70.4333 | 1.744 | 0.0042 | 11.149 | 11.1532 |
| 70.4667 | 1.6791 | 0.0174 | 0 | 0.0174 |
| 70.5 | 1.61 | 0.0174 | 0.002 | 0.0194 |
| 70.5333 | 1.5521 | 0.0042 | 0.002 | 0.0062 |
| 70.5667 | 1.9254 | 0.0174 | 0.0007 | 0.018 |
| 70.6 | 1.8707 | 0.0174 | 0.0007 | 0.018 |
| 70.6333 | 1.8585 | 0.0174 | 0.0007 | 0.018 |
| 70.6667 | -0.0078 | 0.0305 | 0.002 | 0.0325 |
| 70.7 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 70.7333 | -0.0082 | 0.0305 | 0.002 | 0.0325 |
| 70.7667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 70.8 | -0.0052 | 0.0042 | 0.0033 | 0.0075 |
| 70.8333 | -0.0049 | 0.0174 | 0.0033 | 0.0207 |
| 70.8667 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 70.9 | -0.0052 | 0.0174 | 0.0007 | 0.018 |
| 70.9333 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 70.9667 | -0.0062 | 0.0042 | 0.0007 | 0.0049 |
| 71 | -0.0036 | 0.0174 | 0 | 0.0174 |
| 71.0333 | -0.0046 | 0.0174 | 0.0033 | 0.0207 |
| 71.0667 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 71.1 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 71.1333 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 71.1667 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 71.2 | -0.0082 | 0.0305 | 0.002 | 0.0325 |
| 71.2333 | -0.0036 | 0.0174 | 0.0033 | 0.0207 |
| 71.2667 | -0.0019 | 0 | 0 | 0 |
| 71.3 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 71.3333 | -0.0088 | 0.0174 | 0.0007 | 0.018 |
| 71.3667 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 71.4 | -0.0065 | 0.0305 | 0.0007 | 0.0312 |
| 71.4333 | -0.0046 | 0.0042 | 0.0033 | 0.0075 |
| 71.4667 | -0.0069 | 0.0174 | 0 | 0.0174 |
| 71.5 | -0.0055 | 0.0174 | 0.0033 | 0.0207 |
| 71.5333 | -0.0039 | 0.0437 | 0.002 | 0.0457 |
| 71.5667 | -0.0082 | 0.0042 | 0.002 | 0.0062 |
| 71.6 | -0.0049 | 0.0305 | 0.0046 | 0.0351 |
| 71.6333 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 71.6667 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 71.7 | -0.0052 | 0.0305 | 0.0033 | 0.0338 |
| 71.7333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 71.7667 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 71.8 | -0.0046 | 0.0437 | 0.0007 | 0.0443 |
| 71.8333 | -0.0049 | 0.0042 | 0.002 | 0.0062 |
| 71.8667 | -0.0049 | 0.0305 | 0.002 | 0.0325 |
| 71.9 | -0.0049 | 0.0174 | 0.0033 | 0.0207 |
| 71.9333 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 71.9667 | -0.0026 | 0.0042 | 0.0007 | 0.0049 |
| 72 | -0.0065 | 0.0305 | 0.0007 | 0.0312 |
| 72.0333 | -0.0039 | 0.0174 | 0.0033 | 0.0207 |
| 72.0667 | -0.0092 | 0.0174 | 0.0007 | 0.018 |
| 72.1 | -0.0032 | 0.0305 | 0.0007 | 0.0312 |
| 72.1333 | -0.0065 | 0.0042 | 0.0033 | 0.0075 |
| 72.1667 | -0.0075 | 0.0305 | 0.002 | 0.0325 |
| 72.2 | -0.0062 | 0.0305 | 0.0007 | 0.0312 |
| 72.2333 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 72.2667 | -0.0062 | 0.0305 | 0.0007 | 0.0312 |
| 72.3 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 72.3333 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 72.3667 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 72.4 | -0.0072 | 0.0174 | 0.002 | 0.0194 |
| 72.4333 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 72.4667 | -0.0059 | 0.0174 | 0.0007 | 0.018 |
| 72.5 | -0.0046 | 0.0305 | 0.0033 | 0.0338 |
| 72.5333 | -0.0036 | 0.0042 | 0.0033 | 0.0075 |
| 72.5667 | -0.0029 | 0.0174 | 0.0007 | 0.018 |
| 72.6 | -0.0078 | 0.0174 | 0 | 0.0174 |
| 72.6333 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 72.6667 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 72.7 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 72.7333 | -0.0075 | 0.0042 | 0.002 | 0.0062 |
| 72.7667 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 72.8 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 72.8333 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 72.8667 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 72.9 | -0.0082 | 0.0174 | 0 | 0.0174 |
| 72.9333 | -0.0062 | 0.0174 | 0.0007 | 0.018 |
| 72.9667 | -0.0052 | 0.0174 | 0.0007 | 0.018 |
| 73 | -0.0046 | 0 | 0.0033 | 0.0033 |
| 73.0333 | -0.0069 | 0.0042 | 0.002 | 0.0062 |
| 73.0667 | -0.0052 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| , | | | | |
| 73.1 | -0.0078 | 0.0174 | 0 | 0.0174 |
| 73.1333 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 73.1667 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 73.2 | -0.0049 | 0.0174 | 0.0007 | 0.018 |
| 73.2333 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 73.2667 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 73.3 | -0.0065 | 0.0174 | 0.0033 | 0.0207 |
| 73.3333 | -0.0059 | 0.0042 | 0.002 | 0.0062 |
| 73.3667 | -0.0029 | 0.0174 | 0 | 0.0174 |
| 73.4 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 73.4333 | -0.0062 | 0.0042 | 0.0007 | 0.0049 |
| 73.4667 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 73.5 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 73.5333 | -0.0098 | 0.0042 | 0.0007 | 0.0049 |
| 73.5667 | -0.0069 | 0.0174 | 0.0007 | 0.018 |
| 73.6 | -0.0108 | 0.0174 | 0.002 | 0.0194 |
| 73.6333 | -0.0121 | 0.0174 | 0.0033 | 0.0207 |
| 73.6667 | -0.0151 | 0.0305 | 0.0007 | 0.0312 |
| 73.7 | -0.0184 | 0.0174 | 0.0007 | 0.018 |
| 73.7333 | -0.0194 | 0.0174 | 0.002 | 0.0194 |
| 73.7667 | -0.0177 | 0.0174 | 0.002 | 0.0194 |
| 73.8 | -0.019 | 0.0042 | 0.002 | 0.0062 |
| 73.8333 | -0.0187 | 0.0174 | 0.0007 | 0.018 |
| 73.8667 | -0.0263 | 0.0174 | 0.002 | 0.0194 |
| 73.9 | -0.0213 | 0.0042 | 0.002 | 0.0062 |
| 73.9333 | -0.0243 | 0.0305 | 0.0046 | 0.0351 |
| 73.9667 | -0.0223 | 0.0042 | 0.0007 | 0.0049 |
| 74 | -0.0236 | 0.0174 | 0.0007 | 0.018 |
| 74.0333 | -0.0266 | 0.0174 | 0.812 | 0.8294 |
| 74.0667 | -0.0266 | 0.0042 | 0.8304 | 0.8346 |
| 74.1 | -0.0256 | 0.0042 | 0.8567 | 0.8609 |
| 74.1333 | -0.0266 | 0.0042 | 0.8751 | 0.8793 |
| 74.1667 | -0.0253 | 0.0174 | 0.8922 | 0.9096 |
| 74.2 | -0.0256 | 0.0305 | 0.9093 | 0.9398 |
| 74.2333 | -0.0289 | 0.0305 | 0.9185 | 0.949 |
| 74.2667 | -0.0266 | 0.0042 | 0.9317 | 0.9359 |
| 74.3 | -0.0302 | 0.0174 | 0.9435 | 0.9609 |
| 74.3333 | -0.0296 | 0.0305 | 0.9475 | 0.978 |
| 74.3667 | -0.022 | 0.0174 | 0.645 | 0.6624 |
| 74.4 | -0.0151 | 0.0042 | 0.3728 | 0.377 |
| 74.4333 | -0.0128 | 0.0042 | 0.002 | 0.0062 |
| 74.4667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 74.5 | -0.0055 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|--------------------|------------------|-----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| =4 =000 | 0.0000 | 22474 | 2 2227 | 0.010 |
| 74.5333 | -0.0022 | 0.0174 | 0.0007 | 0.018 |
| 74.5667 | -0.0062 | 0.0305 | 0.0007 | 0.0312 |
| 74.6 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 74.6333 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 74.6667 | -0.0042 | 0.0305 | 0.002 | 0.0325 |
| 74.7 | -0.0022 | 0.0174 | 0 | 0.0174 |
| 74.7333 | -0.0059 | 0.0042 | 0.002 | 0.0062 |
| 74.7667 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 74.8 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 74.8333 | -0.0039 | 0.0174 | 0.0033 | 0.0207 |
| 74.8667 | -0.0009 | 0.0174 | 0.002 | 0.0194 |
| 74.9 | -0.0065 | 0.0437 | 0 | 0.0437 |
| 74.9333 | -0.0042 | 0.0042 | 0.0007 | 0.0049 |
| 74.9667 75 | -0.0049 | 0.0174 | 0.0033 | 0.0207 |
| 75.0333 | -0.0046 | 0.0305 0.0042 | 0.002 | 0.0325 |
| 75.0667 | -0.0049 -0.0065 | 0.0042 | 0.0007 0.002 | 0.0049 |
| | | | | 0.0194 |
| 75.1 | -0.0065 | 0.0174 | 0 | 0.0174 |
| 75.1333 75.1667 | -0.0092 | 0.0305 0.0174 | 0.0007 0.002 | 0.0312 0.0194 |
| | -0.0075 | | | |
| 75.2 75.2333 | -0.0085 -0.0092 | 0.0174 0.0174 | 0.002 | 0.0194 0.0207 |
| 75.2667 | -0.0092 | 0.0174 | 0.003 | 0.0207 |
| 75.2667 | 0.003 | 0.0303 | 0.003 | 0.0323 |
| 75.3333 | 0.003 | 0.0174 | 0.0033 | 0.0207 |
| 75.3667 | 0.0358 | 0.0305 | 0.002 | 0.0194 |
| 75.3007 | 0.1281 | 0.0042 | 0.002 | 0.0062 |
| 75.4333 | 0.1251 | 0.0174 | 0.002 | 0.0002 |
| 75.4667 | 0.2374 | 0.0042 | 0.002 | 0.0062 |
| 75.4007 | 0.2864 | 0.0174 | 0.002 | 0.0194 |
| 75.5333 | 0.3375 | 0.0174 | 0.002 | 0.0194 |
| 75.5667 | 0.3835 | 0.0305 | 0 | 0.0305 |
| 75.6 | 0.4319 | 0.0305 | 0.002 | 0.0325 |
| 75.6333 | 0.4747 | 0.0174 | 0.002 | 0.0194 |
| 75.6667 | 0.5168 | 0.0174 | 0.8883 | 0.9056 |
| 75.7 | 0.5623 | 0.0042 | 0.9672 | 0.9714 |
| 75.7333 | 0.6011 | 0.0042 | 1.0487 | 1.0529 |
| 75.7667 | 0.6396 | 0.0174 | 1.1197 | 1.1371 |
| 75.8 | 0.6788 | 0.0174 | 1.2013 | 1.2186 |
| 75.8333 | 0.714 | 0.0042 | 1.2907 | 1.2949 |
| 75.8667 | 0.7512 | 0.0174 | 1.3735 | 1.3909 |
| 75.9 | 0.7878 | 0.0042 | 1.4564 | 1.4606 |
| 75.9333 | 0.8236 | 0.0042 | 1.5497 | 1.5539 |
| | | | | |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow |
|---------------|---------|-------------------------|------------------------|------------|
| (min) | (psi) | (LPIVI) | (LPIVI) | (LPIVI) |
| 75.9667 | 0.8569 | 0.0305 | 1.6352 | 1.6657 |
| 76 | 0.8911 | 0.0303 | 1.722 | 1.722 |
| 76.0333 | 0.9198 | 0.0042 | 1.8101 | 1.8143 |
| 76.0667 | 0.9533 | 0.0174 | 1.9035 | 1.9208 |
| 76.1 | 0.983 | 0.0174 | 1.9889 | 2.0063 |
| 76.1333 | 1.0172 | 0.0305 | 2.077 | 2.1075 |
| 76.1667 | 1.0452 | 0.0174 | 2.1625 | 2.1799 |
| 76.2 | 1.0761 | 0.0042 | 2.2453 | 2.2496 |
| 76.2333 | 1.1038 | 0.0174 | 2.3374 | 2.3547 |
| 76.2667 | 1.1301 | 0.0174 | 2.4281 | 2.4455 |
| 76.3 | 1.1571 | 0.0174 | 2.5149 | 2.5323 |
| 76.3333 | 1.1821 | 0.0174 | 2.5964 | 2.6138 |
| 76.3667 | 1.2088 | 0.0042 | 2.6819 | 2.6861 |
| 76.4 | 1.2331 | 0.0042 | 2.7648 | 2.769 |
| 76.4333 | 1.2558 | 0.0174 | 2.8542 | 2.8715 |
| 76.4667 | 1.2799 | 0.0174 | 2.9331 | 2.9504 |
| 76.5 | 1.3049 | 0.0174 | 3.0225 | 3.0399 |
| 76.5333 | 1.3263 | 0 | 3.1053 | 3.1053 |
| 76.5667 | 1.3467 | 0.0174 | 3.1948 | 3.2121 |
| 76.6 | 1.3717 | 0.0042 | 3.271 | 3.2752 |
| 76.6333 | 1.3931 | 0.0174 | 3.346 | 3.3633 |
| 76.6667 | 1.4125 | 0.0042 | 3.4314 | 3.4357 |
| 76.7 | 1.4326 | 0.0174 | 3.5156 | 3.533 |
| 76.7333 | 1.4494 | 0.0174 | 3.5919 | 3.6092 |
| 76.7667 | 1.4734 | 0.0174 | 3.6747 | 3.6921 |
| 76.8 | 1.4879 | 0.0042 | 3.7536 | 3.7578 |
| 76.8333 | 1.5096 | 0.0174 | 3.8233 | 3.8407 |
| 76.8667 | 1.5307 | 0.0042 | 3.9048 | 3.909 |
| 76.9 | 1.5432 | 0.0174 | 3.9758 | 3.9932 |
| 76.9333 | 1.5629 | 0.0174 | 4.0455 | 4.0629 |
| 76.9667 | 1.5817 | 0.0174 | 4.1297 | 4.1471 |
| 77 | 1.5949 | 0.0174 | 4.202 | 4.2194 |
| 77.0333 | 1.6123 | 0.0174 | 4.2704 | 4.2878 |
| 77.0667 | 1.6278 | 0.0174 | 4.3467 | 4.364 |
| 77.1 | 1.6426 | 0.0305 | 4.4203 | 4.4508 |
| 77.1333 | 1.6577 | 0.0174 | 4.4861 | 4.5034 |
| 77.1667 | 1.6722 | 0.0042 | 4.565 | 4.5692 |
| 77.2 | 1.6874 | 0.0174 | 4.6333 | 4.6507 |
| 77.2333 | 1.6989 | 0.0042 | 4.7122 | 4.7164 |
| 77.2667 | 1.7111 | 0.0437 | 4.7806 | 4.8243 |
| 77.3 | 1.7236 | 0.0174 | 4.8569 | 4.8742 |
| 77.3333 | 1.7387 | 0.0042 | 4.9187 | 4.9229 |
| 77.3667 | 1.7506 | 0.0174 | 4.9923 | 5.0097 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|---------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 77.4 | 1.7664 | 0.0042 | 5.0581 | 5.0623 |
| 77.4333 | 1.7762 | 0.0305 | 5.133 | 5.1635 |
| 77.4667 | 1.7894 | 0.0174 | 5.2067 | 5.224 |
| 77.5 | 1.796 | 0.0174 | 5.2724 | 5.2898 |
| 77.5333 | 1.8108 | 0.0174 | 5.3461 | 5.3634 |
| 77.5667 | 1.821 | 0.0174 | 5.4144 | 5.4318 |
| 77.6 | 1.8315 | 0.0305 | 5.4854 | 5.5159 |
| 77.6333 | 1.8421 | 0.0174 | 5.5433 | 5.5607 |
| 77.6667 | 1.852 | 0.0305 | 5.6038 | 5.6343 |
| 77.7 | 1.8615 | 0.0174 | 5.6603 | 5.6777 |
| 77.7333 | 1.8684 | 0.0174 | 5.7313 | 5.7487 |
| 77.7667 | 1.8799 | 0.0042 | 5.7918 | 5.796 |
| 77.8 | 1.8898 | 0.0305 | 5.8563 | 5.8868 |
| 77.8333 | 1.8984 | 0.0042 | 5.9128 | 5.917 |
| 77.8667 | 1.9053 | 0.0042 | 5.972 | 5.9762 |
| 77.9 | 1.9125 | 0.0042 | 6.0246 | 6.0288 |
| 77.9333 | 1.9221 | 0.0174 | 6.0864 | 6.1037 |
| 77.9667 | 1.93 | 0.0305 | 6.1495 | 6.18 |
| 78 | 1.9382 | 0.0174 | 6.2139 | 6.2313 |
| 78.0333 | 1.9454 | 0.0174 | 6.2639 | 6.2813 |
| 78.0667 | 1.9497 | 0.0042 | 6.3191 | 6.3233 |
| 78.1 | 1.9586 | 0.0042 | 6.3796 | 6.3838 |
| 78.1333 | 1.9645 | 0.0042 | 6.4414 | 6.4456 |
| 78.1667 | 1.9711 | 0.0174 | 6.4901 | 6.5074 |
| 78.2 | 1.9741 | 0.0174 | 6.5453 | 6.5627 |
| 78.2333 | 1.9813 | 0.0174 | 6.5992 | 6.6166 |
| 78.2667 | 1.9895 | 0.0174 | 6.6571 | 6.6744 |
| 78.3 | 1.9922 | 0.0174 | 6.711 | 6.7284 |
| 78.3333 | 1.9981 | 0.0042 | 6.7728 | 6.777 |
| 78.3667 | 2.0021 | 0 | 6.8267 | 6.8267 |
| 78.4 | 2.01 | 0.0174 | 6.878 | 6.8954 |
| 78.4333 | 2.0162 | 0.0174 | 6.9372 | 6.9545 |
| 78.4667 | 2.0198 | 0.0042 | 6.9858 | 6.99 |
| 78.5 | 2.0258 | 0.0305 | 7.0411 | 7.0716 |
| 78.5333 | 2.0274 | 0.0042 | 7.095 | 7.0992 |
| 78.5667 | 2.0323 | 0.0174 | 7.1449 | 7.1623 |
| 78.6 | 2.0297 | 0.0437 | 7.2002 | 7.2438 |
| 78.6333 | 2.0323 | 0.0174 | 7.2488 | 7.2662 |
| 78.6667 | 2.032 | 0.0437 | 7.3119 | 7.3556 |
| 78.7 | 2.032 | 0.0174 | 7.3553 | 7.3727 |
| 78.7333 | 2.0346 | 0.0174 | 7.4079 | 7.4253 |
| 78.7667 | 2.0337 | 0.0042 | 7.4526 | 7.4568 |
| 78.8 | 2.0356 | 0.0174 | 7.5 | 7.5173 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 78.8333 | 2.036 | 0.0042 | 7.5407 | 7.545 |
| 78.8667 | 2.0369 | 0.0042 | 7.5868 | 7.591 |
| 78.9 | 2.035 | 0.0305 | 7.6288 | 7.6594 |
| 78.9333 | 2.0356 | 0.0174 | 7.6762 | 7.6935 |
| 78.9667 | 2.0363 | 0.0174 | 7.7169 | 7.7343 |
| 79 | 2.0379 | 0.0042 | 7.7682 | 7.7724 |
| 79.0333 | 2.0366 | 0.0042 | 7.8077 | 7.8119 |
| 79.0667 | 2.0366 | 0.0174 | 7.8498 | 7.8671 |
| 79.1 | 2.0379 | 0.0042 | 7.8918 | 7.896 |
| 79.1333 | 2.0376 | 0.0174 | 7.9366 | 7.9539 |
| 79.1667 | 2.0399 | 0.0042 | 7.9721 | 7.9763 |
| 79.2 | 2.0376 | 0.0305 | 8.0049 | 8.0354 |
| 79.2333 | 2.0402 | 0.0174 | 8.0444 | 8.0617 |
| 79.2667 | 2.0392 | 0.0174 | 8.0865 | 8.1038 |
| 79.3 | 2.0379 | 0.0305 | 8.1272 | 8.1577 |
| 79.3333 | 2.0396 | 0.0305 | 8.1575 | 8.188 |
| 79.3667 | 2.0376 | 0.0174 | 8.2022 | 8.2195 |
| 79.4 | 2.0373 | 0.0042 | 8.235 | 8.2393 |
| 79.4333 | 2.0369 | 0.0174 | 8.2653 | 8.2827 |
| 79.4667 | 2.0396 | 0.0305 | 8.3087 | 8.3392 |
| 79.5 | 2.0412 | 0.0305 | 8.3363 | 8.3668 |
| 79.5333 | 2.0389 | 0.0305 | 8.3758 | 8.4063 |
| 79.5667 | 2.0392 | 0.0174 | 8.4113 | 8.4286 |
| 79.6 | 2.0369 | 0.0042 | 8.4349 | 8.4391 |
| 79.6333 | 2.0353 | 0.0174 | 8.4757 | 8.493 |
| 79.6667 | 2.03 | 0.0042 | 8.5046 | 8.5088 |
| 79.7 | 2.0254 | 0.0174 | 8.5335 | 8.5509 |
| 79.7333 | 2.0205 | 0.0305 | 8.5664 | 8.5969 |
| 79.7667 | 2.0179 | 0.0042 | 8.594 | 8.5982 |
| 79.8 | 2.0179 | 0.0174 | 8.6295 | 8.6469 |
| 79.8333 | 2.0126 | 0.0174 | 8.6637 | 8.6811 |
| 79.8667 | 2.0086 | 0.0174 | 8.6874 | 8.7048 |
| 79.9 | 2.0067 | 0.0042 | 8.7032 | 8.7074 |
| 79.9333 | 2.0024 | 0.0305 | 8.7334 | 8.7639 |
| 79.9667 | 2.0014 | 0.0042 | 8.7558 | 8.76 |
| 80 | 1.9997 | 0.0174 | 8.7913 | 8.8086 |
| 80.0333 | 1.9951 | 0.0042 | 8.8215 | 8.8257 |
| 80.0667 | 1.9945 | 0.0042 | 8.8268 | 8.831 |
| 80.1 | 1.9942 | 0.0042 | 8.8649 | 8.8691 |
| 80.1333 | 1.9925 | 0.0042 | 8.8925 | 8.8967 |
| 80.1667 | 1.9935 | 0.0174 | 8.907 | 8.9244 |
| 80.2 | 1.9935 | 0.0305 | 8.928 | 8.9585 |
| 80.2333 | 1.9932 | 0.0042 | 8.953 | 8.9572 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 80.2667 | 1.9984 | 0.0174 | 8.9728 | 8.9901 |
| 80.3 | 2.0017 | 0.0174 | 9.0017 | 9.019 |
| 80.3333 | 2.0014 | 0.0042 | 9.0332 | 9.0374 |
| 80.3667 | 1.9981 | 0 | 9.0543 | 9.0543 |
| 80.4 | 2.003 | 0.0305 | 9.0714 | 9.1019 |
| 80.4333 | 2.0024 | 0.0174 | 9.0937 | 9.1111 |
| 80.4667 | 2.0067 | 0.0305 | 9.1174 | 9.1479 |
| 80.5 | 2.0047 | 0.0174 | 9.1319 | 9.1492 |
| 80.5333 | 2.0053 | 0.0174 | 9.1647 | 9.1821 |
| 80.5667 | 2.0093 | 0.0042 | 9.1753 | 9.1795 |
| 80.6 | 2.0103 | 0.0174 | 9.1989 | 9.2163 |
| 80.6333 | 2.0083 | 0.0174 | 9.2187 | 9.236 |
| 80.6667 | 2.0106 | 0.0174 | 9.245 | 9.2623 |
| 80.7 | 2.0109 | 0.0174 | 9.2726 | 9.2899 |
| 80.7333 | 2.0126 | 0.0174 | 9.2831 | 9.3004 |
| 80.7667 | 2.0152 | 0.0042 | 9.3041 | 9.3083 |
| 80.8 | 2.0136 | 0.0174 | 9.3291 | 9.3465 |
| 80.8333 | 2.0136 | 0.0174 | 9.3528 | 9.3701 |
| 80.8667 | 2.0172 | 0.0174 | 9.3791 | 9.3964 |
| 80.9 | 2.0162 | 0.0305 | 9.3857 | 9.4162 |
| 80.9333 | 2.0188 | 0.0042 | 9.4172 | 9.4214 |
| 80.9667 | 2.0208 | 0.0305 | 9.4317 | 9.4622 |
| 81 | 2.0195 | 0.0174 | 9.4488 | 9.4661 |
| 81.0333 | 2.0215 | 0.0305 | 9.4711 | 9.5016 |
| 81.0667 | 2.0211 | 0.0305 | 9.4922 | 9.5227 |
| 81.1 | 2.0231 | 0.0174 | 9.5145 | 9.5319 |
| 81.1333 | 2.0192 | 0.0174 | 9.5356 | 9.5529 |
| 81.1667 | 2.0208 | 0.0305 | 9.5513 | 9.5818 |
| 81.2 | 2.0202 | 0.0174 | 9.5619 | 9.5792 |
| 81.2333 | 2.0241 | 0.0174 | 9.5882 | 9.6055 |
| 81.2667 | 2.0211 | 0.0042 | 9.6079 | 9.6121 |
| 81.3 | 2.0238 | 0.0042 | 9.621 | 9.6252 |
| 81.3333 | 2.0225 | 0.0042 | 9.6447 | 9.6489 |
| 81.3667 | 2.0254 | 0.0174 | 9.6618 | 9.6792 |
| 81.4 | 2.0248 | 0.0042 | 9.6776 | 9.6818 |
| 81.4333 | 2.0241 | 0.0174 | 9.7039 | 9.7212 |
| 81.4667 | 2.0231 | 0.0042 | 9.7039 | 9.7081 |
| 81.5 | 2.0205 | 0.0042 | 9.7394 | 9.7436 |
| 81.5333 | 2.0228 | 0.0042 | 9.7512 | 9.7554 |
| 81.5667 | 2.0211 | 0.0174 | 9.7749 | 9.7922 |
| 81.6 | 2.0234 | 0 | 9.792 | 9.792 |
| 81.6333 | 2.0241 | 0.0174 | 9.8038 | 9.8212 |
| 81.6667 | 2.0241 | 0.0305 | 9.8301 | 9.8606 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 81.7 | 2.0231 | 0.0174 | 9.8433 | 9.8606 |
| 81.7333 | 2.0231 | 0.0174 | 9.863 | 9.8803 |
| 81.7667 | 2.0251 | 0.0174 | 9.8801 | 9.8974 |
| 81.8 | 2.0221 | 0.0305 | 9.8972 | 9.9277 |
| 81.8333 | 2.0231 | 0.0305 | 9.913 | 9.9435 |
| 81.8667 | 2.0218 | 0.0174 | 9.9327 | 9.95 |
| 81.9 | 2.0225 | 0.0042 | 9.9419 | 9.9461 |
| 81.9333 | 2.0228 | 0.0174 | 9.9656 | 9.9829 |
| 81.9667 | 2.0211 | 0.0174 | 9.9748 | 9.9921 |
| 82 | 2.0198 | 0.0174 | 9.9853 | 10.0026 |
| 82.0333 | 2.0225 | 0.0305 | 10.0063 | 10.0368 |
| 82.0667 | 2.0188 | 0.0042 | 10.0182 | 10.0224 |
| 82.1 | 2.0211 | 0.0042 | 10.0366 | 10.0408 |
| 82.1333 | 2.0211 | 0.0305 | 10.0431 | 10.0736 |
| 82.1667 | 2.0192 | 0.0174 | 10.0655 | 10.0829 |
| 82.2 | 2.0221 | 0.0174 | 10.0826 | 10.0999 |
| 82.2333 | 2.0215 | 0.0042 | 10.0997 | 10.1039 |
| 82.2667 | 2.0205 | 0.0174 | 10.0984 | 10.1157 |
| 82.3 | 2.0198 | 0.0042 | 10.1168 | 10.121 |
| 82.3333 | 2.0152 | 0.0174 | 10.1378 | 10.1552 |
| 82.3667 | 2.0192 | 0.0174 | 10.1523 | 10.1696 |
| 82.4 | 2.0198 | 0.0042 | 10.1694 | 10.1736 |
| 82.4333 | 2.0195 | 0.0174 | 10.1773 | 10.1946 |
| 82.4667 | 2.0185 | 0.0042 | 10.1957 | 10.1999 |
| 82.5 | 2.0165 | 0.0174 | 10.1983 | 10.2157 |
| 82.5333 | 2.0198 | 0.0305 | 10.2207 | 10.2512 |
| 82.5667 | 2.0211 | 0.0174 | 10.2299 | 10.2472 |
| 82.6 | 2.0179 | 0.0042 | 10.247 | 10.2512 |
| 82.6333 | 2.0162 | 0.0042 | 10.2641 | 10.2683 |
| 82.6667 | 2.0185 | 0.0174 | 10.2667 | 10.284 |
| 82.7 | 2.0149 | 0.0174 | 10.2733 | 10.2906 |
| 82.7333 | 2.0129 | 0.0174 | 10.2851 | 10.3025 |
| 82.7667 | 2.0155 | 0.0174 | 10.3153 | 10.3327 |
| 82.8 | 2.0119 | 0.0305 | 10.3167 | 10.3472 |
| 82.8333 | 2.0142 | 0.0042 | 10.3298 | 10.334 |
| 82.8667 | 2.0155 | 0.0174 | 10.3364 | 10.3537 |
| 82.9 | 2.0149 | 0.0174 | 10.3456 | 10.3629 |
| 82.9333 | 2.0149 | 0.0174 | 10.3587 | 10.3761 |
| 82.9667 | 2.0109 | 0.0174 | 10.3719 | 10.3892 |
| 83 | 2.0119 | 0.0042 | 10.3916 | 10.3958 |
| 83.0333 | 2.0103 | 0.0042 | 10.4087 | 10.4129 |
| 83.0667 | 2.0136 | 0.0174 | 10.4205 | 10.4379 |
| 83.1 | 2.0152 | 0.0042 | 10.4166 | 10.4208 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow |
|-----------------|--------------------|-------------------------|------------------------|------------------|
| () | (рэт) | (LI IVI) | (LI IVI) | (LI IVI) |
| 83.1333 | 2.0142 | 0.0174 | 10.4311 | 10.4484 |
| 83.1667 | 2.0149 | 0.0174 | 10.4482 | 10.4655 |
| 83.2 | 2.0126 | 0.0174 | 10.4547 | 10.4721 |
| 83.2333 | 2.0139 | 0.0042 | 10.4666 | 10.4708 |
| 83.2667 | 2.0139 | 0.0042 | 10.4797 | 10.4839 |
| 83.3 | 2.0159 | 0.0042 | 10.4889 | 10.4931 |
| 83.3333 | 2.0159 | 0.0174 | 10.5034 | 10.5207 |
| 83.3667 | 2.0175 | 0.0174 | 10.5008 | 10.5181 |
| 83.4 | 2.0202 | 0 | 10.5271 | 10.5271 |
| 83.4333 | 2.0205 | 0.0174 | 10.5192 | 10.5365 |
| 83.4667 | 2.0234 | 0.0174 | 10.5455 | 10.5628 |
| 83.5 | 2.0254 | 0.0042 | 10.5547 | 10.5589 |
| 83.5333 | 2.0284 | 0.0174 | 10.5612 | 10.5786 |
| 83.5667 | 2.0264 | 0.0042 | 10.5691 | 10.5733 |
| 83.6 | 2.0307 | 0.0042 | 10.581 | 10.5852 |
| 83.6333 | 2.0261 | 0.0305 | 10.6007 | 10.6312 |
| 83.6667 | 2.0067 | 0.0042 | 10.5994 | 10.6036 |
| 83.7 | 1.9369 | 0.0042 | 10.6112 | 10.6154 |
| 83.7333 | 1.8674 | 0.0174 | 10.6099 | 10.6273 |
| 83.7667 | 1.7993 | 0.0174 | 10.6059 | 10.6233 |
| 83.8 | 1.7387 | 0 | 10.5954 | 10.5954 |
| 83.8333 | -0.3986 | 0.0042 | 10.5849 | 10.5891 |
| 83.8667 | -0.3966 | 0.0174 | 10.5704 | 10.5878 |
| 83.9 | -0.3982 | 0.0174 | 10.5428 | 10.5602 |
| 83.9333 | -0.3936 | 0.0174 | 10.5113 | 10.5286 |
| 83.9667 | -0.3926 | 0.0174 | 10.4863 | 10.5036 |
| 84 | -0.3917 | 0.0042 | 10.4297 | 10.434 |
| 84.0333 | -0.3722 | 0.0174 | 10.0234 | 10.0408 |
| 84.0667 | -0.0046 | 0.0174 | 8.982 | 8.9993 |
| 84.1 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 84.1333 | -0.0032 | 0.0042 | 0.002 | 0.0062 |
| 84.1667 | -0.0003 | 0.0174 | 0.0007 | 0.018 |
| 84.2 | -0.0049 | 0.0042 | 0.002 | 0.0062 |
| 84.2333 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 84.2667 | -0.0013 | 0.0174 | 0.002 | 0.0194 |
| 84.3 | -0.0042 | 0.0174 | 0 | 0.0174 |
| 84.3333 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 84.3667 | -0.0046 | 0.0305 | 0.002 | 0.0325 |
| 84.4 84.4333 | -0.0069 -0.0046 | 0.0174 0.0174 | 0.002 0.0007 | 0.0194 0.018 |
| 84.4667 | -0.0046 | | | |
| E. 10 1E.E.S | | 0.0174 | 0.0007 | 0.018 |
| 84.5 84.5333 | -0.0069 -0.0029 | 0.0174 0.0042 | 0.0033 | 0.0207 0.0062 |
| 84.5333 | -0.0029 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 84.5667 | -0.0088 | 0.0042 | 0.0007 | 0.0049 |
| 84.6 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 84.6333 | -0.0029 | 0.0042 | 0.0007 | 0.0049 |
| 84.6667 | -0.0078 | 0.0174 | 0.002 | 0.0194 |
| 84.7 | -0.0062 | 0.0174 | 0.0007 | 0.018 |
| 84.7333 | -0.0042 | 0.0174 | 0.0033 | 0.0207 |
| 84.7667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 84.8 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 84.8333 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 84.8667 | -0.0059 | 0.0042 | 0.002 | 0.0062 |
| 84.9 | -0.0026 | 0 | 0 | 0 |
| 84.9333 | -0.0009 | 0.0174 | 0 | 0.0174 |
| 84.9667 | -0.0046 | 0.0042 | 0.0033 | 0.0075 |
| 85 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 85.0333 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 85.0667 | -0.0026 | 0.0042 | 0 | 0.0042 |
| 85.1 | -0.0078 | 0.0174 | 0.0007 | 0.018 |
| 85.1333 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 85.1667 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 85.2 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 85.2333 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 85.2667 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 85.3 | -0.0062 | 0.0042 | 0.002 | 0.0062 |
| 85.3333 | -0.0065 | 0.0174 | 0.0033 | 0.0207 |
| 85.3667 | -0.0075 | 0.0042 | 0.0007 | 0.0049 |
| 85.4 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 85.4333 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 85.4667 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 85.5 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 85.5333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 85.5667 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 85.6 | -0.0042 | 0.0305 | 0.0007 | 0.0312 |
| 85.6333 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 85.6667 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 85.7 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 85.7333 | -0.0085 | 0.0174 | 0.0033 | 0.0207 |
| 85.7667 | -0.0039 | 0.0305 | 0.002 | 0.0325 |
| 85.8 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 85.8333 | -0.0075 | 0.0042 | 0.002 | 0.0062 |
| 85.8667 | -0.0029 | 0.0042 | 0.002 | 0.0062 |
| 85.9 | -0.0016 | 0.0174 | 0.002 | 0.0194 |
| 85.9333 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 85.9667 | -0.0062 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 86 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 86.0333 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 86.0667 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 86.1 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 86.1333 | -0.0039 | 0.0042 | 0 | 0.0042 |
| 86.1667 | -0.0059 | 0.0042 | 0.0007 | 0.0049 |
| 86.2 | -0.0029 | 0.0042 | 0.002 | 0.0062 |
| 86.2333 | -0.0062 | 0.0042 | 0.002 | 0.0062 |
| 86.2667 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 86.3 | -0.0101 | 0.0305 | 0 | 0.0305 |
| 86.3333 | -0.0078 | 0.0305 | 0.0007 | 0.0312 |
| 86.3667 | -0.0069 | 0.0305 | 0.002 | 0.0325 |
| 86.4 | -0.0072 | 0.0042 | 0.0033 | 0.0075 |
| 86.4333 | -0.0069 | 0.0174 | 0.0007 | 0.018 |
| 86.4667 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 86.5 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 86.5333 | -0.0059 | 0.0042 | 0.002 | 0.0062 |
| 86.5667 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 86.6 | -0.0052 | 0.0042 | 0.0033 | 0.0075 |
| 86.6333 | -0.0072 | 0.0174 | 0 | 0.0174 |
| 86.6667 | -0.0088 | 0.0174 | 0.002 | 0.0194 |
| 86.7 | -0.0131 | 0.0174 | 0.0007 | 0.018 |
| 86.7333 | -0.0151 | 0.0174 | 0 | 0.0174 |
| 86.7667 | -0.018 | 0.0174 | 0.002 | 0.0194 |
| 86.8 | -0.0148 | 0.0042 | 0.0033 | 0.0075 |
| 86.8333 | 0.0218 | 0.0174 | 0.0007 | 0.018 |
| 86.8667 | 0.0764 | 0.0174 | 0.0007 | 0.018 |
| 86.9 | 0.1314 | 0.0305 | 0.002 | 0.0325 |
| 86.9333 | 0.1831 | 0.0042 | 0.8778 | 0.882 |
| 86.9667 | 0.2331 | 0.0174 | 0.9738 | 0.9911 |
| 87 | 0.2825 | 0.0174 | 1.0658 | 1.0832 |
| 87.0333 | 0.3404 | 0.0174 | 1.1723 | 1.1897 |
| 87.0667 | 0.402 | 0.0042 | 1.2762 | 1.2804 |
| 87.1 | 0.4648 | 0.0042 | 1.3867 | 1.3909 |
| 87.1333 | 0.5224 | 0.0305 | 1.5024 | 1.5329 |
| 87.1667 | 0.583 | 0.0042 | 1.6115 | 1.6157 |
| 87.2 | 0.6386 | 0.0174 | 1.7286 | 1.7459 |
| 87.2333 | 0.6953 | 0 | 1.8469 | 1.8469 |
| 87.2667 | 0.7486 | 0.0305 | 1.9639 | 1.9944 |
| 87.3 | 0.8009 | 0.0174 | 2.0731 | 2.0904 |
| 87.3333 | 0.848 | 0.0174 | 2.1941 | 2.2114 |
| 87.3667 | 0.9 | 0.0174 | 2.3058 | 2.3232 |
| 87.4 | 0.9474 | 0.0174 | 2.4308 | 2.4481 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 87.4333 | 0.9935 | 0.0174 | 2.5517 | 2.5691 |
| 87.4667 | 1.0402 | 0.0174 | 2.6688 | 2.6861 |
| 87.5 | 1.0889 | 0.0174 | 2.7858 | 2.8032 |
| 87.5333 | 1.1324 | 0.0174 | 2.9015 | 2.9189 |
| 87.5667 | 1.1739 | 0.0174 | 3.0264 | 3.0438 |
| 87.6 | 1.2163 | 0.0042 | 3.1395 | 3.1437 |
| 87.6333 | 1.2578 | 0.0174 | 3.2552 | 3.2726 |
| 87.6667 | 1.2976 | 0.0305 | 3.3736 | 3.4041 |
| 87.7 | 1.3365 | 0.0042 | 3.4893 | 3.4935 |
| 87.7333 | 1.378 | 0.0042 | 3.5971 | 3.6013 |
| 87.7667 | 1.4135 | 0.0174 | 3.7102 | 3.7276 |
| 87.8 | 1.4556 | 0.0042 | 3.822 | 3.8262 |
| 87.8333 | 1.4905 | 0.0174 | 3.9311 | 3.9485 |
| 87.8667 | 1.5251 | 0.0174 | 4.0363 | 4.0537 |
| 87.9 | 1.5616 | 0.0174 | 4.1429 | 4.1602 |
| 87.9333 | 1.5945 | 0.0042 | 4.2559 | 4.2601 |
| 87.9667 | 1.6301 | 0.0042 | 4.3677 | 4.3719 |
| 88 | 1.6627 | 0.0174 | 4.4703 | 4.4876 |
| 88.0333 | 1.6966 | 0.0042 | 4.5768 | 4.581 |
| 88.0667 | 1.7302 | 0.0174 | 4.6846 | 4.702 |
| 88.1 | 1.7601 | 0.0305 | 4.7938 | 4.8243 |
| 88.1333 | 1.7914 | 0.0305 | 4.8976 | 4.9282 |
| 88.1667 | 1.8256 | 0.0042 | 4.9989 | 5.0031 |
| 88.2 | 1.85 | 0.0305 | 5.1054 | 5.1359 |
| 88.2333 | 1.8829 | 0.0174 | 5.2132 | 5.2306 |
| 88.2667 | 1.9102 | 0.0305 | 5.3145 | 5.345 |
| 88.3 | 1.9421 | 0.0174 | 5.4263 | 5.4436 |
| 88.3333 | 1.9678 | 0.0042 | 5.5236 | 5.5278 |
| 88.3667 | 1.9991 | 0.0305 | 5.6209 | 5.6514 |
| 88.4 | 2.0188 | 0.0174 | 5.7064 | 5.7237 |
| 88.4333 | 2.0373 | 0.0305 | 5.7997 | 5.8302 |
| 88.4667 | 2.057 | 0.0305 | 5.8852 | 5.9157 |
| 88.5 | 2.061 | 0.0305 | 5.9825 | 6.013 |
| 88.5333 | 2.0481 | 0.0174 | 6.0653 | 6.0827 |
| 88.5667 | 2.034 | 0.0305 | 6.1534 | 6.184 |
| 88.6 | 2.0221 | 0.0174 | 6.2442 | 6.2615 |
| 88.6333 | 2.0119 | 0.0174 | 6.3218 | 6.3391 |
| 88.6667 | 2.0024 | 0.0042 | 6.3928 | 6.397 |
| 88.7 | 1.9895 | 0.0042 | 6.4664 | 6.4706 |
| 88.7333 | 1.9866 | 0.0174 | 6.5453 | 6.5627 |
| 88.7667 | 1.9889 | 0.0042 | 6.6189 | 6.6232 |
| 88.8 | 1.9994 | 0.0174 | 6.7005 | 6.7178 |
| 88.8333 | 2.0093 | 0.0042 | 6.7728 | 6.777 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|-----------------|------------------|------------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | 2 24 25 | 0.0474 | 6.0270 | |
| 88.8667 | 2.0126 | 0.0174 | 6.8372 | 6.8546 |
| 88.9 88.9333 | | | 6.9043 | 6.9348 |
| | 2.0258 | 0.0042 | 6.9806 | 6.9848 |
| 88.9667 | 2.029 | 0.0174 0.0305 | 7.0424 7.1147 | 7.0597 7.1452 |
| 89 89.0333 | 2.0346 | 0.0305 | | |
| 89.0667 | 2.0389 | 0.0042 | 7.1936 7.2541 | 7.1978 7.2714 |
| 89.0667 | 2.0452 | 0.0174 | 7.2541 | 7.2714 |
| | | | | |
| 89.1333 | 2.0518 | 0.0437 | 7.379 | 7.4227 |
| 89.1667 | 2.0547 | 0.0174 | 7.4395 | 7.4568 |
| 89.2 | 2.0587 | 0.0042 | 7.5026 7.5618 | 7.5068 |
| 89.2333 89.2667 | 2.06 | 0.0174 0.0174 | | 7.5791 7.6462 |
| 89.2667 | 2.062 2.0649 | 0.0174 | 7.6288 7.6749 | 7.6922 |
| 89.3333 | 2.0649 | 0.0174 | 7.6749 | 7.7461 |
| 89.3667 | 2.0633 | 0.0042 | 7.7419 | 7.7461 |
| 89.4 | 2.0639 | 0.0174 | 7.7919 | 7.8093 |
| 89.4333 | 2.0643 | 0.0042 | 7.9037 | 7.9079 |
| 89.4333 | 2.0603 | 0.0042 | 7.9615 | 7.9789 |
| 89.4667 | 2.0608 | 0.0174 | 7.9615 8.0154 | 8.0328 |
| 89.5333 | 2.0613 | 0.0174 | 8.0496 | 8.0538 |
| 89.5333 | 2.0536 | 0.0042 | 8.0496 | 8.1301 |
| 89.5 | 2.0574 | 0.0303 | 8.1522 | 8.1564 |
| 89.6333 | 2.0524 | 0.0174 | 8.2061 | 8.2235 |
| 89.6667 | 2.0524 | 0.0174 | 8.2456 | 8.2629 |
| 89.6667 | 2.0318 | 0.0174 | 8.3008 | 8.3182 |
| 89.7333 | 2.0445 | 0.0174 | 8.3481 | 8.3655 |
| 89.7667 | 2.0443 | 0.0174 | 8.3863 | 8.4036 |
| 89.8 | 2.0422 | 0.0174 | 8.4336 | 8.451 |
| 89.8333 | 2.0432 | 0.0174 | 8.4862 | 8.5036 |
| 89.8667 | 2.0422 | 0.0305 | 8.5165 | 8.547 |
| 89.9 | 2.0366 | 0.0305 | 8.5546 | 8.5851 |
| 89.9333 | 2.0353 | 0.0303 | 8.6072 | 8.6245 |
| 89.9667 | 2.033 | 0.0174 | 8.6453 | 8.6627 |
| 90 | 2.032 | 0.0305 | 8.6808 | 8.7113 |
| 90.0333 | 2.0294 | 0.0174 | 8.7124 | 8.7297 |
| 90.0667 | 2.0294 | 0.0174 | 8.7558 | 8.7731 |
| 90.1 | 2.0234 | 0.0174 | 8.7992 | 8.8165 |
| 90.1333 | 2.0261 | 0.0174 | 8.8294 | 8.8468 |
| 90.1667 | 2.0281 | 0.0174 | 8.8662 | 8.8836 |
| 90.2 | 2.0261 | 0.0174 | 8.9044 | 8.9217 |
| 90.2333 | 2.0254 | 0.0174 | 8.9386 | 8.9559 |
| 90.2667 | 2.0234 | 0.0174 | 8.9806 | 8.998 |
| 20.2007 | 2.0230 | 0.0174 | 0.5000 | 0.550 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 90.3 | 2.0231 | 0.0305 | 9.0109 | 9.0414 |
| 90.3333 | 2.0228 | 0.0174 | 9.0451 | 9.0624 |
| 90.3667 | 2.0215 | 0.0174 | 9.0766 | 9.094 |
| 90.4 | 2.0205 | 0.0042 | 9.1082 | 9.1124 |
| 90.4333 | 2.0185 | 0.0174 | 9.149 | 9.1663 |
| 90.4667 | 2.0198 | 0.0042 | 9.1766 | 9.1808 |
| 90.5 | 2.0225 | 0.0305 | 9.2121 | 9.2426 |
| 90.5333 | 2.0192 | 0.0042 | 9.241 | 9.2452 |
| 90.5667 | 2.0218 | 0.0305 | 9.2712 | 9.3018 |
| 90.6 | 2.0152 | 0.0174 | 9.3028 | 9.3202 |
| 90.6333 | 2.0202 | 0.0305 | 9.3383 | 9.3688 |
| 90.6667 | 2.0169 | 0.0174 | 9.3594 | 9.3767 |
| 90.7 | 2.0165 | 0.0042 | 9.387 | 9.3912 |
| 90.7333 | 2.0169 | 0.0042 | 9.429 | 9.4333 |
| 90.7667 | 2.0162 | 0.0042 | 9.4435 | 9.4477 |
| 90.8 | 2.0146 | 0 | 9.4738 | 9.4738 |
| 90.8333 | 2.0136 | 0.0174 | 9.4909 | 9.5082 |
| 90.8667 | 2.0159 | 0.0174 | 9.5224 | 9.5398 |
| 90.9 | 2.0126 | 0.0042 | 9.5487 | 9.5529 |
| 90.9333 | 2.0126 | 0.0042 | 9.5816 | 9.5858 |
| 90.9667 | 2.0152 | 0.0174 | 9.6092 | 9.6266 |
| 91 | 2.0126 | 0.0174 | 9.6237 | 9.641 |
| 91.0333 | 2.0093 | 0.0042 | 9.6539 | 9.6581 |
| 91.0667 | 2.0123 | 0.0437 | 9.6868 | 9.7304 |
| 91.1 | 2.0096 | 0.0174 | 9.7026 | 9.7199 |
| 91.1333 | 2.0096 | 0.0174 | 9.7341 | 9.7515 |
| 91.1667 | 2.008 | 0.0174 | 9.7565 | 9.7738 |
| 91.2 | 2.0053 | 0.0174 | 9.7775 | 9.7949 |
| 91.2333 | 2.007 | 0.0174 | 9.8038 | 9.8212 |
| 91.2667 | 2.0057 | 0.0174 | 9.8275 | 9.8448 |
| 91.3 | 2.004 | 0.0174 | 9.8498 | 9.8672 |
| 91.3333 | 2.0067 | 0.0174 | 9.8775 | 9.8948 |
| 91.3667 | 2.0027 | 0.0042 | 9.9011 | 9.9053 |
| 91.4 | 2.0017 | 0.0042 | 9.9182 | 9.9224 |
| 91.4333 | 2.0004 | 0.0042 | 9.9393 | 9.9435 |
| 91.4667 | 2.0021 | 0.0174 | 9.9708 | 9.9882 |
| 91.5 | 1.9984 | 0.0042 | 9.98 | 9.9842 |
| 91.5333 | 1.9988 | 0.0042 | 9.9997 | 10.004 |
| 91.5667 | 1.9988 | 0.0174 | 10.0234 | 10.0408 |
| 91.6 | 2.0001 | 0.0174 | 10.0563 | 10.0736 |
| 91.6333 | 2.0021 | 0.0174 | 10.0668 | 10.0842 |
| 91.6667 | 2.0004 | 0.0174 | 10.0878 | 10.1052 |
| 91.7 | 2.0007 | 0.0305 | 10.1115 | 10.142 |



Project No. G101276459SAT-023

| Time | | Ch 2 High Flow | | |
|---------|--------|----------------|---------|---------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 91.7333 | 2.007 | 0.0174 | 10.1299 | 10.1473 |
| 91.7667 | 2.0076 | 0.0042 | 10.1457 | 10.1499 |
| 91.8 | 2.0093 | 0.0042 | 10.176 | 10.1802 |
| 91.8333 | 2.0146 | 0.0042 | 10.1917 | 10.1959 |
| 91.8667 | 2.0152 | 0.0042 | 10.2207 | 10.2207 |
| 91.9 | 2.0139 | 0.0174 | 10.2299 | 10.2472 |
| 91.9333 | 2.0175 | 0.0174 | 10.2549 | 10.2722 |
| 91.9667 | 2.0218 | 0.0042 | 10.2693 | 10.2735 |
| 92 | 2.0198 | 0.0174 | 10.289 | 10.3064 |
| 92.0333 | 2.0215 | 0.0042 | 10.3048 | 10.309 |
| 92.0667 | 2.0244 | 0.0042 | 10.3403 | 10.3445 |
| 92.1 | 2.0251 | 0.0437 | 10.3535 | 10.3971 |
| 92.1333 | 2.0284 | 0.0174 | 10.3719 | 10.3892 |
| 92.1667 | 2.0271 | 0.0174 | 10.389 | 10.4063 |
| 92.2 | 2.0254 | 0.0174 | 10.3982 | 10.4155 |
| 92.2333 | 2.029 | 0.0042 | 10.4324 | 10.4366 |
| 92.2667 | 2.0337 | 0.0174 | 10.4534 | 10.4708 |
| 92.3 | 2.032 | 0.0174 | 10.4692 | 10.4866 |
| 92.3333 | 2.0333 | 0.0042 | 10.485 | 10.4892 |
| 92.3667 | 2.0369 | 0.0305 | 10.4955 | 10.526 |
| 92.4 | 2.035 | 0.0042 | 10.5297 | 10.5339 |
| 92.4333 | 2.0376 | 0.0174 | 10.5455 | 10.5628 |
| 92.4667 | 2.0363 | 0.0174 | 10.5652 | 10.5825 |
| 92.5 | 2.0379 | 0.0174 | 10.5783 | 10.5957 |
| 92.5333 | 2.0422 | 0.0174 | 10.5915 | 10.6088 |
| 92.5667 | 2.0373 | 0.0174 | 10.6257 | 10.643 |
| 92.6 | 2.0399 | 0.0042 | 10.6401 | 10.6443 |
| 92.6333 | 2.0416 | 0.0305 | 10.6651 | 10.6956 |
| 92.6667 | 2.0455 | 0.0174 | 10.6704 | 10.6877 |
| 92.7 | 2.0419 | 0.0305 | 10.6967 | 10.7272 |
| 92.7333 | 2.0452 | 0.0042 | 10.7125 | 10.7167 |
| 92.7667 | 2.0445 | 0.0174 | 10.7269 | 10.7443 |
| 92.8 | 2.0425 | 0.0174 | 10.7427 | 10.7601 |
| 92.8333 | 2.0343 | 0.0174 | 10.7532 | 10.7706 |
| 92.8667 | 2.0356 | 0.0042 | 10.7795 | 10.7837 |
| 92.9 | 2.0327 | 0.0174 | 10.7808 | 10.7982 |
| 92.9333 | 2.029 | 0.0174 | 10.8032 | 10.8206 |
| 92.9667 | 2.0254 | 0.0305 | 10.8269 | 10.8574 |
| 93 | 2.0225 | 0.0305 | 10.8374 | 10.8679 |
| 93.0333 | 2.0188 | 0.0174 | 10.8584 | 10.8758 |
| 93.0667 | 2.0162 | 0.0305 | 10.8611 | 10.8916 |
| 93.1 | 2.0152 | 0.0042 | 10.8729 | 10.8771 |
| 93.1333 | 2.0103 | 0.0174 | 10.9044 | 10.9218 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|--------------------|--------------------|------------------|-----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| (, | (100.7) | (=:, | (=:, | (=:, |
| 93.1667 | 2.009 | 0.0174 | 10.9071 | 10.9244 |
| 93.2 | 2.0103 | 0.0305 | 10.9137 | 10.9442 |
| 93.2333 | 2.0047 | 0.0042 | 10.9386 | 10.9428 |
| 93.2667 | 2.0067 | 0.0174 | 10.9439 | 10.9613 |
| 93.3 | 2.007 | 0.0174 | 10.9623 | 10.9797 |
| 93.3333 | 2.005 | 0.0042 | 10.9623 | 10.9665 |
| 93.3667 | 2.0096 | 0.0174 | 10.9807 | 10.9981 |
| 93.4 | 2.005 | 0.0174 | 10.9991 | 11.0165 |
| 93.4333 | 2.0034 | 0.0042 | 11.0162 | 11.0204 |
| 93.4667 | 2.007 | 0.0174 | 11.0267 | 11.0441 |
| 93.5 | 2.0027 | 0.0174 | 11.0281 | 11.0454 |
| 93.5333 | 1.9968 | 0.0042 | 11.0517 | 11.0559 |
| 93.5667 | 1.9283 | 0.0174 | 11.0478 | 11.0651 |
| 93.6 | 1.8612 | 0.0174 | 11.0596 | 11.077 |
| 93.6333 | 1.7904 | 0.0174 | 11.0504 | 11.0678 |
| 93.6667 | 1.7265 | 0.0042 | 11.053 | 11.0572 |
| 93.7 | 1.6656 | 0.0174 | 11.0412 | 11.0586 |
| 93.7333 | 1.6117 | 0.0042 | 10.9321 | 10.9363 |
| 93.7667 | 1.5942 | 0.0174 | 9.9064 | 9.9237 |
| 93.8 | 1.5758 | 0.0305 | 8.9635 | 8.9941 |
| 93.8333 | 1.5554 | 0.0305 | 8.0917 | 8.1222 |
| 93.8667 | -0.2643 | 0.0174 | 7.2896 | 7.3069 |
| 93.9 | -0.2356 | 0.0042 | 6.5387 | 6.5429 |
| 93.9333 | -0.208 | 0.0174 | 5.8339 | 5.8513 |
| 93.9667 | -0.183 | 0.0174 | 5.2067 | 5.224 |
| 94 | -0.1622 | 0.0174 | 4.5899 | 4.6073 |
| 94.0333 | -0.1395 | 0.0174 | 4.0258 | 4.0432 |
| 94.0667 | -0.1168 | 0.0042 | 3.509 | 3.5132 |
| 94.1 | -0.1007 | 0.0174 | 3.0172 | 3.0346 |
| 94.1333 | -0.0849 | 0.0042 | 2.5649 | 2.5691 |
| 94.1667 | -0.0055 | 0.0305 | 0.002 | 0.0325 |
| 94.2 | -0.0039 | 0.0042 | 0.0007 | 0.0049 |
| 94.2333 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 94.2667 | -0.0075 | 0.0305 | 0.002 | 0.0325 |
| 94.3 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 94.3333 94.3667 | -0.0065 -0.0036 | 0.0305 | 0.0007 | 0.0312 0.0207 |
| 94.3667 | -0.0036 | 0.0174 | 0.0033 | |
| 94.4 | | 0.0174 | | 0.018 |
| 94.4333 | -0.0069 -0.0052 | 0.0042 | 0.002 | 0.0062 0.0194 |
| 94.4667 | -0.0052 | 0.0174 0.0305 | 0.002 | 0.0194 |
| 94.5 | -0.0019 | | | |
| 94.5333 | -0.0049 | 0.0174 0.0174 | 0.0007 0.002 | 0.018 0.0194 |
| 94.500/ | -0.0052 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 94.6 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 94.6333 | -0.0059 | 0.0305 | 0.002 | 0.0325 |
| 94.6667 | -0.0069 | 0.0042 | 0.002 | 0.0062 |
| 94.7 | -0.0062 | 0.0174 | 0.0007 | 0.018 |
| 94.7333 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 94.7667 | -0.0032 | 0.0305 | 0.0033 | 0.0338 |
| 94.8 | -0.0055 | 0.0042 | 0.0007 | 0.0049 |
| 94.8333 | -0.0046 | 0.0042 | 0.0007 | 0.0049 |
| 94.8667 | -0.0072 | 0.0174 | 0.002 | 0.0194 |
| 94.9 | -0.0049 | 0 | 0.0007 | 0.0007 |
| 94.9333 | -0.0078 | 0.0305 | 0.002 | 0.0325 |
| 94.9667 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 95 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 95.0333 | -0.0088 | 0 | 0.002 | 0.002 |
| 95.0667 | -0.0046 | 0.0174 | 0.0033 | 0.0207 |
| 95.1 | -0.0032 | 0.0042 | 0.002 | 0.0062 |
| 95.1333 | -0.0052 | 0.0305 | 0.002 | 0.0325 |
| 95.1667 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 95.2 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 95.2333 | -0.0072 | 0.0174 | 0 | 0.0174 |
| 95.2667 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 95.3 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 95.3333 | -0.0088 | 0.0042 | 0.0007 | 0.0049 |
| 95.3667 | -0.0049 | 0.0174 | 0.0007 | 0.018 |
| 95.4 | -0.0029 | 0.0042 | 0.0007 | 0.0049 |
| 95.4333 | -0.0055 | 0.0042 | 0.0007 | 0.0049 |
| 95.4667 | -0.0032 | 0.0305 | 0.002 | 0.0325 |
| 95.5 | -0.0059 | 0.0305 | 0.002 | 0.0325 |
| 95.5333 | -0.0062 | 0.0042 | 0.0007 | 0.0049 |
| 95.5667 | -0.0049 | 0.0174 | 0.0033 | 0.0207 |
| 95.6 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 95.6333 | -0.0082 | 0.0174 | 0.002 | 0.0194 |
| 95.6667 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 95.7 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 95.7333 | -0.0029 | 0.0174 | 0.0007 | 0.018 |
| 95.7667 | -0.0062 | 0.0305 | 0.002 | 0.0325 |
| 95.8 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 95.8333 | -0.0049 | 0.0305 | 0.002 | 0.0325 |
| 95.8667 | -0.0062 | 0.0305 | 0.002 | 0.0325 |
| 95.9 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 95.9333 | -0.0065 | 0.0437 | 0.0007 | 0.0443 |
| 95.9667 | -0.0046 | 0.0305 | 0.002 | 0.0325 |
| 96 | -0.0065 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|--------------------|--------------------|------------------|-----------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 00 0222 | 0.0050 | 0.0042 | 0.0033 | 0.0075 |
| 96.0333 96.0667 | -0.0059 -0.0078 | 0.0042 0.0174 | 0.0033 | 0.0075 0.0194 |
| 96.1 | -0.0078 | 0.0174 | 0.002 | 0.0194 |
| 96.1333 | | | | |
| | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 96.1667 | -0.0039 | 0.0042 | | 0.0042 |
| 96.2 | -0.0052 | 0.0305 | 0.002 0.0007 | 0.0325 |
| 96.2333 96.2667 | -0.0062 | 0.0174 | | 0.018 |
| | -0.0065 | 0.0305 | 0.0007 | 0.0312 |
| 96.3 | -0.0032 | 0.0305 | 0.0007 | 0.0312 |
| 96.3333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 96.3667 | -0.0055 -0.0042 | 0.0174 0.0174 | 0.0033 | 0.0207 |
| 96.4 96.4333 | -0.0042 | 0.0174 | 0.0007 | 0.018 0.0194 |
| 96.4333 | -0.0016 | | | 0.0194 |
| 96.4667 | | 0.0305 | 0.002 | |
| | -0.0046 | 0.0174 | 0.0033 | 0.0207 |
| 96.5333 96.5667 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| | -0.0055 -0.0042 | 0.0174 | 0.0033 | 0.0207 0.0443 |
| 96.6 | | 0.0437 | 0.0007 | |
| 96.6333 96.6667 | -0.0042 -0.0042 | 0.0305 0.0174 | 0.002 0.0007 | 0.0325 0.018 |
| | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 96.7 96.7333 | | | | |
| 96.7667 | -0.0042 -0.0055 | 0.0174 0.0437 | 0.002 0.002 | 0.0194 0.0457 |
| 96.8 | -0.0039 | 0.0042 | 0.002 | 0.0457 |
| 96.8333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 96.8333 | -0.0088 | 0.0174 | 0.002 | 0.0194 |
| | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 96.9 96.9333 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 96.9333 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 90.9007 | -0.0032 | 0.0174 | 0.0007 | 0.018 |
| 97.0333 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 97.0667 | -0.0046 | 0.0305 | 0.0007 | 0.002 |
| 97.1 | -0.0046 | 0.0303 | 0.0007 | 0.002 |
| 97.1333 | -0.0036 | 0.0174 | 0.002 | 0.002 |
| 97.1667 | -0.0048 | 0.0042 | 0.0007 | 0.018 |
| 97.1007 | -0.0072 | 0.0042 | 0.0007 | 0.0049 |
| 97.2333 | -0.0075 | 0.0305 | 0.0033 | 0.018 |
| 97.2667 | -0.0062 | 0.0174 | 0.0033 | 0.0338 |
| 97.2007 | -0.0082 | 0.0305 | 0.0033 | 0.0207 |
| 97.3333 | -0.0073 | 0.0305 | 0.0033 | 0.0338 |
| 97.3667 | -0.0052 | 0.0303 | 0.0007 | 0.0312 |
| 97.3667 | -0.0032 | 0.0174 | 0.0007 | 0.018 |
| 97.4 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 37.4333 | -0.0046 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|---------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 97.4667 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 97.5 | -0.0042 | 0.0305 | 0.002 | 0.0325 |
| 97.5333 | -0.0016 | 0 | 0.002 | 0.002 |
| 97.5667 | -0.0078 | 0.0042 | 0.0007 | 0.0049 |
| 97.6 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 97.6333 | -0.0069 | 0.0174 | 0.0007 | 0.018 |
| 97.6667 | -0.0078 | 0.0042 | 0.002 | 0.0062 |
| 97.7 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 97.7333 | -0.0042 | 0.0305 | 0.002 | 0.0325 |
| 97.7667 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 97.8 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 97.8333 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 97.8667 | -0.0022 | 0.0174 | 0.0007 | 0.018 |
| 97.9 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 97.9333 | -0.0032 | 0.0042 | 0.002 | 0.0062 |
| 97.9667 | -0.0039 | 0.0174 | 0.0033 | 0.0207 |
| 98 | -0.0026 | 0.0305 | 0.002 | 0.0325 |
| 98.0333 | -0.0062 | 0.0305 | 0.0007 | 0.0312 |
| 98.0667 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 98.1 | -0.0036 | 0.0042 | 0.0007 | 0.0049 |
| 98.1333 | -0.0078 | 0.0174 | 0.0007 | 0.018 |
| 98.1667 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 98.2 | -0.0069 | 0.0305 | 0.0007 | 0.0312 |
| 98.2333 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 98.2667 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 98.3 | -0.0022 | 0.0305 | 0.0007 | 0.0312 |
| 98.3333 | -0.0072 | 0.0437 | 0.0033 | 0.047 |
| 98.3667 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 98.4 | -0.0049 | 0.0042 | 0.002 | 0.0062 |
| 98.4333 | -0.0046 | 0.0042 | 0.0007 | 0.0049 |
| 98.4667 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 98.5 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 98.5333 | -0.0085 | 0.0305 | 0.002 | 0.0325 |
| 98.5667 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 98.6 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 98.6333 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 98.6667 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 98.7 | -0.0042 | 0.0305 | 0.002 | 0.0325 |
| 98.7333 | -0.0029 | 0 | 0.002 | 0.002 |
| 98.7667 | -0.0046 | 0.0174 | 0.0033 | 0.0207 |
| 98.8 | -0.0078 | 0.0305 | 0.002 | 0.0325 |
| 98.8333 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 98.8667 | -0.0095 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 98.9 | -0.0072 | 0.0042 | 0 | 0.0042 |
| 98.9333 | -0.0092 | 0.0042 | 0.002 | 0.0062 |
| 98.9667 | -0.0085 | 0.0174 | 0.0033 | 0.0207 |
| 99 | 0.0224 | 0.0174 | 0.0033 | 0.0207 |
| 99.0333 | 0.0893 | 0.0174 | 0.0033 | 0.0207 |
| 99.0667 | 0.166 | 0.0174 | 0.002 | 0.0194 |
| 99.1 | 0.2423 | 0.0042 | 0.0033 | 0.0075 |
| 99.1333 | 0.3138 | 0.0042 | 0.002 | 0.0062 |
| 99.1667 | 0.3858 | 0.0174 | 0 | 0.0174 |
| 99.2 | 0.4507 | 0.0174 | 0.002 | 0.0194 |
| 99.2333 | 0.5175 | 0.0042 | 0.002 | 0.0062 |
| 99.2667 | 0.5807 | 0.0042 | 0.002 | 0.0062 |
| 99.3 | 0.6436 | 0.0174 | 0.816 | 0.8333 |
| 99.3333 | 0.7018 | 0.0174 | 0.9133 | 0.9306 |
| 99.3667 | 0.7637 | 0.0042 | 1.025 | 1.0293 |
| 99.4 | 0.823 | 0.0042 | 1.1276 | 1.1318 |
| 99.4333 | 0.8783 | 0.0174 | 1.2354 | 1.2528 |
| 99.4667 | 0.9306 | 0.0042 | 1.3446 | 1.3488 |
| 99.5 | 0.9839 | 0.0174 | 1.455 | 1.4724 |
| 99.5333 | 1.0392 | 0.0042 | 1.5708 | 1.575 |
| 99.5667 | 1.0909 | 0.0042 | 1.6786 | 1.6828 |
| 99.6 | 1.1423 | 0.0042 | 1.7956 | 1.7998 |
| 99.6333 | 1.19 | 0.0437 | 1.9061 | 1.9497 |
| 99.6667 | 1.2358 | 0.0174 | 2.0231 | 2.0405 |
| 99.7 | 1.2825 | 0.0042 | 2.1375 | 2.1417 |
| 99.7333 | 1.3289 | 0.0174 | 2.2493 | 2.2666 |
| 99.7667 | 1.378 | 0.0174 | 2.3624 | 2.3797 |
| 99.8 | 1.4221 | 0.0305 | 2.4755 | 2.506 |
| 99.8333 | 1.4655 | 0.0042 | 2.5925 | 2.5967 |
| 99.8667 | 1.5106 | 0.0042 | 2.7069 | 2.7111 |
| 99.9 | 1.5521 | 0.0305 | 2.8174 | 2.8479 |
| 99.9333 | 1.5945 | 0.0305 | 2.9423 | 2.9728 |
| 99.9667 | 1.6357 | 0.0305 | 3.0514 | 3.0819 |
| 100 | 1.6782 | 0.0042 | 3.1698 | 3.174 |
| 100.0333 | 1.716 | 0.0174 | 3.2894 | 3.3068 |
| 100.0667 | 1.7565 | 0.0305 | 3.3973 | 3.4278 |
| 100.1 | 1.793 | 0.0305 | 3.5051 | 3.5356 |
| 100.1333 | 1.8335 | 0.0305 | 3.6169 | 3.6474 |
| 100.1667 | 1.8687 | 0.0174 | 3.7234 | 3.7407 |
| 100.2 | 1.9092 | 0.0042 | 3.8404 | 3.8446 |
| 100.2333 | 1.9441 | 0.0437 | 3.9509 | 3.9945 |
| 100.2667 | 1.977 | 0.0174 | 4.0442 | 4.0616 |
| 100.3 | 2.0146 | 0.0174 | 4.1494 | 4.1668 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 100.3333 | 2.0406 | 0.0174 | 4.2691 | 4.2864 |
| 100.3667 | 2.057 | 0.0305 | 4.373 | 4.4035 |
| 100.4 | 2.0475 | 0.0042 | 4.4755 | 4.4797 |
| 100.4333 | 2.032 | 0.0174 | 4.5742 | 4.5915 |
| 100.4667 | 2.0231 | 0.0305 | 4.6728 | 4.7033 |
| 100.5 | 2.0179 | 0.0042 | 4.7675 | 4.7717 |
| 100.5333 | 2.0159 | 0.0174 | 4.8582 | 4.8756 |
| 100.5667 | 2.0192 | 0.0174 | 4.9463 | 4.9637 |
| 100.6 | 2.0192 | 0.0042 | 5.0357 | 5.0399 |
| 100.6333 | 2.0185 | 0.0174 | 5.1317 | 5.1491 |
| 100.6667 | 2.0211 | 0.0305 | 5.2198 | 5.2503 |
| 100.7 | 2.0218 | 0.0174 | 5.2987 | 5.3161 |
| 100.7333 | 2.0231 | 0.0174 | 5.3908 | 5.4081 |
| 100.7667 | 2.0244 | 0.0174 | 5.4657 | 5.4831 |
| 100.8 | 2.0267 | 0.0305 | 5.5446 | 5.5751 |
| 100.8333 | 2.0304 | 0.0174 | 5.6169 | 5.6343 |
| 100.8667 | 2.032 | 0.0305 | 5.6932 | 5.7237 |
| 100.9 | 2.036 | 0.0174 | 5.7682 | 5.7855 |
| 100.9333 | 2.0363 | 0.0042 | 5.83 | 5.8342 |
| 100.9667 | 2.0396 | 0.0174 | 5.901 | 5.9183 |
| 101 | 2.0419 | 0.0174 | 5.972 | 5.9893 |
| 101.0333 | 2.0422 | 0.0174 | 6.0417 | 6.059 |
| 101.0667 | 2.0452 | 0.0437 | 6.114 | 6.1577 |
| 101.1 | 2.0488 | 0.0174 | 6.1771 | 6.1945 |
| 101.1333 | 2.0527 | 0.0174 | 6.2494 | 6.2668 |
| 101.1667 | 2.055 | 0.0174 | 6.3139 | 6.3312 |
| 101.2 | 2.0574 | 0.0305 | 6.3757 | 6.4062 |
| 101.2333 | 2.061 | 0.0174 | 6.4401 | 6.4575 |
| 101.2667 | 2.0636 | 0.0042 | 6.5019 | 6.5061 |
| 101.3 | 2.062 | 0.0042 | 6.5677 | 6.5719 |
| 101.3333 | 2.0653 | 0.0305 | 6.64 | 6.6705 |
| 101.3667 | 2.0666 | 0.0174 | 6.6952 | 6.7126 |
| 101.4 | 2.06 | 0.0042 | 6.7596 | 6.7639 |
| 101.4333 | 2.0537 | 0.0042 | 6.8241 | 6.8283 |
| 101.4667 | 2.0488 | 0.0174 | 6.8806 | 6.898 |
| 101.5 | 2.0409 | 0.0174 | 6.9451 | 6.9624 |
| 101.5333 | 2.0327 | 0.0174 | 6.9924 | 7.0098 |
| 101.5667 | 2.032 | 0.0174 | 7.0424 | 7.0597 |
| 101.6 | 2.0271 | 0.0174 | 7.0963 | 7.1136 |
| 101.6333 | 2.0218 | 0.0042 | 7.1594 | 7.1636 |
| 101.6667 | 2.0192 | 0.0042 | 7.2094 | 7.2136 |
| 101.7 | 2.0142 | 0.0174 | 7.2712 | 7.2885 |
| 101.7333 | 2.0132 | 0.0174 | 7.3159 | 7.3332 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|----------|---------|----------------|--------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 101.7667 | 2.008 | 0.0174 | 7.3645 | 7.3819 |
| 101.7007 | 2.003 | 0.0437 | 7.404 | 7.4476 |
| 101.8333 | 2.0021 | 0.0174 | 7.4566 | 7.4739 |
| 101.8667 | 2.0021 | 0.0042 | 7.5013 | 7.5055 |
| 101.8007 | 1.9968 | 0.0174 | 7.5447 | 7.562 |
| 101.9333 | 1.9955 | 0.0042 | 7.5855 | 7.5897 |
| 101.9667 | 1.9971 | 0.0174 | 7.6367 | 7.6541 |
| 102 | 2.0001 | 0.0305 | 7.6696 | 7.7001 |
| 102.0333 | 2.0014 | 0.0042 | 7.7196 | 7.7238 |
| 102.0667 | 2.0017 | 0.0042 | 7.7603 | 7.7603 |
| 102.0007 | 2.0017 | 0.0042 | 7.7985 | 7.8027 |
| 102.1333 | 2.0021 | 0.0042 | 7.8327 | 7.8369 |
| 102.1667 | 1.9997 | 0.0042 | 7.8813 | 7.8855 |
| 102.1007 | 1.9991 | 0.0305 | 7.9155 | 7.946 |
| 102.2333 | 2.004 | 0.0042 | 7.9628 | 7.9671 |
| 102.2667 | 2.004 | 0.0042 | 7.9931 | 7.9973 |
| 102.2007 | 2.0014 | 0.0174 | 8.0378 | 8.0552 |
| 102.3333 | 2.0063 | 0.0437 | 8.0733 | 8.117 |
| 102.3667 | 2.0003 | 0.0437 | 8.1101 | 8.1538 |
| 102.3007 | 2.007 | 0.0174 | 8.1469 | 8.1643 |
| 102.4333 | 2.005 | 0.0305 | 8.1877 | 8.2182 |
| 102.4667 | 2.0053 | 0.0305 | 8.2206 | 8.2511 |
| 102.4007 | 2.005 | 0.0042 | 8.2495 | 8.2537 |
| 102.5333 | 2.0067 | 0.0174 | 8.2824 | 8.2997 |
| 102.5667 | 2.007 | 0.0174 | 8.3179 | 8.3353 |
| 102.6 | 2.0103 | 0.0174 | 8.3547 | 8.3721 |
| 102.6333 | 2.007 | 0.0174 | 8.385 | 8.4023 |
| 102.6667 | 2.007 | 0.0305 | 8.4284 | 8.4589 |
| 102.7 | 2.0109 | 0.0305 | 8.4573 | 8.4878 |
| 102.7333 | 2.01 | 0.0042 | 8.4888 | 8.493 |
| 102.7667 | 2.0093 | 0.0042 | 8.5125 | 8.5167 |
| 102.8 | 2.009 | 0.0174 | 8.5441 | 8.5614 |
| 102.8333 | 2.0096 | 0.0174 | 8.5717 | 8.589 |
| 102.8667 | 2.0103 | 0.0305 | 8.6032 | 8.6338 |
| 102.9 | 2.008 | 0.0174 | 8.6309 | 8.6482 |
| 102.9333 | 2.01 | 0.0174 | 8.6664 | 8.6837 |
| 102.9667 | 2.0123 | 0.0305 | 8.6953 | 8.7258 |
| 103 | 2.0113 | 0.0437 | 8.7308 | 8.7745 |
| 103.0333 | 2.0109 | 0.0042 | 8.765 | 8.7692 |
| 103.0667 | 2.0109 | 0.0042 | 8.7873 | 8.7915 |
| 103.1 | 2.0119 | 0.0174 | 8.8136 | 8.831 |
| 103.1333 | 2.0119 | 0.0305 | 8.8426 | 8.8731 |
| 103.1667 | 2.0119 | 0.0042 | 8.8702 | 8.8744 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 103.2 | 2.0123 | 0.0174 | 8.9031 | 8.9204 |
| 103.2333 | 2.0119 | 0.0174 | 8.9333 | 8.9507 |
| 103.2667 | 2.0113 | 0.0174 | 8.9622 | 8.9796 |
| 103.3 | 2.0152 | 0.0174 | 8.9833 | 9.0006 |
| 103.3333 | 2.0149 | 0.0174 | 9.0161 | 9.0335 |
| 103.3667 | 2.0132 | 0.0174 | 9.0319 | 9.0493 |
| 103.4 | 2.0162 | 0.0174 | 9.0714 | 9.0887 |
| 103.4333 | 2.0185 | 0.0042 | 9.0872 | 9.0914 |
| 103.4667 | 2.0218 | 0.0042 | 9.1135 | 9.1177 |
| 103.5 | 2.0205 | 0.0042 | 9.1384 | 9.1426 |
| 103.5333 | 2.0218 | 0.0174 | 9.1595 | 9.1768 |
| 103.5667 | 2.0231 | 0.0174 | 9.1818 | 9.1992 |
| 103.6 | 2.0244 | 0.0174 | 9.2094 | 9.2268 |
| 103.6333 | 2.0225 | 0.0305 | 9.2305 | 9.261 |
| 103.6667 | 2.0251 | 0.0042 | 9.2607 | 9.2649 |
| 103.7 | 2.0238 | 0.0174 | 9.2831 | 9.3004 |
| 103.7333 | 2.0258 | 0.0174 | 9.3146 | 9.332 |
| 103.7667 | 2.0281 | 0.0174 | 9.3344 | 9.3517 |
| 103.8 | 2.0284 | 0.0174 | 9.3646 | 9.382 |
| 103.8333 | 2.0297 | 0 | 9.387 | 9.387 |
| 103.8667 | 2.0317 | 0.0174 | 9.4067 | 9.4241 |
| 103.9 | 2.0307 | 0.0305 | 9.4317 | 9.4622 |
| 103.9333 | 2.03 | 0.0174 | 9.4435 | 9.4609 |
| 103.9667 | 2.029 | 0.0174 | 9.4816 | 9.499 |
| 104 | 2.0287 | 0.0174 | 9.5014 | 9.5187 |
| 104.0333 | 2.0304 | 0.0174 | 9.525 | 9.5424 |
| 104.0667 | 2.029 | 0.0174 | 9.5382 | 9.5555 |
| 104.1 | 2.0304 | 0.0042 | 9.5605 | 9.5648 |
| 104.1333 | 2.032 | 0.0042 | 9.5829 | 9.5871 |
| 104.1667 | 2.0313 | 0.0174 | 9.6066 | 9.6239 |
| 104.2 | 2.0307 | 0.0042 | 9.6289 | 9.6331 |
| 104.2333 | 2.0353 | 0.0174 | 9.6552 | 9.6726 |
| 104.2667 | 2.0337 | 0.0174 | 9.6684 | 9.6857 |
| 104.3 | 2.032 | 0.0042 | 9.6907 | 9.6949 |
| 104.3333 | 2.0294 | 0.0042 | 9.7131 | 9.7173 |
| 104.3667 | 2.0304 | 0.0174 | 9.7131 | 9.7304 |
| 104.4 | 2.0307 | 0.0042 | 9.7433 | 9.7475 |
| 104.4333 | 2.031 | 0.0174 | 9.7578 | 9.7751 |
| 104.4667 | 2.0277 | 0.0174 | 9.7683 | 9.7857 |
| 104.5 | 2.029 | 0.0042 | 9.7959 | 9.8001 |
| 104.5333 | 2.031 | 0.0174 | 9.8156 | 9.833 |
| 104.5667 | 2.0277 | 0 | 9.8354 | 9.8354 |
| 104.6 | 2.0304 | 0.0174 | 9.8525 | 9.8698 |
| | | | | |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 104.6333 | 2.0277 | 0.0174 | 9.8748 | 9.8922 |
| 104.6667 | 2.03 | 0.0174 | 9.8867 | 9.904 |
| 104.7 | 2.029 | 0.0174 | 9.909 | 9.9264 |
| 104.7333 | 2.0264 | 0.0174 | 9.9274 | 9.9448 |
| 104.7667 | 2.0254 | 0.0174 | 9.9458 | 9.9632 |
| 104.8 | 2.0267 | 0.0174 | 9.959 | 9.9763 |
| 104.8333 | 2.029 | 0.0174 | 9.9734 | 9.9908 |
| 104.8667 | 2.0277 | 0.0042 | 9.9958 | 10 |
| 104.9 | 2.0264 | 0.0305 | 10.0195 | 10.05 |
| 104.9333 | 2.0244 | 0.0042 | 10.0234 | 10.0276 |
| 104.9667 | 2.0277 | 0.0174 | 10.0353 | 10.0526 |
| 105 | 2.0241 | 0.0042 | 10.0642 | 10.0684 |
| 105.0333 | 2.0261 | 0.0042 | 10.0734 | 10.0776 |
| 105.0667 | 2.0287 | 0.0174 | 10.0918 | 10.1092 |
| 105.1 | 2.0241 | 0.0042 | 10.1036 | 10.1078 |
| 105.1333 | 2.0241 | 0.0042 | 10.1207 | 10.1249 |
| 105.1667 | 2.0228 | 0.0174 | 10.1339 | 10.1512 |
| 105.2 | 2.0248 | 0.0174 | 10.1523 | 10.1696 |
| 105.2333 | 2.0244 | 0.0174 | 10.1667 | 10.1841 |
| 105.2667 | 2.0238 | 0.0174 | 10.1825 | 10.1999 |
| 105.3 | 2.0251 | 0.0042 | 10.1957 | 10.1999 |
| 105.3333 | 2.0267 | 0.0174 | 10.2207 | 10.238 |
| 105.3667 | 2.0238 | 0.0437 | 10.2272 | 10.2709 |
| 105.4 | 2.0264 | 0.0305 | 10.2351 | 10.2656 |
| 105.4333 | 2.0228 | 0.0042 | 10.2575 | 10.2617 |
| 105.4667 | 2.0238 | 0.0042 | 10.2693 | 10.2735 |
| 105.5 | 2.0248 | 0.0042 | 10.2864 | 10.2906 |
| 105.5333 | 2.0218 | 0.0174 | 10.3048 | 10.3222 |
| 105.5667 | 2.0221 | 0.0174 | 10.3088 | 10.3261 |
| 105.6 | 2.0211 | 0.0174 | 10.3245 | 10.3419 |
| 105.6333 | 2.0228 | 0.0042 | 10.3337 | 10.338 |
| 105.6667 | 2.0248 | 0.0042 | 10.3364 | 10.3406 |
| 105.7 | 2.0202 | 0.0174 | 10.3561 | 10.3735 |
| 105.7333 | 2.0261 | 0.0042 | 10.3732 | 10.3774 |
| 105.7667 | 2.0442 | 0.0174 | 10.3798 | 10.3971 |
| 105.8 | 2.0764 | 0.0174 | 10.4034 | 10.4208 |
| 105.8333 | 2.1117 | 0.0042 | 10.4126 | 10.4169 |
| 105.8667 | 2.1419 | 0.0305 | 10.4311 | 10.4616 |
| 105.9 | 2.1788 | 0 | 10.4626 | 10.4626 |
| 105.9333 | 2.2154 | 0.0042 | 10.481 | 10.4852 |
| 105.9667 | 2.247 | 0.0174 | 10.5086 | 10.526 |
| 106 | 2.2812 | 0.0174 | 10.5336 | 10.551 |
| 106.0333 | 2.3105 | 0.0042 | 10.5612 | 10.5654 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 106.0667 | 2.3441 | 0.0305 | 10.581 | 10.6115 |
| 106.1 | 2.376 | 0.0042 | 10.6125 | 10.6167 |
| 106.1333 | 2.4046 | 0.0174 | 10.6375 | 10.6549 |
| 106.1667 | 2.431 | 0.0042 | 10.6664 | 10.6706 |
| 106.2 | 2.4471 | 0.0042 | 10.7059 | 10.7101 |
| 106.2333 | 2.4425 | 0.0174 | 10.7296 | 10.7469 |
| 106.2667 | 2.43 | 0.0174 | 10.7559 | 10.7732 |
| 106.3 | 2.4125 | 0.0042 | 10.7953 | 10.7995 |
| 106.3333 | 2.4 | 0.0042 | 10.8216 | 10.8258 |
| 106.3667 | 2.3921 | 0.0174 | 10.8558 | 10.8732 |
| 106.4 | 2.3911 | 0.0042 | 10.8742 | 10.8784 |
| 106.4333 | 2.3878 | 0.0042 | 10.9018 | 10.906 |
| 106.4667 | 2.3845 | 0.0305 | 10.9294 | 10.9599 |
| 106.5 | 2.3859 | 0.0042 | 10.9531 | 10.9573 |
| 106.5333 | 2.3878 | 0.0174 | 10.9755 | 10.9928 |
| 106.5667 | 2.3865 | 0.0174 | 11.0057 | 11.0231 |
| 106.6 | 2.3862 | 0.0042 | 11.0333 | 11.0375 |
| 106.6333 | 2.3901 | 0.0042 | 11.0478 | 11.052 |
| 106.6667 | 2.3957 | 0.0305 | 11.0728 | 11.1033 |
| 106.7 | 2.3987 | 0.0042 | 11.0964 | 11.1006 |
| 106.7333 | 2.405 | 0.0174 | 11.1241 | 11.1414 |
| 106.7667 | 2.4105 | 0.0174 | 11.1451 | 11.1624 |
| 106.8 | 2.4145 | 0.0174 | 11.1701 | 11.1874 |
| 106.8333 | 2.4184 | 0.0437 | 11.1911 | 11.2348 |
| 106.8667 | 2.4296 | 0.0305 | 11.2174 | 11.2479 |
| 106.9 | 2.4326 | 0.0174 | 11.2371 | 11.2545 |
| 106.9333 | 2.4421 | 0.0174 | 11.2595 | 11.2769 |
| 106.9667 | 2.4425 | 0.0042 | 11.2858 | 11.29 |
| 107 | 2.4468 | 0.0305 | 11.3095 | 11.34 |
| 107.0333 | 2.456 | 0 | 11.3358 | 11.3358 |
| 107.0667 | 2.4573 | 0.0042 | 11.3581 | 11.3623 |
| 107.1 | 2.4589 | 0.0174 | 11.37 | 11.3873 |
| 107.1333 | 2.4622 | 0.0305 | 11.3989 | 11.4294 |
| 107.1667 | 2.4682 | 0.0174 | 11.4265 | 11.4439 |
| 107.2 | 2.4682 | 0.0174 | 11.4475 | 11.4649 |
| 107.2333 | 2.4705 | 0.0305 | 11.462 | 11.4925 |
| 107.2667 | 2.4695 | 0.0042 | 11.483 | 11.4872 |
| 107.3 | 2.4675 | 0.0042 | 11.5146 | 11.5188 |
| 107.3333 | 2.4675 | 0.0174 | 11.5317 | 11.5491 |
| 107.3667 | 2.4688 | 0.0042 | 11.558 | 11.5622 |
| 107.4 | 2.4649 | 0.0174 | 11.579 | 11.5964 |
| 107.4333 | 2.4685 | 0.0174 | 11.5948 | 11.6122 |
| 107.4667 | 2.4635 | 0.0042 | 11.6224 | 11.6266 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow |
|---------------|---------|-------------------------|------------------------|------------|
| (, | (1) | , | | |
| 107.5 | 2.4642 | 0.0042 | 11.6382 | 11.6424 |
| 107.5333 | 2.4655 | 0.0305 | 11.6461 | 11.6766 |
| 107.5667 | 2.4612 | 0.0042 | 11.6763 | 11.6805 |
| 107.6 | 2.4639 | 0.0174 | 11.6882 | 11.7055 |
| 107.6333 | 2.4622 | 0.0174 | 11.7053 | 11.7226 |
| 107.6667 | 2.4599 | 0.0305 | 11.7184 | 11.7489 |
| 107.7 | 2.4589 | 0.0305 | 11.7447 | 11.7752 |
| 107.7333 | 2.4616 | 0.0174 | 11.7644 | 11.7818 |
| 107.7667 | 2.4603 | 0.0174 | 11.775 | 11.7923 |
| 107.8 | 2.4593 | 0.0174 | 11.8039 | 11.8213 |
| 107.8333 | 2.4573 | 0.0042 | 11.817 | 11.8213 |
| 107.8667 | 2.4576 | 0.0174 | 11.8289 | 11.8462 |
| 107.9 | 2.4596 | 0.0042 | 11.842 | 11.8462 |
| 107.9333 | 2.4573 | 0.0042 | 11.8618 | 11.866 |
| 107.9667 | 2.4603 | 0.0174 | 11.8815 | 11.8988 |
| 108 | 2.455 | 0.0042 | 11.892 | 11.8962 |
| 108.0333 | 2.4579 | 0.0174 | 11.9249 | 11.9422 |
| 108.0667 | 2.4524 | 0.0174 | 11.9367 | 11.9541 |
| 108.1 | 2.4563 | 0.0174 | 11.9564 | 11.9738 |
| 108.1333 | 2.457 | 0.0042 | 11.9709 | 11.9751 |
| 108.1667 | 2.4517 | 0.0042 | 11.9748 | 11.979 |
| 108.2 | 2.4556 | 0.0174 | 11.9919 | 12.0093 |
| 108.2333 | 2.4507 | 0.0042 | 12.0117 | 12.0159 |
| 108.2667 | 2.4533 | 0.0174 | 12.0353 | 12.0527 |
| 108.3 | 2.455 | 0 | 12.0419 | 12.0419 |
| 108.3333 | 2.4537 | 0.0174 | 12.0498 | 12.0672 |
| 108.3667 | 2.4514 | 0.0174 | 12.0603 | 12.0777 |
| 108.4 | 2.4533 | 0.0174 | 12.0748 | 12.0921 |
| 108.4333 | 2.4494 | 0.0042 | 12.0906 | 12.0948 |
| 108.4667 | 2.4484 | 0.0305 | 12.105 | 12.1355 |
| 108.5 | 2.4441 | 0.0174 | 12.1234 | 12.1408 |
| 108.5333 | 2.4415 | 0.0042 | 12.1418 | 12.146 |
| 108.5667 | 2.4402 | 0.0042 | 12.1589 | 12.1631 |
| 108.6 | 2.4379 | 0.0042 | 12.1616 | 12.1658 |
| 108.6333 | 2.4339 | 0.0042 | 12.1852 | 12.1894 |
| 108.6667 | 2.4316 | 0.0174 | 12.1866 | 12.2039 |
| 108.7 | 2.43 | 0.0305 | 12.1905 | 12.221 |
| 108.7333 | 2.4267 | 0.0174 | 12.1971 | 12.2144 |
| 108.7667 | 2.425 | 0.0042 | 12.2142 | 12.2184 |
| 108.8 | 2.426 | 0.0174 | 12.2286 | 12.246 |
| 108.8333 | 2.4234 | 0.0042 | 12.2365 | 12.2407 |
| 108.8667 | 2.4204 | 0.0042 | 12.2562 | 12.2605 |
| 108.9 | 2.4175 | 0.0174 | 12.2628 | 12.2802 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 108.9333 | 2.4175 | 0.0305 | 12.276 | 12.3065 |
| 108.9667 | 2.4148 | 0.0305 | 12.2786 | 12.3091 |
| 109 | 2.4168 | 0.0174 | 12.3049 | 12.3223 |
| 109.0333 | 2.4096 | 0.0042 | 12.3049 | 12.3091 |
| 109.0667 | 2.4112 | 0.0174 | 12.3207 | 12.338 |
| 109.1 | 2.4102 | 0.0174 | 12.3207 | 12.338 |
| 109.1333 | 2.4129 | 0.0174 | 12.3325 | 12.3499 |
| 109.1667 | 2.4069 | 0.0042 | 12.343 | 12.3472 |
| 109.2 | 2.4063 | 0.0305 | 12.3588 | 12.3893 |
| 109.2333 | 2.4056 | 0.0174 | 12.3601 | 12.3775 |
| 109.2667 | 2.4096 | 0.0174 | 12.3693 | 12.3867 |
| 109.3 | 2.4082 | 0.0174 | 12.3956 | 12.413 |
| 109.3333 | 2.4105 | 0.0174 | 12.3812 | 12.3985 |
| 109.3667 | 2.4112 | 0.0174 | 12.4048 | 12.4222 |
| 109.4 | 2.4142 | 0.0042 | 12.4127 | 12.4169 |
| 109.4333 | 2.4125 | 0.0174 | 12.4154 | 12.4327 |
| 109.4667 | 2.4158 | 0.0042 | 12.4259 | 12.4301 |
| 109.5 | 2.4158 | 0.0042 | 12.4311 | 12.4353 |
| 109.5333 | 2.4148 | 0.0042 | 12.439 | 12.4432 |
| 109.5667 | 2.4138 | 0.0174 | 12.4588 | 12.4761 |
| 109.6 | 2.4135 | 0.0174 | 12.4693 | 12.4866 |
| 109.6333 | 2.4175 | 0.0174 | 12.4758 | 12.4932 |
| 109.6667 | 2.4366 | 0.0042 | 12.4601 | 12.4643 |
| 109.7 | 2.4313 | 0.0305 | 12.489 | 12.5195 |
| 109.7333 | 2.4296 | 0.0174 | 12.5061 | 12.5234 |
| 109.7667 | 2.427 | 0.0042 | 12.51 | 12.5142 |
| 109.8 | 2.427 | 0.0174 | 12.5271 | 12.5445 |
| 109.8333 | 2.4254 | 0.0042 | 12.5363 | 12.5405 |
| 109.8667 | 2.4198 | 0.0174 | 12.5508 | 12.5682 |
| 109.9 | 2.4175 | 0.0174 | 12.5482 | 12.5655 |
| 109.9333 | 2.4194 | 0.0305 | 12.5666 | 12.5971 |
| 109.9667 | 2.4168 | 0.0174 | 12.5718 | 12.5892 |
| 110 | 2.4152 | 0.0042 | 12.5784 | 12.5826 |
| 110.0333 | 2.4145 | 0.0174 | 12.5876 | 12.605 |
| 110.0667 | 2.4148 | 0.0042 | 12.5837 | 12.5879 |
| 110.1 | 2.4099 | 0.0305 | 12.6021 | 12.6326 |
| 110.1333 | 2.4105 | 0.0174 | 12.6126 | 12.63 |
| 110.1667 | 2.4122 | 0.0174 | 12.6205 | 12.6379 |
| 110.2 | 2.4092 | 0.0305 | 12.635 | 12.6655 |
| 110.2333 | 2.4079 | 0.0174 | 12.635 | 12.6523 |
| 110.2667 | 2.4073 | 0.0305 | 12.6468 | 12.6773 |
| 110.3 | 2.4099 | 0.0174 | 12.6468 | 12.6641 |
| 110.3333 | 2.4073 | 0.0305 | 12.6599 | 12.6904 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| 110.3667 | 2.4059 | 0.0042 | 12.6639 | 12.6681 |
| 110.3007 | 2.4086 | 0.0042 | 12.6705 | 12.6747 |
| 110.4333 | 2.4079 | 0.0305 | 12.6784 | 12.7089 |
| 110.4555 | 2.4115 | 0.0042 | 12.6784 | 12.6826 |
| 110.4007 | 2.4119 | 0.0174 | 12.6994 | 12.7167 |
| 110.5333 | 2.4161 | 0.0305 | 12.702 | 12.7325 |
| 110.5667 | 2.4178 | 0.0042 | 12.706 | 12.7102 |
| 110.5007 | 2.4191 | 0.0042 | 12.7244 | 12.7286 |
| 110.6333 | 2.4201 | 0.0174 | 12.7217 | 12.7391 |
| 110.6667 | 2.4201 | 0.0174 | 12.7349 | 12.7523 |
| 110.7 | 2.4231 | 0.0042 | 12.7467 | 12.7509 |
| 110.7333 | 2.424 | 0.0305 | 12.7375 | 12.768 |
| 110.7667 | 2.4231 | 0.0174 | 12.7467 | 12.7641 |
| 110.8 | 2.427 | 0.0174 | 12.7507 | 12.768 |
| 110.8333 | 2.4263 | 0.0042 | 12.7599 | 12.7641 |
| 110.8667 | 2.4287 | 0.0174 | 12.7665 | 12.7838 |
| 110.9 | 2.4306 | 0.0042 | 12.7783 | 12.7825 |
| 110.9333 | 2.429 | 0.0174 | 12.7822 | 12.7996 |
| 110.9667 | 2.4326 | 0.0174 | 12.7954 | 12.8127 |
| 111 | 2.43 | 0.0042 | 12.8006 | 12.8049 |
| 111.0333 | 2.43 | 0.0174 | 12.7967 | 12.8141 |
| 111.0667 | 2.4306 | 0.0174 | 12.8125 | 12.8298 |
| 111.1 | 2.428 | 0.0042 | 12.8375 | 12.8417 |
| 111.1333 | 2.4293 | 0.0174 | 12.8322 | 12.8496 |
| 111.1667 | 2.4263 | 0.0174 | 12.8309 | 12.8482 |
| 111.2 | 2.424 | 0.0174 | 12.8388 | 12.8561 |
| 111.2333 | 2.4231 | 0.0305 | 12.8427 | 12.8732 |
| 111.2667 | 2.424 | 0.0042 | 12.8611 | 12.8653 |
| 111.3 | 2.4231 | 0.0174 | 12.8532 | 12.8706 |
| 111.3333 | 2.4211 | 0.0174 | 12.8743 | 12.8916 |
| 111.3667 | 2.4208 | 0.0174 | 12.8861 | 12.9035 |
| 111.4 | 2.4198 | 0.0174 | 12.8835 | 12.9008 |
| 111.4333 | 2.4175 | 0.0305 | 12.8887 | 12.9193 |
| 111.4667 | 2.4178 | 0.0174 | 12.9006 | 12.9179 |
| 111.5 | 2.4201 | 0.0305 | 12.9072 | 12.9377 |
| 111.5333 | 2.4201 | 0.0174 | 12.9085 | 12.9258 |
| 111.5667 | 2.4175 | 0.0174 | 12.9229 | 12.9403 |
| 111.6 | 2.4165 | 0.0174 | 12.9177 | 12.935 |
| 111.6333 | 2.4181 | 0.0305 | 12.9269 | 12.9574 |
| 111.6667 | 2.4152 | 0.0042 | 12.9308 | 12.935 |
| 111.7 | 2.4142 | 0.0174 | 12.9308 | 12.9482 |
| 111.7333 | 2.4142 | 0.0042 | 12.9598 | 12.964 |
| 111.7667 | 2.4165 | 0.0174 | 12.9624 | 12.9797 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| 111.8 | 2.4148 | 0.0174 | 12.9506 | 12.9679 |
| 111.8333 | 2.4109 | 0.0042 | 12.9611 | 12.9653 |
| 111.8667 | 2.4142 | 0.0042 | 12.969 | 12.9732 |
| 111.9 | 2.4115 | 0.0174 | 12.9834 | 13.0008 |
| 111.9333 | 2.4109 | 0.0174 | 12.969 | 12.9863 |
| 111.9667 | 2.4132 | 0.0305 | 12.9755 | 13.006 |
| 112 | 2.4099 | 0.0042 | 13.0005 | 13.0047 |
| 112.0333 | 2.4109 | 0.0042 | 12.9979 | 13.0021 |
| 112.0667 | 2.4082 | 0.0042 | 13.011 | 13.0152 |
| 112.1 | 2.4115 | 0.0174 | 13.011 | 13.0284 |
| 112.1333 | 2.4109 | 0.0174 | 13.0084 | 13.0258 |
| 112.1667 | 2.4132 | 0.0305 | 13.0255 | 13.056 |
| 112.2 | 2.4132 | 0.0174 | 13.0137 | 13.031 |
| 112.2333 | 2.4125 | 0.0174 | 13.0452 | 13.0626 |
| 112.2667 | 2.4135 | 0.0042 | 13.0373 | 13.0415 |
| 112.3 | 2.4122 | 0.0305 | 13.0216 | 13.0521 |
| 112.3333 | 2.4178 | 0.0042 | 13.0479 | 13.0521 |
| 112.3667 | 2.3928 | 0.0174 | 13.0479 | 13.0652 |
| 112.4 | 2.3131 | 0.0042 | 13.0426 | 13.0468 |
| 112.4333 | 2.2404 | 0 | 13.036 | 13.036 |
| 112.4667 | 2.1633 | 0.0174 | 13.0413 | 13.0586 |
| 112.5 | -0.524 | 0.0042 | 13.0163 | 13.0205 |
| 112.5333 | -0.5266 | 0.0042 | 13.0176 | 13.0218 |
| 112.5667 | -0.521 | 0.0042 | 12.9953 | 12.9995 |
| 112.6 | -0.5177 | 0.0174 | 12.9532 | 12.9705 |
| 112.6333 | -0.5197 | 0.0042 | 12.9203 | 12.9245 |
| 112.6667 | -0.4776 | 0.0174 | 12.2129 | 12.2302 |
| 112.7 | -0.0022 | 0.0042 | 11.0189 | 11.0231 |
| 112.7333 | -0.0059 | 0.0305 | 0.3189 | 0.3494 |
| 112.7667 | -0.0055 | 0.0174 | 0.0007 | 0.018 |
| 112.8 | -0.0072 | 0.0174 | 0 | 0.0174 |
| 112.8333 | -0.0069 | 0.0174 | 0.0033 | 0.0207 |
| 112.8667 | -0.0059 | 0.0174 | 0.0007 | 0.018 |
| 112.9 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 112.9333 | -0.0062 | 0.0042 | 0.0007 | 0.0049 |
| 112.9667 | -0.0052 | 0.0305 | 0.0007 | 0.0312 |
| 113 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 113.0333 | -0.0049 | 0.0305 | 0.002 | 0.0325 |
| 113.0667 | -0.0049 | 0.0174 | 0.0007 | 0.018 |
| 113.1 | -0.0046 | 0.0042 | 0 | 0.0042 |
| 113.1333 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 113.1667 | -0.0026 | 0.0174 | 0.0033 | 0.0207 |
| 113.2 | -0.0036 | 0.0174 | 0 | 0.0174 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 113.2333 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 113.2667 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 113.3 | -0.0026 | 0.0042 | 0.002 | 0.0062 |
| 113.3333 | -0.0036 | 0.0042 | 0.0007 | 0.0049 |
| 113.3667 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 113.4 | -0.0032 | 0.0042 | 0.0007 | 0.0049 |
| 113.4333 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 113.4667 | -0.0055 | 0.0305 | 0.002 | 0.0325 |
| 113.5 | -0.0052 | 0.0042 | 0 | 0.0042 |
| 113.5333 | -0.0055 | 0.0042 | 0.0033 | 0.0075 |
| 113.5667 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 113.6 | -0.0052 | 0.0174 | 0.0033 | 0.0207 |
| 113.6333 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 113.6667 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 113.7 | -0.0065 | 0.0174 | 0 | 0.0174 |
| 113.7333 | -0.0062 | 0.0042 | 0.0033 | 0.0075 |
| 113.7667 | -0.0029 | 0.0174 | 0.002 | 0.0194 |
| 113.8 | -0.0019 | 0.0174 | 0.0007 | 0.018 |
| 113.8333 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 113.8667 | -0.0059 | 0.0042 | 0.0007 | 0.0049 |
| 113.9 | -0.0049 | 0.0042 | 0.002 | 0.0062 |
| 113.9333 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 113.9667 | -0.0039 | 0.0042 | 0.0007 | 0.0049 |
| 114 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 114.0333 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 114.0667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 114.1 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 114.1333 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 114.1667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 114.2 | -0.0026 | 0.0174 | 0.002 | 0.0194 |
| 114.2333 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 114.2667 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 114.3 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 114.3333 | -0.0072 | 0.0305 | 0.0007 | 0.0312 |
| 114.3667 | -0.0065 | 0.0174 | 0.0007 | 0.018 |
| 114.4 | -0.0069 | 0.0042 | 0.0007 | 0.0049 |
| 114.4333 | -0.0052 | 0.0174 | 0.0033 | 0.0207 |
| 114.4667 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 114.5 | -0.0062 | 0.0174 | 0.0007 | 0.018 |
| 114.5333 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 114.5667 | -0.0055 | 0.0174 | 0.0033 | 0.0207 |
| 114.6 | -0.0016 | 0.0042 | 0.002 | 0.0062 |
| 114.6333 | -0.0036 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | Total Flow |
|----------|---------|--------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 114.6667 | -0.0039 | 0.0042 | 0.0033 | 0.0075 |
| 114.7 | -0.0078 | 0.0305 | 0.0033 | 0.0338 |
| 114.7333 | -0.0003 | 0.0174 | 0.002 | 0.0194 |
| 114.7667 | -0.0036 | 0.0174 | 0.0007 | 0.0134 |
| 114.8 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 114.8333 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 114.8667 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 114.9 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 114.9333 | -0.0039 | 0.0174 | 0.0033 | 0.0207 |
| 114.9667 | -0.0055 | 0.0174 | 0.0033 | 0.0207 |
| 115 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 115.0333 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 115.0667 | -0.0026 | 0.0305 | 0.0007 | 0.0312 |
| 115.1 | -0.0032 | 0.0305 | 0.002 | 0.0325 |
| 115.1333 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 115.1667 | -0.0032 | 0.0305 | 0.0033 | 0.0338 |
| 115.2 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 115.2333 | -0.0042 | 0.0305 | 0.0007 | 0.0312 |
| 115.2667 | -0.0032 | 0.0042 | 0.002 | 0.0062 |
| 115.3 | -0.0065 | 0.0042 | 0.002 | 0.0062 |
| 115.3333 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 115.3667 | -0.0039 | 0.0174 | 0.002 | 0.0194 |
| 115.4 | -0.0049 | 0 | 0.002 | 0.002 |
| 115.4333 | -0.0052 | 0.0305 | 0.002 | 0.0325 |
| 115.4667 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 115.5 | -0.0059 | 0.0305 | 0.002 | 0.0325 |
| 115.5333 | -0.0078 | 0.0042 | 0.0007 | 0.0049 |
| 115.5667 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 115.6 | -0.0039 | 0.0437 | 0.002 | 0.0457 |
| 115.6333 | -0.0072 | 0.0042 | 0 | 0.0042 |
| 115.6667 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 115.7 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 115.7333 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 115.7667 | -0.0075 | 0.0042 | 0.002 | 0.0062 |
| 115.8 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 115.8333 | -0.0055 | 0.0042 | 0.0033 | 0.0075 |
| 115.8667 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 115.9 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 115.9333 | -0.0052 | 0.0174 | 0.0033 | 0.0207 |
| 115.9667 | -0.0046 | 0.0174 | 0 | 0.0174 |
| 116 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 116.0333 | -0.0046 | 0.0042 | 0.0007 | 0.0049 |
| 116.0667 | -0.0078 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | Total Flow |
|----------|---------|--------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 116.1 | -0.0078 | 0.0174 | 0.002 | 0.0194 |
| 116.1333 | -0.0078 | 0.0042 | 0.0007 | 0.0134 |
| 116.1667 | -0.0052 | 0.0042 | 0.0007 | 0.0043 |
| 116.2 | -0.0062 | 0.0174 | 0 | 0.0174 |
| 116.2333 | -0.0046 | 0.0042 | 0 | 0.0042 |
| 116.2667 | -0.0059 | 0.0042 | 0.0007 | 0.0042 |
| 116.3 | -0.0092 | 0.0042 | 0.002 | 0.0043 |
| 116.3333 | -0.0052 | 0.0305 | 0.0007 | 0.0312 |
| 116.3667 | -0.0115 | 0.0042 | 0.0007 | 0.0049 |
| 116.4 | -0.0113 | 0.0174 | 0.002 | 0.0194 |
| 116.4333 | -0.0134 | 0.0174 | 0.002 | 0.0194 |
| 116.4667 | -0.0121 | 0.0174 | 0.002 | 0.0194 |
| 116.5 | -0.0131 | 0.0174 | 0.002 | 0.0194 |
| 116.5333 | -0.0171 | 0.0174 | 0.002 | 0.0194 |
| 116.5667 | -0.019 | 0.0174 | 0.002 | 0.0194 |
| 116.6 | -0.0204 | 0.0174 | 0.002 | 0.0194 |
| 116.6333 | -0.0204 | 0 | 0.002 | 0.002 |
| 116.6667 | -0.0194 | 0.0042 | 0.002 | 0.0062 |
| 116.7 | -0.02 | 0.0174 | 0.0007 | 0.018 |
| 116.7333 | -0.0194 | 0.0042 | 0.0007 | 0.0049 |
| 116.7667 | -0.022 | 0.0437 | 0.0007 | 0.0443 |
| 116.8 | -0.0227 | 0.0174 | 0.002 | 0.0194 |
| 116.8333 | -0.022 | 0.0042 | 0.002 | 0.0062 |
| 116.8667 | -0.0263 | 0.0174 | 0.0007 | 0.018 |
| 116.9 | -0.0243 | 0.0174 | 0.0007 | 0.018 |
| 116.9333 | -0.025 | 0.0305 | 0 | 0.0305 |
| 116.9667 | -0.0243 | 0.0042 | 0.0007 | 0.0049 |
| 117 | -0.0292 | 0.0174 | 0.816 | 0.8333 |
| 117.0333 | -0.0266 | 0.0042 | 0.8304 | 0.8346 |
| 117.0667 | -0.0246 | 0.0174 | 0.8383 | 0.8557 |
| 117.1 | -0.0256 | 0.0042 | 0.8541 | 0.8583 |
| 117.1333 | -0.0259 | 0.0174 | 0.8594 | 0.8767 |
| 117.1667 | -0.0266 | 0.0174 | 0.8699 | 0.8872 |
| 117.2 | -0.0269 | 0.0042 | 0.8751 | 0.8793 |
| 117.2333 | -0.0246 | 0.0174 | 0.883 | 0.9004 |
| 117.2667 | -0.0236 | 0.0174 | 0.8922 | 0.9096 |
| 117.3 | -0.023 | 0.0174 | 0.8975 | 0.9149 |
| 117.3333 | -0.023 | 0.0042 | 0.9028 | 0.907 |
| 117.3667 | -0.021 | 0.0174 | 0.9054 | 0.9227 |
| 117.4 | -0.0154 | 0.0042 | 0.6319 | 0.6361 |
| 117.4333 | -0.0088 | 0.0042 | 0.3557 | 0.3599 |
| 117.4667 | -0.0039 | 0.0042 | 0.0033 | 0.0075 |
| 117.5 | -0.0006 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | 0.000 | | | 2.01.0 |
| 117.5333 | 0.004 | 0.0174 | 0.0007 | 0.018 |
| 117.5667 | 0.0017 | 0.0042 | 0.002 | 0.0062 |
| 117.6 | 0.0017 | 0.0042 | 0.002 | 0.0062 |
| 117.6333 | -0.0003 | 0.0305 | 0.0007 | 0.0312 |
| 117.6667 | -0.0016 | 0.0042 | 0.0033 | 0.0075 |
| 117.7 | 0.0478 | 0.0174 | 0.0033 | 0.0207 |
| 117.7333 | 0.1087 | 0.0174 | 0.002 | 0.0194 |
| 117.7667 | 0.1729 | 0.0174 | 0.0033 | 0.0207 |
| 117.8 | 0.2321 | 0.0174 | 0.002 | 0.0194 |
| 117.8333 | 0.3088 | 0.0305 | 0.0007 | 0.0312 |
| 117.8667 | 0.3845 | 0.0174 | 0.0007 | 0.018 |
| 117.9 | 0.4563 | 0.0174 | 0.0033 | 0.0207 |
| 117.9333 | 0.5287 | 0.0042 | 0.0007 | 0.0049 |
| 117.9667 | 0.5995 | 0.0042 | 0.9028 | 0.907 |
| 118 | 0.6683 | 0.0305 | 1.0132 | 1.0437 |
| 118.0333 | 0.7331 | 0.0174 | 1.1224 | 1.1397 |
| 118.0667 | 0.7957 | 0.0305 | 1.2394 | 1.2699 |
| 118.1 | 0.8549 | 0.0174 | 1.3591 | 1.3764 |
| 118.1333 | 0.9165 | 0.0042 | 1.4827 | 1.4869 |
| 118.1667 | 0.9767 | 0.0174 | 1.605 | 1.6223 |
| 118.2 | 1.0359 | 0.0174 | 1.7351 | 1.7525 |
| 118.2333 | 1.0896 | 0.0174 | 1.8535 | 1.8708 |
| 118.2667 | 1.1433 | 0.0305 | 1.9771 | 2.0076 |
| 118.3 | 1.1969 | 0 | 2.0994 | 2.0994 |
| 118.3333 | 1.2509 | 0.0305 | 2.2256 | 2.2561 |
| 118.3667 | 1.3045 | 0.0042 | 2.3558 | 2.36 |
| 118.4 | 1.3533 | 0.0042 | 2.4768 | 2.481 |
| 118.4333 | 1.4026 | 0.0042 | 2.5978 | 2.602 |
| 118.4667 | 1.4507 | 0.0042 | 2.7253 | 2.7295 |
| 118.5 | 1.4994 | 0.0305 | 2.8542 | 2.8847 |
| 118.5333 | 1.5491 | 0.0174 | 2.9778 | 2.9951 |
| 118.5667 | 1.5929 | 0.0042 | 3.104 | 3.1082 |
| 118.6 | 1.636 | 0.0042 | 3.2237 | 3.2279 |
| 118.6333 | 1.6834 | 0 | 3.3552 | 3.3552 |
| 118.6667 | 1.7275 | 0.0174 | 3.4709 | 3.4883 |
| 118.7 | 1.7716 | 0.0042 | 3.5985 | 3.6027 |
| 118.7333 | 1.8121 | 0.0174 | 3.7234 | 3.7407 |
| 118.7667 | 1.8533 | 0.0305 | 3.847 | 3.8775 |
| 118.8 | 1.8961 | 0.0174 | 3.9693 | 3.9866 |
| 118.8333 | 1.9369 | 0.0174 | 4.0797 | 4.0971 |
| 118.8667 | 1.9777 | 0.0305 | 4.2033 | 4.2338 |
| 118.9 | 2.0162 | 0.0042 | 4.3191 | 4.3233 |
| 118.9333 | 2.0557 | 0.0174 | 4.4361 | 4.4534 |
| | | | | |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 118.9667 | 2.0942 | 0.0437 | 4.5479 | 4.5915 |
| 118.9667 | 2.1186 | 0.0437 | 4.6531 | 4.5915 |
| 119.0333 | 2.1186 | 0.0042 | 4.7767 | 4.7809 |
| | | | 100.0 | |
| 119.0667 | 2.0909 | 0.0305 | 4.8911 | 4.9216 |
| 119.1 | 2.0656 | 0.0042 | 4.9897 | 4.9939 |
| 119.1333 | 2.0409 | 0.0305 | 5.0896 | 5.1201 |
| 119.1667 | 2.0225 | 0.0305 | 5.1922 | 5.2227 |
| 119.2 | 2.0027 | 0.0174 | 5.2869 | 5.3042 |
| 119.2333 | 1.9843 | 0.0042 | 5.3802 | 5.3844 |
| 119.2667 | 1.9932 | 0.0042 | 5.4644 | 5.4686 |
| 119.3 | 2.0021 | 0.0174 | 5.5538 | 5.5712 |
| 119.3333 | 2.0116 | 0.0042 | 5.638 | 5.6422 |
| 119.3667 | 2.0281 | 0.0174 | 5.7169 | 5.7342 |
| 119.4 | 2.0333 | 0.0174 | 5.7997 | 5.8171 |
| 119.4333 | 2.0435 | 0.0042 | 5.872 | 5.8762 |
| 119.4667 | 2.0465 | 0.0174 | 5.943 | 5.9604 |
| 119.5 | 2.0531 | 0.0174 | 6.0298 | 6.0472 |
| 119.5333 | 2.0669 | 0.0042 | 6.1101 | 6.1143 |
| 119.5667 | 2.083 | 0.0042 | 6.1889 | 6.1932 |
| 119.6 | 2.1021 | 0.0174 | 6.2797 | 6.297 |
| 119.6333 | 2.1304 | 0.0174 | 6.352 | 6.3694 |
| 119.6667 | 2.1531 | 0.0174 | 6.4375 | 6.4548 |
| 119.7 | 2.1729 | 0.0305 | 6.5137 | 6.5443 |
| 119.7333 | 2.1946 | 0.0305 | 6.5966 | 6.6271 |
| 119.7667 | 2.217 | 0.0305 | 6.6781 | 6.7086 |
| 119.8 | 2.2391 | 0.0305 | 6.7675 | 6.798 |
| 119.8333 | 2.2575 | 0.0174 | 6.8359 | 6.8533 |
| 119.8667 | 2.2802 | 0.0437 | 6.928 | 6.9716 |
| 119.9 | 2.2963 | 0.0174 | 7.0121 | 7.0295 |
| 119.9333 | 2.3174 | 0.0174 | 7.0923 | 7.1097 |
| 119.9667 | 2.3358 | 0.0042 | 7.1712 | 7.1754 |
| 120 | 2.3543 | 0.0174 | 7.2567 | 7.2741 |
| 120.0333 | 2.372 | 0.0042 | 7.333 | 7.3372 |
| 120.0667 | 2.3872 | 0.0174 | 7.4237 | 7.4411 |
| 120.1 | 2.4076 | 0.0174 | 7.4921 | 7.5094 |
| 120.1333 | 2.4217 | 0.0174 | 7.5802 | 7.5976 |
| 120.1667 | 2.4366 | 0.0174 | 7.6525 | 7.6699 |
| 120.2 | 2.4547 | 0.0305 | 7.7327 | 7.7632 |
| 120.2333 | 2.4616 | 0 | 7.8103 | 7.8103 |
| 120.2667 | 2.4705 | 0.0305 | 7.8879 | 7.9184 |
| 120.3 | 2.4823 | 0.0174 | 7.9576 | 7.9749 |
| 120.3333 | 2.4886 | 0.0174 | 8.0378 | 8.0552 |
| 120.3667 | 2.4974 | 0.0174 | 8.1128 | 8.1301 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 120.4 | 2.5024 | 0.0174 | 8.189 | 8.2064 |
| 120.4333 | 2.5109 | 0.0174 | 8.2679 | 8.2853 |
| 120.4667 | 2.5142 | 0.0305 | 8.3324 | 8.3629 |
| 120.5 | 2.5179 | 0.0174 | 8.3981 | 8.4155 |
| 120.5333 | 2.5142 | 0 | 8.4704 | 8.4704 |
| 120.5667 | 2.51 | 0.0305 | 8.5467 | 8.5772 |
| 120.6 | 2.4935 | 0.0305 | 8.5967 | 8.6272 |
| 120.6333 | 2.483 | 0.0174 | 8.665 | 8.6824 |
| 120.6667 | 2.4691 | 0.0174 | 8.719 | 8.7363 |
| 120.7 | 2.4635 | 0.0042 | 8.7768 | 8.781 |
| 120.7333 | 2.4514 | 0.0174 | 8.8465 | 8.8639 |
| 120.7667 | 2.4448 | 0.0042 | 8.8952 | 8.8994 |
| 120.8 | 2.4385 | 0.0437 | 8.9504 | 8.9941 |
| 120.8333 | 2.4313 | 0.0174 | 9.0043 | 9.0217 |
| 120.8667 | 2.4211 | 0.0174 | 9.0609 | 9.0782 |
| 120.9 | 2.4135 | 0.0042 | 9.1082 | 9.1124 |
| 120.9333 | 2.4115 | 0.0042 | 9.1542 | 9.1584 |
| 120.9667 | 2.4099 | 0.0042 | 9.22 | 9.2242 |
| 121 | 2.4115 | 0.0174 | 9.2712 | 9.2886 |
| 121.0333 | 2.4112 | 0.0174 | 9.312 | 9.3294 |
| 121.0667 | 2.4132 | 0.0174 | 9.3567 | 9.3741 |
| 121.1 | 2.4115 | 0.0174 | 9.4054 | 9.4227 |
| 121.1333 | 2.4152 | 0.0174 | 9.4593 | 9.4766 |
| 121.1667 | 2.4148 | 0.0174 | 9.5001 | 9.5174 |
| 121.2 | 2.4155 | 0.0174 | 9.5461 | 9.5634 |
| 121.2333 | 2.4165 | 0.0174 | 9.5895 | 9.6068 |
| 121.2667 | 2.4198 | 0.0305 | 9.6368 | 9.6673 |
| 121.3 | 2.4204 | 0.0174 | 9.6749 | 9.6923 |
| 121.3333 | 2.4198 | 0.0174 | 9.7157 | 9.7331 |
| 121.3667 | 2.4217 | 0.0042 | 9.7644 | 9.7686 |
| 121.4 | 2.424 | 0.0174 | 9.8091 | 9.8264 |
| 121.4333 | 2.4211 | 0.0174 | 9.8538 | 9.8711 |
| 121.4667 | 2.4184 | 0.0174 | 9.888 | 9.9053 |
| 121.5 | 2.4208 | 0.0042 | 9.9406 | 9.9448 |
| 121.5333 | 2.4204 | 0.0042 | 9.9892 | 9.9934 |
| 121.5667 | 2.4181 | 0.0174 | 10.0142 | 10.0316 |
| 121.6 | 2.4145 | 0.0305 | 10.0523 | 10.0829 |
| 121.6333 | 2.4142 | 0.0042 | 10.0918 | 10.096 |
| 121.6667 | 2.4135 | 0.0174 | 10.1312 | 10.1486 |
| 121.7 | 2.4129 | 0.0042 | 10.1707 | 10.1749 |
| 121.7333 | 2.4115 | 0.0305 | 10.2062 | 10.2367 |
| 121.7667 | 2.4152 | 0.0305 | 10.2509 | 10.2814 |
| 121.8 | 2.4129 | 0.0174 | 10.2759 | 10.2932 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------------------|---------|------------------|--------------------|--------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 424 0222 | 2 4425 | 0.0174 | 10 2210 | 10 2202 |
| 121.8333 121.8667 | 2.4125 | 0.0174 0.0174 | 10.3219 | 10.3393 |
| | | | 10.364 | 10.3814 |
| 121.9 | 2.4069 | 0.0305 | 10.389 | 10.4195 |
| 121.9333 121.9667 | 2.4096 | 0.0174 0.0174 | 10.4245 10.456 | 10.4418 10.4734 |
| | | | | |
| 122 122.0333 | 2.4102 | 0.0174 0.0042 | 10.4942 10.5284 | 10.5115 10.5326 |
| 122.0333 | 2.4089 | 0.0042 | 10.5284 | 10.5326 |
| 122.0667 | 2.4063 | 0.0042 | 10.5994 | |
| 122.1 | 2.4086 | 0.0174 | 10.5994 | 10.6167 10.6273 |
| 122.1333 | 2.4086 | 0.0042 | 10.623 | 10.6273 |
| 122.1667 | 2.4079 | 0.0174 | 10.6927 | 10.8799 |
| 122.2 | 2.4059 | 0.0174 | 10.6927 | 10.7101 |
| 122.2667 | 2.4039 | 0.0174 | 10.7238 | 10.743 |
| 122.2007 | 2.4076 | 0.0174 | 10.7927 | 10.7322 |
| 122.3333 | 2.4079 | 0.0174 | 10.8269 | 10.81 |
| 122.3667 | 2.4079 | 0.0174 | 10.8571 | 10.8442 |
| 122.3007 | 2.4069 | 0.0174 | 10.8768 | 10.8743 |
| 122.4333 | 2.4089 | 0.0174 | 10.9071 | 10.8942 |
| 122.4555 | 2.4112 | 0.0174 | 10.9413 | 10.9455 |
| 122.5 | 2.4096 | 0.0174 | 10.9689 | 10.9862 |
| 122.5333 | 2.4089 | 0.0174 | 11.0031 | 11.0204 |
| 122.5667 | 2.4092 | 0.0042 | 11.0136 | 11.0204 |
| 122.5007 | 2.4092 | 0.0042 | 11.0452 | 11.0494 |
| 122.6333 | 2.4086 | 0.0042 | 11.0452 | 11.0901 |
| 122.6667 | 2.4102 | 0.0174 | 11.107 | 11.1243 |
| 122.7 | 2.4059 | 0.0174 | 11.1254 | 11.1427 |
| 122.7333 | 2.4089 | 0.0174 | 11.1661 | 11.1835 |
| 122.7667 | 2.4099 | 0.0174 | 11.1806 | 11.198 |
| 122.8 | 2.4082 | 0.0174 | 11.2214 | 11.2387 |
| 122.8333 | 2.4086 | 0.0174 | 11.2398 | 11.2571 |
| 122.8667 | 2.4109 | 0.0042 | 11.2661 | 11.2703 |
| 122.9 | 2.4109 | 0.0174 | 11.2911 | 11.3084 |
| 122.9333 | 2.4099 | 0.0305 | 11.3213 | 11.3518 |
| 122.9667 | 2.4043 | 0.0174 | 11.3371 | 11.3544 |
| 123 | 2.4096 | 0.0042 | 11.37 | 11.3742 |
| 123.0333 | 2.4066 | 0.0042 | 11.3844 | 11.3886 |
| 123.0667 | 2.4096 | 0.0174 | 11.4212 | 11.4386 |
| 123.1 | 2.4082 | 0.01,4 | 11.4396 | 11.4396 |
| 123.1333 | 2.4046 | 0.0042 | 11.4633 | 11.4675 |
| 123.1667 | 2.4096 | 0.0042 | 11.4936 | 11.4978 |
| 123.2 | 2.4082 | 0.0174 | 11.5212 | 11.5385 |
| 123.2333 | 2.4089 | 0.0305 | 11.5475 | 11.578 |
| | | 0.0000 | 11.5.75 | |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| (11111) | (psi) | (LFIVI) | (LFIVI) | (LFIVI) |
| 123.2667 | 2.4056 | 0.0174 | 11.5554 | 11.5727 |
| 123.3 | 2.4059 | 0.0174 | 11.5896 | 11.6069 |
| 123.3333 | 2.4082 | 0.0174 | 11.6198 | 11.6372 |
| 123.3667 | 2.4059 | 0.0305 | 11.6408 | 11.6713 |
| 123.4 | 2.4043 | 0.0042 | 11.6606 | 11.6648 |
| 123.4333 | 2.4073 | 0.0174 | 11.6869 | 11.7042 |
| 123.4667 | 2.4069 | 0.0042 | 11.7132 | 11.7174 |
| 123.5 | 2.4066 | 0.0174 | 11.7342 | 11.7516 |
| 123.5333 | 2.4089 | 0.0174 | 11.7381 | 11.7555 |
| 123.5667 | 2.4079 | 0.0174 | 11.7684 | 11.7857 |
| 123.6 | 2.4076 | 0.0042 | 11.7894 | 11.7936 |
| 123.6333 | 2.4079 | 0.0305 | 11.8052 | 11.8357 |
| 123.6667 | 2.4046 | 0.0174 | 11.8368 | 11.8541 |
| 123.7 | 2.4079 | 0.0305 | 11.8565 | 11.887 |
| 123.7333 | 2.4076 | 0.0042 | 11.8578 | 11.862 |
| 123.7667 | 2.4099 | 0.0174 | 11.9012 | 11.9186 |
| 123.8 | 2.4082 | 0.0305 | 11.9196 | 11.9501 |
| 123.8333 | 2.4099 | 0.0174 | 11.938 | 11.9554 |
| 123.8667 | 2.4122 | 0.0305 | 11.9564 | 11.9869 |
| 123.9 | 2.4112 | 0.0042 | 11.984 | 11.9883 |
| 123.9333 | 2.4132 | 0.0174 | 11.9906 | 12.008 |
| 123.9667 | 2.4112 | 0.0305 | 12.0103 | 12.0409 |
| 124 | 2.4122 | 0.0174 | 12.0498 | 12.0672 |
| 124.0333 | 2.4152 | 0.0305 | 12.059 | 12.0895 |
| 124.0667 | 2.4142 | 0.0042 | 12.0814 | 12.0856 |
| 124.1 | 2.4148 | 0.0174 | 12.0945 | 12.1119 |
| 124.1333 | 2.4129 | 0.0305 | 12.1129 | 12.1434 |
| 124.1667 | 2.4161 | 0.0042 | 12.1287 | 12.1329 |
| 124.2 | 2.4181 | 0.0042 | 12.1576 | 12.1618 |
| 124.2333 | 2.4175 | 0.0174 | 12.1747 | 12.1921 |
| 124.2667 | 2.4168 | 0.0174 | 12.1734 | 12.1908 |
| 124.3 | 2.4194 | 0.0174 | 12.1958 | 12.2131 |
| 124.3333 | 2.4204 | 0.0305 | 12.2142 | 12.2447 |
| 124.3667 | 2.4211 | 0.0042 | 12.2431 | 12.2473 |
| 124.4 | 2.4175 | 0.0305 | 12.2615 | 12.292 |
| 124.4333 | 2.4204 | 0.0305 | 12.276 | 12.3065 |
| 124.4667 | 2.4208 | 0.0042 | 12.2839 | 12.2881 |
| 124.5 | 2.4214 | 0.0174 | 12.2996 | 12.317 |
| 124.5333 | 2.4208 | 0.0305 | 12.3233 | 12.3538 |
| 124.5667 | 2.4227 | 0.0174 | 12.3496 | 12.367 |
| 124.6 | 2.4204 | 0.0042 | 12.3549 | 12.3591 |
| 124.6333 | 2.4204 | 0.0042 | 12.3654 | 12.3696 |
| 124.6667 | 2.4221 | 0.0174 | 12.3838 | 12.4012 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|-------------------|---------|------------------|--------------------|--------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 1247 | 2 4244 | 0.0174 | 12 4114 | 12 4200 |
| 124.7 124.7333 | 2.4244 | 0.0174 0.0174 | 12.4114 12.4259 | 12.4288 12.4432 |
| 124.7333 | 2.4194 | 0.0174 | 12.439 | 12.4432 |
| 124.7667 | 2.4227 | 0.0174 | 12.468 | 12.4364 |
| 124.8 | 2.424 | 0.0042 | 12.468 | 12.4722 |
| 124.8333 | 2.4204 | 0.0174 | 12.4798 | 12.4853 |
| 124.8667 | 2.4175 | 0.0174 | 12.5087 | 12.5261 |
| 124.9333 | 2.4211 | 0.0174 | 12.5206 | 12.5379 |
| 124.9553 | 2.4211 | 0.0174 | 12.539 | 12.5563 |
| 124.9007 | 2.4231 | 0.0174 | 12.5482 | 12.5655 |
| 125.0333 | 2.424 | 0.0174 | 12.5679 | 12.5853 |
| 125.0667 | 2.4224 | 0.0042 | 12.581 | 12.5853 |
| 125.0667 | 2.424 | 0.0042 | 12.6073 | 12.6247 |
| 125.1333 | 2.424 | 0.0042 | 12.6073 | 12.6116 |
| 125.1667 | 2.4204 | 0.0305 | 12.6336 | 12.6641 |
| 125.2 | 2.4227 | 0.0305 | 12.6389 | 12.6694 |
| 125.2333 | 2.4194 | 0.0042 | 12.6521 | 12.6563 |
| 125.2667 | 2.4227 | 0.0305 | 12.6757 | 12.7062 |
| 125.3 | 2.4204 | 0.0174 | 12.6757 | 12.6931 |
| 125.3333 | 2.4175 | 0.0174 | 12.6889 | 12.7062 |
| 125.3667 | 2.3559 | 0.0042 | 12.7165 | 12.7207 |
| 125.4 | 2.2739 | 0.0305 | 12.7099 | 12.7404 |
| 125.4333 | 2.2019 | 0.0042 | 12.6994 | 12.7036 |
| 125.4667 | 2.1647 | 0.0305 | 12.0419 | 12.0724 |
| 125.5 | 2.134 | 0.0042 | 11.0728 | 11.077 |
| 125.5333 | 2.0429 | 0.0174 | 10.1694 | 10.1867 |
| 125.5667 | -0.3515 | 0.0042 | 9.3528 | 9.357 |
| 125.6 | -0.3199 | 0.0305 | 8.5506 | 8.5812 |
| 125.6333 | -0.2873 | 0.0305 | 7.7866 | 7.8172 |
| 125.6667 | -0.258 | 0.0042 | 7.0424 | 7.0466 |
| 125.7 | -0.2221 | 0.0174 | 6.3349 | 6.3523 |
| 125.7333 | -0.0032 | 0.0042 | 0.4583 | 0.4625 |
| 125.7667 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 125.8 | -0.0075 | 0.0437 | 0.0033 | 0.047 |
| 125.8333 | -0.0013 | 0.0042 | 0.002 | 0.0062 |
| 125.8667 | -0.0062 | 0.0042 | 0.002 | 0.0062 |
| 125.9 | -0.0029 | 0.0174 | 0 | 0.0174 |
| 125.9333 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 125.9667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 126 | -0.0052 | 0.0174 | 0.0007 | 0.018 |
| 126.0333 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 126.0667 | -0.0072 | 0.0174 | 0.002 | 0.0194 |
| 126.1 | -0.0026 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| () | (1001) | (2.111) | (2.11) | (LI IVI) |
| 126.1333 | -0.0029 | 0.0174 | 0.002 | 0.0194 |
| 126.1667 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 126.2 | -0.0072 | 0.0042 | 0.002 | 0.0062 |
| 126.2333 | -0.0065 | 0.0305 | 0.0007 | 0.0312 |
| 126.2667 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 126.3 | -0.0042 | 0 | 0.002 | 0.002 |
| 126.3333 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 126.3667 | -0.0059 | 0.0174 | 0 | 0.0174 |
| 126.4 | -0.0072 | 0.0042 | 0.0007 | 0.0049 |
| 126.4333 | -0.0032 | 0.0174 | 0.0033 | 0.0207 |
| 126.4667 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 126.5 | -0.0059 | 0.0042 | 0.0007 | 0.0049 |
| 126.5333 | -0.0039 | 0.0174 | 0 | 0.0174 |
| 126.5667 | -0.0052 | 0.0305 | 0.002 | 0.0325 |
| 126.6 | -0.0082 | 0.0174 | 0.002 | 0.0194 |
| 126.6333 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 126.6667 | -0.0049 | 0 | 0.0007 | 0.0007 |
| 126.7 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 126.7333 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 126.7667 | -0.0069 | 0.0305 | 0.002 | 0.0325 |
| 126.8 | -0.0082 | 0.0174 | 0.002 | 0.0194 |
| 126.8333 | -0.0059 | 0.0042 | 0.0007 | 0.0049 |
| 126.8667 | -0.0032 | 0.0174 | 0.0007 | 0.018 |
| 126.9 | -0.0032 | 0.0305 | 0.0007 | 0.0312 |
| 126.9333 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 126.9667 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 127 | -0.0082 | 0.0174 | 0.002 | 0.0194 |
| 127.0333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 127.0667 | -0.0032 | 0.0174 | 0.0007 | 0.018 |
| 127.1 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 127.1333 | -0.0036 | 0.0174 | 0.0033 | 0.0207 |
| 127.1667 | -0.0042 | 0.0305 | 0.002 | 0.0325 |
| 127.2 | -0.0075 | 0.0042 | 0.0007 | 0.0049 |
| 127.2333 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 127.2667 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 127.3 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 127.3333 | -0.0075 | 0.0174 | 0.002 | 0.0194 |
| 127.3667 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 127.4 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 127.4333 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 127.4667 | -0.0062 | 0.0174 | 0.002 | 0.0194 |
| 127.5 | -0.0036 | 0.0042 | 0.0007 | 0.0049 |
| 127.5333 | -0.0059 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 127.5667 | -0.0016 | 0.0305 | 0.002 | 0.0325 |
| 127.5007 | -0.0016 | 0.0303 | 0.002 | 0.0323 |
| 127.6333 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 127.6667 | -0.0055 | 0.0305 | 0.0007 | 0.0134 |
| 127.7 | -0.0035 | 0.0174 | 0.0007 | 0.0312 |
| 127.7333 | -0.0022 | 0.0174 | 0.0007 | 0.0134 |
| 127.7667 | -0.0062 | 0.0305 | 0.002 | 0.0325 |
| 127.8 | -0.0055 | 0.0174 | 0.002 | 0.0194 |
| 127.8333 | -0.0039 | 0.0305 | 0.002 | 0.0325 |
| 127.8667 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 127.9 | -0.0052 | 0.0174 | 0.0033 | 0.0207 |
| 127.9333 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 127.9667 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 128 | -0.0039 | 0.0042 | 0.0007 | 0.0049 |
| 128.0333 | -0.0022 | 0.0174 | 0.002 | 0.0194 |
| 128.0667 | -0.0022 | 0.0042 | 0.002 | 0.0062 |
| 128.1 | -0.0062 | 0.0305 | 0.0007 | 0.0312 |
| 128.1333 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 128.1667 | -0.0042 | 0.0042 | 0.0007 | 0.0049 |
| 128.2 | -0.0059 | 0.0174 | 0.002 | 0.0194 |
| 128.2333 | -0.0032 | 0.0174 | 0.0033 | 0.0207 |
| 128.2667 | 0.0014 | 0.0305 | 0.002 | 0.0325 |
| 128.3 | 0.0001 | 0.0042 | 0.002 | 0.0062 |
| 128.3333 | -0.0013 | 0.0042 | 0.002 | 0.0062 |
| 128.3667 | -0.0019 | 0.0305 | 0.002 | 0.0325 |
| 128.4 | -0.0029 | 0.0042 | 0.002 | 0.0062 |
| 128.4333 | -0.0059 | 0.0174 | 0.0007 | 0.018 |
| 128.4667 | -0.0108 | 0.0305 | 0.002 | 0.0325 |
| 128.5 | -0.0118 | 0.0174 | 0.0033 | 0.0207 |
| 128.5333 | -0.0144 | 0.0174 | 0.0033 | 0.0207 |
| 128.5667 | -0.0151 | 0.0174 | 0 | 0.0174 |
| 128.6 | -0.0157 | 0.0042 | 0.0007 | 0.0049 |
| 128.6333 | -0.0187 | 0.0174 | 0.0033 | 0.0207 |
| 128.6667 | -0.0174 | 0.0042 | 0.0033 | 0.0075 |
| 128.7 | -0.0154 | 0.0174 | 0.0007 | 0.018 |
| 128.7333 | 0.0501 | 0.0174 | 0.002 | 0.0194 |
| 128.7667 | 0.112 | 0.0174 | 0.0007 | 0.018 |
| 128.8 | 0.1739 | 0.0305 | 0.8436 | 0.8741 |
| 128.8333 | 0.241 | 0.0174 | 0.9093 | 0.9267 |
| 128.8667 | 0.3167 | 0.0174 | 0.9935 | 1.0108 |
| 128.9 | 0.4033 | 0.0174 | 1.0855 | 1.1029 |
| 128.9333 | 0.482 | 0.0042 | 1.1736 | 1.1778 |
| 128.9667 | 0.56 | 0.0174 | 1.2696 | 1.287 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | | Ch 3 Low Flow | |
|----------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 420 | 0.6252 | 0.0174 | 1 2000 | 1 2000 |
| 129 | 0.6353 | 0.0174 | 1.3696 | 1.3869 |
| 129.0333 | 0.7078 | 0.0042 | 1.48 | 1.4842 |
| 129.0667 | 0.7795 | 0.0042 | 1.5879 | 1.5921 |
| 129.1 | 0.848 | 0.0174 | 1.7036 | 1.7209 |
| 129.1333 | 0.9158 | 0.0305 | 1.8285 | 1.859 |
| 129.1667 | 0.9813 | 0.0305 | 1.9429 | 1.9734 |
| 129.2 | 1.0468 | 0.0042 | 2.0639 | 2.0681 |
| 129.2333 | 1.1117 | 0.0042 | 2.1796 | 2.1838 |
| 129.2667 | 1.1745 | 0.0174 | 2.3058 | 2.3232 |
| 129.3 | 1.2371 | 0.0174 | 2.4281 | 2.4455 |
| 129.3333 | 1.2966 | 0.0174 | 2.5478 | 2.5651 |
| 129.3667 | 1.3536 | 0.0174 | 2.6688 | 2.6861 |
| 129.4 | 1.4109 | 0.0174 | 2.7897 | 2.8071 |
| 129.4333 | 1.4688 | 0.0174 | 2.916 | 2.9333 |
| 129.4667 | 1.5221 | 0.0174 | 3.037 | 3.0543 |
| 129.5 | 1.5807 | 0.0568 | 3.1685 | 3.2253 |
| 129.5333 | 1.6344 | 0.0305 | 3.2894 | 3.3199 |
| 129.5667 | 1.6893 | 0.0174 | 3.4091 | 3.4265 |
| 129.6 | 1.7381 | 0.0042 | 3.534 | 3.5382 |
| 129.6333 | 1.7894 | 0.0174 | 3.6524 | 3.6697 |
| 129.6667 | 1.8434 | 0.0042 | 3.7786 | 3.7828 |
| 129.7 | 1.8901 | 0.0305 | 3.9035 | 3.934 |
| 129.7333 | 1.9402 | 0.0305 | 4.014 | 4.0445 |
| 129.7667 | 1.9905 | 0.0174 | 4.1323 | 4.1497 |
| 129.8 | 2.0373 | 0.0305 | 4.2533 | 4.2838 |
| 129.8333 | 2.085 | 0.0042 | 4.3743 | 4.3785 |
| 129.8667 | 2.1321 | 0.0305 | 4.4913 | 4.5218 |
| 129.9 | 2.1811 | 0.0042 | 4.607 | 4.6112 |
| 129.9333 | 2.2246 | 0.0042 | 4.728 | 4.7322 |
| 129.9667 | 2.2657 | 0.0305 | 4.8503 | 4.8808 |
| 130 | 2.3088 | 0.0042 | 4.9673 | 4.9715 |
| 130.0333 | 2.3513 | 0.0042 | 5.0936 | 5.0978 |
| 130.0667 | 2.3901 | 0.0174 | 5.2067 | 5.224 |
| 130.1 | 2.4263 | 0.0174 | 5.3276 | 5.345 |
| 130.1333 | 2.451 | 0.0042 | 5.4499 | 5.4541 |
| 130.1667 | 2.4652 | 0.0174 | 5.563 | 5.5804 |
| 130.2 | 2.4652 | 0.0174 | 5.6682 | 5.6856 |
| 130.2333 | 2.4672 | 0.0174 | 5.7787 | 5.796 |
| 130.2667 | 2.4698 | 0.0174 | 5.8707 | 5.8881 |
| 130.3 | 2.4754 | 0.0042 | 5.9746 | 5.9788 |
| 130.3333 | 2.4764 | 0.0042 | 6.0693 | 6.0735 |
| 130.3667 | 2.4777 | 0.0174 | 6.1797 | 6.1971 |
| 130.4 | 2.4767 | 0.0174 | 6.2784 | 6.2957 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 130.4333 | 2.4757 | 0.0174 | 6.3704 | 6.3878 |
| 130.4667 | 2.4761 | 0.0174 | 6.4559 | 6.4732 |
| 130.5 | 2.4744 | 0.0305 | 6.5453 | 6.5758 |
| 130.5333 | 2.4688 | 0.0174 | 6.6374 | 6.6547 |
| 130.5667 | 2.4642 | 0.0174 | 6.7347 | 6.752 |
| 130.6 | 2.4619 | 0.0174 | 6.8162 | 6.8335 |
| 130.6333 | 2.4576 | 0.0174 | 6.9043 | 6.9217 |
| 130.6667 | 2.456 | 0.0042 | 6.995 | 6.9992 |
| 130.7 | 2.4524 | 0.0174 | 7.0647 | 7.0821 |
| 130.7333 | 2.4517 | 0.0174 | 7.1528 | 7.1702 |
| 130.7667 | 2.4474 | 0.0174 | 7.2278 | 7.2451 |
| 130.8 | 2.4468 | 0.0042 | 7.3093 | 7.3135 |
| 130.8333 | 2.4454 | 0 | 7.3895 | 7.3895 |
| 130.8667 | 2.4458 | 0.0174 | 7.4553 | 7.4726 |
| 130.9 | 2.4421 | 0.0174 | 7.5342 | 7.5515 |
| 130.9333 | 2.4438 | 0.0174 | 7.5933 | 7.6107 |
| 130.9667 | 2.4435 | 0.0305 | 7.6722 | 7.7027 |
| 131 | 2.4392 | 0.0174 | 7.7327 | 7.7501 |
| 131.0333 | 2.4402 | 0.0305 | 7.7919 | 7.8224 |
| 131.0667 | 2.4372 | 0.0042 | 7.8524 | 7.8566 |
| 131.1 | 2.4398 | 0.0174 | 7.9168 | 7.9342 |
| 131.1333 | 2.4389 | 0.0305 | 7.9878 | 8.0183 |
| 131.1667 | 2.4405 | 0.0042 | 8.0325 | 8.0368 |
| 131.2 | 2.4392 | 0.0174 | 8.1022 | 8.1196 |
| 131.2333 | 2.4392 | 0.0174 | 8.1654 | 8.1827 |
| 131.2667 | 2.4392 | 0.0174 | 8.2166 | 8.234 |
| 131.3 | 2.4395 | 0.0174 | 8.2784 | 8.2958 |
| 131.3333 | 2.4359 | 0.0174 | 8.331 | 8.3484 |
| 131.3667 | 2.4405 | 0.0305 | 8.3863 | 8.4168 |
| 131.4 | 2.4372 | 0.0305 | 8.4376 | 8.4681 |
| 131.4333 | 2.4385 | 0.0042 | 8.4875 | 8.4917 |
| 131.4667 | 2.4395 | 0 | 8.5401 | 8.5401 |
| 131.5 | 2.4412 | 0.0042 | 8.5901 | 8.5943 |
| 131.5333 | 2.4385 | 0.0305 | 8.6493 | 8.6798 |
| 131.5667 | 2.4379 | 0.0042 | 8.7019 | 8.7061 |
| 131.6 | 2.4372 | 0.0305 | 8.7453 | 8.7758 |
| 131.6333 | 2.4398 | 0.0174 | 8.7965 | 8.8139 |
| 131.6667 | 2.4398 | 0.0174 | 8.8413 | 8.8586 |
| 131.7 | 2.4392 | 0.0042 | 8.886 | 8.8902 |
| 131.7333 | 2.4421 | 0.0174 | 8.9359 | 8.9533 |
| 131.7667 | 2.4431 | 0.0305 | 8.9728 | 9.0033 |
| 131.8 | 2.4398 | 0.0174 | 9.024 | 9.0414 |
| 131.8333 | 2.4435 | 0.0174 | 9.0727 | 9.09 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 131.8667 | 2.4412 | 0.0042 | 9.1095 | 9.1137 |
| 131.9 | 2.4402 | 0.0174 | 9.1529 | 9.1703 |
| 131.9333 | 2.4333 | 0.0174 | 9.1976 | 9.215 |
| 131.9667 | 2.4339 | 0.0174 | 9.2318 | 9.2492 |
| 132 | 2.4326 | 0.0042 | 9.2778 | 9.282 |
| 132.0333 | 2.427 | 0.0042 | 9.3199 | 9.3241 |
| 132.0667 | 2.4221 | 0.0174 | 9.3541 | 9.3715 |
| 132.1 | 2.4191 | 0.0305 | 9.3922 | 9.4227 |
| 132.1333 | 2.4168 | 0.0174 | 9.433 | 9.4503 |
| 132.1667 | 2.4178 | 0.0174 | 9.4659 | 9.4832 |
| 132.2 | 2.4152 | 0.0042 | 9.5145 | 9.5187 |
| 132.2333 | 2.4129 | 0.0042 | 9.5474 | 9.5516 |
| 132.2667 | 2.4086 | 0.0174 | 9.5763 | 9.5937 |
| 132.3 | 2.4082 | 0.0174 | 9.6053 | 9.6226 |
| 132.3333 | 2.4086 | 0.0174 | 9.6539 | 9.6713 |
| 132.3667 | 2.4086 | 0.0042 | 9.6855 | 9.6897 |
| 132.4 | 2.4082 | 0.0174 | 9.7183 | 9.7357 |
| 132.4333 | 2.4089 | 0.0042 | 9.7565 | 9.7607 |
| 132.4667 | 2.4082 | 0 | 9.7801 | 9.7801 |
| 132.5 | 2.4115 | 0.0305 | 9.813 | 9.8435 |
| 132.5333 | 2.4112 | 0.0042 | 9.8406 | 9.8448 |
| 132.5667 | 2.4119 | 0.0174 | 9.8722 | 9.8896 |
| 132.6 | 2.4122 | 0.0042 | 9.9143 | 9.9185 |
| 132.6333 | 2.4158 | 0.0042 | 9.9445 | 9.9487 |
| 132.6667 | 2.4109 | 0.0174 | 9.9761 | 9.9934 |
| 132.7 | 2.4115 | 0.0174 | 10.0116 | 10.0289 |
| 132.7333 | 2.4168 | 0.0042 | 10.0431 | 10.0473 |
| 132.7667 | 2.4155 | 0.0174 | 10.0642 | 10.0815 |
| 132.8 | 2.4129 | 0.0042 | 10.1036 | 10.1078 |
| 132.8333 | 2.4175 | 0.0305 | 10.122 | 10.1525 |
| 132.8667 | 2.4148 | 0.0305 | 10.1694 | 10.1999 |
| 132.9 | 2.4168 | 0.0174 | 10.1852 | 10.2025 |
| 132.9333 | 2.4155 | 0.0174 | 10.2049 | 10.2222 |
| 132.9667 | 2.4155 | 0.0174 | 10.2509 | 10.2683 |
| 133 | 2.4161 | 0.0042 | 10.2733 | 10.2775 |
| 133.0333 | 2.4142 | 0.0174 | 10.3022 | 10.3195 |
| 133.0667 | 2.4171 | 0.0174 | 10.3285 | 10.3458 |
| 133.1 | 2.4152 | 0.0174 | 10.364 | 10.3814 |
| 133.1333 | 2.4175 | 0.0042 | 10.3929 | 10.3971 |
| 133.1667 | 2.4188 | 0.0174 | 10.4074 | 10.4247 |
| 133.2 | 2.4227 | 0.0042 | 10.4508 | 10.455 |
| 133.2333 | 2.4204 | 0.0042 | 10.4771 | 10.4813 |
| 133.2667 | 2.4214 | 0.0174 | 10.4902 | 10.5076 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow |
|---------------|---------|-------------------------|------------------------|------------|
| (min) | (psi) | (LPIVI) | (LPIVI) | (LPIVI) |
| 133.3 | 2.4234 | 0.0042 | 10.5284 | 10.5326 |
| 133.3333 | 2.4217 | 0.0174 | 10.5455 | 10.5628 |
| 133.3667 | 2,425 | 0.0174 | 10.5691 | 10.5865 |
| 133.4 | 2.4263 | 0.0042 | 10.602 | 10.6062 |
| 133.4333 | 2.426 | 0.0042 | 10.627 | 10.6312 |
| 133.4667 | 2.4277 | 0.0174 | 10.6533 | 10.6706 |
| 133.5 | 2.43 | 0.0305 | 10.6796 | 10.7101 |
| 133.5333 | 2.4283 | 0.0174 | 10.7019 | 10.7193 |
| 133.5667 | 2.4273 | 0.0305 | 10.7256 | 10.7561 |
| 133.6 | 2.427 | 0.0174 | 10.7453 | 10.7627 |
| 133.6333 | 2.4293 | 0.0174 | 10.7795 | 10.7969 |
| 133.6667 | 2.431 | 0.0042 | 10.7979 | 10.8021 |
| 133.7 | 2.4293 | 0.0174 | 10.8282 | 10.8455 |
| 133.7333 | 2.4319 | 0.0305 | 10.8426 | 10.8732 |
| 133.7667 | 2.43 | 0.0042 | 10.8663 | 10.8705 |
| 133.8 | 2.4336 | 0.0305 | 10.886 | 10.9165 |
| 133.8333 | 2.4303 | 0.0174 | 10.9084 | 10.9258 |
| 133.8667 | 2.4306 | 0.0174 | 10.9386 | 10.956 |
| 133.9 | 2.4323 | 0.0174 | 10.9584 | 10.9757 |
| 133.9333 | 2.431 | 0.0174 | 10.9741 | 10.9915 |
| 133.9667 | 2.4293 | 0.0305 | 11.011 | 11.0415 |
| 134 | 2.4313 | 0.0174 | 11.0189 | 11.0362 |
| 134.0333 | 2.43 | 0.0174 | 11.0557 | 11.073 |
| 134.0667 | 2.4326 | 0.0174 | 11.0662 | 11.0835 |
| 134.1 | 2.4313 | 0.0174 | 11.0899 | 11.1072 |
| 134.1333 | 2.4313 | 0 | 11.1227 | 11.1227 |
| 134.1667 | 2.4323 | 0.0042 | 11.1398 | 11.144 |
| 134.2 | 2.4333 | 0.0042 | 11.1596 | 11.1638 |
| 134.2333 | 2.4339 | 0.0042 | 11.1635 | 11.1677 |
| 134.2667 | 2.43 | 0.0042 | 11.1766 | 11.1809 |
| 134.3 | 2.4303 | 0.0042 | 11.2056 | 11.2098 |
| 134.3333 | 2.4296 | 0.0042 | 11.2214 | 11.2256 |
| 134.3667 | 2.4313 | 0.0174 | 11.2411 | 11.2584 |
| 134.4 | 2.4306 | 0.0042 | 11.2582 | 11.2624 |
| 134.4333 | 2.43 | 0.0174 | 11.2792 | 11.2966 |
| 134.4667 | 2.4296 | 0.0174 | 11.3042 | 11.3216 |
| 134.5 | 2.4277 | 0.0174 | 11.3213 | 11.3387 |
| 134.5333 | 2.429 | 0.0305 | 11.3423 | 11.3728 |
| 134.5667 | 2.4316 | 0.0174 | 11.3529 | 11.3702 |
| 134.6 | 2.429 | 0.0042 | 11.3778 | 11.382 |
| 134.6333 | 2.427 | 0.0042 | 11.4002 | 11.4044 |
| 134.6667 | 2.4306 | 0.0174 | 11.4133 | 11.4307 |
| 134.7 | 2.428 | 0.0174 | 11.4278 | 11.4452 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| | | | | |
| 134.7333 | 2.429 | 0.0305 | 11.441 | 11.4715 |
| 134.7667 | 2.4287 | 0.0174 | 11.4633 | 11.4807 |
| 134.8 | 2.4244 | 0.0305 | 11.4817 | 11.5122 |
| 134.8333 | 2.4254 | 0.0042 | 11.5001 | 11.5043 |
| 134.8667 | 2.4244 | 0.0042 | 11.512 | 11.5162 |
| 134.9 | 2.426 | 0.0042 | 11.5383 | 11.5425 |
| 134.9333 | 2.425 | 0.0174 | 11.5554 | 11.5727 |
| 134.9667 | 2.4237 | 0.0305 | 11.5764 | 11.6069 |
| 135 | 2.4244 | 0.0174 | 11.5948 | 11.6122 |
| 135.0333 | 2.424 | 0.0042 | 11.6093 | 11.6135 |
| 135.0667 | 2.4217 | 0.0174 | 11.6185 | 11.6358 |
| 135.1 | 2.4247 | 0.0437 | 11.6343 | 11.6779 |
| 135.1333 | 2.4221 | 0.0042 | 11.6592 | 11.6635 |
| 135.1667 | 2.4194 | 0.0174 | 11.679 | 11.6963 |
| 135.2 | 2.4221 | 0.0042 | 11.6816 | 11.6858 |
| 135.2333 | 2.4201 | 0.0042 | 11.7013 | 11.7055 |
| 135.2667 | 2.4175 | 0.0174 | 11.7171 | 11.7345 |
| 135.3 | 2.3371 | 0.0305 | 11.7224 | 11.7529 |
| 135.3333 | 2.2621 | 0.0174 | 11.725 | 11.7424 |
| 135.3667 | 2.1874 | 0.0174 | 11.7289 | 11.7463 |
| 135.4 | -0.4591 | 0.0042 | 11.7263 | 11.7305 |
| 135.4333 | -0.4555 | 0.0042 | 11.725 | 11.7292 |
| 135.4667 | -0.4542 | 0.0042 | 11.704 | 11.7082 |
| 135.5 | -0.4529 | 0.0305 | 11.6934 | 11.7239 |
| 135.5333 | -0.4532 | 0.0042 | 11.6685 | 11.6727 |
| 135.5667 | -0.4539 | 0.0174 | 11.6395 | 11.6569 |
| 135.6 | -0.4493 | 0.0174 | 11.6145 | 11.6319 |
| 135.6333 | -0.4512 | 0.0042 | 11.5672 | 11.5714 |
| 135.6667 | -0.414 | 0.0174 | 10.8597 | 10.8771 |
| 135.7 | -0.3762 | 0.0174 | 0 | 0.0174 |
| 135.7333 | 0.0129 | 0.0042 | 0.002 | 0.0062 |
| 135.7667 | -0.0065 | 0.0042 | 0.0007 | 0.0049 |
| 135.8 | -0.0049 | 0.0305 | 0.0033 | 0.0338 |
| 135.8333 | -0.0072 | 0.0042 | 0.002 | 0.0062 |
| 135.8667 | -0.0072 | 0.0174 | 0.0007 | 0.018 |
| 135.9 | -0.0029 | 0.0305 | 0.002 | 0.0325 |
| 135.9333 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 135.9667 | -0.0055 | 0.0305 | 0.0007 | 0.0312 |
| 136 | -0.0092 | 0.0174 | 0.0007 | 0.018 |
| 136.0333 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 136.0667 | -0.0055 | 0.0042 | 0.0007 | 0.0049 |
| 136.1 | -0.0022 | 0.0174 | 0.002 | 0.0194 |
| 136.1333 | -0.0049 | 0.0305 | 0.002 | 0.0325 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 136.1667 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 136.2 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 136.2333 | -0.0016 | 0.0042 | 0.0007 | 0.0049 |
| 136.2667 | -0.0042 | 0.0042 | 0.0007 | 0.0049 |
| 136.3 | -0.0019 | 0.0042 | 0.002 | 0.0062 |
| 136.3333 | -0.0029 | 0.0174 | 0.002 | 0.0194 |
| 136.3667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 136.4 | -0.0042 | 0.0042 | 0.002 | 0.0062 |
| 136.4333 | -0.0055 | 0.0174 | 0.0033 | 0.0207 |
| 136.4667 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 136.5 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 136.5333 | -0.0055 | 0.0305 | 0.002 | 0.0325 |
| 136.5667 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 136.6 | -0.0078 | 0.0305 | 0.0007 | 0.0312 |
| 136.6333 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 136.6667 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 136.7 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 136.7333 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 136.7667 | -0.0049 | 0.0174 | 0.0007 | 0.018 |
| 136.8 | -0.0022 | 0.0042 | 0.0007 | 0.0049 |
| 136.8333 | -0.0049 | 0.0042 | 0.0033 | 0.0075 |
| 136.8667 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 136.9 | -0.0065 | 0 | 0.0007 | 0.0007 |
| 136.9333 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 136.9667 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 137 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 137.0333 | -0.0039 | 0.0174 | 0.0033 | 0.0207 |
| 137.0667 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 137.1 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 137.1333 | -0.0039 | 0 | 0.0007 | 0.0007 |
| 137.1667 | -0.0055 | 0.0174 | 0.0007 | 0.018 |
| 137.2 | -0.0059 | 0.0174 | 0.0033 | 0.0207 |
| 137.2333 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 137.2667 | -0.0092 | 0.0174 | 0.002 | 0.0194 |
| 137.3 | -0.0046 | 0.0305 | 0.0007 | 0.0312 |
| 137.3333 | -0.0026 | 0.0174 | 0.0033 | 0.0207 |
| 137.3667 | -0.0059 | 0.0042 | 0.002 | 0.0062 |
| 137.4 | -0.0019 | 0.0042 | 0.002 | 0.0062 |
| 137.4333 | -0.0046 | 0.0042 | 0.0033 | 0.0075 |
| 137.4667 | -0.0052 | 0.0174 | 0.0007 | 0.018 |
| 137.5 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 137.5333 | -0.0062 | 0.0305 | 0.002 | 0.0325 |
| 137.5667 | -0.0072 | 0.0042 | 0.0007 | 0.0049 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 137.6 | -0.0065 | 0.0174 | 0.0033 | 0.0207 |
| 137.6333 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 137.6667 | -0.0052 | 0.0305 | 0.002 | 0.0325 |
| 137.7 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 137.7333 | -0.0055 | 0.0174 | 0.0007 | 0.018 |
| 137.7667 | -0.0032 | 0.0174 | 0 | 0.0174 |
| 137.8 | -0.0072 | 0.0305 | 0.002 | 0.0325 |
| 137.8333 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 137.8667 | -0.0036 | 0.0042 | 0.002 | 0.0062 |
| 137.9 | -0.0046 | 0.0305 | 0.002 | 0.0325 |
| 137.9333 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 137.9667 | -0.0059 | 0 | 0.0007 | 0.0007 |
| 138 | -0.0049 | 0.0305 | 0.0033 | 0.0338 |
| 138.0333 | -0.0059 | 0.0042 | 0.0007 | 0.0049 |
| 138.0667 | -0.0046 | 0.0042 | 0.0007 | 0.0049 |
| 138.1 | -0.0036 | 0.0174 | 0.0033 | 0.0207 |
| 138.1333 | -0.0046 | 0.0305 | 0.002 | 0.0325 |
| 138.1667 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 138.2 | -0.0062 | 0.0042 | 0.002 | 0.0062 |
| 138.2333 | -0.0065 | 0.0174 | 0.0033 | 0.0207 |
| 138.2667 | -0.0052 | 0.0305 | 0.0033 | 0.0338 |
| 138.3 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 138.3333 | -0.0026 | 0.0174 | 0.0007 | 0.018 |
| 138.3667 | -0.0029 | 0.0042 | 0.002 | 0.0062 |
| 138.4 | -0.0039 | 0.0042 | 0.0033 | 0.0075 |
| 138.4333 | -0.0039 | 0 | 0.002 | 0.002 |
| 138.4667 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 138.5 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 138.5333 | -0.0062 | 0.0305 | 0.0007 | 0.0312 |
| 138.5667 | -0.0055 | 0.0174 | 0.0007 | 0.018 |
| 138.6 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 138.6333 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 138.6667 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 138.7 | -0.0049 | 0.0305 | 0.0007 | 0.0312 |
| 138.7333 | -0.0052 | 0.0305 | 0.002 | 0.0325 |
| 138.7667 | -0.0032 | 0.0305 | 0.002 | 0.0325 |
| 138.8 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 138.8333 | -0.0042 | 0.0174 | 0.0007 | 0.018 |
| 138.8667 | -0.0032 | 0.0174 | 0.002 | 0.0194 |
| 138.9 | -0.0036 | 0.0174 | 0.002 | 0.0194 |
| 138.9333 | -0.0049 | 0.0174 | 0.002 | 0.0194 |
| 138.9667 | -0.0075 | 0.0174 | 0.0007 | 0.018 |
| 139 | -0.0069 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|----------|---------|--------|---------------|--------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 139.0333 | -0.0085 | 0.0305 | 0.002 | 0.0325 |
| 139.0667 | -0.0065 | 0.0305 | 0.002 | 0.0325 |
| 139.0667 | -0.0059 | 0.0305 | 0.002 | 0.0325 |
| 139.1333 | -0.0052 | 0.0303 | 0.002 | 0.0323 |
| 139.1667 | -0.0052 | 0.0174 | 0.002 | 0.0194 |
| 139.2 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 139.2333 | -0.0046 | 0.0174 | 0.0033 | 0.0207 |
| 139.2667 | -0.0016 | 0.0174 | 0.003 | 0.0194 |
| 139.3 | -0.0046 | 0.0174 | 0.0046 | 0.022 |
| 139.3333 | -0.0026 | 0.0042 | 0.0007 | 0.0049 |
| 139.3667 | -0.0049 | 0.0042 | 0.0007 | 0.0049 |
| 139.4 | -0.0042 | 0.0174 | 0.002 | 0.0194 |
| 139.4333 | -0.0022 | 0.0042 | 0.002 | 0.0062 |
| 139.4667 | -0.0026 | 0.0042 | 0.0007 | 0.0049 |
| 139.5 | -0.0029 | 0.0174 | 0.0007 | 0.018 |
| 139.5333 | -0.0029 | 0.0174 | 0.0007 | 0.018 |
| 139.5667 | -0.0029 | 0.0305 | 0.0033 | 0.0338 |
| 139.6 | -0.0036 | 0.0174 | 0.0007 | 0.018 |
| 139.6333 | -0.0039 | 0.0174 | 0.0007 | 0.018 |
| 139.6667 | -0.0039 | 0.0305 | 0.002 | 0.0325 |
| 139.7 | -0.0046 | 0.0042 | 0.0007 | 0.0049 |
| 139.7333 | -0.0022 | 0.0174 | 0.002 | 0.0194 |
| 139.7667 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 139.8 | -0.0042 | 0.0042 | 0.0033 | 0.0075 |
| 139.8333 | -0.0065 | 0.0174 | 0.002 | 0.0194 |
| 139.8667 | -0.0049 | 0.0174 | 0.0033 | 0.0207 |
| 139.9 | -0.0049 | 0.0174 | 0.0033 | 0.0207 |
| 139.9333 | -0.0019 | 0.0174 | 0.002 | 0.0194 |
| 139.9667 | -0.0019 | 0.0042 | 0.0007 | 0.0049 |
| 140 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 140.0333 | -0.0072 | 0.0305 | 0.002 | 0.0325 |
| 140.0667 | -0.0032 | 0.0042 | 0.002 | 0.0062 |
| 140.1 | -0.0052 | 0.0042 | 0.0007 | 0.0049 |
| 140.1333 | -0.0029 | 0.0174 | 0.002 | 0.0194 |
| 140.1667 | -0.0046 | 0.0042 | 0.002 | 0.0062 |
| 140.2 | -0.0052 | 0.0042 | 0.002 | 0.0062 |
| 140.2333 | -0.0062 | 0.0174 | 0.0033 | 0.0207 |
| 140.2667 | -0.0046 | 0.0174 | 0.002 | 0.0194 |
| 140.3 | -0.0039 | 0.0042 | 0.002 | 0.0062 |
| 140.3333 | -0.0055 | 0.0042 | 0.002 | 0.0062 |
| 140.3667 | -0.0046 | 0.0174 | 0.0007 | 0.018 |
| 140.4 | -0.0095 | 0.0042 | 0.002 | 0.0062 |
| 140.4333 | -0.0088 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 140.4667 | -0.0085 | 0.0305 | 0.0033 | 0.0338 |
| 140.5 | -0.0092 | 0.0174 | 0.0007 | 0.018 |
| 140.5333 | -0.0138 | 0.0305 | 0.0033 | 0.0338 |
| 140.5667 | -0.0118 | 0.0174 | 0.002 | 0.0194 |
| 140.6 | -0.0111 | 0.0174 | 0.0046 | 0.022 |
| 140.6333 | -0.0128 | 0.0305 | 0.0033 | 0.0338 |
| 140.6667 | -0.0141 | 0.0174 | 0.002 | 0.0194 |
| 140.7 | -0.0154 | 0.0042 | 0.0033 | 0.0075 |
| 140.7333 | -0.0128 | 0.0174 | 0.002 | 0.0194 |
| 140.7667 | -0.0157 | 0.0305 | 0.0007 | 0.0312 |
| 140.8 | -0.0141 | 0.0174 | 0.002 | 0.0194 |
| 140.8333 | -0.0131 | 0.0305 | 0.0033 | 0.0338 |
| 140.8667 | -0.0171 | 0.0042 | 0.0033 | 0.0075 |
| 140.9 | -0.0167 | 0.0042 | 0.002 | 0.0062 |
| 140.9333 | -0.0134 | 0.0174 | 0.002 | 0.0194 |
| 140.9667 | -0.0167 | 0.0042 | 0 | 0.0042 |
| 141 | -0.018 | 0.0305 | 0.002 | 0.0325 |
| 141.0333 | -0.0161 | 0.0174 | 0.0007 | 0.018 |
| 141.0667 | -0.018 | 0.0174 | 0.0007 | 0.018 |
| 141.1 | -0.0167 | 0.0174 | 0.002 | 0.0194 |
| 141.1333 | -0.0069 | 0.0174 | 0.002 | 0.0194 |
| 141.1667 | 0.0544 | 0.0042 | 0.0007 | 0.0049 |
| 141.2 | 0.1205 | 0 | 0.0033 | 0.0033 |
| 141.2333 | 0.2002 | 0.0174 | 0.002 | 0.0194 |
| 141.2667 | 0.2868 | 0.0042 | 0.002 | 0.0062 |
| 141.3 | 0.373 | 0.0174 | 0.0033 | 0.0207 |
| 141.3333 | 0.455 | 0.0042 | 0.0007 | 0.0049 |
| 141.3667 | 0.5356 | 0.0174 | 0.8765 | 0.8938 |
| 141.4 | 0.614 | 0.0042 | 0.9724 | 0.9767 |
| 141.4333 | 0.6893 | 0.0305 | 1.0724 | 1.1029 |
| 141.4667 | 0.7608 | 0.0174 | 1.1776 | 1.1949 |
| 141.5 | 0.8305 | 0.0305 | 1.2894 | 1.3199 |
| 141.5333 | 0.8993 | 0.0174 | 1.4038 | 1.4211 |
| 141.5667 | 0.9658 | 0.0305 | 1.5247 | 1.5552 |
| 141.6 | 1.0304 | 0.0174 | 1.647 | 1.6644 |
| 141.6333 | 1.0975 | 0.0305 | 1.7693 | 1.7998 |
| 141.6667 | 1.1594 | 0.0174 | 1.8903 | 1.9077 |
| 141.7 | 1.2206 | 0.0174 | 2.0192 | 2.0365 |
| 141.7333 | 1.2825 | 0.0174 | 2.1428 | 2.1601 |
| 141.7667 | 1.3417 | 0.0174 | 2.2664 | 2.2837 |
| 141.8 | 1.397 | 0.0305 | 2.4018 | 2.4323 |
| 141.8333 | 1.4546 | 0.0174 | 2.5228 | 2.5402 |
| 141.8667 | 1.5142 | 0.0042 | 2.6582 | 2.6625 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 141.9 | 1.5669 | 0.0305 | 2.7805 | 2.811 |
| 141.9333 | 1.6186 | 0.0174 | 2.912 | 2.9294 |
| 141.9667 | 1.6752 | 0.0174 | 3.0422 | 3.0596 |
| 142 | 1.7288 | 0.0305 | 3.1671 | 3.1976 |
| 142.0333 | 1.7776 | 0.0042 | 3.2986 | 3.3028 |
| 142.0667 | 1.8306 | 0.0042 | 3.4249 | 3.4291 |
| 142.1 | 1.8789 | 0.0174 | 3.5551 | 3.5724 |
| 142.1333 | 1.9273 | 0.0042 | 3.6787 | 3.6829 |
| 142.1667 | 1.9751 | 0.0305 | 3.8088 | 3.8394 |
| 142.2 | 2.0228 | 0.0174 | 3.9482 | 3.9656 |
| 142.2333 | 2.0679 | 0.0174 | 4.0705 | 4.0879 |
| 142.2667 | 2.114 | 0.0042 | 4.1941 | 4.1983 |
| 142.3 | 2.1594 | 0.0174 | 4.3204 | 4.3377 |
| 142.3333 | 2.2025 | 0.0174 | 4.4532 | 4.4705 |
| 142.3667 | 2.2456 | 0.0042 | 4.5794 | 4.5836 |
| 142.4 | 2.2884 | 0.0174 | 4.7135 | 4.7309 |
| 142.4333 | 2.3315 | 0.0174 | 4.8358 | 4.8532 |
| 142.4667 | 2.3724 | 0.0174 | 4.9608 | 4.9781 |
| 142.5 | 2.4161 | 0.0174 | 5.0857 | 5.103 |
| 142.5333 | 2.4461 | 0.0042 | 5.2185 | 5.2227 |
| 142.5667 | 2.4524 | 0.0174 | 5.3395 | 5.3568 |
| 142.6 | 2.4491 | 0.0174 | 5.4736 | 5.491 |
| 142.6333 | 2.4435 | 0.0174 | 5.5841 | 5.6014 |
| 142.6667 | 2.4438 | 0 | 5.7037 | 5.7037 |
| 142.7 | 2.4425 | 0.0174 | 5.8116 | 5.8289 |
| 142.7333 | 2.4389 | 0.0174 | 5.9023 | 5.9196 |
| 142.7667 | 2.4418 | 0.0174 | 6.0141 | 6.0314 |
| 142.8 | 2.4402 | 0.0042 | 6.1127 | 6.1169 |
| 142.8333 | 2.4412 | 0.0174 | 6.2218 | 6.2392 |
| 142.8667 | 2.4428 | 0.0042 | 6.3165 | 6.3207 |
| 142.9 | 2.4448 | 0.0174 | 6.4164 | 6.4338 |
| 142.9333 | 2.4451 | 0.0174 | 6.5085 | 6.5258 |
| 142.9667 | 2.4431 | 0.0174 | 6.6137 | 6.631 |
| 143 | 2.4464 | 0.0305 | 6.707 | 6.7376 |
| 143.0333 | 2.4484 | 0.0305 | 6.8096 | 6.8401 |
| 143.0667 | 2.4537 | 0.0042 | 6.9004 | 6.9046 |
| 143.1 | 2.4537 | 0.0174 | 6.9924 | 7.0098 |
| 143.1333 | 2.4576 | 0.0305 | 7.0766 | 7.1071 |
| 143.1667 | 2.4579 | 0.0174 | 7.1712 | 7.1886 |
| 143.2 | 2.4629 | 0.0174 | 7.258 | 7.2754 |
| 143.2333 | 2.4649 | 0.0305 | 7.3566 | 7.3872 |
| 143.2667 | 2.4668 | 0 | 7.429 | 7.429 |
| 143.3 | 2.4606 | 0.0305 | 7.5197 | 7.5502 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 143.3333 | 2.4586 | 0.0042 | 7.5947 | 7.5989 |
| 143.3667 | 2.4497 | 0.0042 | 7.6709 | 7.6751 |
| 143.4 | 2.4474 | 0.0305 | 7.7551 | 7.7856 |
| 143.4333 | 2.4448 | 0.0042 | 7.8221 | 7.8264 |
| 143.4667 | 2.4385 | 0.0305 | 7.8892 | 7.9197 |
| 143.5 | 2.4362 | 0.0042 | 7.9721 | 7.9763 |
| 143.5333 | 2.4319 | 0.0305 | 8.0352 | 8.0657 |
| 143.5667 | 2.4316 | 0.0174 | 8.1075 | 8.1249 |
| 143.6 | 2.4306 | 0.0174 | 8.1719 | 8.1893 |
| 143.6333 | 2.4267 | 0.0042 | 8.2429 | 8.2471 |
| 143.6667 | 2.4227 | 0.0174 | 8.3074 | 8.3247 |
| 143.7 | 2.4201 | 0.0042 | 8.3718 | 8.376 |
| 143.7333 | 2.4211 | 0.0305 | 8.4349 | 8.4654 |
| 143.7667 | 2.4191 | 0.0174 | 8.5059 | 8.5233 |
| 143.8 | 2.4178 | 0.0174 | 8.5585 | 8.5759 |
| 143.8333 | 2.4171 | 0.0174 | 8.623 | 8.6403 |
| 143.8667 | 2.4211 | 0.0174 | 8.6756 | 8.6929 |
| 143.9 | 2.426 | 0.0042 | 8.7347 | 8.7389 |
| 143.9333 | 2.4323 | 0.0305 | 8.7992 | 8.8297 |
| 143.9667 | 2.4346 | 0.0042 | 8.8452 | 8.8494 |
| 144 | 2.4339 | 0.0042 | 8.9096 | 8.9138 |
| 144.0333 | 2.4372 | 0.0174 | 8.9701 | 8.9875 |
| 144.0667 | 2.4339 | 0.0042 | 9.0188 | 9.023 |
| 144.1 | 2.4366 | 0.0042 | 9.0793 | 9.0835 |
| 144.1333 | 2.4342 | 0.0042 | 9.1227 | 9.1269 |
| 144.1667 | 2.4352 | 0.0174 | 9.1805 | 9.1979 |
| 144.2 | 2.4346 | 0.0174 | 9.2213 | 9.2386 |
| 144.2333 | 2.4389 | 0.0042 | 9.2831 | 9.2873 |
| 144.2667 | 2.4375 | 0.0305 | 9.3396 | 9.3701 |
| 144.3 | 2.4369 | 0.0174 | 9.383 | 9.4004 |
| 144.3333 | 2.4375 | 0.0305 | 9.4277 | 9.4582 |
| 144.3667 | 2.4402 | 0.0174 | 9.4777 | 9.4951 |
| 144.4 | 2.4405 | 0.0042 | 9.5329 | 9.5371 |
| 144.4333 | 2.4385 | 0.0174 | 9.5605 | 9.5779 |
| 144.4667 | 2.4375 | 0.0305 | 9.6184 | 9.6489 |
| 144.5 | 2.4398 | 0.0042 | 9.6631 | 9.6673 |
| 144.5333 | 2.4389 | 0.0174 | 9.7118 | 9.7291 |
| 144.5667 | 2.4379 | 0.0042 | 9.7604 | 9.7646 |
| 144.6 | 2.4385 | 0.0174 | 9.8038 | 9.8212 |
| 144.6333 | 2.4398 | 0.0042 | 9.8498 | 9.854 |
| 144.6667 | 2.4379 | 0.0174 | 9.8893 | 9.9066 |
| 144.7 | 2.4398 | 0.0042 | 9.9327 | 9.9369 |
| 144.7333 | 2.4375 | 0.0174 | 9.9813 | 9.9987 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | |
|----------|---------|--------|---------------|---------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 144.7667 | 2.4418 | 0.0042 | 10.0195 | 10.0237 |
| 144.7007 | 2.4385 | 0.0042 | 10.0155 | 10.0237 |
| 144.8333 | 2.4385 | 0.0174 | 10.1076 | 10.1249 |
| 144.8667 | 2.4379 | 0.0174 | 10.1391 | 10.1565 |
| 144.9 | 2.4408 | 0.0174 | 10.1812 | 10.1986 |
| 144.9333 | 2.4389 | 0.0042 | 10.2272 | 10.2314 |
| 144.9667 | 2.4379 | 0.0042 | 10.2719 | 10.2762 |
| 145 | 2.4402 | 0.0305 | 10.3022 | 10.3327 |
| 145.0333 | 2.4392 | 0.0042 | 10.3495 | 10.3537 |
| 145.0667 | 2.4415 | 0.0042 | 10.389 | 10.3932 |
| 145.1 | 2.4421 | 0.0174 | 10.4113 | 10.4287 |
| 145.1333 | 2.4385 | 0.0042 | 10.4521 | 10.4563 |
| 145.1667 | 2.4392 | 0.0174 | 10.5008 | 10.5181 |
| 145.2 | 2.4366 | 0.0174 | 10.5323 | 10.5497 |
| 145.2333 | 2.4395 | 0.0174 | 10.5665 | 10.5839 |
| 145.2667 | 2.4375 | 0.0305 | 10.602 | 10.6325 |
| 145.3 | 2.4402 | 0.0174 | 10.6388 | 10.6562 |
| 145.3333 | 2.4395 | 0.0305 | 10.6796 | 10.7101 |
| 145.3667 | 2.4349 | 0.0174 | 10.7164 | 10.7338 |
| 145.4 | 2.4372 | 0.0042 | 10.7401 | 10.7443 |
| 145.4333 | 2.4316 | 0.0174 | 10.7795 | 10.7969 |
| 145.4667 | 2.426 | 0.0042 | 10.8019 | 10.8061 |
| 145.5 | 2.4263 | 0.0174 | 10.8413 | 10.8587 |
| 145.5333 | 2.4214 | 0.0174 | 10.8755 | 10.8929 |
| 145.5667 | 2.4168 | 0.0174 | 10.9018 | 10.9192 |
| 145.6 | 2.4129 | 0.0042 | 10.936 | 10.9402 |
| 145.6333 | 2.4119 | 0.0174 | 10.9702 | 10.9876 |
| 145.6667 | 2.4063 | 0.0174 | 10.9926 | 11.0099 |
| 145.7 | 2.4076 | 0.0042 | 11.0189 | 11.0231 |
| 145.7333 | 2.3997 | 0.0174 | 11.0557 | 11.073 |
| 145.7667 | 2.401 | 0.0305 | 11.0688 | 11.0993 |
| 145.8 | 2.3951 | 0.0174 | 11.1109 | 11.1283 |
| 145.8333 | 2.3928 | 0.0174 | 11.1319 | 11.1493 |
| 145.8667 | 2.3931 | 0.0174 | 11.1596 | 11.1769 |
| 145.9 | 2.3947 | 0.0174 | 11.1806 | 11.198 |
| 145.9333 | 2.3941 | 0.0042 | 11.2122 | 11.2164 |
| 145.9667 | 2.3957 | 0.0042 | 11.2463 | 11.2506 |
| 146 | 2.3951 | 0.0174 | 11.2648 | 11.2821 |
| 146.0333 | 2.3971 | 0.0042 | 11.2976 | 11.3018 |
| 146.0667 | 2.3971 | 0.0174 | 11.3187 | 11.336 |
| 146.1 | 2.3987 | 0.0305 | 11.3358 | 11.3663 |
| 146.1333 | 2.4 | 0.0305 | 11.3686 | 11.3991 |
| 146.1667 | 2.3997 | 0.0042 | 11.387 | 11.3913 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|-------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 146.2 | 2.3984 | 0.0174 | 11.4265 | 11.4439 |
| 146.2333 | 2.4026 | 0.0174 | 11.4502 | 11.4675 |
| 146.2667 | 2.4023 | 0.0042 | 11.4725 | 11.4767 |
| 146.3 | 2.4066 | 0.0042 | 11.4922 | 11.4965 |
| 146.3333 | 2.4096 | 0.0042 | 11.5146 | 11.5188 |
| 146.3667 | 2.4063 | 0.0042 | 11.537 | 11.5412 |
| 146.4 | 2.4109 | 0.0174 | 11.558 | 11.5753 |
| 146.4333 | 2.4148 | 0.0174 | 11.5896 | 11.6069 |
| 146.4667 | 2.4152 | 0.0042 | 11.6132 | 11.6174 |
| 146.5 | 2.4175 | 0.0174 | 11.6369 | 11.6542 |
| 146.5333 | 2.4214 | 0.0174 | 11.6645 | 11.6819 |
| 146.5667 | 2.4231 | 0.0174 | 11.6803 | 11.6976 |
| 146.6 | 2.4221 | 0.0174 | 11.7 | 11.7174 |
| 146.6333 | 2.4244 | 0.0174 | 11.7342 | 11.7516 |
| 146.6667 | 2.4287 | 0.0174 | 11.7552 | 11.7726 |
| 146.7 | 2.4257 | 0.0174 | 11.771 | 11.7884 |
| 146.7333 | 2.4323 | 0.0174 | 11.7999 | 11.8173 |
| 146.7667 | 2.4293 | 0.0042 | 11.8223 | 11.8265 |
| 146.8 | 2.4323 | 0.0174 | 11.8512 | 11.8686 |
| 146.8333 | 2.4336 | 0.0305 | 11.8696 | 11.9001 |
| 146.8667 | 2.4346 | 0.0042 | 11.8894 | 11.8936 |
| 146.9 | 2.4352 | 0.0042 | 11.9104 | 11.9146 |
| 146.9333 | 2.4385 | 0.0042 | 11.9354 | 11.9396 |
| 146.9667 | 2.4359 | 0.0174 | 11.9538 | 11.9712 |
| 147 | 2.4392 | 0.0042 | 11.9762 | 11.9804 |
| 147.0333 | 2.4412 | 0.0174 | 12.0051 | 12.0224 |
| 147.0667 | 2.4418 | 0.0174 | 12.0209 | 12.0382 |
| 147.1 | 2.4395 | 0.0174 | 12.0353 | 12.0527 |
| 147.1333 | 2.4418 | 0.0174 | 12.0669 | 12.0842 |
| 147.1667 | 2.4425 | 0.0174 | 12.0735 | 12.0908 |
| 147.2 | 2.4428 | 0.0174 | 12.1011 | 12.1184 |
| 147.2333 | 2.4405 | 0.0174 | 12.1221 | 12.1395 |
| 147.2667 | 2.4412 | 0.0174 | 12.1458 | 12.1631 |
| 147.3 | 2.4448 | 0.0174 | 12.1576 | 12.175 |
| 147.3333 | 2.4445 | 0.0174 | 12.1813 | 12.1986 |
| 147.3667 | 2.4418 | 0.0174 | 12.2063 | 12.2236 |
| 147.4 | 2.4438 | 0.0174 | 12.226 | 12.2434 |
| 147.4333 | 2.4445 | 0.0042 | 12.2405 | 12.2447 |
| 147.4667 | 2.4454 | 0 | 12.2654 | 12.2654 |
| 147.5 | 2.4481 | 0.0174 | 12.2839 | 12.3012 |
| 147.5333 | 2.4425 | 0.0042 | 12.297 | 12.3012 |
| 147.5667 | 2.4458 | 0.0174 | 12.3207 | 12.338 |
| 147.6 | 2.4448 | 0.0042 | 12.3483 | 12.3525 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 147.6333 | 2.4477 | 0.0042 | 12.3483 | 12.3525 |
| 147.6667 | 2.4474 | 0 | 12.3759 | 12.3759 |
| 147.7 | 2.4385 | 0.0174 | 12.3943 | 12.4117 |
| 147.7333 | 2.3645 | 0.0174 | 12.4009 | 12.4182 |
| 147.7667 | 2.2878 | 0.0042 | 12.4127 | 12.4169 |
| 147.8 | 2.2088 | 0.0174 | 12.4206 | 12.438 |
| 147.8333 | 2.1383 | 0.0305 | 12.4272 | 12.4577 |
| 147.8667 | 2.0672 | 0.0174 | 12.4154 | 12.4327 |
| 147.9 | 1.9951 | 0.0042 | 12.4154 | 12.4196 |
| 147.9333 | 1.9303 | 0.0174 | 12.4009 | 12.4182 |
| 147.9667 | 1.8852 | 0.0174 | 12.0393 | 12.0566 |
| 148 | 1.8684 | 0.0174 | 11.0083 | 11.0257 |
| 148.0333 | 1.8467 | 0.0042 | 10.0905 | 10.0947 |
| 148.0667 | 1.8243 | 0.0042 | 9.2436 | 9.2478 |
| 148.1 | 1.7976 | 0.0042 | 8.4494 | 8.4536 |
| 148.1333 | 1.7706 | 0.0174 | 7.7012 | 7.7185 |
| 148.1667 | 1.7476 | 0.0305 | 6.9937 | 7.0242 |
| 148.2 | 1.719 | 0.0174 | 6.3178 | 6.3352 |
| 148.2333 | 1.6916 | 0.0174 | 5.7379 | 5.7553 |
| 148.2667 | 1.6627 | 0.0042 | 5.2053 | 5.2096 |
| 148.3 | 1.6291 | 0.0174 | 4.6912 | 4.7086 |
| 148.3333 | 1.6034 | 0.0042 | 4.2231 | 4.2273 |
| 148.3667 | 1.5692 | 0.0174 | 3.8075 | 3.8249 |
| 148.4 | 1.5389 | 0 | 3.4222 | 3.4222 |
| 148.4333 | 1.509 | 0.0174 | 3.0698 | 3.0872 |
| 148.4667 | 1.4747 | 0 | 2.7503 | 2.7503 |
| 148.5 | 1.4412 | 0.0042 | 2.4571 | 2.4613 |
| 148.5333 | 1.4099 | 0.0042 | 2.2046 | 2.2088 |
| 148.5667 | 1.3766 | 0.0174 | 1.9758 | 1.9931 |
| 148.6 | 1.3457 | 0.0305 | 1.7693 | 1.7998 |
| 148.6333 | 1.3128 | 0.0174 | 1.5944 | 1.6118 |
| 148.6667 | 1.2756 | 0.0042 | 1.4353 | 1.4395 |
| 148.7 | 1.2466 | 0.0174 | 1.3025 | 1.3199 |
| 148.7333 | 1.2479 | 0.0174 | 1.1881 | 1.2055 |
| 148.7667 | 1.2575 | 0.0305 | 1.0895 | 1.12 |
| 148.8 | 1.2667 | 0.0174 | 1.0145 | 1.0319 |
| 148.8333 | 1.2746 | 0.0174 | 0.9435 | 0.9609 |
| 148.8667 | 1.2789 | 0.0174 | 0.8949 | 0.9122 |
| 148.9 | 1.2845 | 0 | 0.8475 | 0.8475 |
| 148.9333 | 1.3141 | 0.0042 | 0.812 | 0.8162 |
| 148.9667 | 1.3134 | 0.0174 | 0.791 | 0.8083 |
| 149 | 1.3177 | 0.0174 | 0.7699 | 0.7873 |
| 149.0333 | 1.3197 | 0.0174 | 0.0007 | 0.018 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| () | (1231) | (LI IVI) | (LI IVI) | (LI IVI) |
| 149.0667 | 1.3187 | 0.0174 | 0.0007 | 0.018 |
| 149.1 | 1.324 | 0.0174 | 0.0007 | 0.018 |
| 149.1333 | 1.3282 | 0.0174 | 0.002 | 0.0194 |
| 149.1667 | 1.3243 | 0.0305 | 0.0007 | 0.0312 |
| 149.2 | 1.3259 | 0.0174 | 0.0033 | 0.0207 |
| 149.2333 | 1.3286 | 0.0437 | 0.002 | 0.0457 |
| 149.2667 | 1.3289 | 0.0174 | 0.002 | 0.0194 |
| 149.3 | 1.3282 | 0.0174 | 0 | 0.0174 |
| 149.3333 | 1.3286 | 0.0437 | 0.002 | 0.0457 |
| 149.3667 | 1.3289 | 0.0174 | 0.002 | 0.0194 |
| 149.4 | 1.3279 | 0.0042 | 0.0007 | 0.0049 |
| 149.4333 | 1.3273 | 0.0042 | 0.002 | 0.0062 |
| 149.4667 | 1.323 | 0.0174 | 0.002 | 0.0194 |
| 149.5 | 1.3256 | 0.0174 | 0.002 | 0.0194 |
| 149.5333 | 1.3243 | 0.0174 | 0.0033 | 0.0207 |
| 149.5667 | 1.323 | 0.0042 | 0.0007 | 0.0049 |
| 149.6 | 1.3213 | 0.0174 | 0.002 | 0.0194 |
| 149.6333 | 1.3187 | 0.0042 | 0.0007 | 0.0049 |
| 149.6667 | 1.3184 | 0.0042 | 0.0007 | 0.0049 |
| 149.7 | 1.3187 | 0.0174 | 0.002 | 0.0194 |
| 149.7333 | 1.3128 | 0.0174 | 0.0007 | 0.018 |
| 149.7667 | 1.3105 | 0.0174 | 0.002 | 0.0194 |
| 149.8 | 1.3082 | 0.0174 | 0.0007 | 0.018 |
| 149.8333 | 1.3065 | 0.0042 | 0.002 | 0.0062 |
| 149.8667 | 1.3019 | 0.0174 | 0.002 | 0.0194 |
| 149.9 | 1.3016 | 0.0042 | 0.0007 | 0.0049 |
| 149.9333 | 1.2983 | 0.0042 | 0 | 0.0042 |
| 149.9667 | 1.2934 | 0.0174 | 0.002 | 0.0194 |
| 150 | 1.2937 | 0.0174 | 0.0007 | 0.018 |
| 150.0333 | 1.2907 | 0.0174 | 0.0007 | 0.018 |
| 150.0667 | 1.2861 | 0.0042 | 0.002 | 0.0062 |
| 150.1 | 1.2845 | 0.0305 | 0.002 | 0.0325 |
| 150.1333 | 1.2799 | 0.0305 | 0.002 | 0.0325 |
| 150.1667 | 1.2762 | 0.0042 | 0.0007 | 0.0049 |
| 150.2 | 1.2746 | 0.0042 | 0.0007 | 0.0049 |
| 150.2333 | 1.271 | 0.0042 | 0.002 | 0.0062 |
| 150.2667 | 1.265 | 0.0042 | 0.002 | 0.0062 |
| 150.3 | 1.2667 | 0.0174 | 0.002 | 0.0194 |
| 150.3333 | 1.2624 | 0.0174 | 0.002 | 0.0194 |
| 150.3667 | 1.2578 | 0.0174 | 0.0007 | 0.018 |
| 150.4 | 1.2542 | 0.0042 | 0.002 | 0.0062 |
| 150.4333 | 1.2492 | 0.0174 | 0.0007 | 0.018 |
| 150.4667 | 1.2466 | 0.0174 | 0.0007 | 0.018 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| () | (100.7) | (=:, | (=:, | (=:, |
| 150.5 | 1.2437 | 0.0174 | 0.0007 | 0.018 |
| 150.5333 | 1.2387 | 0.0174 | 0.002 | 0.0194 |
| 150.5667 | 1.2358 | 0.0042 | 0.002 | 0.0062 |
| 150.6 | 1.2331 | 0.0174 | 0.002 | 0.0194 |
| 150.6333 | 1.2282 | 0.0042 | 0.002 | 0.0062 |
| 150.6667 | 1.2285 | 0.0174 | 0.0007 | 0.018 |
| 150.7 | 1.2219 | 0.0174 | 0.0033 | 0.0207 |
| 150.7333 | 1.2173 | 0.0305 | 0.002 | 0.0325 |
| 150.7667 | 1.2163 | 0.0174 | 0.0007 | 0.018 |
| 150.8 | 1.2104 | 0.0174 | 0.002 | 0.0194 |
| 150.8333 | 1.2094 | 0.0042 | 0 | 0.0042 |
| 150.8667 | 1.2038 | 0.0174 | 0.002 | 0.0194 |
| 150.9 | 1.1989 | 0.0174 | 0.002 | 0.0194 |
| 150.9333 | 1.1953 | 0.0174 | 0.002 | 0.0194 |
| 150.9667 | 1.1913 | 0.0042 | 0.0007 | 0.0049 |
| 151 | 1.1884 | 0.0174 | 0.0033 | 0.0207 |
| 151.0333 | 1.186 | 0.0174 | 0.0033 | 0.0207 |
| 151.0667 | 1.1808 | 0.0042 | 0.002 | 0.0062 |
| 151.1 | 1.1795 | 0.0042 | 0.0007 | 0.0049 |
| 151.1333 | 1.1716 | 0.0174 | 0.0007 | 0.018 |
| 151.1667 | 1.1726 | 0.0174 | 0.002 | 0.0194 |
| 151.2 | 1.1673 | 0.0042 | 0.002 | 0.0062 |
| 151.2333 | 1.1643 | 0.0174 | 0.002 | 0.0194 |
| 151.2667 | 1.1564 | 0.0042 | 0.0007 | 0.0049 |
| 151.3 | 1.1551 | 0.0042 | 0.0007 | 0.0049 |
| 151.3333 | 1.1531 | 0.0174 | 0.0007 | 0.018 |
| 151.3667 | 1.1485 | 0.0174 | 0.002 | 0.0194 |
| 151.4 | 1.1429 | 0.0174 | 0.002 | 0.0194 |
| 151.4333 | 1.141 | 0.0305 | 0.0007 | 0.0312 |
| 151.4667 | 1.1377 | 0.0305 | 0.002 | 0.0325 |
| 151.5 | 1.1317 | 0.0305 | 0.0007 | 0.0312 |
| 151.5333 | 1.1261 | 0.0042 | 0.002 | 0.0062 |
| 151.5667 | 1.1268 | 0.0042 | 0.0007 | 0.0049 |
| 151.6 | 1.1252 | 0.0305 | 0.002 | 0.0325 |
| 151.6333 | 1.1189 | 0.0174 | 0.0007 | 0.018 |
| 151.6667 | 1.114 | 0.0174 | 0.0007 | 0.018 |
| 151.7 | 1.109 | 0.0305 | 0.002 | 0.0325 |
| 151.7333 | 1.1054 | 0.0305 | 0.0007 | 0.0312 |
| 151.7667 | 1.1054 | 0.0174 | 0.0007 | 0.018 |
| 151.8 | 1.1015 | 0.0174 | 0.002 | 0.0194 |
| 151.8333 | 1.0959 | 0.0042 | 0.002 | 0.0062 |
| 151.8667 | 1.0945 | 0.0174 | 0.0046 | 0.022 |
| 151.9 | 1.0893 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| () | (1001) | (21111) | (2.11) | (LI IVI) |
| 151.9333 | 1.0857 | 0.0174 | 0.0007 | 0.018 |
| 151.9667 | 1.084 | 0.0042 | 0.002 | 0.0062 |
| 152 | 1.0764 | 0.0305 | 0.002 | 0.0325 |
| 152.0333 | 1.0741 | 0.0174 | 0.002 | 0.0194 |
| 152.0667 | 1.0715 | 0.0042 | 0.002 | 0.0062 |
| 152.1 | 1.0669 | 0.0042 | 0.002 | 0.0062 |
| 152.1333 | 1.0636 | 0.0042 | 0.002 | 0.0062 |
| 152.1667 | 1.0593 | 0.0174 | 0.002 | 0.0194 |
| 152.2 | 1.0577 | 0.0174 | 0.0007 | 0.018 |
| 152.2333 | 1.0547 | 0.0042 | 0.0007 | 0.0049 |
| 152.2667 | 1.0527 | 0.0174 | 0.0033 | 0.0207 |
| 152.3 | 1.0475 | 0.0305 | 0.002 | 0.0325 |
| 152.3333 | 1.0415 | 0.0174 | 0.0033 | 0.0207 |
| 152.3667 | 1.0383 | 0.0174 | 0.002 | 0.0194 |
| 152.4 | 1.0323 | 0.0042 | 0.002 | 0.0062 |
| 152.4333 | 1.031 | 0.0042 | 0.002 | 0.0062 |
| 152.4667 | 1.0287 | 0.0174 | 0.0007 | 0.018 |
| 152.5 | 1.0261 | 0.0042 | 0.0007 | 0.0049 |
| 152.5333 | 1.0215 | 0.0042 | 0.002 | 0.0062 |
| 152.5667 | 1.0175 | 0.0174 | 0.002 | 0.0194 |
| 152.6 | 1.0159 | 0.0305 | 0.0046 | 0.0351 |
| 152.6333 | 1.0106 | 0.0042 | 0.0007 | 0.0049 |
| 152.6667 | 1.0086 | 0.0305 | 0.002 | 0.0325 |
| 152.7 | 1.0037 | 0.0174 | 0.0033 | 0.0207 |
| 152.7333 | 1.0007 | 0.0042 | 0.0007 | 0.0049 |
| 152.7667 | 0.9974 | 0.0042 | 0.0007 | 0.0049 |
| 152.8 | 0.9941 | 0.0042 | 0.002 | 0.0062 |
| 152.8333 | 0.9912 | 0.0042 | 0.0007 | 0.0049 |
| 152.8667 | 0.9843 | 0.0042 | 0.002 | 0.0062 |
| 152.9 | 0.9833 | 0.0174 | 0.002 | 0.0194 |
| 152.9333 | 0.9793 | 0.0042 | 0.002 | 0.0062 |
| 152.9667 | 0.9764 | 0.0305 | 0.0007 | 0.0312 |
| 153 | 0.9731 | 0.0305 | 0.002 | 0.0325 |
| 153.0333 | 0.9691 | 0.0305 | 0.002 | 0.0325 |
| 153.0667 | 0.9695 | 0.0174 | 0.002 | 0.0194 |
| 153.1 | 0.9622 | 0.0042 | 0.002 | 0.0062 |
| 153.1333 | 0.9586 | 0.0042 | 0.002 | 0.0062 |
| 153.1667 | 0.956 | 0.0042 | 0.002 | 0.0062 |
| 153.2 | 0.9533 | 0.0174 | 0.0033 | 0.0207 |
| 153.2333 | 0.9481 | 0.0042 | 0.002 | 0.0062 |
| 153.2667 | 0.9458 | 0.0305 | 0 | 0.0305 |
| 153.3 | 0.9408 | 0.0174 | 0.002 | 0.0194 |
| 153.3333 | 0.9388 | 0 | 0.002 | 0.002 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|----------|---------|----------------|--------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 153.3667 | 0.9359 | 0.0174 | 0.002 | 0.0194 |
| 153.4 | 0.9332 | 0.0174 | 0.002 | 0.0194 |
| 153.4333 | 0.9283 | 0.0174 | 0.002 | 0.0194 |
| 153,4667 | 0.9263 | 0.0042 | 0.002 | 0.0062 |
| 153.5 | 0.923 | 0.0042 | 0.002 | 0.0062 |
| 153.5333 | 0.9178 | 0.0305 | 0.002 | 0.0325 |
| 153.5667 | 0.9168 | 0.0305 | 0 | 0.0305 |
| 153.6 | 0.9102 | 0.0042 | 0.002 | 0.0062 |
| 153.6333 | 0.9092 | 0.0042 | 0.002 | 0.0062 |
| 153.6667 | 0.9063 | 0.0174 | 0.002 | 0.0194 |
| 153.7 | 0.902 | 0.0042 | 0.002 | 0.0062 |
| 153.7333 | 0.899 | 0.0305 | 0.0007 | 0.0312 |
| 153.7667 | 0.8993 | 0.0174 | 0.002 | 0.0194 |
| 153.8 | 0.8954 | 0.0174 | 0.0007 | 0.018 |
| 153.8333 | 0.8905 | 0.0174 | 0 | 0.0174 |
| 153.8667 | 0.8891 | 0.0042 | 0.0007 | 0.0049 |
| 153.9 | 0.8855 | 0.0174 | 0.002 | 0.0194 |
| 153.9333 | 0.8826 | 0.0305 | 0.0033 | 0.0338 |
| 153.9667 | 0.8766 | 0.0174 | 0.0007 | 0.018 |
| 154 | 0.8766 | 0.0042 | 0.002 | 0.0062 |
| 154.0333 | 0.8727 | 0.0174 | 0.0007 | 0.018 |
| 154.0667 | 0.8724 | 0.0042 | 0.002 | 0.0062 |
| 154.1 | 0.8674 | 0.0305 | 0.002 | 0.0325 |
| 154.1333 | 0.8631 | 0.0042 | 0.002 | 0.0062 |
| 154.1667 | 0.8579 | 0.0174 | 0.0007 | 0.018 |
| 154.2 | 0.8542 | 0.0174 | 0.002 | 0.0194 |
| 154.2333 | 0.8556 | 0.0042 | 0.0033 | 0.0075 |
| 154.2667 | 0.85 | 0.0042 | 0.0033 | 0.0075 |
| 154.3 | 0.8487 | 0.0042 | 0.002 | 0.0062 |
| 154.3333 | 0.8454 | 0.0174 | 0.002 | 0.0194 |
| 154.3667 | 0.8391 | 0.0305 | 0.0033 | 0.0338 |
| 154.4 | 0.8398 | 0.0174 | 0.0033 | 0.0207 |
| 154.4333 | 0.8348 | 0.0305 | 0.0007 | 0.0312 |
| 154.4667 | 0.8299 | 0.0042 | 0.002 | 0.0062 |
| 154.5 | 0.8305 | 0.0305 | 0.0007 | 0.0312 |
| 154.5333 | 0.8253 | 0.0174 | 0.002 | 0.0194 |
| 154.5667 | 0.824 | 0.0174 | 0.0007 | 0.018 |
| 154.6 | 0.82 | 0.0042 | 0.0033 | 0.0075 |
| 154.6333 | 0.8194 | 0.0305 | 0.002 | 0.0325 |
| 154.6667 | 0.8138 | 0.0174 | 0.0033 | 0.0207 |
| 154.7 | 0.8121 | 0.0305 | 0.002 | 0.0325 |
| 154.7333 | 0.8088 | 0.0042 | 0.0007 | 0.0049 |
| 154.7667 | 0.8075 | 0.0042 | 0 | 0.0042 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| 154.8 | 0.8022 | 0.0174 | 0.002 | 0.0194 |
| 154.8333 | 0.8022 | 0.0042 | 0.002 | 0.0062 |
| 154.8667 | 0.7983 | 0.0305 | 0.0007 | 0.0312 |
| 154.9 | 0.7927 | 0.0305 | 0.0007 | 0.0312 |
| 154.9333 | 0.7904 | 0.0174 | 0.002 | 0.0194 |
| 154.9667 | 0.7897 | 0.0042 | 0.0033 | 0.0075 |
| 155 | 0.7874 | 0.0042 | 0.0007 | 0.0049 |
| 155.0333 | 0.7845 | 0.0174 | 0.002 | 0.0194 |
| 155.0667 | 0.7818 | 0.0305 | 0.002 | 0.0325 |
| 155.1 | 0.7756 | 0.0042 | 0.0007 | 0.0049 |
| 155.1333 | 0.7746 | 0.0174 | 0.002 | 0.0194 |
| 155.1667 | 0.7697 | 0.0174 | 0.0007 | 0.018 |
| 155.2 | 0.769 | 0.0042 | 0.0033 | 0.0075 |
| 155.2333 | 0.7641 | 0.0305 | 0.002 | 0.0325 |
| 155.2667 | 0.7637 | 0.0174 | 0.002 | 0.0194 |
| 155.3 | 0.7585 | 0.0042 | 0.002 | 0.0062 |
| 155.3333 | 0.7578 | 0.0042 | 0.0033 | 0.0075 |
| 155.3667 | 0.7552 | 0.0174 | 0.002 | 0.0194 |
| 155.4 | 0.7522 | 0.0305 | 0.002 | 0.0325 |
| 155.4333 | 0.7492 | 0.0174 | 0.0033 | 0.0207 |
| 155.4667 | 0.7453 | 0.0042 | 0.0007 | 0.0049 |
| 155.5 | 0.7456 | 0.0174 | 0.002 | 0.0194 |
| 155.5333 | 0.7417 | 0.0174 | 0.002 | 0.0194 |
| 155.5667 | 0.7394 | 0.0042 | 0.002 | 0.0062 |
| 155.6 | 0.7381 | 0.0042 | 0.0007 | 0.0049 |
| 155.6333 | 0.7334 | 0.0174 | 0.0007 | 0.018 |
| 155.6667 | 0.7305 | 0.0174 | 0.0007 | 0.018 |
| 155.7 | 0.7275 | 0.0174 | 0.0007 | 0.018 |
| 155.7333 | 0.7252 | 0.0042 | 0.002 | 0.0062 |
| 155.7667 | 0.7206 | 0.0174 | 0.0033 | 0.0207 |
| 155.8 | 0.719 | 0.0174 | 0.0007 | 0.018 |
| 155.8333 | 0.7157 | 0.0042 | 0.0007 | 0.0049 |
| 155.8667 | 0.7167 | 0.0174 | 0.002 | 0.0194 |
| 155.9 | 0.7101 | 0.0305 | 0.002 | 0.0325 |
| 155.9333 | 0.7097 | 0.0305 | 0.002 | 0.0325 |
| 155.9667 | 0.7058 | 0.0174 | 0.002 | 0.0194 |
| 156 | 0.7055 | 0.0174 | 0.002 | 0.0194 |
| 156.0333 | 0.7045 | 0.0174 | 0.002 | 0.0194 |
| 156.0667 | 0.6982 | 0.0174 | 0.0033 | 0.0207 |
| 156.1 | 0.6936 | 0.0042 | 0.0007 | 0.0049 |
| 156.1333 | 0.691 | 0.0174 | 0.0033 | 0.0207 |
| 156.1667 | 0.692 | 0.0174 | 0 | 0.0174 |
| 156.2 | 0.6893 | 0.0305 | 0.0007 | 0.0312 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | • | Ch 3 Low Flow | Total Flow |
|-------------------|------------------|------------------|-----------------|------------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 156.2333 | 0.6837 | 0.0305 | 0.002 | 0.0325 |
| 156.2667 | 0.6821 | 0.0174 | 0.0033 | 0.0207 |
| 156.3 | 0.6801 | 0.0174 | 0.0033 | 0.0207 |
| 156.3333 | 0.6778 | 0.0042 | 0.002 | 0.0062 |
| 156.3667 | 0.6781 | 0.0174 | 0.002 | 0.0194 |
| 156.4 | 0.6745 | 0.0174 | 0.0007 | 0.018 |
| 156.4333 | 0.6699 | 0.0174 | 0.0033 | 0.0207 |
| 156.4667 | 0.6696 | 0.0042 | 0.002 | 0.0062 |
| 156.5 | 0.665 | 0.0305 | 0.002 | 0.0325 |
| 156.5333 | 0.6627 | 0.0305 | 0.0007 | 0.0312 |
| 156.5667 | 0.66 | 0.0174 | 0 | 0.0174 |
| 156.6 | 0.6584 | 0.0174 | 0.002 | 0.0194 |
| 156.6333 | 0.6544 | 0.0174 | 0.002 | 0.0194 |
| 156.6667 | 0.6531 | 0.0174 | 0.002 | 0.0194 |
| 156.7 | 0.6521 | 0.0174 | 0.0033 | 0.0207 |
| 156.7333 | 0.6485 | 0.0174 | 0.002 | 0.0194 |
| 156.7667 | 0.6456 | 0.0042 | 0.002 | 0.0062 |
| 156.8 | 0.6436 | 0.0174 | 0.0007 | 0.018 |
| 156.8333 | 0.6419 | 0.0174 | 0.0007 | 0.018 |
| 156.8667 | 0.638 | 0.0042 | 0.002 | 0.0062 |
| 156.9 | 0.6353 | 0.0042 | 0.002 | 0.0062 |
| 156.9333 | 0.634 | 0.0437 | 0.002 | 0.0457 |
| 156.9667 | 0.6278 | 0.0042 | 0.002 | 0.0062 |
| 157 | 0.6307 | 0.0174 | 0.002 | 0.0194 |
| 157.0333 | 0.6268 | 0.0042 | 0.002 | 0.0062 |
| 157.0667 | 0.6242 | 0.0437 | 0.002 | 0.0457 |
| 157.1 | 0.6248 | 0.0174 | 0.0033 | 0.0207 |
| 157.1333 | 0.6189 | 0.0042 | 0.002 | 0.0062 |
| 157.1667 | 0.6199 | 0.0174 | 0.0007 | 0.018 |
| 157.2 | 0.6166 | 0.0174 | 0.0007 | 0.018 |
| 157.2333 | 0.6113 | 0.0042 | 0.002 | 0.0062 |
| 157.2667 | 0.6107 | 0.0174 | 0.0007 | 0.018 |
| 157.3 | 0.6077 | 0.0042 | 0.0007 | 0.0049 |
| 157.3333 | 0.6037 | 0.0042 | 0.002 | 0.0062 |
| 157.3667 | 0.6014 | 0.0042 | 0.002 | 0.0062 |
| 157.4 | 0.5991 | 0.0042 | 0.0007 | 0.0049 |
| 157.4333 | 0.5975 | 0.0174 | 0.0033 | 0.0207 |
| 157.4667 | 0.5962 | 0.0174 | 0.0007 | 0.018 |
| 157.5 157.5333 | 0.5939 0.5916 | 0.0174 0.0174 | 0.002 0.0033 | 0.0194 0.0207 |
| 157.5333 | 0.5866 | 0.0174 | 0.0033 | 0.0207 |
| 157.5667 | 0.5886 | 0.0042 | 0.002 | 0.0062 |
| 157.6333 | 0.5886 | 0.0174 | 0.002 | 0.0194 |
| 137.0333 | 0.582 | 0.0042 | U | 0.0042 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow |
|---------------|------------------|-------------------------|------------------------|------------|
| () | (1) | , | | (=: :; |
| 157.6667 | 0.581 | 0.0174 | 0.002 | 0.0194 |
| 157.7 | 0.58 | 0.0174 | 0.0033 | 0.0207 |
| 157.7333 | 0.5771 | 0.0042 | 0.002 | 0.0062 |
| 157.7667 | 0.5745 | 0.0305 | 0.002 | 0.0325 |
| 157.8 | 0.5745 | 0.0305 | 0.0033 | 0.0338 |
| 157.8333 | 0.5715 | 0.0305 | 0.0007 | 0.0312 |
| 157.8667 | 0.5656 | 0.0174 | 0.0007 | 0.018 |
| 157.9 | 0.5666 | 0.0174 | 0.002 | 0.0194 |
| 157.9333 | 0.5619 | 0.0174 | 0.002 | 0.0194 |
| 157.9667 | 0.5619 | 0.0042 | 0.002 | 0.0062 |
| 158 | 0.5593 | 0.0305 | 0.002 | 0.0325 |
| 158.0333 | 0.5593 | 0.0174 | 0.002 | 0.0194 |
| 158.0667 | 0.5554 | 0.0042 | 0.0046 | 0.0088 |
| 158.1 | 0.5534 | 0.0042 | 0.0007 | 0.0049 |
| 158.1333 | 0.5527 | 0.0174 | 0.002 | 0.0194 |
| 158.1667 | 0.5494 | 0.0174 | 0.0007 | 0.018 |
| 158.2 | 0.5465 | 0.0174 | 0.002 | 0.0194 |
| 158.2333 | 0.5432 | 0.0042 | 0.002 | 0.0062 |
| 158.2667 | 0.5419 | 0.0042 | 0.002 | 0.0062 |
| 158.3 | 0.5415 | 0.0305 | 0.002 | 0.0325 |
| 158.3333 | 0.5373 | 0.0042 | 0.002 | 0.0062 |
| 158.3667 | 0.5376 | 0.0174 | 0.002 | 0.0194 |
| 158.4 | 0.5336 | 0.0305 | 0.0033 | 0.0338 |
| 158.4333 | 0.5307 | 0.0174 | 0.002 | 0.0194 |
| 158.4667 | 0.5267 | 0.0174 | 0.002 | 0.0194 |
| 158.5 | 0.5251 | 0.0174 | 0.0033 | 0.0207 |
| 158.5333 | 0.5257 | 0.0174 | 0.002 | 0.0194 |
| 158.5667 | 0.5231 | 0.0174 | 0.002 | 0.0194 |
| 158.6 | 0.5215 | 0.0042 | 0.002 | 0.0062 |
| 158.6333 | 0.5192 | 0.0174 | 0.0033 | 0.0207 |
| 158.6667 | 0.5155 | 0.0174 | 0.0007 | 0.018 |
| 158.7 | 0.5119 | 0.0174 | 0.002 | 0.0194 |
| 158.7333 | 0.5126 | 0.0042 | 0.002 | 0.0062 |
| 158.7667 | 0.5086 | 0.0174 | 0.002 | 0.0194 |
| 158.8 | 0.5089 | 0.0042 | 0.002 | 0.0062 |
| 158.8333 | 0.505 | 0.0042 | 0.0007 | 0.0049 |
| 158.8667 | 0.5037 | 0.0174 | 0.0033 | 0.0207 |
| 158.9 | 0.5037 | 0.0174 | 0.002 | 0.0194 |
| 158.9333 | 0.5001 | 0.0305 | 0.002 | 0.0325 |
| 158.9667 | 0.5001 | 0.0174 | 0.0033 | 0.0207 |
| 159 | 0.4958 | 0.0174 | 0.0033 | 0.0207 |
| 159.0333 | 0.4951 | 0.0174 | 0.002 | 0.0194 |
| 159.0667 | 0.4922 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| | | | | |
| 159.1 | 0.4918 | 0.0174 | 0.0007 | 0.018 |
| 159.1333 | 0.4899 | 0.0174 | 0.0007 | 0.018 |
| 159.1667 | 0.4882 | 0.0305 | 0.0007 | 0.0312 |
| 159.2 | 0.4859 | 0.0042 | 0.002 | 0.0062 |
| 159.2333 | 0.4816 | 0.0174 | 0.002 | 0.0194 |
| 159.2667 | 0.4797 | 0.0305 | 0.0007 | 0.0312 |
| 159.3 | 0.4777 | 0.0042 | 0.0033 | 0.0075 |
| 159.3333 | 0.4783 | 0.0174 | 0.002 | 0.0194 |
| 159.3667 | 0.475 | 0.0174 | 0.002 | 0.0194 |
| 159.4 | 0.4727 | 0.0174 | 0.002 | 0.0194 |
| 159.4333 | 0.4698 | 0.0305 | 0.002 | 0.0325 |
| 159.4667 | 0.4701 | 0.0174 | 0.002 | 0.0194 |
| 159.5 | 0.4675 | 0.0174 | 0.0007 | 0.018 |
| 159.5333 | 0.4671 | 0.0174 | 0.002 | 0.0194 |
| 159.5667 | 0.4612 | 0.0042 | 0.002 | 0.0062 |
| 159.6 | 0.4639 | 0.0042 | 0.002 | 0.0062 |
| 159.6333 | 0.4619 | 0.0042 | 0.0007 | 0.0049 |
| 159.6667 | 0.4599 | 0.0305 | 0.0007 | 0.0312 |
| 159.7 | 0.4586 | 0.0174 | 0.0033 | 0.0207 |
| 159.7333 | 0.501 | 0.0305 | 0.002 | 0.0325 |
| 159.7667 | 0.5577 | 0 | 0.0007 | 0.0007 |
| 159.8 | 0.6215 | 0.0174 | 0.0033 | 0.0207 |
| 159.8333 | 0.6933 | 0.0174 | 0.0033 | 0.0207 |
| 159.8667 | 0.7726 | 0.0305 | 0.0007 | 0.0312 |
| 159.9 | 0.8473 | 0.0305 | 0.0007 | 0.0312 |
| 159.9333 | 0.925 | 0.0305 | 0.002 | 0.0325 |
| 159.9667 | 1.0083 | 0.0042 | 0.002 | 0.0062 |
| 160 | 1.0781 | 0.0174 | 0.002 | 0.0194 |
| 160.0333 | 1.1505 | 0.0042 | 0.002 | 0.0062 |
| 160.0667 | 1.2127 | 0.0174 | 0.0033 | 0.0207 |
| 160.1 | 1.1943 | 0.0042 | 0.002 | 0.0062 |
| 160.1333 | 1.1801 | 0.0042 | 0.0033 | 0.0075 |
| 160.1667 | 1.1647 | 0.0305 | 0.002 | 0.0325 |
| 160.2 | 1.1558 | 0.0042 | 0.002 | 0.0062 |
| 160.2333 | 1.1423 | 0.0174 | 0.002 | 0.0194 |
| 160.2667 | 1.1327 | 0.0042 | 0.0046 | 0.0088 |
| 160.3 | 1.1199 | 0.0042 | 0.002 | 0.0062 |
| 160.3333 | 1.107 | 0.0042 | 0.002 | 0.0062 |
| 160.3667 | 1.1001 | 0.0174 | 0.0007 | 0.018 |
| 160.4 | 1.0903 | 0.0174 | 0.0007 | 0.018 |
| 160.4333 | 1.0837 | 0.0174 | 0.002 | 0.0194 |
| 160.4667 | 1.0708 | 0.0042 | 0.002 | 0.0062 |
| 160.5 | 1.0633 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|----------|---------|----------------|--------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 160.5333 | 1.056 | 0.0305 | 0.002 | 0.0325 |
| 160.5667 | 1.0462 | 0.0042 | 0.0007 | 0.0049 |
| 160.6 | 1.0363 | 0.0174 | 0.002 | 0.0194 |
| 160.6333 | 1.0307 | 0.0305 | 0.0033 | 0.0134 |
| 160.6667 | 1.0211 | 0.0174 | 0.002 | 0.0194 |
| 160.7 | 1.0182 | 0.0305 | 0.002 | 0.0325 |
| 160.7333 | 1.007 | 0.0174 | 0.0033 | 0.0207 |
| 160.7667 | 0.9988 | 0.0042 | 0.002 | 0.0062 |
| 160.8 | 0.9958 | 0.0174 | 0.0007 | 0.018 |
| 160.8333 | 0.9872 | 0.0305 | 0.002 | 0.0325 |
| 160.8667 | 0.9833 | 0.0174 | 0.0007 | 0.018 |
| 160.9 | 0.9747 | 0.0174 | 0.0033 | 0.0207 |
| 160.9333 | 0.9665 | 0.0174 | 0.002 | 0.0194 |
| 160.9667 | 0.9639 | 0.0174 | 0.0033 | 0.0207 |
| 161 | 0.9589 | 0.0174 | 0.0007 | 0.018 |
| 161.0333 | 0.9487 | 0.0174 | 0.0046 | 0.022 |
| 161.0667 | 0.9448 | 0.0042 | 0.002 | 0.0062 |
| 161.1 | 0.9402 | 0 | 0.002 | 0.002 |
| 161.1333 | 0.9332 | 0.0174 | 0.002 | 0.0194 |
| 161.1667 | 0.9283 | 0.0174 | 0.002 | 0.0194 |
| 161.2 | 0.9237 | 0.0042 | 0.0007 | 0.0049 |
| 161.2333 | 0.9168 | 0.0305 | 0.0033 | 0.0338 |
| 161.2667 | 0.9138 | 0.0042 | 0.002 | 0.0062 |
| 161.3 | 0.9112 | 0.0305 | 0.002 | 0.0325 |
| 161.3333 | 0.9007 | 0.0042 | 0.0007 | 0.0049 |
| 161.3667 | 0.899 | 0.0042 | 0.0007 | 0.0049 |
| 161.4 | 0.8885 | 0.0174 | 0 | 0.0174 |
| 161.4333 | 0.8908 | 0.0305 | 0.002 | 0.0325 |
| 161.4667 | 0.8832 | 0.0174 | 0.002 | 0.0194 |
| 161.5 | 0.8806 | 0.0305 | 0.002 | 0.0325 |
| 161.5333 | 0.8743 | 0.0174 | 0.0033 | 0.0207 |
| 161.5667 | 0.8697 | 0.0042 | 0.002 | 0.0062 |
| 161.6 | 0.8664 | 0.0174 | 0.0033 | 0.0207 |
| 161.6333 | 0.8575 | 0.0042 | 0.002 | 0.0062 |
| 161.6667 | 0.8569 | 0.0174 | 0.002 | 0.0194 |
| 161.7 | 0.8552 | 0.0174 | 0.0007 | 0.018 |
| 161.7333 | 0.85 | 0.0174 | 0.002 | 0.0194 |
| 161.7667 | 0.847 | 0.0305 | 0.0007 | 0.0312 |
| 161.8 | 0.8404 | 0.0174 | 0.0033 | 0.0207 |
| 161.8333 | 0.8355 | 0.0174 | 0.0007 | 0.018 |
| 161.8667 | 0.8322 | 0.0042 | 0.002 | 0.0062 |
| 161.9 | 0.8259 | 0.0042 | 0.0007 | 0.0049 |
| 161.9333 | 0.8253 | 0.0174 | 0.0007 | 0.018 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|----------|---------|----------------|--------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 161.9667 | 0.8217 | 0.0174 | 0.002 | 0.0194 |
| 162 | 0.8154 | 0.0042 | 0.0033 | 0.0075 |
| 162.0333 | 0.8134 | 0.0174 | 0.0033 | 0.0207 |
| 162.0667 | 0.8101 | 0.0305 | 0.003 | 0.0325 |
| 162.1 | 0.8045 | 0.0042 | 0.002 | 0.0062 |
| 162.1333 | 0.8006 | 0.0042 | 0.002 | 0.0062 |
| 162.1667 | 0.7943 | 0.0174 | 0.0007 | 0.0002 |
| 162.2 | 0.7934 | 0.0305 | 0.0007 | 0.0312 |
| 162.2333 | 0.7894 | 0.0042 | 0.002 | 0.0062 |
| 162.2667 | 0.7858 | 0.0042 | 0 | 0.0042 |
| 162.3 | 0.7822 | 0.0042 | 0.002 | 0.0062 |
| 162.3333 | 0.7802 | 0.0042 | 0.0007 | 0.0049 |
| 162.3667 | 0.7762 | 0.0042 | 0.002 | 0.0062 |
| 162.4 | 0.7743 | 0.0042 | 0.002 | 0.0062 |
| 162.4333 | 0.7693 | 0.0174 | 0.002 | 0.0194 |
| 162.4667 | 0.7644 | 0.0174 | 0.002 | 0.0194 |
| 162.5 | 0.7614 | 0.0174 | 0.002 | 0.0194 |
| 162.5333 | 0.7581 | 0.0042 | 0.002 | 0.0062 |
| 162.5667 | 0.7575 | 0.0174 | 0.0033 | 0.0207 |
| 162.6 | 0.7499 | 0.0174 | 0.0033 | 0.0207 |
| 162.6333 | 0.7476 | 0.0174 | 0.002 | 0.0194 |
| 162.6667 | 0.7486 | 0.0174 | 0.0007 | 0.018 |
| 162.7 | 0.7417 | 0.0305 | 0.0033 | 0.0338 |
| 162.7333 | 0.7371 | 0.0042 | 0.0033 | 0.0075 |
| 162.7667 | 0.7357 | 0.0305 | 0 | 0.0305 |
| 162.8 | 0.7311 | 0.0305 | 0.002 | 0.0325 |
| 162.8333 | 0.7272 | 0.0174 | 0.0033 | 0.0207 |
| 162.8667 | 0.7232 | 0.0174 | 0.0007 | 0.018 |
| 162.9 | 0.7236 | 0.0042 | 0.002 | 0.0062 |
| 162.9333 | 0.7193 | 0.0042 | 0.0007 | 0.0049 |
| 162.9667 | 0.7176 | 0.0174 | 0.002 | 0.0194 |
| 163 | 0.714 | 0.0042 | 0.002 | 0.0062 |
| 163.0333 | 0.7091 | 0.0042 | 0.002 | 0.0062 |
| 163.0667 | 0.7061 | 0.0042 | 0.002 | 0.0062 |
| 163.1 | 0.7012 | 0 | 0.002 | 0.002 |
| 163.1333 | 0.7025 | 0.0174 | 0.0033 | 0.0207 |
| 163.1667 | 0.6966 | 0.0042 | 0.002 | 0.0062 |
| 163.2 | 0.6933 | 0.0174 | 0.0007 | 0.018 |
| 163.2333 | 0.693 | 0.0174 | 0.002 | 0.0194 |
| 163.2667 | 0.6897 | 0.0042 | 0.0033 | 0.0075 |
| 163.3 | 0.6883 | 0.0174 | 0.002 | 0.0194 |
| 163.3333 | 0.6831 | 0.0174 | 0.0007 | 0.018 |
| 163.3667 | 0.6798 | 0.0174 | 0.0007 | 0.018 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| (IIIIII) | (psi) | (LPIVI) | (LFIVI) | (LFIVI) |
| 163.4 | 0.6788 | 0.0042 | 0.0007 | 0.0049 |
| 163.4333 | 0.6742 | 0.0174 | 0.0033 | 0.0207 |
| 163.4667 | 0.6742 | 0.0174 | 0.0007 | 0.018 |
| 163.5 | 0.6702 | 0.0042 | 0.0033 | 0.0075 |
| 163.5333 | 0.6689 | 0.0042 | 0.002 | 0.0062 |
| 163.5667 | 0.6643 | 0 | 0.0046 | 0.0046 |
| 163.6 | 0.6633 | 0.0042 | 0.0007 | 0.0049 |
| 163.6333 | 0.6581 | 0.0174 | 0.0007 | 0.018 |
| 163.6667 | 0.6551 | 0.0174 | 0.002 | 0.0194 |
| 163.7 | 0.6502 | 0.0174 | 0.0007 | 0.018 |
| 163.7333 | 0.6485 | 0.0042 | 0.002 | 0.0062 |
| 163.7667 | 0.6469 | 0.0305 | 0.002 | 0.0325 |
| 163.8 | 0.6426 | 0.0174 | 0 | 0.0174 |
| 163.8333 | 0.6429 | 0.0305 | 0.0007 | 0.0312 |
| 163.8667 | 0.64 | 0.0042 | 0.0033 | 0.0075 |
| 163.9 | 0.6373 | 0.0305 | 0.002 | 0.0325 |
| 163.9333 | 0.6344 | 0.0305 | 0.0033 | 0.0338 |
| 163.9667 | 0.6307 | 0.0174 | 0.0033 | 0.0207 |
| 164 | 0.6304 | 0.0174 | 0.0033 | 0.0207 |
| 164.0333 | 0.6278 | 0.0305 | 0.0007 | 0.0312 |
| 164.0667 | 0.6235 | 0.0305 | 0.0033 | 0.0338 |
| 164.1 | 0.6195 | 0.0042 | 0.0033 | 0.0075 |
| 164.1333 | 0.6166 | 0.0042 | 0.002 | 0.0062 |
| 164.1667 | 0.6172 | 0.0174 | 0.0007 | 0.018 |
| 164.2 | 0.6146 | 0.0174 | 0.002 | 0.0194 |
| 164.2333 | 0.6123 | 0.0174 | 0 | 0.0174 |
| 164.2667 | 0.6097 | 0.0305 | 0.0033 | 0.0338 |
| 164.3 | 0.6057 | 0.0042 | 0.0007 | 0.0049 |
| 164.3333 | 0.6116 | 0.0174 | 0 | 0.0174 |
| 164.3667 | 0.6976 | 0.0305 | 0.0007 | 0.0312 |
| 164.4 | 0.7897 | 0.0174 | 0 | 0.0174 |
| 164.4333 | 0.8826 | 0 | 0.002 | 0.002 |
| 164.4667 | 0.9701 | 0.0174 | 0.0046 | 0.022 |
| 164.5 | 1.0521 | 0.0174 | 0.002 | 0.0194 |
| 164.5333 | 1.1363 | 0.0174 | 0.002 | 0.0194 |
| 164.5667 | 1.1485 | 0.0305 | 0.0007 | 0.0312 |
| 164.6 | 1.1334 | 0.0174 | 0.002 | 0.0194 |
| 164.6333 | 1.1255 | 0.0174 | 0.002 | 0.0194 |
| 164.6667 | 1.1107 | 0.0042 | 0.002 | 0.0062 |
| 164.7 | 1.1041 | 0.0305 | 0.002 | 0.0325 |
| 164.7333 | 1.0912 | 0.0042 | 0.002 | 0.0062 |
| 164.7667 | 1.0824 | 0.0174 | 0.002 | 0.0194 |
| 164.8 | 1.0745 | 0.0174 | 0.002 | 0.0194 |



Project No. G101276459SAT-023

| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| 164.8333 | 1.0656 | 0.0174 | 0.002 | 0.0194 |
| 164.8667 | 1.0564 | 0.0305 | 0.0007 | 0.0134 |
| 164.9 | 1.0508 | 0.0042 | 0.002 | 0.0062 |
| 164.9333 | 1.0392 | 0.0042 | 0.0007 | 0.0049 |
| 164.9667 | 1.0313 | 0.0174 | 0.002 | 0.0194 |
| 165 | 1.0264 | 0.0174 | 0.0007 | 0.018 |
| 165.0333 | 1.0211 | 0.0174 | 0.002 | 0.0194 |
| 165.0667 | 1.0116 | 0.0174 | 0.002 | 0.0194 |
| 165.1 | 1.002 | 0.0174 | 0.002 | 0.0194 |
| 165.1333 | 0.9991 | 0.0174 | 0.0033 | 0.0207 |
| 165.1667 | 0.9882 | 0.0174 | 0.002 | 0.0194 |
| 165.2 | 0.9826 | 0.0174 | 0.002 | 0.0194 |
| 165.2333 | 0.9751 | 0.0305 | 0.002 | 0.0325 |
| 165.2667 | 0.9691 | 0.0437 | 0 | 0.0437 |
| 165.3 | 0.9642 | 0.0437 | 0.002 | 0.0457 |
| 165.3333 | 0.9593 | 0.0174 | 0.002 | 0.0194 |
| 165.3667 | 0.9553 | 0.0042 | 0 | 0.0042 |
| 165.4 | 0.9467 | 0.0174 | 0.002 | 0.0194 |
| 165.4333 | 0.9418 | 0.0174 | 0.002 | 0.0194 |
| 165.4667 | 0.9362 | 0.0042 | 0.0033 | 0.0075 |
| 165.5 | 0.9306 | 0.0174 | 0.002 | 0.0194 |
| 165.5333 | 0.926 | 0.0174 | 0.0033 | 0.0207 |
| 165.5667 | 0.9168 | 0.0305 | 0.002 | 0.0325 |
| 165.6 | 0.9138 | 0.0042 | 0.0007 | 0.0049 |
| 165.6333 | 0.9079 | 0.0174 | 0.002 | 0.0194 |
| 165.6667 | 0.9049 | 0.0305 | 0.002 | 0.0325 |
| 165.7 | 0.9016 | 0.0174 | 0.002 | 0.0194 |
| 165.7333 | 0.8921 | 0.0174 | 0.0007 | 0.018 |
| 165.7667 | 0.8924 | 0 | 0.002 | 0.002 |
| 165.8 | 0.8849 | 0.0174 | 0.002 | 0.0194 |
| 165.8333 | 0.8796 | 0.0174 | 0.002 | 0.0194 |
| 165.8667 | 0.8733 | 0.0174 | 0.0007 | 0.018 |
| 165.9 | 0.8677 | 0.0174 | 0.002 | 0.0194 |
| 165.9333 | 0.8681 | 0.0174 | 0.0007 | 0.018 |
| 165.9667 | 0.8615 | 0.0042 | 0.0007 | 0.0049 |
| 166 | 0.8595 | 0.0305 | 0 | 0.0305 |
| 166.0333 | 0.8516 | 0.0042 | 0.0007 | 0.0049 |
| 166.0667 | 0.85 | 0.0174 | 0.0033 | 0.0207 |
| 166.1 | 0.8444 | 0.0174 | 0.002 | 0.0194 |
| 166.1333 | 0.8391 | 0.0305 | 0.0007 | 0.0312 |
| 166.1667 | 0.8338 | 0.0174 | 0.002 | 0.0194 |
| 166.2 | 0.8335 | 0.0042 | 0.002 | 0.0062 |
| 166.2333 | 0.8299 | 0.0042 | 0.002 | 0.0062 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | | Total Flow |
|----------|---------|----------------|--------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| 166.2667 | 0.8253 | 0.0174 | 0.002 | 0.0194 |
| 166.3 | 0.8217 | 0.0042 | 0.0033 | 0.0075 |
| 166.3333 | 0.8131 | 0.0174 | 0.0033 | 0.0207 |
| 166.3667 | 0.8111 | 0.0174 | 0.003 | 0.0194 |
| 166.4 | 0.8052 | 0.0174 | 0.002 | 0.0194 |
| 166.4333 | 0.8032 | 0.0174 | 0.0033 | 0.0207 |
| 166.4667 | 0.8032 | 0.0305 | 0.003 | 0.0325 |
| 166.5 | 0.7983 | 0.0042 | 0.0007 | 0.0049 |
| 166.5333 | 0.793 | 0.0174 | 0.002 | 0.0194 |
| 166.5667 | 0.791 | 0.0305 | 0.0033 | 0.0134 |
| 166.6 | 0.7891 | 0.0174 | 0.0007 | 0.0338 |
| 166.6333 | 0.7802 | 0.0174 | 0.002 | 0.0194 |
| 166.6667 | 0.7762 | 0.0305 | 0.002 | 0.0134 |
| 166.7 | 0.7759 | 0.0042 | 0.0007 | 0.0049 |
| 166.7333 | 0.7726 | 0.0042 | 0.002 | 0.0062 |
| 166.7667 | 0.769 | 0.0305 | 0.0007 | 0.0312 |
| 166.8 | 0.7667 | 0.0042 | 0.0033 | 0.0075 |
| 166.8333 | 0.7641 | 0.0305 | 0.0033 | 0.0338 |
| 166.8667 | 0.7575 | 0.0174 | 0.0007 | 0.018 |
| 166.9 | 0.7532 | 0.0174 | 0.002 | 0.0194 |
| 166.9333 | 0.7525 | 0.0174 | 0.002 | 0.0194 |
| 166.9667 | 0.7509 | 0.0042 | 0 | 0.0042 |
| 167 | 0.7466 | 0.0305 | 0.0007 | 0.0312 |
| 167.0333 | 0.7453 | 0.0305 | 0.0007 | 0.0312 |
| 167.0667 | 0.7427 | 0.0042 | 0.0007 | 0.0049 |
| 167.1 | 0.739 | 0.0042 | 0.002 | 0.0062 |
| 167.1333 | 0.7348 | 0.0305 | 0.0007 | 0.0312 |
| 167.1667 | 0.7348 | 0.0174 | 0.0033 | 0.0207 |
| 167.2 | 0.7295 | 0.0305 | 0.0033 | 0.0338 |
| 167.2333 | 0.7262 | 0.0174 | 0.002 | 0.0194 |
| 167.2667 | 0.7223 | 0.0305 | 0.0033 | 0.0338 |
| 167.3 | 0.7236 | 0.0174 | 0.0007 | 0.018 |
| 167.3333 | 0.7193 | 0.0042 | 0.0046 | 0.0088 |
| 167.3667 | 0.719 | 0.0174 | 0.002 | 0.0194 |
| 167.4 | 0.7088 | 0.0042 | 0.002 | 0.0062 |
| 167.4333 | 0.7107 | 0.0042 | 0.0007 | 0.0049 |
| 167.4667 | 0.7068 | 0.0042 | 0.002 | 0.0062 |
| 167.5 | 0.7012 | 0.0174 | 0.0033 | 0.0207 |
| 167.5333 | 0.7035 | 0.0174 | 0.0033 | 0.0207 |
| 167.5667 | 0.6992 | 0.0305 | 0.002 | 0.0325 |
| 167.6 | 0.6946 | 0.0174 | 0.002 | 0.0194 |
| 167.6333 | 0.6923 | 0.0042 | 0.0033 | 0.0075 |
| 167.6667 | 0.6916 | 0.0174 | 0.0033 | 0.0207 |



Project No. G101276459SAT-023

| Time | Ch 1 dP | Ch 2 High Flow | Ch 3 Low Flow | Total Flow |
|----------|---------|----------------|---------------|------------|
| (min) | (psi) | (LPM) | (LPM) | (LPM) |
| () | (1001) | (21111) | (2.11) | (LI IVI) |
| 167.7 | 0.6851 | 0.0042 | 0.002 | 0.0062 |
| 167.7333 | 0.6804 | 0.0042 | 0.0007 | 0.0049 |
| 167.7667 | 0.6801 | 0.0305 | 0.0007 | 0.0312 |
| 167.8 | 0.6765 | 0.0042 | 0.0033 | 0.0075 |
| 167.8333 | 0.6745 | 0.0174 | 0.0033 | 0.0207 |
| 167.8667 | 0.6716 | 0.0174 | 0.0007 | 0.018 |
| 167.9 | 0.6702 | 0.0174 | 0.0007 | 0.018 |
| 167.9333 | 0.6646 | 0.0305 | 0.002 | 0.0325 |
| 167.9667 | 0.6646 | 0.0174 | 0.0007 | 0.018 |
| 168 | 0.662 | 0.0042 | 0.0007 | 0.0049 |
| 168.0333 | 0.6561 | 0.0174 | 0.002 | 0.0194 |
| 168.0667 | 0.6558 | 0.0174 | 0.0033 | 0.0207 |
| 168.1 | 0.6515 | 0.0042 | 0.002 | 0.0062 |
| 168.1333 | 0.6515 | 0.0174 | 0.002 | 0.0194 |
| 168.1667 | 0.6479 | 0.0174 | 0.002 | 0.0194 |
| 168.2 | 0.6465 | 0.0174 | 0.0007 | 0.018 |
| 168.2333 | 0.6403 | 0.0174 | 0.0007 | 0.018 |
| 168.2667 | 0.6416 | 0.0174 | 0.0033 | 0.0207 |
| 168.3 | 0.6419 | 0.0174 | 0 | 0.0174 |
| 168.3333 | 0.6324 | 0.0042 | 0.002 | 0.0062 |
| 168.3667 | 0.6314 | 0.0042 | 0.0007 | 0.0049 |
| 168.4 | 0.6298 | 0.0174 | 0.0033 | 0.0207 |
| 168.4333 | 0.6251 | 0.0305 | 0 | 0.0305 |
| 168.4667 | 0.6245 | 0.0305 | 0.0033 | 0.0338 |
| 168.5 | 0.6199 | 0.0305 | 0.0007 | 0.0312 |
| 168.5333 | 0.6172 | 0.0174 | 0.002 | 0.0194 |
| 168.5667 | 0.6172 | 0.0174 | 0.002 | 0.0194 |
| 168.6 | 0.6166 | 0.0305 | 0.0033 | 0.0338 |
| 168.6333 | 0.6077 | 0.0042 | 0.002 | 0.0062 |
| 168.6667 | 0.6087 | 0.0174 | 0 | 0.0174 |
| 168.7 | 0.6031 | 0.0174 | 0.0007 | 0.018 |
| 168.7333 | 0.6008 | 0.0174 | 0.002 | 0.0194 |
| 168.7667 | 0.5985 | 0.0174 | 0.002 | 0.0194 |
| 168.8 | 0.5991 | 0.0042 | 0.0033 | 0.0075 |
| 168.8333 | 0.5952 | 0.0174 | 0.002 | 0.0194 |
| 168.8667 | 0.5962 | 0.0174 | 0.002 | 0.0194 |
| 168.9 | 0.5926 | 0 | 0.0007 | 0.0007 |
| 168.9333 | 0.5873 | 0.0174 | 0.002 | 0.0194 |
| 168.9667 | 0.587 | 0.0174 | 0.002 | 0.0194 |
| 169 | 0.5827 | 0.0174 | 0.0033 | 0.0207 |
| 169.0333 | 0.5824 | 0.0174 | 0.0007 | 0.018 |
| 169.0667 | 0.581 | 0.0042 | 0.0007 | 0.0049 |
| 169.1 | 0.5764 | 0.0174 | 0.0007 | 0.018 |




Project No. G101276459SAT-023


| Time (min) | Ch 1 dP (psi) | Ch 2 High Flow (LPM) | Ch 3 Low Flow (LPM) | Total Flow (LPM) |
|---------------|------------------|-------------------------|------------------------|---------------------|
| 169.1333 | 0.5741 | 0.0042 | 0.002 | 0.0062 |
| 169.1667 | 0.5741 | 0.0174 | 0 | 0.0174 |
| 169.2 | 0.5692 | 0.0042 | 0.002 | 0.0062 |
| 169.2333 | 0.5689 | 0.0174 | 0.0007 | 0.018 |
| 169.2667 | 0.5626 | 0.0174 | 0.0007 | 0.018 |
| 169.3 | 0.5646 | 0.0042 | 0.0033 | 0.0075 |
| 169.3333 | 0.5613 | 0.0174 | 0.002 | 0.0194 |
| 169.3667 | 0.5583 | 0.0042 | 0.002 | 0.0062 |
| 169.4 | 0.5547 | 0.0174 | 0.002 | 0.0194 |
| 169.4333 | 0.5514 | 0.0042 | 0.002 | 0.0062 |
| 169.4667 | 0.5511 | 0.0042 | 0.002 | 0.0062 |
| 169.5 | 0.5531 | 0 | 0.002 | 0.002 |
| 169.5333 | 0.5442 | 0.0174 | 0.002 | 0.0194 |
| 169.5667 | 0.5432 | 0.0042 | 0.0007 | 0.0049 |
| 169.6 | 0.5412 | 0.0042 | 0.002 | 0.0062 |
| 169.6333 | 0.5382 | 0.0174 | 0.002 | 0.0194 |
| 169.6667 | 0.5396 | 0.0174 | 0.0033 | 0.0207 |
| 169.7 | 0.5284 | 0.0174 | 0.002 | 0.0194 |
| 169.7333 | 0.5017 | 0.0174 | 0.0033 | 0.0207 |
| 169.7667 | 0.4711 | 0.0042 | 0 | 0.0042 |
| 169.8 | 0.4454 | 0.0174 | 0.002 | 0.0194 |
| 169.8333 | 0.4211 | 0.0174 | 0.0033 | 0.0207 |
| 169.8667 | 0.3944 | 0.0305 | 0.0007 | 0.0312 |
| 169.9 | 0.3704 | 0.0174 | 0.002 | 0.0194 |
| 169.9333 | 0.3529 | 0.0042 | 0.002 | 0.0062 |
| 169.9667 | 0.3312 | 0.0174 | 0.0033 | 0.0207 |
| 170 | 0.3098 | 0.0174 | 0 | 0.0174 |
| 170.0333 | 0.2901 | 0.0174 | 0.002 | 0.0194 |
| 170.0667 | 0.2729 | 0.0305 | 0.0007 | 0.0312 |
| 170.1 | 0.2575 | 0.0305 | 0.002 | 0.0325 |




APPENDIX C Photographs



























APPENDIX D Test Plan





20004-020 (10/21/2013)

AREVA NP Inc.

Engineering Information Record

Document No.: 51 - 9217475 - 000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

Mike Dey Staff Engineer

Michael A. Brown Quality Supervisor

Page 1 of 27



| A | | | | | 20004-020 (10/21/2013 nt No.: 51-9217475-00 |
|--|---|-------------------------|--------------|---------------------|---|
| AREVA | | | | Docume | IL NO 51-5217475-00 |
| | Detailed Test Plan for | Conducting MO | X Seismic Pr | essure Test 9 | |
| Safety Related? | YES NO | | | | |
| Does this document est | tablish design or technica | al requirements | YES | | |
| Does this document co | ntain assumptions requir | _ | | | |
| Does this document co. | ntain Customer Required | Format? | YES 🔀 | NO | |
| | S | ignature B | lock | | |
| Name and Title/Discipline | Signature | P/LP, R/LR, A-CRF, A | Date | Prep | ges/Sections ared/Reviewed/ red or Comments |
| Aaron Adrian Princ Des Eng Spec II / PEYFI-A | | P | 1-22-14 | All | |
| Derrick Risner Engineer I / PEYF1-A | | R | 1-22-14 | All | |
| Scott Groesbeck Manager Tech Ops / PEYF1-A | | A | 1/22/14 | All | |
| | - | | | | , |
| Notes P/I P designate | s Preparer (P), Lead Prep | eviewer (LR) | mor Poquiros | Format (A-C | RF) |
| R/LR designate A-CRF designates A designates A | tes Project Manager App Approver/RTM – Verifica Approval of Custom | ation of Review | er Independe | nce | ole) |
| R/LR designate A-CRF designates A designates A | ates Project Manager App Approver/RTM – Verifica Approval of Custom Title | er Referenc | er Independe | nce | Dete |
| R/LR designate A-CRF designate A designates A Project Manager A Name | ates Project Manager App Approver/RTM – Verifica Approval of Custom Title | er Referenc | er Independe | nce not applical | 1 |
| R/LR designate A-CRF designate A designates A Project Manager A Name (printed or typed) | Approval of Custom (printed or the Project Manager / Project | er Referenc | er Independe | nce not applical | Date |
| R/LR designate A-CRF designate A designates A Project Manager A Name (printed or typed) | Approval of Custom (printed or the Project Manager / Project | er Referenc | er Independe | nce not applical | Date |
| R/LR designate A-CRF designate A designates A Project Manager A Name (printed or typed) Perry Calos | Approval of Custom (printed or the Project Manager / Project | ation of Review | es (N/A if I | nce not applical | Date |





20004-020 (10/21/2013) Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

Record of Revision

| Revision No. | Pages/Sections/ Paragraphs Changed | Brief Description / Chan28ge Authorization |
|-----------------|---------------------------------------|---|
| 000 | All | Initial Issue. This document contains the main body of the report (pages 1-19), Appendix A (1 page), Appendix B (1 page), Appendix C (4 pages), and Appendix D (2 pages) for a total of 27 pages. |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

Table of Contents

| | | P | age |
|-------|------------|---|-----|
| SIGNA | ATURE | BLOCK | 2 |
| RECO | RD OF | REVISION | 3 |
| LIST | OF TAB | LES | 6 |
| ACRO | NYMS. | | 7 |
| BACK | GROUN | ND | 8 |
| 1.0 | PURP | OSE | 8 |
| 2.0 | | CTIVE | |
| | 2.1 | Test Deck Description | |
| | 2.2 | Test Description | 9 |
| | 2.3 | Critical Characteristics and Limiting Parameters Being Tested | 10 |
| 3.0 | ACCE | PTANCE CRITERIA | 10 |
| 4.0 | RESP | ONSIBILITIES | 11 |
| | 4.1 | MOX Services | 11 |
| | 4.2 | AREVA | 11 |
| | 4.3 | Testing Laboratory | |
| | 4.4 | Other Subcontracted Entities | |
| 5.0 | | UREMENT PLAN | |
| | 5.1 | Penetration Seal Materials | |
| | 5.2 5.3 | Test Deck/Test Slab Penetrating Items | |
| 6.0 | | IAL PRECAUTIONS | |
| 6.0 | 6.1 | Precautions for Construction of Test Assemblies | |
| | 6.2 | Precautions for Installation of Seal Assemblies | |
| | 6.3 | Precautions for Conducting Seismic Pressure Tests | |
| 7.0 | PRER | EQUISITES | |
| | 7.1 | General Test Configuration Requirements | |
| | 7.2 | Safety Related Materials | 14 |
| | 7.3 | Dimensioned Drawings | 14 |
| | 7.4 | Test Configuration | 15 |
| | | | |





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

Table of Contents (continued)

| | | | Page |
|-------|----------|---------------------------------|------|
| 8.0 | TEST | ASSEMBLY CONSTRUCTION | 15 |
| | 8.1 | Test Slab Construction | 15 |
| | 8.2 | Penetration Seal Installation | |
| | 8.3 | Pre-Test Verifications | 15 |
| 9.0 | PROC | EDURE | 15 |
| | 9.1 | Seismic Pressure Test Apparatus | 15 |
| | 9.2 | Process | |
| | 9.3 | Post Test Examination | 17 |
| 10.0 | | SYSTEMS | |
| 11.0 | TEST | REPORT | 18 |
| 12.0 | REFE | RENCES | 19 |
| APPEN | NDIX A : | TEST DECK/TEST SLAB DRAWINGS | A-1 |
| APPEN | NDIX B : | TEST PENETRATION DRAWINGS | B-1 |
| APPEN | IDIX C : | BILL OF MATERIALS | C-1 |
| APPEN | NDIX D : | DESIGN VERIFICATION CHECKLIST | D-1 |





Document No.: 51-9217475-000

| Detailed Test Plan for Conducting MOX Seismic Pressure Test 9 | |
|---|------|
| List of Tables | |
| | Page |
| ABLE 9-1: DIFFERENTIAL SEISMIC PRESSURE TEST LEVELS | 16 |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

ACRONYMS

ABC Alternate Building Construction
CGD Commercial Grade Dedication
CGI Commercial Grade Item
IROFS Items Relied On For Safety

MOX Mixed Oxide

MFFF Mixed Oxide Fuel Fabrication Facility

QA Quality Assurance
QC Quality Control
QL Quality Level

pcf pounds per cubic foot psf pounds per square foot

SSC Structures, Systems and Components

w.g. Water Gauge

Penetration Seal Materials

QSil 5558MC Quantum Silicones QSil 5558MC Silicone Elastomer

DC-170 Dow Corning Sylgard 170 Silicone Elastomer

DC-790 Dow Corning 790 Silicone Building Sealant





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

BACKGROUND

AREVA Inc. (AREVA) is assisting Shaw AREVA MOX Services (MOX Services) in the development and implementation of a penetration seal program for the Mixed Oxide Fuel Fabrication Facility (MFFF). One aspect of the MOX penetration seal program includes conducting various types of qualification tests of penetration seal assemblies to substantiate the performance capabilities of specific penetration seal designs. Seismic pressure testing is one type of qualification testing that needs to be performed in order to demonstrate the capability of MOX penetration seal designs to survive a seismic event. Other types of qualification testing, such as fire testing and pressure testing of penetration seal assemblies, are addressed by other test plans.

1.0 PURPOSE

The purpose of this test plan is to define the test assemblies, test methods and acceptance criteria for conducting a seismic pressure test in support of the MOX penetration seal program.

This test plan defines the test methods, acceptance criteria and test report documentation requirements for Seismic Pressure Test 9. Additionally, this detailed test plan defines the roles and responsibilities of MOX Services, AREVA, the selected testing laboratory, and any other subcontracted entity engaged in support of seismic pressure testing efforts.

This detailed test plan also describes the procurement plan for materials associated with penetration seals in Seismic Pressure Test 9 and identifies the entities responsible for procuring the various components of the test assembly based on the quality level assigned to each component.

This test plan also establishes minimum quality requirements for the penetration seal materials used in the test assembly and links quality requirements in the AREVA QA program to customer/project quality requirements.

The configuration being tested by Seismic Pressure Test 9 is the same assembly that was tested under Pressure Test 11 (51-9215844 [Ref. 12.6]). This configuration is described in detail in Section 2.2 of this Test Plan.

2.0 OBJECTIVE

The primary objective of this test plan is to evaluate the seismic resistance capabilities of elastomer penetration seals for the sealing of openings in alternate building construction (ABC) walls using alternating pressures at the air pressure increments above atmospheric pressure provided in Section 9.2.

The primary construction material used in the MOX facility is MOX-Crete, a special concrete blend mixed and installed on site. Penetration seal designs have been developed and tested in concrete applications for use in the MOX facility. In addition, MOX uses a type of alternate building construction (ABC) for forming interior corridor walls and partitions. Penetration seal designs for damper closures, pressure resistance, and for fire ratings have been developed and tested, however, the seismic resistance capability of elastomer seals in ABC walls has not been established.

MOX specific designs for ABC walls are provided on Drawing DCS01-BMF-DS-PLF-A-04509 Sheets 1-3 [Reference 12.7] and Drawing DCS01-BMF-DS-PLS-B-01692 [Reference 12.8]. However, this test is not intended to evaluate the pressure resistance capability of the ABC wall, but rather the elastomer seal to Structo Crete material interface.

The specific configurations to be tested are described below. Critical characteristics and the associated limiting parameters that will be substantiated by a successful test are also provided.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

2.1 Test Deck Description

The test deck will consist of a 12" thick concrete slab measuring approximately 96" x 96" (8' x 8') [Note: Final test slab size to be determined by Intertek and documented in the final test report]. Within this slab there will be two openings into which Structo Crete material will be fastened. The concrete openings will be 14" x 20" without beveled edges. Details for the two penetrations are provided in Section 2.2. The penetrations will be unlined (bare concrete). The test deck will be horizontally oriented with a hemispherical 72" diameter steel pressure vessel mounted on each side of the precast openings in the slab.

Note: It is anticipated that the slab with the silicone elastomer seals used for Pressure Test 11 will not be damaged during Pressure Test 11 and will be available for reuse in this seismic pressure test. For the purpose of Seismic Pressure Test 9, no changes will be made to the silicone elastomer seals installed for Pressure Test 11 (51-9215844 Ref. 12.6).

Additionally, most of the openings (penetrations) in the MOX facility have been cast with a ¾" bevel on both sides of the opening. For testing and qualification purposes, this feature is considered aesthetic, and it has no adverse effect on the functional performance of the penetration seal installation. In fact for some applications, such as in the case of seismically qualified penetrations seals, the bevel provides a benefit over non-beveled openings. Beveled edges are cast into concrete openings and do not apply to ABC barriers. Therefore, for the purposes of the penetration seal test program, the bevel feature will not be included for the seismic pressure test covered in this test plan.

Drawings showing the general layout of the test deck (test slab) for this seismic pressure test can be found in Appendix A.

Note: If the slab from Pressure Test 11 was damaged during testing or is otherwise not available, this test plan will require revision.

2.2 Test Description

There are two openings in the test deck that will be lined with ABC wall material (Structo Crete) creating two penetrations to be sealed and tested in Seismic Pressure Test 9.

- Penetration P1 Test penetration P1 is a 14" x 20" concrete opening containing no penetrating items. Structo Crete panels will be installed within the opening as shown in Appendix B. Structo Crete panels are generally provided with one side smoother than the other (as a result of the manufacturing process). Two sides of the penetration will be lined with the smoother side of the Structo Crete panels facing the seal material and two sides with the smoother side facing away. This penetration will be sealed with an 8" depth of Dow Corning Sylgard® 170 Silicone Elastomer (DC-170) with no permanent damming.
- Penetration P2 Test penetration P1 is a 14" x 20" concrete opening containing no penetrating items. Structo Crete panels will be installed within the opening as shown in Appendix B. Structo Crete panels are generally provided with one side smoother than the other (as a result of the manufacturing process). Two sides of the penetration will be lined with the smoother side of the Structo Crete panels facing the seal material and two sides with the smoother side facing away. This penetration will be sealed with a 8" depth of Quantum Silicones QSil 5558MC Silicone Elastomer (QSil 5558MC) with no permanent damming.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

The Structo Crete and penetration seal materials will be located within the openings as shown in Appendix B. The test will be performed with the test deck oriented in the horizontal position and in accordance with Section 9.0.

2.3 Critical Characteristics and Limiting Parameters Being Tested

The specific critical characteristics and associated limiting parameters being tested for Seismic Pressure Test 9 are as follows:

- P1: Dow Corning 170 silicone elastomer installed within a Structo Crete lined opening having a total bond area of approximately 496 in², a total pressurized area of approximately 231 in². This results in a "pressurized area" to "bond area" ratio of approximately 1:2.15 (231:496).
- P2: QSil 5558MC silicone elastomer installed within a Structo Crete lined opening having a total bond area of approximately 496 in², a total pressurized area of approximately 231 in². This results in a "pressurized area" to "bond area" ratio of approximately 1:2.15 (231:496).

3.0 ACCEPTANCE CRITERIA

Seismically qualified penetration seals at the MOX facility are required to remain in the opening (penetration) during and after a Design Earthquake seismic event. In order demonstrate that a penetration seal will remain in place, the seal will have to be evaluated for two conditions: 1) The seismic inertia of the self-weight of the seal will have to be evaluated; and 2) The seismic deflection of the commodities penetrating the seal will have to be considered.

Seismic pressure testing will be used to evaluate the seismic inertia of the self-weight of the seal assembly. This will be accomplished by applying a pressure to alternating sides of the penetration seal to demonstrate that the seal will not become dislodged from the opening due to the seismic inertia of the self-weight of the seal. The seismic deflection of commodities that penetrate the seal will be addressed by a separate analysis.

Ultimately, the overall seismic qualification of MOX penetration seal assemblies will be captured in a penetration seal seismic qualification report that will tie together the results of seismic pressure testing with other analyses performed to address seismic deflection of commodities that penetrate the seal.

The acceptance criterion for evaluating the seismic inertia of the seal self-weight is calculated in MOX Services Calculation "Penetration Seal Seismic Requirements" [Reference 12.1] and expressed as an equivalent pressure. Testing at this equivalent pressure will qualify that a penetration seal assembly will remain in place (i.e., the penetration seal cannot become dislodged from the opening or otherwise catastrophically fail such that a substantial leakage path is created) during the design earthquake seismic event.

The relative movement of the items penetrating the seal during a seismic event are not considered as a part of this test. A separate engineering evaluation is required to evaluate the effect of movement on a seal with penetrating items during a seismic event.

No pressure inducing events are required to be considered concurrently with a seismic event.

Table 9-1 identifies the differential pressure levels (stages) for conducting this seismic pressure test, as well as, the acceptance criteria in order for the penetration seal assemblies to meet the seismic pressure testing requirements.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

4.0 RESPONSIBILITIES

The following roles and responsibilities apply to this detailed test plan.

4.1 MOX Services

- 4.1.1 Provide review and concurrence of this detailed seismic pressure test plan.
- 4.1.2 Provide concurrence for any revisions made to this detailed seismic pressure test plan during test specimen construction activities.
- 4.1.3 Provide some of the materials for test assembly construction from MOX Services surplus or scrap (if available).
- 4.1.4 Reserves the right to witness seismic pressure testing.

4.2 AREVA

- 4.2.1 Develop this detailed seismic pressure test plan.
- 4.2.2 Provide management and oversight of all aspects of the MOX penetration seal test program.
- 4.2.3 Select the seismic pressure testing facility and establish sub-contract agreements.
- 4.2.4 Provide engineering instructions to the testing laboratory for performance of the test including test parameters, acceptance criteria, requirements for documenting the test results in a final test report, etc.
- 4.2.5 Procure any penetration seal materials, devices or components required to be Safety Related (QL-1) as designated in the procurement plan section of the test plan.
- 4.2.6 Notify MOX Services at least 10 days prior to test date to facilitate MOX Services decision to witness the seismic pressure test.
- 4.2.7 Witness the seismic pressure tests.
- 4.2.8 Perform post-test examinations.
- 4.2.9 Review, approve and issue final test report.

4.3 Testing Laboratory

- 4.3.1 Notify AREVA at least 5 days prior to the start of test assembly construction activities.
- 4.3.2 Construct test deck in accordance with this detailed test plan and AREVA direction.
- 4.3.3 Procure test deck materials and any other test assembly components identified under the Testing Laboratory scope in the procurement plan section of this detailed test plan.
- 4.3.4 Procure testing equipment necessary for seismic pressure testing services in accordance with the detailed seismic pressure test plans and verify that the testing equipment is properly calibrated.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

- 4.3.5 Provide seismic pressure testing services in accordance with this approved detailed seismic pressure test plan.
- 4.3.6 Assist AREVA, as necessary, in conducting detailed post-test destructive examinations of the test assembly.
- 4.3.7 Dispose of test assembly upon completion of the seismic pressure test.
- 4.3.8 Generate a final test report in accordance with test plan requirements.

4.4 Other Subcontracted Entities

There are no other Subcontractors for this seismic pressure test plan.

5.0 PROCUREMENT PLAN

Penetration seal seismic pressure testing involves many elements beyond the penetration seal material being qualified. Some of these elements include the test deck or test slab, several different types of penetrating items, supports for penetrating items, various fasteners for securing test articles and laboratory instrumentation to the test assembly, etc. Not all elements of the test program are required to be procured to the same quality level as the penetration seal material to satisfy the quality requirements of the end product (e.g., QL-1 qualified penetration seals). The following procurement plan takes into consideration the required quality level of the various materials envisioned to be required for a typical penetration seal seismic pressure test and prescribes an approach for material procurement which considers cost, schedule and quality requirements.

5.1 Penetration Seal Materials

The vast majority of penetration seals that will be installed throughout the MFFF are designated QL-1. MOX Services defines QL-1 in PP9-1, "SSC Quality Levels & Marking Design Documents" [Reference 12.2] as follows:

QL-1 SSCs are typically IROFS (all IROFS are QL-1 and may be either SSCs or Administrative Controls) credited in the Integrated Safety Analysis with a required function to prevent or mitigate design basis events such that high-consequence events are made highly unlikely; intermediate-consequence events are made unlikely; or to prevent criticality. For example, the failure of an IROFS item could cause:

- Loss of a primary confinement feature leading to release of material resulting in exceeding 10CFR70.61 performance requirements;
- Failure to satisfy the double contingency principle for the prevention of a criticality accident; or
- 3. Loss of other safety function required to meet 10CFR70.61 performance requirements.

This definition correlates with the following definition of "Nuclear Safety Related" in AREVA Administrative Procedure (AP) 1702-25, "Assignment of Nuclear Safety Classification to Products and Services" [Reference 12.3]:

Definition of "Nuclear Safety Related"





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

Company products and services are considered to be nuclear safety related if they involve the evaluation, specification, design or change in design, operation, or performance of structures, systems, and components which must function directly, or must support other systems which function, to ensure any of the following:

- · The integrity of the reactor coolant pressure boundary
- The capability to shut down the reactor and maintain it in a safe shutdown condition
- The capability to prevent or mitigate the consequences of accidents which could result in potential offsite radiation exposures greater than accepted limits.

On this basis, permanent penetration seal materials used in this test program shall be procured by AREVA or supplied by MOX Services and suitably base-lined so that future procurements of the same commercial materials can undergo the commercial grade dedication process in support Nuclear Safety Related (i.e., MOX QL-1) plant installations. Only the primary seal material specified as a part of the final seal design and which are left in place during testing become an integral part of the seal assembly and need to be base-lined for future dedication of similarly procured materials.

The quality level of the penetration seal materials procured for this test plan is Non-Safety.

Note: Commercial Grade Dedication (CGD) must be performed for Commercial Grade Items (CGIs) used in Safety Related applications when procured from suppliers where specific quality controls for nuclear applications cannot be imposed in a practical manner in accordance with 56-9141754-001, "AREVA NP Inc. Quality Assurance Program" [Reference 12.4]. However, none of the seal materials to be procured and used in the test program are intended or approved for installation in the MOX facility. Therefore, CGD of penetration seal materials used for test purposes is not required.

For this seismic pressure test, the following materials shall be procured by AREVA and base-lined for future dedication activities.

- 1. Quantum Silicones QSil 5558MC Silicone Elastomer
- 2. Dow Corning Sylgard 170 Silicone Elastomer

5.2 Test Deck/Test Slab

The test deck/test slab will be used to simulate a boundary in which the penetration seal assemblies may be installed. The test deck/test slab is not considered an integral part of the penetration seal assembly being tested and therefore is not intended to replicate MOX-specific plant conditions and not considered integral in bounding the performance of the penetration seal assemblies (e.g., concrete blend, compressive strength, rebar size and spacing). The test deck/test slab will be comprised of normal weight reinforced concrete, unless otherwise stipulated in the detailed test plan.

Openings cast into the test deck/test slab will simulate certain features consistent with MOX penetrations (e.g., painted or coated interior finishes, etc.) as defined by detailed test plan drawings contained in Appendix A.

The testing laboratory shall be responsible for procuring all materials and components associated with the construction of the test deck/test slab, unless otherwise specified in the detailed test plan. The test deck shall comply with the requirements of the approved detailed test plan drawings contained in Appendix A, and shall be constructed in accordance with the testing facility's Quality Assurance Program.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

The quality level of the test deck is Non-safety.

5.3 Penetrating Items

There are no penetrating items (e.g., conduits, cable trays and wire ways) associated with this seismic pressure test.

6.0 SPECIAL PRECAUTIONS

6.1 Precautions for Construction of Test Assemblies

Observe testing facilities safe work practices for construction, lifting, and moving of test assemblies.

6.2 Precautions for Installation of Seal Assemblies

Observe specific precautions recommended by seal material manufacturer as noted on product literature and material safety data sheets contained in AREVA NP Inc. Document 01-9198306, *Installation Instruction Manual for MOX Penetration Seal Test Program* [Reference 12.5].

6.3 Precautions for Conducting Seismic Pressure Tests

Proper safety precautions shall be exercised to preclude personnel from direct exposure to loss of pressure events, unexpected disengaging of testing equipment from the test deck, and all other related hazards.

7.0 PREREQUISITES

7.1 General Test Configuration Requirements

The test assembly, including slab layout and penetration seal configurations shall be as specified by AREVA and in accordance with the drawings and information contained in Appendix A and Appendix B of this test plan, and AREVA NP Inc. Document 01-9198306, Installation Instruction Manual for MOX Penetration Seal Test Program [Reference 12.5].

7.2 Safety Related Materials

Penetration seal materials that are purchased **Non-Safety** for this test program but are to be base-lined for future Nuclear Safety Related via the Commercial Grade Dedication process are indicated on the AREVA Bill of Materials (Appendix C.1).

7.3 Dimensioned Drawings

All test articles shall conform to the dimensioned drawings supplied by AREVA and contained in Appendix A and Appendix B of this test plan. Any differences between designed and constructed/tested assemblies shall be noted in final drawings contained within the test report.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

7.4 Test Configuration

All test articles shall be securely fastened to the test apparatus by the laboratory. All openings shall be sealed in accordance with test plan instructions, drawings (Appendix A and Appendix B) and AREVA Document 01-9198306 [Reference 12.5].

8.0 TEST ASSEMBLY CONSTRUCTION

8.1 Test Slab Construction

The Testing Laboratory shall construct the test slab, including location and size of openings and placement of penetrating items, in accordance with the drawings contained in Appendices A and B of this Test Plan.

AREVA quality control representative (or approved designee) shall conduct an inspection of the test slab for compliance with the approved Test Plan drawings prior to installation of individual penetration seal test assemblies. Any differences between the approved Test Plan drawings and the as-built test slab configuration shall be corrected (if deemed necessary by the ARVEA Test Engineer) or noted by the QC Inspector (if correction is not required). Completion of this verification shall be documented as required by AREVA Document 01-9198306, Installation Instruction Manual for MOX Penetration Seal Test Program [Reference 12.5].

8.2 Penetration Seal Installation

AREVA (or approved designee) shall install the penetration seal test assemblies in accordance with the drawings contained in Appendix A and Appendix B of this detailed test plan and in accordance with AREVA Document 01-9198306, *Installation Instruction Manual for MOX Penetration Seal Test Program* [Reference 12.5].

QA/QC verification of penetration seal installations shall be documented as required by AREVA Inc. Document 01-9198306, Installation Instruction Manual for MOX Penetration Seal Test Program [Reference 12.5]. For the purposes of this test plan, the "seal assemblies" requiring QA/QC verification under 01-9198306 are limited to the installations of Dow Corning Sylgard® 170 Silicone Elastomer (DC-170) and Quantum Silicones QSil 5558MC Silicone Elastomer (QSil 5558MC).

8.3 Pre-Test Verifications

Prior to conducting the seismic pressure test, the AREVA Test Engineer shall sign-off indicating that the test article (test penetration) is complete and ready for testing as required by AREVA Document 01-9198306, *Installation Instruction Manual for MOX Penetration Seal Test Program* [Reference 12.5].

9.0 PROCEDURE

9.1 Seismic Pressure Test Apparatus

The seismic pressure test apparatus to be used for this seismic pressure test shall be constructed and maintained by the testing laboratory. Two hemispherical 72" diameter steel pressure vessels shall be used to construct the assembly. One side shall be used to induce the testing pressures above atmospheric pressure based on Table 9-1, while the other side shall measure the pressure increase or "leakage" through the penetration. The test apparatus shall be "leak-tight" and substantial enough to





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

withstand the pressures created for test purposes. Attachment shall be sufficient to withstand the forces imposed on the pressure vessels during the test.

9.2 Process

The differential pressures calculated for seismic pressure testing purposes, as they apply to MFFF penetration seal designs, are discussed in Calculation DCS01-ZEQ-EQ-CAL-M-10118-0 [Reference 12.1]. The seismic pressure testing will be performed using the requirements for the seal material being tested based upon the seal weight per square foot found in Calculation DCS01-ZEQ-EQ-CAL-M-10118-0 [Reference 12.1].

The pressure levels to be used for the seismic pressure are specified in Table 9-1. The pressure used in each seismic pressure test is intended to bound a calculated differential pressure based on the penetration seal material's weight per square foot as detailed in the referenced calculation, with additional margin. The penetration seal seismic requirements in the referenced calculation are based upon the seal system type and the seal material. The bounding differential pressure to be used for each penetration seal seismic pressure test, the test hold time at each pressure, the acceptance criteria to meet the seismic pressure testing requirements, and the basis for each pressure are identified in Table 9-1.

A hold time of 5 minutes has been established for each test stage to ensure that sufficient time at pressure is maintained to confirm that the penetration seal will not catastrophically fail (i.e., will not become dislodged from the opening. This hold time provides reasonable assurance that the penetration seal meets the requirements stated in Calculation DCS01-ZEQ-EQ-CAL-M-10118-0 [Reference 12.1].

Differential Required Test Acceptance Pressure **Hold Time Basis for the Selected Differential Pressure** Stage Criteria (inch w.g.) (minutes) Penetration Seal Remains in Testing at this differential pressure meets the seismic 45 5 1-4 Opening (Does (Note 1) demand expressed as a pressure [Reference 12.1] not become dislodged)

Table 9-1: Differential Seismic Pressure Test Levels

Note 1: For Seismic Pressure Test 9, a nominal density of 85 pcf was used for the silicone elastomer seal material installed for the purposes of determining the test penetration seal's weight per square foot. 85 pcf bounds the installed seal material with margin. 85 pcf times a seal depth of 8", yields a seal weight of approximately 56.7 psf. Based on Figure B-2.1 of Reference 12.1, the corresponding seismic pressure for a seal weight of 56.7 psf is approximately 44.7 inches w.g. Therefore, for Seismic Pressure Test 9 an equivalent seismic pressure of 45 inches w.g. shall be used.

The test assembly shall be attached to the seismic pressure test apparatus and subjected to the pressures identified in Table 9-1 as described below.

- 9.2.1 For Stage 1, the test assembly shall be attached to the pressure test apparatus and subjected to air pressure test at the select pressure level identified in Table 9-1. Once this pressure has been obtained, the pressure shall be maintained for the hold time specified in Table 9-1. If the penetration seal catastrophically fails during this time, the time of failure shall be noted and the test shall be stopped.
- 9.2.2 Once the designated hold time for Stage 1 has been achieved, the pressure shall be vented from the test chamber. Next, the pressure identified in Table 9-1 for Stage 2 shall





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

be applied to the opposite side of the penetration seal and held for the designated hold time. If the penetration seal catastrophically fails during this time, the time of failure shall be noted and the test shall be stopped.

- 9.2.3 Once the designated hold time for Stage 2 has been achieved, the pressure shall be vented from the test chamber. Next, the pressure identified in Table 9-1 for Stage 3 shall be applied to the original side of the penetration seal and held for the designated hold time. If the penetration seal catastrophically fails during this time, the time of failure shall be noted and the test shall be stopped.
- 9.2.4 Once the designated hold time for Stage 3 has been achieved, the pressure shall be vented from the test chamber. Finally, the pressure identified in Table 9-1 for Stage 4 shall be applied to the opposite side of the penetration seal and held for the designated hold time. If the penetration seal catastrophically fails during this time, the time of failure shall be noted and the test shall be stopped.
- 9.2.5 Following completion of Stage 4 pressure testing, the pressure shall be vented from the test chamber. At this point, the test may continue at the discretion of the AREVA test engineer and the testing laboratory manager in charge. Subsequent pressures, and hold times shall be recorded as directed by the AREVA test engineer.

NOTE: The pressure used for the testing performed above is based on a seal material depth of 8 inches and a seal material density of 85 pcf. Should the test be successful, possible subsequent testing pressures may include those for a 10 inch depth of material (56 inches w.g.) and a 12 inch depth of material (67 inches w.g.).

9.2.6 If at any pressure level (or test stage) the penetration seal becomes dislodged from the opening or otherwise catastrophically fails, the pressure test shall be terminated and the time to failure and pressure at which the failure occurred shall be recorded.

9.3 Post Test Examination

Following completion of the seismic pressure test, visual and destructive (if deemed necessary) post-test examinations shall be performed. These examinations shall include, but not necessarily be limited to, the following:

Visual observations of penetration seal condition including:

- · Integrity of seal and conditions on both sides of the penetration
- · Location of greatest degradation
- · Condition of seal to barrier interface

10.0 DATA SYSTEMS

During the seismic pressure test, the any data systems connected to the test apparatus shall be controlled and monitored by the testing laboratory. Data recorded for these components shall be compiled and contained in the final seismic pressure test report.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

11.0 TEST REPORT

The testing laboratory shall submit a report on the results of the test. The test report shall contain the collected data and required quality control documentation. The final test report shall be prepared in sufficient detail to summarize the total testing activity. The final report shall include as a minimum:

- · Date of test
- · Location of test
- · Description of test apparatus and test articles
- · Calibration documentation for all data systems connected to the test apparatus
- Test procedures used
- Acceptance criteria
- · Provide quality control records
- · Color digital photographs of the test project





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

12.0 REFERENCES

References identified with an (*) are maintained within the MOX Records System and are not retrievable from AREVA Records Management. These are acceptable references per AREVA Administrative Procedure 0402-01, Attachment 8. See page 2 for Project Manager Approval of customer references.

- 12.1 *Shaw AREVA MOX Services Calculation DCS01-ZEQ-EQ-CAL-M-10118-0, "Penetration Seal Seismic Requirements"
- 12.2 *Shaw AREVA MOX Services Procedure PP9-1, Revision 14, "SSC Quality Levels & Marking Design Documents"
- 12.3 AREVA NP Inc. Procedure 1702-25, Revision 018, "Assignment of Nuclear Safety Classification to Products and Services"
- 12.4 AREVA NP Inc. Document 56-9141754-001, "AREVA NP Inc. Quality Assurance Program"
- 12.5 AREVA NP Inc. Document 01-9198306, latest revision, "Installation Instruction Manual for MOX Penetration Seal Test Program"
- 12.6 AREVA NP Inc. Document 51-9215844, latest revision, "Detailed Test Plan for Conducting MOX Pressure Test 11"
- 12.7 *Shaw AREVA MOX Services Drawing DCS01-BMF-DS-PLF-A-04509, Sheets 1-3, Revision 3
- 12.8 *Shaw AREVA MOX Services Drawing DCS01-BMF-DS-PLS-B-01692, Revision 0







Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

APPENDIX A: TEST DECK/TEST SLAB DRAWINGS

It is anticipated that the slab with the silicone elastomer seal material used for Pressure Test 11 will not be damaged during Pressure Test 11 and will be available for reuse in this seismic pressure test. For the purpose of Seismic Pressure Test 9, no changes will be made to the seal assemblies installed for Pressure Test 11. For test slab drawings see Pressure Test 11 drawings in Appendix A of Document 51-9215844, "Detailed Test Plan for Conducting MOX Pressure Test 11" [Reference 12.6].

Page A-1





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

APPENDIX B: TEST PENETRATION DRAWINGS

It is anticipated that the slab with the silicone elastomer seal material and penetrants used for Pressure Test 11 will not be damaged during Pressure Test 11 and will be available for reuse in this seismic pressure test. For the purpose of Seismic Pressure Test 9, no changes will be made to the seal assemblies installed for Pressure Test 11. For penetration drawings see Pressure Test 11 drawings in Appendix B of Document 51-9215844, "Detailed Test Plan for Conducting MOX Pressure Test 11" [Reference 12.6].

Page B-1





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

APPENDIX C: BILL OF MATERIALS

This appendix contains the Bill of Materials for this seismic pressure test. The Bill of Materials in Section C.1 identifies materials to be provided by AREVA. The Bill of Materials in Section C.2 identifies materials to be provided by MOX Services. The Bill of Materials in Section C.3 identifies materials to be provided by Intertek.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

C.1 Table Bill of Materials for AREVA Supplied Items

| | Bill of Material for AREVA Supplied Items | | | | | | | | | | |
|---|---|--|--|--|--|--|--|--|--|--|--|
| Item Description Part Number Quantity Units | | | | | | | | | | | |
| | None* | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

None* - Assuming a successful Pressure Test 11, the seal will already be in place, no additional materials will be necessary.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

C.2 Bill of Materials for MOX Services Supplied Items

| | Bill of Material for MOX Services Supplied Items | | | | | | | | | |
|------|--|-------------|----------|-------|-------|--|--|--|--|--|
| Item | Description | Part Number | Quantity | Units | Total | | | | | |
| | None* | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

None* - Assuming a successful Pressure Test 11, the seals will already be in place, no additional materials will be necessary.





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

C.3 Bill of Materials for Intertek Supplied Items

| Bill of Material for Intertek Supplied Items** | | | | | | | | | |
|--|-------------|-------------|----------|-------|-------|--|--|--|--|
| Item | Description | Part Number | Quantity | Units | Total | | | | |
| | None* | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

None* - Assuming a successful Pressure Test 11, the seals will already be in place, no additional materials will be necessary



^{**} This BOM applies to Intertek Supplied Items other than materials required to construct the test slab. Construction of the test slab, including procurement of any materials required for the test slab, is the responsibility of Intertek.



Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9

APPENDIX D: DESIGN VERIFICATION CHECKLIST

| AR | DESIGN VERIFICATION CH | ECK | LIST | |
|-----|---|-----|------|-----|
| | Document Identifier 51 - 9217475 - 000 Title Detailed Test Plan for Conducting Seismic Pressure Test 9 | | | |
| 1. | Were the inputs correctly selected and incorporated into design or analysis? | ⊠ Y | □ N | |
| 2. | Are assumptions necessary to perform the design or analysis activity adequately described and reasonable? Where necessary, are the assumptions identified for subsequent re-verifications when the detailed design activities are completed? Note: If there are no assumptions (of any type), then N/A shall be checked. | □ Y | □N | × E |
| 3. | Are the appropriate quality and quality assurance requirements specified? Or, for documents prepared per AREVA NP Inc. procedures, have the procedural requirements been mel? | ⊠ Y | □ N | |
| 4. | If the design or analysis cites or is required to cite requirements or criteria based upon applicable codes, standards, specific regulatory requirements, including issue and addenda, are these properly identified, and are the requirements/criteria for design or analysis met? | ⊠ Y | □ N | |
| 5. | Have applicable construction and operating experience been considered? | XY | □ N | 0 |
| 6. | Have the design interface requirements been satisfied? | ⊠ Y | □ N | 0 |
| 7. | Was an appropriate design or analytical method used? | ⊠ Y | □ N | |
| 8. | Is the output reasonable compared to inputs? | ⊠ Y | □ N | |
| 9. | Are the specified parts, equipment and processes suitable for the required application? | ⊠ Y | □ N | |
| 10. | Are the specified materials compatible with each other and the design environmental conditions to which the material will be exposed? | ⊠ Y | □ N | |
| 11. | Have adequate maintenance features and requirements been specified? | □ Y | □ N | ⊠ 1 |
| 12. | Are accessibility and other design provisions adequate for performance of needed maintenance and repair? | O Y | | × 1 |
| 13. | Has adequate accessibility been provided to perform the in-service inspection expected to be required during the plant life? | □ Y | Пи | × 1 |
| 14. | Has the design properly considered radiation exposure to the public and plant personnel? | □ Y | □ N | |
| 15. | Are the acceptance criteria incorporated in the design documents sufficient to allow verification that design requirements have been satisfactorily accomplished? | ⊠ Y | Пи | |
| 16. | Have adequate preoperational and subsequent periodic test requirements been appropriately specified? | ПΥ | □ N | ⊠ ! |
| 17. | Are adequate handling, storage, cleaning and shipping requirements specified? | ⊠ Y | □ N | |
| 18. | Are adequate identification requirements specified? | ⊠ Y | □ N | |
| 19. | Is the document prepared and being released under the AREVA NP Inc. Quality Assurance Program? If not, are requirements for record preparation review, approval, retention, etc., adequately specified? | ⊠ Y | □ N | |

Page D-1





Document No.: 51-9217475-000

Detailed Test Plan for Conducting MOX Seismic Pressure Test 9



Page D-2



AREVA NP Inc. Report No. 101276459SAT-023

APPENDIX E Commercial Grade Dedication-Related Documents



The vast majority of penetration seals that will be installed throughout the MFFF will be designated as quality level QL-1. For this reason, permanent penetration seal materials used in this test program were procured by AREVA or supplied by MOX Services and suitably baselined so that future procurements of the same commercial materials can undergo the Commercial Grade Dedication process in support Nuclear Safety Related (i.e., MOX QL-1) plant installations.

Only the primary seal material(s) that were specified as a part of the final penetration seal design and left in place during the test needed to be base-lined for future dedication of similarly procured materials. For this test, the following AREVA documents contain information associated with materials that underwent the base-lining process. These documents establish material critical characteristics as a baseline for future Commercial Grade Dedication.

- AREVA Document 51-9212659-000, "Dow Corning Sylgard 170 Silicone Elastomer Critical Characteristics"
- AREVA Document 51-9212663-000, "Quantum Silicones QSil 5558MC Silicone Elastomer Critical Characteristics"
- AREVA Document 51-9212668-000, "Dow Corning 790 Silicone Building Sealant Critical Characteristics"

These documents are available from the AREVA Records Management System or the MOX Records Management System.

Note: Even though the DC-790 material used in Pressure Test 11 was only intended as a construction aid to reduce the chance of leakage occurring through the Structo-Crete to concrete interfaces, the DC-790 material used in this test was conservatively included in the MOX Penetration Seal Test Program's material baseline process.

The Structo-Crete (procured by Intertek) used in this test was not base-lined by AREVA because MOX Services is responsible for determining critical characteristics of Structo-Crete, as well as, any associated Commercial Grade Dedication of similar components.



AREVA NP Inc. Report No. 101276459SAT-023 September 4, 2014 Page 177 of 189

APPENDIX F Quality Documents

The test assembly used in Seismic Pressure Test 9 was the same assembly tested in Pressure Test 11. For Quality Records of installation, Certificates of Conformance of the sealant materials, and QA Receiving Documents of the penetration materials for this, assembly, please see the Appendices in Intertek Report No. 101276459SAT-019, (Pressure Test 11) [AREVA document 58-9224202-000].



LIST OF CALIBRATED EQUIPMENT

| Description | Serial No. | Calibration Due Date |
|-------------------------|---------------|-------------------------|
| Thermo-Hygrometer | 130548237 | 9/19/2015 |
| Data Acquisition System | 18041FE | 8/11/2014 |
| Pressure Transducer | 406707 | 1/30/2015 |
| Mass Flowmeter | 4270050001001 | 1/30/2015 |
| Mass Flowmeter | 4270050003001 | 1/30/2015 |
| Stop watch | 122601005 | 10/23/2014 |







Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001

Build B



Cert. No.: 4096-5373559

Traceable® Certificate of Calibration for Digital Humidity/Temp. Meter

Manufactured for and distributed by: Fisher Scientific, 300 Industry Drive, Pittsburgh, PA 15275-1001 Instrument Identification:

Model Numbers: 11-661-13, FB61254, 245C5 S/N: 130548237 Manufacturer: Control Company

Standards/Equipment:

Description Chilled Mirror Hygrometer Digital Thermometer

Serial Number 31874/H2048MCR 41334977/41335007

Due Date 6/14/15

NIST Traceable Reference

11081 4000-4643062

Certificate Information:

Technician: 104

Procedure: CAL-17

Cal Date: 9/19/13

23.0°C

Test Conditions:

51.0 %RH 1013 mBar

Cal Due: 9/19/15

Calibration Data: (New Instrument)

| | Unit(s) | Nominal | As Found | In Tol | Nominal | As Left | In Tol | Min | Max | ±U | TUR |
|---|---------|---------|----------|--------|---------|---------|--------|-----|-----|-------|-------|
| ď | %RH | | N.A. | | 42.95 | 42 | Y | 39 | 47 | 1.30 | 3.1:1 |
| - | °C | 1 | N.A. | | 24.218 | 24 | Y | 23 | 25 | 0.590 | 1.7:1 |

This instrument was calibrated in compliance with ISO/IEC 17025:2005 and ANSI/NCSL 2540-1-1994 Part 1.

A Test Uncertainty Ratto of at least 4:1 is ministened unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under lest and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM). The uncertainty represents an expanded uncertainty using a coverage factor ke2 to approximate a 95% confidence level, in tolerance conditions are based on test results falling within specific limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This cartificate shall not be reproduced except in full, without written approval of Control Company.

The calibration results published in this certificate were obtained using equipment capable of producing results that are traceable to NIST and through NIST to the International System of Unite (SI).

Nominal=Standard's Reading: As Left+Instrument's Reading: In Tol='n Tolerance; Min/Max=Acceptance Range; ±U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=#(Max-Min)/2; Min = As Left Nominal(Rounded) - Tolerance; Max = As Left Nominal(Rounded) +, Tolerance; Date=MM/DD/YY

Maintaining Accuracy:

In our opinion once calibrates your Digital Humidity/Temp. Moter should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Digital Humidity/Temp. Meters change little, if any at all, but can be affected by eging, temperature, shock, and contamination.

Recalibration:

This device was calibrated using a single test point. Should additional test points be required, please contact Control Company for factory calibration and re-cartification traceable to National institute of standards and Technology.

CONTROL COMPANY 4455 Rex Road Friendswood, TX 77546 USA Phone 281 482-1714 Fax 281 482-9448 service@control3.com www.control3.com

pany is an ISO 170252005 Calibration Laboratory Accredited by (A2LA) American Association for Laboratory Accreditation, Certificate No. 1750.01.
Control Company is ISO 9301:2008 Quality Certified by (DNV) Det Norske Verilas, Certificate No. CERT-01805-2006-AQ-HOU-RVA
International Laboratory Accreditation Cooperation (ILAC) - Multilateral Recognition Arrangement (MRA).

Traceable® is a registered trademark of Control Company

© 2009 Control Company





16015 Shady Falls Road Elmendorf, TX 78112 210-635-8100 210-635-8101 fax

Certificate of Verification

Verification Date: 02/11/2014

Re-verification Date: 08/11/2014

Manufacturer: National Insturments

Model No.: USB-6210

(Only use 3 channels)

Serial No.: 18041FE

Equipment Description: Data Acquisition System

Calibration Sources: Ronan SN: 11380 due 4/6/2014


Performance: See the attached sheet


Verification Performed By: Verification Approved By:

Mike Dey Jen Patterson
Staff Engineer Test Engineer


This Data Acquisition System was verified following the Draft "Work Instruction for Verifying Yokogawa Darwin Data Acquisition Systems" dated 8/28/2013















Calibration complies with ISO 9001 ISO/IEC 17025 AND ANSI/NCSL Z540-1

MIKE 804 5/15/13

Cert. No.: 1042-4689088

Traceable® Certificate of Calibration for Waterproof Stopwatch

Manufactured for and distributed by: Fisher Scientific, 300 Industry Drive, Pittsburgh, PA 15275-1001 Instrument Identification:

Model Numbers: 0666256, FB70240 S/N: 122601005 Manufacturer: Control Company

Standards/Equipment:

Description Non-contact Frequency Counter Serial Number

Due Date

NIST Traceable Reference

3/06/13 26.6 2025

1000313632

Certificate Information:

Technician: 67

Procedure: CAL-01 22.5°C 45.0 %RH 1015 mBar Cal Date: 10/23/12

Cal Due: 10/23/14

Test Conditions: Calibration Data: (New Instrument)

| Unit(s) | Nominal | As Found | In Tol | Nominal | As Left | In Tol | Min | Max | ±U | TUR |
|----------|---------|----------|--------|---------|---------|--------|--------|-------|-------|------|
| Sec/24hr | | N.A. | | 0.000 | -0.600 | Y | -8.640 | 8.640 | 0.130 | >4:1 |

This Instrument was calibrated using Instruments Traceable to National Institute of Standards and Technology.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement" (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 55% confidence feroi. Into terescence confidence are a leading within special limits with no reduction by the uncertainty of the measurement. The results contained herein related only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal-Stendard's Reading; As Left-Instrument's Reading; In Tol-In Tolerance; Min/Max=Acceptance Renge; ±U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Reto; Accuracy=±(Max-Min)/2; Min = Nominal(Rounded) - Tolerance; Max = Nominal(Rounded) + Tolerance; Date=MM/DD/YY

Maintaining Accuracy:

In our opinion once calibrated your Waterproof Stopwarch should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Waterproof Stopwarchs change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contect Control Company.

CONTROL COMPANY 4455 Rex Road Friendswood, TX 77546 USA Phone 281 482-1714 Fax 281 482-9448 service@control3.com www.control3.com

Control Company is an ISO 17025:2005 Calibration Laboratory Accredited by (A2LA) American Association for Laboratory Accreditation, Certificate No. 1750.01.

Control Company is ISO 9001:2008 Quality Certified by (INV) Det Norske Veritas, Certificate No. CERT-01805-2006-AQ-HOU-ANAB.

International Laboratory Accreditation Cooperation (ILAC) - Nuttilateral Recognition Arrangement (MRA).

Page 1 of 1

Traceable® is a registered trademark of Control Company

© 2009 Control Company



| PRO | DECT NO: G1012764593AT-023 CLIENT: AREVA |
|--------|---|
| Proje | ect Description SEISMIC PRESSURE #9 |
| I. | ASSEMBLY |
| | Proper materials used Material documentation complete Configuration/dimensions in accordance w/ approved drawings Description of assembly: MOX ACEVA RESSURE #9 |
| H. | ELECTRICAL CABLE |
| | Correct material used |
| 161. | THERMOCOUPLES |
| , | Correct thermocouple type, certs received Thermocouples positioned in accordance with test plan Adequately labeled and secured Quality Assurance verification done Description of thermocouples: |
| IV. | FIRE BARRIER |
| | Name or type of material QSIL + SIRUCIO RETE INTERTEK received material documentation provided by Client Materials provided by INTERTEK properly documented Materials installed by INTERTEK in accordance with test plan INTERTEK Quality Assurance responsibilities determined QA responsibilities of Client installation determined Moisture check required Special requirements |
| ٧. | FINAL PREBURN VERIFICATION Client |
| | Final visual inspection & approval (initials) |
| | CALIBRATION DOCUMENTATION (S/N and calibration due date) Data Acquisition Equipment: Other Measurement Devices: |
| | Temperature 55 Humidity 41 Date 2-12-14 Time of Test start 2511 P |
| | INTERTEK pre-burn checklist performed by |
| | Client representative present to witness test |



Intertek **TEST ACTIVITIES EVENT LOG** This Log is used to document the date and note the significant events during the completion of Test Project #G101276459SAT-023 for AREVA NP, Inc. Page 1 of 1 ITEM DATE INIT'L Concrete poured by Alamo Concrete 1/10/14 MD Concrete conditioned 1/13/14 MD Critical attributes of test slab verified 1/29/14 MD Completed seal assemblies verified against the test plan 2/10/14 MD Pressure Test #11 conducted MD 2/12/14 2/12/14 Seismic Test #9 conducted using the same assembly MD

9/12 NQAP-007.7.3



| Certificate | of Conformance | |
|--|---|--|
| | | |
| Client Name: AREVA NP Inc. | Date: September 4, 2014 | |
| Project No: G101276459SAT-023 | | |
| seismic pressure resistance capabiliti Elastomer, (DC-170), Quantum Silicon 5558MC) and Dow Corning [®] 790 Silicon concrete deck for compliance with the ap | as conducted testing for AREVA NP Inc., on the ies of Dow Corning® Sylgard 170 Silicone nes QSil 5558MC Silicone Elastomer (QSil e Building Sealant (DC-790) through a 12" thick oplicable requirements of and in accordance with 17475-000, Detailed Test Plan for Conducting took place on February 12, 2014. | |
| The materials, processes), and delivera | ble(s) in this project were managed under and | |
| conform to the test laboratory's 10CFR5L |) Appendix B Quality Assurance Program. | |
| | | |
| | 725000000000000000000000000000000000000 | |
| | September 4, 2014 | |
| Michael A Brown Quality Supervisor | Date | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| Intertek Testing Lahoratory 16015 Shady Falls Road, Elmendorf TX 781 210-635-8100 | 112 | |
| | | |
| | | |



Quality Assurance Statement

Intertek is devoted to engineering, inspection, quality assurance and testing of building materials, products and assemblies. Intertek has developed and implemented a Quality Assurance Program designed to provide its clients with a planned procedure of order and document processing for inspection and testing services it provides to assure conformity to requirements, codes, standards and specifications. The Program is designed to meet the intent of ANSI 45.2 Quality Assurance Program Requirements for Nuclear Power Plants, and complies with the requirements of the ASME Code, SPPE, Military Standards and other less stringent programs. It is the Laboratory's intention to adhere strictly to this Program, to assure that the services offered to its clients remains of the highest quality and accuracy possible.

All QA Surveillance documents remain on file at the Laboratory, and are available for inspection by authorized personnel in the performance of an on-site QA Audit. All materials, services and supplies used herein were obtained with appropriate QA Certifications of Compliance.



September 4, 2014 Page 189 of 189

AREVA NP Inc. Report No. 101276459SAT-023

REVISION SUMMARY

| DATE | SUMMARY |
|-------------------|---------------------|
| | |
| September 4, 2014 | Original Issue Date |
| | |

