USAEC - AECL COOPERATIVE PROGRAM MONTHLY PROGRESS REPORT

May 1967

Compiled by:

H. S. Hilborn Technical Information Service





This document is furnished pursuant to the memorandum of understanding of June 7, 1960, between the U. S. and Canadian Governments establishing a Cooperative Program on the development of heavy water moderated power reactors.

E. I. du Pont de Nemours and Co. Savannah River Laboratory Aiken, South Carolina 29801

Contract AT(07-2)-1 with the United States Atomic Energy Commission

CONTENTS

<u>Section</u>		Page
I	Physics Experiments for CANDU lattices	3
· II	AECL In-Core Flux Monitors	5

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

SECTION I

PHYSICS EXPERIMENTS FOR CANDU LATTICES

J. L. Crandall

Experimental Physics Division Savannah River Laboratory

INTRODUCTION

Experiments are underway in the PDP to measure $1/\eta~d\eta/dT$ and the effects of asymmetric control rod placement in simple lattices of natural uranium fuel rods in D_2O_{\bullet}

SUMMARY

The $1/\eta$ d η /dT experiments are slightly ahead of schedule for a June 30 completion. The measurements on the 5.05-inch lattice have been completed.

DISCUSSION

The first lattice of the $d\eta/dT$ program was brought to criticality in the PDP on May 29, 1967. The fuel rods for this lattice consist of 1-inch diameter natural uranium slugs loaded into copper cladding tubes of ~ 0.034 -inch wall thickness. The following series of experiments has been completed for a 5.05-inch square lattice:

- buckling measurements at 20°C
- period measurements at 20°C
- gold pin irradiations at 20° C
- buckling measurements at $60^{\circ}\mathrm{C}$
- period measurements at $60^{\circ}\mathrm{C}$

The period measurements were made to determine M^2 , the neutron migration area. The gold pin irradiations were made to determine the neutron extrapolation distances at the reactor boundaries. Preliminary material buckling values are 252 μB at $20^{\circ}C$, and 227 μB at $60^{\circ}C$.

A similar series of experiments is planned for a 7.0-inch triangular lattice pitch. A tentative startup date for this lattice is June 12, 1967.

SECTION II

AECL IN-CORE FLUX MONITORS

R. F. Byars

Reactor Technology Section Savannah River Plant

An irradiation test of in-core flux monitors was made in one of the Savannah River Plant reactors to determine the life characteristics of a selection of flux detectors and of the mineral insulation used in their construction. Self-powered flux detectors are relatively new; therefore, confidence in their use hinges to a great extent on proven performance at large integrated exposures. The chief points of interest are 1) integrity of the conductors and sheath during life, 2) life of insulation, and 3) sensitivity.

Irradiation testing of the AECL neutron detector rod described in DPST-66-83-5 has been completed. A separate report is being written on the irradiation test.

EXTERNAL DISTRIBUTION

RDT Site Representative, SR (2)

G. O. Robinson, SROO

J. A. Koch

Chief, Heavy Water Organic Cooled Reactors Branch, RDT Chief, Instrumentation and Control Branch, RDT Chief, Core Desgin Branch, RDT

Chief, Fuel Fabrication Branch, RDT

Chief, Control Mechanism Branch, RDT

Assistant Director for Reactor Technology, RDT

Chief, Fuels and Materials Branch, RDT

Chief, Reactor Physics Branch, RDT

Assistant Director for Program Analysis, RDT

Senior Site Representative, AI Senior Site Representative, CE

USAEC Scientific Representative, Chalk River (10) USAEC Technical Representative, Whiteshell

Director, HWOCR Program Office, Atomics International (6) HWOCR Program Office-Windsor Representative (3)

HWOCR Project Manager, Babcock and Wilcox Division of Metals and Ceramics, Oak Ridge National Laboratory Associate Director, Pacific Northwest Laboratory (2) Manager, Engineering Research Laboratories/Department of Chemical Engineering, Columbia University

INTERNAL DISTRIBUTION

- L. Squires M. H. Wahl, Wilm
- C. W. J. Wende L. C. Evans
- S. A. McNeight
- D. F. Babeeck
- W. P. Bebbington, SRP
- L. W. Fox
- E. O. Kiger O. A. Towler
- R. F. Byars
- J. E. Gregory
- W. P. Overbeck A. A. Johnson, SRL
- G. Dessauer
- J.W. Morris
- C. H. Ice
- J. L. Crandall
- G. F. O'Neill
- J. E. Beach
- TIS File (5)
- TIS File Record Copy
- Vital Records Copy