

Contract No:

This document was prepared in conjunction with work accomplished under Contract No. DE-AC09-09SR22505 with the U.S. Department of Energy (DOE) National Nuclear Security Administration (NA).

Disclaimer:

This work was prepared under an agreement with and funded by the U.S. Government. Neither the U. S. Government or its employees, nor any of its contractors, subcontractors or their employees, makes any express or implied:

- 1) warranty or assumes any legal liability for the accuracy, completeness, or for the use or results of such use of any information, product, or process disclosed; or
- 2) representation that such use or results of such use would not infringe privately owned rights; or
- 3) endorsement or recommendation of any specifically identified commercial product, process, or service.

Any views and opinions of authors expressed in this work do not necessarily state or reflect those of the United States Government, or its contractors, or subcontractors.

Tank 51 Sludge Batch 10 Low Temperature Aluminum Dissolution (LTAD)

Azi Samadi, Eric Barrowclough, Celia Aponte, and William Lewitus
Savannah River Remediation

Overview


Background:

High Level Waste:

- Stored in 5,000,000 liter underground tanks in the form of insoluble sludge solids and soluble salts

Sludge Waste:

- Metal oxides and hydroxides from uranium and plutonium chemical separations
- Activity ~ 115 MCi (46% of total waste activity)
- Makes up over 11 million liters (8% of total waste inventory)
- Aluminum is > 12% of sludge



Waste Vitrification:

- Salt and sludge waste blended with frit to form borosilicate glass poured into canisters
- Each can contains between 620-750 kg sludge solids as oxides
- >4,000 canisters produced to date (sludge waste + ARP/MCU Low Activity Salt Waste)



Thick and Thin – Best to Blend when Possible



H-Area Sludge
(Includes THOREX material)

HM Sludge


- Thick – Harder to Pump
- High Aluminum / Low Iron
- Contains Mercury
- Slow Settling Solids
- Aluminum Removal Candidate

PUREX Sludge

- Thinner – Easier to Pump
- Low Aluminum / High Iron
- Little Mercury
- Fast Settling Solids




PUREX Sludge
(F Area)



Sludge Batch Feed Preparation and Qualification

- Waste removal operations performed to assemble sludge in Tank 51**
- Low Temperature Aluminum Dissolution (LTAD)**
 - Performed on discrete sludge batch component with high Al concentration prior to final batch assembly and sludge washing evolution
 - Typically conducted in Tank 51
 - System Plan specified aluminum dissolution for Sludge Batch 10; LTAD was previously performed for Sludge Batch 5 and Sludge Batch 6
- Sludge Washing**
 - Reduces soluble sodium salts in waste feed
 - Consists of repetitive dilution with water, gravity settling, and decanting
 - Gravity settling periods major contributor to schedule
 - Washing schedule requires maintaining enough tank space to support evaporator operations to receive and evaporate decants from sludge washing in a timely manner
- Sludge Batch Qualification**
 - Ensure acceptability for DWPF
 - Performed in parallel with sludge washing evolution
- After Sludge batch is assembled, washed, and qualified in Tank 51 it is transferred to Tank 40 for feed to DWPF**

Sludge Batch 10 Preparation Sequence



Sludge Batch Preparation – Recent Challenges


- Hydrogen produced by radiolysis builds up in the sludge matrix and must be released by periodic agitation of the sludge
- Slurried sludge retains a higher percentage of hydrogen than settled sludge, so slurried sludge requires more frequent agitation to meet nuclear safety requirements
- Quiescent time (Q-time) is the calculated amount of time that can elapse before sludge has to be agitated/mixed to release the hydrogen that is retained in the sludge over time
- Q-time program did not apply to source tanks for previous sludge batches since the entire tank sludge volume was not considered slurried
- Safety Basis changes now require application of Q-time program to tanks that contain any volume of slurried sludge – applies to source tanks as well as receipt tanks
- Sludge Batch 10 is the first sludge batch being prepared with these new Q-time requirements

Sludge Batch 10 LTAD Objectives


- Improve settling behavior to accomplish sludge washing
- Improve rheology for waste transfer and Chemical Process Cell (CPC) processing
- Improve projected canister waste loadings
- Effectively reduce the sludge mass from Sludge Batch 10, thereby reducing the amount of HLW canisters produced

Sludge Batch 10 Al Dissolution Operating Conditions

- Performed dissolution in Tank 51 for Sludge Batch 10
- Approximately 160 kgal of 50 wt.% caustic was added intermittently
- The target temperature for LTAD was 55-65 °C



Summary/Conclusions



Activity		Planned	Executed
Caustic Addition	Time	3 – 4 weeks	4 weeks
	Volume	160 kgal	164 kgal
Temperature Range		55 °C – 65 °C	55 °C – 65 °C
Bearing Water Addition from SLPs		60 kgal (conservative)	20 kgal
Dissolution Time		3 – 4 weeks	~3 weeks
Dissolution Projections	Sample #1	15 – 20%	14%
	Sample #2	25 – 30%	27%
	Sample #3	35 – 45%	35%
	Estimated Final	40%	47 – 50% ⁽¹⁾
Total Time		7 – 8 weeks	7 weeks

⁽¹⁾ Although the percentage of aluminum dissolved is higher than the goal of 40%, the total aluminum removed from the system is expected to be closer to 40%.