

This document was prepared in conjunction with work accomplished under Contract No. DE-AC09-76SR00001 with the U.S. Department of Energy.

## **DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available for sale to the public, in paper, from: U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161, phone: (800) 553-6847, fax: (703) 605-6900, email: [orders@ntis.fedworld.gov](mailto:orders@ntis.fedworld.gov) online ordering: <http://www.ntis.gov/ordering.htm>

Available electronically at <http://www.doe.gov/bridge>

Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from: U.S. Department of Energy, Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831-0062, phone: (865 ) 576-8401, fax: (865) 576-5728, email: [reports@adonis.osti.gov](mailto:reports@adonis.osti.gov)

DPST-84-751

DISTRIBUTION

ACC. NO. 146 313

L. HIBBARD, 773-A  
M. R. BUCKNER, 773-A  
A. J. GARRETT, 786-1A

D. D. HANLE, 786-1A\*  
D. W. PEPPER, 777-10A  
SRL RECORDS\*

SRL FILE  
RECORD COPY

\*Includes copies of Appendices A, B, C, D, E, and F. Copies of Appendices B, D, E and F are available from the author on floppy disks.

DPST-84-751

INTERFACIAL REFRACTION THROUGH CURVED AND PLANE-LAYERED MEDIA

A. B. KEHOE

SAVANNAH RIVER LABORATORY

DPST-84-751

SEPTEMBER 6, 1984

## TABLE OF CONTENTS

|                                                          | <u>Page</u> |
|----------------------------------------------------------|-------------|
| I. INTRODUCTION. . . . .                                 | 1           |
| II. SUMMARY . . . . .                                    | 1           |
| III. BACKGROUND . . . . .                                |             |
| 1. The Fringe Model. . . . .                             | 1           |
| 2. Operation of the LDA. . . . .                         | 2           |
| IV. ANALYSIS OF PLANE-LAYERED INTERFACES                 |             |
| 1. Problem Description . . . . .                         | 3           |
| 2. Problem Solution. . . . .                             | 5           |
| 3. Determination of the Direction Angle. . . . .         | 7           |
| 4. Placement of the LDA. . . . .                         | 11          |
| 5. Determination of LDA Optical Parameters . . . . .     | 12          |
| 6. Computerization of the Calculational Process. . . . . | 12          |
| V. ANALYSIS OF CYLINDRICALLY LAYERED INTERFACES          |             |
| 1. Problem Description . . . . .                         | 12          |
| 2. Governing Equations . . . . .                         | 13          |
| 3. Computerization of the Calculational Process. . . . . | 13          |
| VI. DISCUSSION OF RESULTS                                |             |
| 1. Plane-Layered Media . . . . .                         | 14          |
| 2. Cylindrically Layered Media . . . . .                 | 14          |
| VII. APPENDIX A                                          |             |
| VIII. APPENDIX B                                         |             |
| IX. APPENDIX C                                           |             |
| X. APPENDIX D                                            |             |
| XI. APPENDIX E                                           |             |
| XII. APPENDIX F                                          |             |

# INTERFACIAL REFRACTION THROUGH CURVED AND PLANE-LAYERED MEDIA

## I. INTRODUCTION

In 1983, the Heat Transfer Laboratory of the Savannah River Laboratory (SRL) acquired a Laser Doppler Anemometer (LDA) for use in measuring complicated flows. One of the first applications of the LDA at SRL is to measure the velocity field in the Mark 22 bottom fitting insert.

Index of refraction changes associated with plexiglas, air, and water interfaces can alter a laser beam path. In order to obtain accurate velocity measurements with the LDA, it must be determined by how much these index of refraction changes will alter a laser beam path. This problem has been addressed by others, but their analysis is insufficient for the geometry of the Mark 22 bottom fitting insert [1, 2, 3, 4]. This report documents an analysis which determines how index of refraction changes associated with plane and cylindrical interfaces will alter a laser beam path.

## II. SUMMARY

Two laser beam tracing codes, AXIAL and CYLINDER, have been written to determine a laser beam path through plane and cylindrical interfaces. For cylindrical interfaces, an equation set was derived which describes the path of the laser beam. For plane interfaces, it was not possible to derive a single equation set. Instead, it was necessary to divide the domain up into small elements or regions. The laser beam path was then determined by calculating the path of the laser beam through each region. AXIAL and CYLINDER can be used to determine where an LDA should be positioned so that velocity measurements can be made at a specified point.

## III. BACKGROUND

### III.1 THE FRINGE MODEL

The operation of the LDA is explained through the use of a fringe model. When two coherent light beams of equal intensity intersect, constructive and destructive electromagnetic interference takes place. This interference causes the formation of alternating regions of bright light and darkness. The regions of bright light are known as fringes, and the volume in space defined by the two intersecting beams is known as the probe volume. Figure 1 is a simplified schematic illustrating these concepts.

As a particle in the fluid enters the probe volume, it scatters light as it passes through a fringe. When the particle goes through a region of darkness, it does not scatter light. This series of intermittent bursts of light will continue for as long as the particle is moving through the probe volume.

The time elapsed between each burst of light is the time it takes the particle to travel from one fringe to another. If the distance between each fringe is known, and if the time between two bursts of light is known, the velocity of the particle can be computed. Assuming the particle travels at the same velocity as the fluid, the velocity of the fluid can be determined.

The distance between each fringe is calculated from the following formula

$$(1) \quad d_f = \frac{\lambda}{2n \sin \frac{\theta}{2}},$$

where,

$d_f$  = distance between each one of the fringes

$\lambda$  = wavelength of the incident laser beams in a vacuum

$n$  = index of refraction of the material in which the probe volume is located and

$\frac{\theta}{2}$  = half angle of the incident laser beams.

Because the time between each burst of light is very short and the intensity of each burst is very low, a photomultiplier tube is used to determine the time between each burst of light.

### III.2 OPERATION OF THE LDA

One of the requirements for using an LDA is that a clear optical path to the flow field must exist. Many potential users of a LDA are hampered with obstructions which hide the flow area to be analyzed. One way to avoid this obstacle is to build plexiglas models. Another way is to use fiber optical cables.

While using plexiglas models does permit flow observation, plexiglas models can create their own problems. Index of refraction changes associated with water, plexiglas, and air interfaces alter the beam path. These changes to the laser beam path can be determined by using Snell's law

$$(2) \quad n_1 \sin \theta_1 = n_2 \sin \theta_2,$$

where,

$n_1$  = index of refraction in medium 1,

$n_2$  = index of refraction in medium 2,

$\theta_1$  = angle between the normal to the interface and the laser beam itself in medium 1 and

$\theta_2$  = angle between the normal to the interface and the laser beam itself in medium 2.

Figure 2 illustrates how index of refraction changes alter not only the half angle between two laser beams, but also the location at which the two beams intersect. For this particular example, Snell's law and simple geometrical laws were used to determine the change in the half angle and the change in the location of the probe volume. It was determined that the half angle changed by  $1.367^\circ$  and that the probe volume was shifted by 3.504 inches.

In addition to altering the half angle and the location of the probe volume, index of refraction changes can also alter the direction of the velocity vector. As shown in Figure 1, the velocity vector is oriented in a direction perpendicular to the bisector of the two incident laser beams. Altering the half angle between the two incident laser beams may also alter the bisector between the two beams and, hence, the direction of the velocity vector. This effect is shown qualitatively in Figure 3 for velocity measurements in two concentric annuli.

The objective of this study is to determine how index of refraction changes alter the following:

- (1) The half angle between two laser beams,
- (2) The direction of the velocity vector and
- (3) The point at which velocity measurements are being made.

A computer graphics routine is used to allow a quick visual check of the results. Both straight and circular interfaces are analyzed.

#### IV. ANALYSIS OF PLANE-LAYERED INTERFACES

##### IV.1 PROBLEM DESCRIPTION

Laser Doppler Anemometers may be used to measure the flow in

plexiglas models where the walls of the plexiglas model appear to be plane interfaces. These plane walls may be at an angle with respect to the vertical, and they may have different indices of refraction. Figure 4 illustrates a possible configuration of water, plexiglas, and air interfaces.

The shape of each medium, the index of refraction of each medium, and the half angle of the laser beams in air will determine the path that the beams will take through the plexiglas model shown in Figure 4. If the LDA could be arbitrarily positioned it would be a simple matter to apply Snell's law and calculate the path of the laser beams from the laser through the plexiglas test section. With the beam paths determined, the location of the probe volume and the direction of the velocity vector could be calculated. The laser beam half angle in the fluid medium could then be determined.

The above problem is usually the inverse problem that an LDA user faces. Most LDA users do not arbitrarily position an LDA and then try to determine the location of the probe volume. Usually they specify the location of the probe volume and then try to determine where the laser should be placed.

The problem of where to position the LDA in order to obtain measurements at a specified point is complicated. For discontinuous, plane-layered media, it is difficult to formulate a single set of equations relating the laser beam path to the specified measuring point. These equations depend upon the geometrical configuration of the various media which compose the test section. The equations also depend upon the angle that the laser beam makes with respect to the horizontal at the measuring point (herein referred to as the direction angle).

Moving the specified measurement point from one part of the test section to another part might result in a different geometrical configuration of the various media through which the laser beam would travel. This different geometrical configuration would require a second set of equations to describe the path of the laser beam; a third location might require a third set of equations.

For example, Figure 5a shows a plexiglas test section consisting of discontinuous sections of plexiglas and water. For point P1, one set of equations could be written which would describe the path of the laser beam through the test section. For point P2, a second set of equations would be necessary. This is because point P2 "sees" a configuration of plexiglas and water different from point P1. For point P3, a third set of equations would be necessary.

Rather than write numerous equations with each equation valid



only for a small portion of the test section, the concept of using small, discrete regions to determine a laser beam path is introduced. The concept of solving a continuum problem on a discrete basis has been in existence for a number of years. The most obvious example of solving a continuum problem on a discrete basis is the application of finite elements to solve problems in structural and fluid mechanics [5]. The term "finite regions" is used to describe the technique developed in this analysis. While this technique solves a continuum problem on a discrete basis, it does not use any of the sophisticated mathematics associated with finite elements.

The best way to determine the path of the laser beam through the plexiglas test section shown in Figure 5 is to discretize the test section into small regions (or elements) as shown in Figure 5b. Snell's law can then be applied at the interface of each region. By applying Snell's law on this discontinuous basis, the path of a laser beam through the plexiglas test section can be determined.

#### IV.2 PROBLEM SOLUTION

A simple example is used to explain how finite regions can be used to determine a laser beam path through a plexiglas test section. In Figure 5c, the discretized test section of Figure 5b is shown with a measurement point specified. It can be determined from equations derived in the next section that, for an LDA system with a half angle of  $5.5^\circ$ , the direction angle of the laser beam in the water section is  $4.1325^\circ$ .

A linear equation describes the path of a laser beam through transparent materials

$$(3) \quad y = mx + b,$$

where,

$m$  = slope of the laser beam (equal to  $\tan \theta$ , where  $\theta$  is the direction angle),

$b$  =  $y$  axis intercept of the equation,

$y$  =  $y$  coordinate of a point on the laser beam path and

$x$  =  $x$  coordinate of a point on the laser beam path.

Once the measurement point has been selected, and the direction angle in the region containing the measurement point has been determined,  $m$  and  $b$  in equation (3) can be calculated.

For the portion of the laser beam in region 10 as shown in Figure 5c,  $m$  is equal to 0.072251 and  $b$  is equal to 0.063875.

The next step is to find the point at which the laser beam exits region 10. This can be accomplished by simply determining the intersection of equation (3) with the region boundary. In this example, the portion of the laser beam in region 10 exits the boundary at the point  $x = 1.0$ ,  $y = 0.13612$ .

Once the exit point for the region containing the specified measurement point has been calculated, the next step is to determine the next region that the laser beam will enter. By visual inspection of Figure 5c, it can be determined that the ray will enter region 9.

After determining the next region that the laser beam has entered, Snell's law must be applied at the region interface to determine the direction angle in the new region. Applying Snell's law here at the region interface results in a direction angle of  $3.688^\circ$  for the laser beam in the new region.

The point at which the laser beam enters region 9, and the direction angle while the beam is in region 9 have already been determined. Thus  $m$  and  $b$  in equation (3) can be recalculated for the portion of the laser beam passing through region 9. The exit point of the beam for region 9 could then be determined, and the third region into which the beam is entering could also be determined.

This process is repeated until the path of the laser beam through the remaining regions has been determined. Algorithm I describes the process by which finite regions can be used to determine the path of a laser beam through a plexiglas model. This algorithm is valid only for plexiglas models with vertical plexiglas and water sections.

#### ALGORITHM I

1. The plexiglas model is discretized into rectangular regions.
2. A point in a specified region is selected as the point where velocity measurements will be made.
3. The direction angle in the specified water region is determined assuming that no angled surfaces are present.
4. With the direction angle known, an equation for the beam is formulated. The point at which the beam exits the region is determined from the intersection of the laser beam equation with the region boundary.

5. With the exit point known, a search of all regions adjacent to the current one is performed to determine the next region that the beam has entered.
6. The direction angle for the new region is calculated using Snell's law.
7. Steps 4-6 are repeated until the beam exits the test section.

The algorithm can be used to analyze a laser beam path through plexiglas models which are much more complicated than the one shown in Figures 5a, 5b, and 5c.

A modified version of Algorithm I is in Appendix A which allows complicated plexiglas models to be analyzed. This modified algorithm includes the effect that one angled plexiglas-water interface may have on a laser beam as it passes through a plexiglas model.

#### IV.3 DETERMINATION OF THE DIRECTION ANGLE

Using finite regions to determine a laser beam path through a plexiglas model can be done only if the direction angle of the laser beam in the region containing the measurement point is known. This section outlines some assumptions that are made which allow the direction angle in the region containing the measurement point to be determined. It should be noted that the forthcoming discussion assumes that the LDA system is placed to the right of the plexiglas model shown in Figure 4.

The half angle of an LDA in air is a parameter of each particular system. Applying Snell's law at the air-plexiglas interface shown in Figure 4 yields the following result for the direction angle in the first plexiglas section

$$(4) \quad \theta_2 = \text{INVSIN} \left[ \frac{n_1}{n_2} \sin \theta_1 \right],$$

where,

$\theta_1$  = direction angle in the air section (equal to the LDA half angle in air for this particular example),

$\theta_2$  = direction angle in the first plexiglas section,

$n_1$  = index of refraction for air and

$n_2$  = index of refraction for first plexiglas section.

Applying Snell's law to the first plexiglas-water interface yields

$$(5) \quad \theta_3 = \text{INVSIN} \left[ \frac{n_2}{n_3} \sin \theta_2 \right],$$

where,

$\theta_3$  = direction angle in the first water section and

$n_3$  = index of refraction for the first water section.

Applying Snell's law to the second water-plexiglas interface yields,

$$(6) \quad \theta_4 = \text{INVSIN} \left[ \frac{n_3}{n_4} \sin \theta_3 \right],$$

where,

$\theta_4$  = direction angle in the second plexiglas section and

$n_4$  = index of refraction for the second plexiglas section.

Applying Snell's law to the third plexiglas-water interface yields,

$$(7) \quad \theta_5 = \text{INVSIN} \left[ \frac{n_4}{n_5} \sin \theta_4 \right],$$

where,

$\theta_5$  = direction angle while it is in the second water section and

$n_5$  = index of refraction for the second water section.

Successive substitutions can be made for  $\theta_4$  in equation (7) by using equations (4), (5), and (6) until an expression for  $\theta_5$  in terms of  $\theta_1$  is obtained. The result is

$$(8) \quad \theta_5 = \text{INVSIN} \left[ \frac{n_1}{n_5} \sin \theta_1 \right].$$

Thus the direction angle in the second water section is independent of the indices of refraction in the two plexiglas sections and the water section. It should be noted that the independence of this angle with the above mentioned indices of refraction is a function of the geometry. For other geometrical configurations, the direction angle may be dependent upon the indices of refraction of the intermediate materials.

Substituting in for  $\theta_2$  in equation (5) by using equation (4) results in

$$(9) \quad \theta_3 = \text{INVSIN} \left[ \frac{n_1}{n_3} \sin \theta_1 \right].$$

Again, it should be noted that the independence of  $\theta_3$  with  $n_2$  is because of this particular geometrical configuration.

If it is assumed that the index of refraction for the two plexiglas sections are the same, then  $\theta_5$  equals  $\theta_3$ . This means that the direction angle for a laser beam in water sections sandwiched between vertical plexiglas sections is the same in all the water sections.

Not all plexiglas models will have vertical plexiglas-water interfaces. A plexiglas model with a plexiglas-water interface at an angle to the vertical is illustrated in Figure 6.

Figure 7 is a close up of the angled plexiglas-water interface in Figure 6. Applying Snell's law and geometrical laws to the figure, the following relationship for the direction angle  $\theta_4$  in the water section is obtained

$$(10) \quad \theta_4 = \text{INVSIN} \left[ \frac{n_2}{n_3} \sin (\theta_3 + 90 - \alpha) \right] + \alpha - 90,$$

where,

$n_2$  = index of refraction for plexiglas,

$n_3$  = index of refraction for water

$\theta_3$  = direction angle for the laser beam in the plexiglas section to the right of the water-plexiglas interface,

$\theta_4$  = direction angle for the laser beam in the water section to the left of the water-plexiglas interface and

$\alpha$  = angle that water/plexiglas interface makes with the horizontal.

If the water-plexiglas interface shown in Figure 6 was reversed, (i.e., the plexiglas section was on the left and the water section was on the right) the direction angle for water sections to the left of the interface would have to be calculated in several steps. First equation (8) would be used to calculate the direction angle in the water section to the right of the angled plexiglas-water interface

$$(11) \quad \theta_4 = \text{INVSIN} \left[ \frac{n_1}{n_5} \sin \theta_1 \right],$$

where,

$\theta_4$  = direction angle of the laser beam in the water section to the right of the plexiglas-water interface,

$\theta_1$  = half angle of the LDA system,

$n_1$  = index of refraction for air and

$n_5$  = index of refraction for water.

Next a slightly altered version of equation (10) would be used to calculate the direction angle of the laser beam in the plexiglas section. This equation is

$$(12) \quad \theta_p = \text{INVSIN} \left[ \frac{n_3}{n_2} \sin (\theta_4 + 90 - \alpha) \right] + \alpha - 90,$$

where,

$\theta_p$  = direction angle of the laser beam in plexiglas sections to the left of the angled plexiglas-water interface,

$\theta_4$  = direction angle of the laser beam in water sections to the right of the plexiglas-water interface,

$\alpha$  = angle that plexiglas-water interface makes with the horizontal,

$n_3$  = index of refraction for water and

$n_2$  = index of refraction for plexiglas.

Finally, Snell's law would be used at the vertical water-plexiglas interface to calculate the direction angle for the water section to the left of the angled plexiglas-water interface. The result is

$$(13) \quad \theta_w = \text{INVSIN} \left[ \frac{n_2}{n_3} \theta_p \right],$$

where,

$\theta_w$  = direction angle in water sections to the left of the angled plexiglas-water interface,

$\theta_p$  = direction angle in plexiglas sections to the left of the plexiglas-water interface,

$n_3$  = index of refraction for water and

$n_2$  = index of refraction for plexiglas.

#### IV.4 PLACEMENT OF THE LDA

Algorithm I determines the path of two laser beams through a plexiglas test section. This information, along with the knowledge of where the two laser beams exit the focusing lens of a LDA, is enough to determine where the LDA should be placed in order to make velocity measurements at a specified point.

However, because of the curvature of the lens, it is difficult to determine exactly where the two laser beams will exit the LDA. Because of this, the concept of a reference point is introduced. The reference point concept allows the LDA user to avoid any errors that lens curvature may introduce.

Use of a reference point in conjunction with Algorithm I to determine LDA placement is described in Algorithm II.

#### ALGORITHM II

- (1) A point with a well known physical location (such as the corner of a wall) is chosen as the reference point.
- (2) The measurement point is selected.
- (3) Using the Algorithm I, the two laser beam paths from the reference point through the test section are calculated.

- (4) Using the Algorithm I, the two laser beam paths from the measurement point through the test section are computed.
- (5) Equations specifying how far the LDA system must be moved in the horizontal and vertical directions so that the probe volume moves from the reference point to the measurement point are shown in Figure 8.
- (6) The LDA system is aligned so that the probe volume is located at the reference point, then the LDA is moved the horizontal and vertical distances specified by the equations shown in Figure 8.

#### IV.5 DETERMINATION OF LDA OPTICAL PARAMETERS

Equations relating the LDA half angle in the fluid medium and the direction of the velocity vector to the two direction angles are shown in Figure 9.

#### IV.6 COMPUTERIZATION OF THE CALCULATIONAL PROCESS

The computer program AXIAL was written to mechanize the calculations and algorithms outlined in the previous four sections. The structure of the program is fairly basic. The code first reads in the input data which describes the plexiglas model which will be analyzed. Next the code reads in the location of the reference point and the location of the measurement point. The code then calculates the path of the two reference beams using the method of finite regions as outlined in Appendix A. Next the code calculates the path of the two measurement point beams using the method outlined in Appendix A.

Once the paths of the two reference beams and the two measurement point beams have been determined, the code uses the method outlined in Algorithm II to position the LDA. After determining the placement of the LDA system, the code then determines the magnitude of the half angle and the direction of the velocity vector through the use of the equations shown in Figure 9. At this point all calculations are complete.

Figures 10 through 13 are flow charts for the program AXIAL and some of its subroutines. The flow charts shown here are rather brief; their purpose is to show the overall structure of the program. A brief description of the code AXIAL as well as its FORTRAN listing is included in Appendix B.

### V. ANALYSIS OF CYLINDRICALLY LAYERED INTERFACES

#### V.1 PROBLEM DESCRIPTION

The radii of each tube, the index of refraction of the water,



the index of refraction of each tube, and the half angle of the laser beams in air determine the path that the laser beams take through the water and the plexiglas tubes.

The analysis of cylindrically layered interfaces is somewhat easier than the analysis of plane-layered interfaces. Unlike plane-layered interfaces, analytical equations can be derived to describe the path of a laser beam through cylindrically layered interfaces.

## V.2 GOVERNING EQUATIONS

The equations which describe the path of a laser beam through nested, cylindrical tubes situated in a plexiglas box are shown in Table I. Appendix C contains the derivation of the equations. Figure 15 shows the corresponding geometrical configuration. The variables are defined in Table II.

Indicial notation is used to show the repetitive nature of the equations. The addition of extra cylinders is not troublesome and results only in additional equation segments.

## V.3 COMPUTERIZATION OF THE CALCULATIONAL PROCESS

The computer program CYLINDER was written to solve the equations shown in Table I and determine where the LDA system should be placed. A linear interpolation technique is used to solve the equations in Table I for the laser beam path. After both laser beam paths have been determined, the code uses Algorithm II to determine the LDA placement. The code then uses the equations shown in Figure 9 to determine the half angle and the direction of the velocity vector.

Figure 14 is a flow chart for the program CYLINDER. The FORTRAN listing of CYLINDER is included in Appendix D.

## VI. DISCUSSION OF RESULTS

Several test runs were made with both AXIAL and CYLINDER. In all the figures, the plexiglas regions appear as shaded sections and the water regions appear as white sections. The laser beams appear as dark black lines.

Because of the low resolution of the graphics printer, the laser beams appear to be slightly staggered. Some of the figures have inserts included with them. These inserts are close-ups of the region around the measurement point.

## VI.1 PLANE-LAYERED MEDIA

Figures 16, 17, and 18 are cross sectional views of the bottom portion of a Mark 22 assembly. When trying to measure axial velocities in fuel assemblies, the cylinders appear as plane interfaces. Thus, the code AXIAL was used to determine where an LDA should be placed in order to make measurements at specified points. The input data file specifying the geometry is in Appendix E.

Figure 16 shows the path that the laser beams would take if LDA velocity measurements were made at the specified point. As the results show, the direction of the velocity vector is unaffected; it is still oriented at  $90^\circ$ . This is because both laser beams travel through vertical interfaces. Index of refraction changes in these vertical interfaces affect both direction angles equally. Hence, the direction of the velocity vector is unaffected.

Figure 17 shows the path that the two laser beams would take if LDA velocity measurements were made to the left of the angled surface. As can be seen, the direction of the velocity vector is altered by  $4.1^\circ$ .

Figure 18 shows the path that the laser beams would take if LDA velocity measurements were made in the lower left hand corner of the test section. The gently sloping plexiglas section alters the direction of the velocity vector only slightly.

## VI.2 CYLINDRICALLY LAYERED MEDIA

Figures 19 through 26 are cross sectional views of 4 concentric cylinders located inside a plexiglas box. Figure 27 has the same geometrical configuration as Figures 19 through 26 except that the three inner cylinders have been removed. The input data file for Figures 19 through 26 is in Appendix F.

Figures 19 through 22 show the paths that the laser beams would take for a measurement point with the same radius located in four different quadrants. Figures 19 and 20 show that curvature effects alter the direction of the velocity vector by the same magnitude but in different directions. Figures 21 and 22 show the same phenomenon. Also, these figures show that for concentric geometries, there will not be any "blind spots". Curvature effects from the cylinders will cause the beams to bend upwards toward the boundaries of the cylinders.

Figures 23 through 26 are included to illustrate how moving the measurement point around inside the inner cylinder reduces the curvature effects of the cylinder walls. As the curvature effect

is reduced, the direction of the velocity vector comes closer to  $90^\circ$ .

Figure 27 is included to illustrate what effect removing the three inner cylinders has on the direction of the velocity vector. The measurement point in this figure is the same as the one in Figure 22. In Figure 22, the direction of the velocity vector is  $85.471^\circ$ . In this figure, the direction of the velocity vector is  $89.91^\circ$ .

ABK:cjl

## REFERENCES

- [1] Boadway, J. D. and Karahan, E., "Correction of Laser Doppler Anemometer Readings for Refraction at Cylindrical Interfaces", DISA Information, Number 26, 1981, pp. 4-6.
- [2] Bicen, A. F., "Refraction Correction for LDA Measurements in Flows with Curved Optical Boundaries", TSI Quarterly, Volume 8, Number 2, 1982, pp. 10-11.
- [3] Schock, H. J., Case, S. and Konicek, L., "Window Aberration Correction in Laser Velocimetry Using Multifaceted Holographic Optical Elements", Applied Optics, Volume 23, Number 5, 1984, pp. 752 - 756.
- [4] Hanle, D. D., "In Vitro Fluid Dynamics of Prosthetic Aortic Heart Valves in Steady and Pulsatile Flow", Ph.D. Thesis, California Institute of Technology, Pasadena, California, 1984.
- [5] Gallagher, R. H., Oden, J. T., Taylor, C. and Zienkiewicz, O. C., Finite Elements in Fluids, John Wiley and Sons, New York, 1975.

TABLE I  
EQUATIONS WHICH DESCRIBE THE PATH OF A  
LASER BEAM THROUGH CYLINDRICALLY LAYERED MEDIA

$$(14) \quad \beta = \text{INVTAN } (y/x)$$

$$(15) \quad R_p = x / \cos (\beta)$$

$$(16) \quad \alpha_{1,1,1} = \text{INVSIN} \left[ \frac{R_p}{R_{1,1}} \sin [\beta - \text{ALPH4G}] \right]$$

$$(17) \quad \alpha_{1,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\alpha_{1,1,1}) \right]$$

$$(18) \quad \alpha_{1,2,1} = \text{INVSIN} \left[ \frac{R_{1,1}}{R_{1,2}} \sin (\alpha_{1,1,2}) \right]$$

$$(19) \quad \alpha_{1,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin (\alpha_{1,2,1}) \right]$$

$$(20) \quad \alpha_{2,1,1} = \text{INVSIN} \left[ \frac{R_{1,2}}{R_{2,1}} \sin (\alpha_{1,2,2}) \right]$$

$$(21) \quad \alpha_{2,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\alpha_{2,1,1}) \right]$$

$$(22) \quad \alpha_{2,2,1} = \text{INVSIN} \left[ \frac{R_{2,1}}{R_{2,2}} \sin (\alpha_{2,1,2}) \right]$$

$$(23) \quad \alpha_{2,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin (\alpha_{2,2,1}) \right]$$

$$\alpha_{i,1,1} = \text{INVSIN} \left[ \frac{R_{(i-1),2}}{R_{i,1}} \sin (\alpha_{(i-1),2,2}) \right]$$

$$\alpha_{i,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\alpha_{i,1,1}) \right]$$

$$\alpha_{i,2,1} = \text{INVSIN} \left[ \frac{R_{i,1}}{R_{i,2}} \sin (\alpha_{i,1,2}) \right]$$

$$\alpha_{i,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin (\alpha_{i,2,1}) \right]$$

TABLE I (cont'd)

EQUATIONS WHICH DESCRIBE THE PATH OF A  
LASER BEAM THROUGH CYLINDRICALLY LAYERED MEDIA

$$(24) \quad \begin{aligned} \text{ALPHW} = \text{ALPH4G} + & \alpha_{1,1,1} - \alpha_{1,1,2} + \alpha_{1,2,1} - \alpha_{1,2,2} \\ & + \alpha_{2,1,1} + \alpha_{2,1,2} + \alpha_{2,2,1} - \alpha_{2,2,2} \\ & \dots\dots\dots + \alpha_{i,1,1} - \alpha_{i,1,2} + \alpha_{i,2,1} - \alpha_{i,2,2} \end{aligned}$$

$$(25) \quad \text{ALPHP} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\text{ALPHW}) \right]$$

$$(26) \quad \text{ALPHGH} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{air}}} \sin (\text{ALPHP}) \right]$$

$$(27) \quad \text{ANGLE} = \text{ALPHW} + \alpha_{i,2,2}$$


$$(28) \quad \begin{aligned} Y1 = R_{i,2} * \sin (\text{ANGLE}) + [D - R_{i,2} \cos (\text{ANGLE})] * [\tan (\text{ALPHW})] \\ + t * \tan (\text{ALPHP}) \end{aligned}$$

TABLE II

DEFINITION OF NOMENCLATURE

|                  |   |                                                                                                                                                                                                                                                                                                |
|------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                | = | x coordinate of laser beam crossing point                                                                                                                                                                                                                                                      |
| y                | = | y coordinate of laser beam crossing point                                                                                                                                                                                                                                                      |
| $R_p$            | = | radius of laser beam crossing point                                                                                                                                                                                                                                                            |
| $R_{i,j}$        | = | radius of a particular cylinder. i indicates the cylinder (from center outwards). j indicates which radius (1 means inner radius, 2 means outer radius)                                                                                                                                        |
| $\alpha_{i,j,k}$ | = | angle that the laser beam makes with respect to the normal at the cylinder-water interface. i indicates the cylinder (from center outwards). j indicates inner or outer radius (1 means inner radius, 2 means outer radius). k indicates the angle (1 means inner angle, 2 means outer angle). |
| ALPHW            | = | direction angle for the laser beam in the water between the outer cylinder and the plexiglas box                                                                                                                                                                                               |
| ALPHP            | = | direction angle for the laser beam in the plexiglas box                                                                                                                                                                                                                                        |
| ALPH4G           | = | direction angle of the laser beam in the fluid at the beam crossing.                                                                                                                                                                                                                           |
| ALPHGH           | = | Half angle of the LDA in air.                                                                                                                                                                                                                                                                  |
| Y1               | = | y coordinate of the point at which the laser beam exits the plexiglas box.                                                                                                                                                                                                                     |
| D                | = | distance between the origin and the inside of the plexiglas wall.                                                                                                                                                                                                                              |
| t                | = | thickness of the plexiglas box                                                                                                                                                                                                                                                                 |
| ANGLE            | = | angle between the line from the origin through the point where the laser beam exits the outermost cylinder, and the horizontal.                                                                                                                                                                |
| i                | = | number of cylidners.                                                                                                                                                                                                                                                                           |

# THE FRINGE MODEL



Fringes are parallel to the bisector of the two laser beams. Thus, the measured velocity has a direction perpendicular to the bisector.

FIGURE 1




# INDEX OF REFRACTION CHANGES

$$\begin{aligned}\theta &= 5.5^\circ \\ n_1 &= 1.00 \\ n_2 &= 1.490 \\ n_3 &= 1.330\end{aligned}$$

Applying Snell's law results in

$$\begin{aligned}\theta_2 &= 3.688^\circ \\ \theta_3 &= 4.1326^\circ \\ x &= 10.39" \\ x^1 &= 13.89"\end{aligned}$$




----- actual beam path  
 ..... unaltered beam path

NOTE: Figure is not to scale.  
 Dimensions have been altered  
 to exaggerate changes in the  
 angles.


FIGURE 2

FIGURE 3  
ORIENTATION OF THE VELOCITY VECTOR



BECAUSE OF INDEX OF REFRACTION CHANGES  
 $\alpha \neq 90^\circ$

FIGURE 4  
SOLVING FOR THE DIRECTION ANGLE



A PLEXIGLAS MODEL  
WITH AN IRREGULAR GEOMETRY




FIGURE 5a

# THE DISCRETIZED PLEXIGLAS MODEL





FIGURE 5b

THE LASER BEAM PATH THROUGH  
THE DISCRETIZED MODEL



$P(x,y)$  = measurement point  
= (0.5, 0.1)



 plexiglas  
 water

FIGURE 5c

FIGURE 6

A PLEXIGLAS MODEL WITH AN ANGLED SURFACE




FIGURE 7

CLOSE UP OF THE PLEXIGLAS MODEL





FIGURE 8




$$\Delta x = \frac{\frac{(Y1R - Y2R)}{2} - \frac{(Y1M - Y2M)}{2}}{\tan \theta_1}$$

$$\Delta y = \frac{\frac{(Y1M + Y2M)}{2} - \frac{(Y1R + Y2R)}{2}}{\tan \theta_1}$$

FIGURE 9

LDA OPTICAL PARAMETERS





FLOW CHART FOR PROGRAM AXIAL




FIGURE 10

# FLOW CHART FOR SUBROUTINE LASER




FIGURE 11

# FLOW CHART FOR SUBROUTINE Y POINT




FIGURE 12

# FLOW CHART FOR SUBROUTINE REGI





FIGURE 13


FLOW CHART FOR PROGRAM CYLINDER



Subroutine ANGLE is a subroutine which uses a linear interpolation technique to solve equations (14)-(26). Subroutine HCalc is a subroutine which solves equation (28).

FIGURE 14


# CYLINDRICALLY LAYERED INTERFACES



water

FIGURE 15

FIGURE 16




WAVELENGTH 22 BOTTOM FITTING INSERT

INDEX OF REFRACTION FOR WATER= 0.13300D+01 INDEX OF REFRACTION FOR PLEXIGLASS= 0.14900D+01  
 REFERENCE POINT IS X= 0.0 Y= 0.31600D+01  
 HALF ANGLE OF THE BEAM IN WATER WITH NO ANGLED SURFACES = 0.41326D+01

ALTERED HALF ANGLE = 0.41326D+01 ANGLE OF VELOCITY VECTOR(MEASURED FROM THE HORIZONTAL)= 0.90000D+02  
 HALF ANGLE OF THE LASER IN AIR 0.55000D+01  
 MEASUREMENT POINT IS X = 0.98550D+00 Y = 0.39450D+01  
 DELTA Y = 0.78500 DELTA X = 0.77251

FIGURE 17


# MARK 22 BOTTOM FITTING INSERT



INDEX OF REFRACTION FOR WATER= 0.13300D+01 INDEX OF REFRACTION FOR PLEXIGLASS= 0.14900D+01  
 REFERENCE POINT IS X= 0.0 Y= 0.31600D+01  
 HALF ANGLE OF THE BEAM IN WATER WITH NO ANGLED SURFACES = 0.41326D+01

ALTERED HALF ANGLE = 0.43222D+01 ANGLE OF VELOCITY VECTOR(MEASURED FROM THE HORIZONTAL)= 0.85904D+02  
 HALF ANGLE OF THE LASER IN AIR 0.55000D+01  
 MEASUREMENT POINT IS X = 0.25500D+00 Y = 0.38500D+01  
 DELTA Y = 0.66529 DELTA X = 0.21206





APR 22 ECTION FITTING INSERT

FIGURE 18

INDEX OF REFRACTION FOR WATER= 0.13300D+01 INDEX OF REFRACTION FOR PLEXIGLASS= 0.14900D+01  
 REFERENCE POINT IS X= 0.0 Y= 0.31600D+01  
 HALF ANGLE OF THE BEAM IN WATER WITH NO ANGLED SURFACES = 0.41326D+01

ALTERED HALF ANGLE = 0.41366D+01 ANGLE OF VELOCITY VECTOR(MEASURED FROM THE HORIZONTAL)= 0.89394D+02  
 HALF ANGLE OF THE LASER IN AIR 0.55000D+01  
 MEASUREMENT POINT IS X = 0.79260D+00 Y = 0.63375D+00  
 DELTA Y = -2.53414 DELTA X = 0.63663

FIGURE 19

REFERENCE POINT: XO= 0.70000D+00 YO= 0.00000D+00  
 DATA POINT : X= 0.30000D+00 Y= 0.72000D+00  
 CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
 CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
 CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
 CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
 LASER MUST BE MOVED -0.33026D+00 IN THE HORIZONTAL DIRECTION  
 LASER MUST BE MOVED 0.75058D+00 IN THE VERTICAL DIRECTION  
 HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.56435D+01  
 DIRECTION OF THE VELOCITY VECTOR 0.82702D+02





FIGURE 20

## CYLINDRICAL TEST CASE

REFERENCE POINT: X0= 0.70000D+00 Y0= 0.0  
DATA POINT : X= 0.30000D+00 Y= -0.72000D+00  
CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
LASER MUST BE MOVED -0.33026D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED -0.75058D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.56435D+01  
DIRECTION OF THE VELOCITY VECTOR 0.97297D+02




FIGURE 21

## CYLINDRICAL TEST CASE

REFERENCE POINT: X0= 0.70000D+00 Y0= 0.0  
DATA POINT : X= -0.30000D+00 Y= -0.72000D+00  
CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
LASER MUST BE MOVED -0.76652D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED -0.69459D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.34834D+01  
DIRECTION OF THE VELOCITY VECTOR 0.94529D+02




FIGURE 22

## CYLINDRICAL TEST CASE

REFERENCE POINT: X= 0.70000D+00 Y= 0.0  
DATA POINT : X= -0.30000D+00 Y= 0.72000D+00  
CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
LASER MUST BE MOVED -0.76652D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED 0.69459D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.34834D+01  
DIRECTION OF THE VELOCITY VECTOR 0.85471D+02




FIGURE 23

## CYLINDRICAL TEST CASE

REFERENCE POINT: X0= 0.70000D+00 Y0= 0.00000D+00  
DATA POINT : X= 0.00000D+00 Y= 0.75000D+00  
CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
LASER MUST BE MOVED -0.60073D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED 0.74530D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.37691D+01  
DIRECTION OF THE VELOCITY VECTOR 0.83360D+02




FIGURE 24

# CYLINDRICAL TEST CASE

REFERENCE POINT: X0= 0.70000D+00 Y0= 0.00000D+00  
 DATA POINT : X= 0.20000D+00 Y= 0.60000D+00  
 CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
 CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
 CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
 CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
 LASER MUST BE MOVED -0.40815D+00 IN THE HORIZONTAL DIRECTION  
 LASER MUST BE MOVED 0.60887D+00 IN THE VERTICAL DIRECTION  
 HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.43006D+01  
 DIRECTION OF THE VELOCITY VECTOR 0.87220D+02





FIGURE 25

## CYLINDRICAL TEST CASE

REFERENCE POINT: X0= 0.70000D+00 Y0= 0.0  
DATA POINT : X= 0.30000D+00 Y= 0.40000D+00  
CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
LASER MUST BE MOVED -0.31738D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED 0.40632D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.42318D+01  
DIRECTION OF THE VELOCITY VECTOR 0.88762D+02






FIGURE 26

## CYLINDRICAL TEST CASE

REFERENCE POINT: X= 0.70000D+00 Y= 0.0  
DATA POINT : X= -0.10000D+00 Y= 0.20000D+00  
CYLINDER 1 INNER RADIUS= 0.80000D+00 OUTER RADIUS= 0.10000D+01  
CYLINDER 2 INNER RADIUS= 0.17000D+01 OUTER RADIUS= 0.20000D+01  
CYLINDER 3 INNER RADIUS= 0.27000D+01 OUTER RADIUS= 0.30000D+01  
CYLINDER 4 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
LASER MUST BE MOVED -0.61735D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED 0.19911D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.41121D+01  
DIRECTION OF THE VELOCITY VECTOR 0.89493D+02





FIGURE 27

## CYLINDRICAL TEST CASE

REFERENCE POINT: X= 0.70000D+00 Y= 0.0  
DATA POINT : X= -0.30000D+00 Y= 0.72000D+00  
CYLINDER 1 INNER RADIUS= 0.37000D+01 OUTER RADIUS= 0.40000D+01  
CYLINDER 2 INNER RADIUS= 0.0 OUTER RADIUS= 0.0  
CYLINDER 3 INNER RADIUS= 0.0 OUTER RADIUS= 0.0  
CYLINDER 4 INNER RADIUS= 0.0 OUTER RADIUS= 0.0  
LASER MUST BE MOVED -0.75188D+00 IN THE HORIZONTAL DIRECTION  
LASER MUST BE MOVED 0.71951D+00 IN THE VERTICAL DIRECTION  
HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM 0.41295D+01  
DIRECTION OF THE VELOCITY VECTOR 0.89906D+02



## VII APPENDIX A

This appendix is a modified version of Algorithm I. This algorithm includes the effect that one angled surface may have on the path of a laser beam.

### ALGORITHM A-I

- (1) The test section is descretized into quadralaterals.
- (2) A point in a particular region is specified as the desired measurement point.
- (3) Using equation (9), the direction angle in the region containing the measurement point is calculated. With the direction angle known, an equation for the beam is formulated.
- (4) The point at which the beam exits from the current region is determined by the intersection of the beam equation with the region boundary.
- (5) With the exit point known, a search of all regions adjacent to the current one is performed to determine the next region that the beam has entered.
- (6) With the next region known, Snell's law is used to determine the direction angle in the new region (i.e., equation (5) or equation (6)). With the direction angle known, an equation for the beam in the new region is formulated.
- (7) A check is made to determine if the side of the new region through which the laser beam passes is at an angle with respect to the vertical. If the beam has encountered an angled surface, the following steps are taken:
  - a) A notation of the region containing the angled surface is made.
  - b) The direction angle for the beam in the region containing the measurement point is recalculated using equation (10) or equations (11), (12), and (13). An equation for the beam is formulated using this new direction angle.
  - c) Steps 4,5,6, & 7 are repeated until the original angled region is found.
  - d) If the angled region is not found, no physical solution exists. It is not possible to make measurements at this point.

- e) If the angled region is found, the direction angle for this region is calculated using equation (8) or equation (4).
  - f) The calculation resumes with step 8.
- (8) A check is made to determine if this new region is a boundary region. If this region is a boundary region, the following steps are taken:
- a) The exit point for this region is calculated.
  - b) The calculational procedure is terminated as the laser beam path has been determined.
- (9) Steps (4) - (8) are repeated until the laser beam path has been determined.

## VIII. APPENDIX B

As previously discussed, finite regions can be used to calculate the path of a laser beam through a plexiglas model. This concept is based upon the idea of finite elements. Finite elements are currently being used in many areas of engineering. Programs to generate meshes necessary for use with finite element codes have been written. These mesh generating programs frequently require the user to first generate a very coarse mesh of many "super elements". These super elements are rather large; their only function is to define the geometry which will be discretized.

These super elements are sufficiently small for analyzing the path of a laser beam through a plexiglas model. Thus, the input data necessary for using a mesh generator code is essentially the same input data that is necessary for using AXIAL.

As with the mesh generator codes, an element connectivity matrix and node number coordinate matrix are necessary for use with AXIAL. AXIAL also requires two additional input data matrices. One matrix is an adjacent region matrix. This matrix defines for a specified region all the regions which are in physical contact with this region.

The second additional matrix is an angle specification matrix. This matrix specifies which side, if any, of a region is at an angle with respect to the vertical.

These two additional matrices are essential to the operation of AXIAL. The adjacent region matrix is used by the code AXIAL to determine the next region that the laser beam will enter as it exits a given region. The second matrix is used by AXIAL to determine if the laser beam has encountered a plexiglas-water interface at an angle with respect to the vertical. The FORTRAN listing of AXIAL starts on the next page.



PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 02 OF 22

MESHREP2

TART  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
6      *XENT1(50),YENT1(50),XEXT1(50),YEXT1(50),THETA(50),
6      *TINDX(50),XENT2(50),YENT2(50),XEXT2(50),YEXT2(50),
6      *SCXADJ,SCYADJ,SHALF,TINW,TINP,XTEMP,YTEMP,
6      *MATNO(1501),NPOIN,NELEM,
6      *LNADJ(50,20),NREGIO(50),NREGI2(50),IANG(50),
6      *INODS(1501,8),
6      *NTITLE(10),NCOL(100),NDGRAF,
6      *J3,J4,J,
6      *IFLAG5,IFLAG6,IFLAG7,IFLAG8,IFLAG9
```

```
1      C
1      C---- THIS SUBROUTINE ACCEPTS ALL INPUT DATA
1      C
1      C              DEFINITION OF THE VARIABLES.
1      C
1      C
1      C
1      C---- LNADJ(I,J): THIS ARRAY DEFINES ALL THE ELEMENTS WHICH ARE
1      C---- ADJACENT TO ELEMENT I.
1      C
1      C---- NREGIO(J): THIS ARRAY SPECIFIES THE ELEMENT NUMBER CORRESPONDING
1      C---- TO THE J TH REGION THAT THE FIRST BEAM IS IN.
1      C
1      C---- NREGI2(J): THIS ARRAY SPECIFIES THE ELEMENT NUMBER CORRESPONDING
1      C---- TO THE J TH REGION THAT THE SECOND BEAM IS IN.
1      C
1      C---- NTITLE: THE TITLE OF THE TEST PIECE. UP TO 48 LETTERS.
1      C
1      C---- NPOIN:THE NUMBER OF NODES USED TO DESCRIBE THE TEST SECTION
1      C
1      C---- NELEM:THE NUMBER OF INPUT BLOCKS USED TO DESCRIBE THE
1      C---- TEST SECTION
1      C
1      C---- INODS(I,J): CONNECTIVITY MATRIX.THIS IS AN ARRAY SPECIFYING THE
1      C---- NODE NUMBERS OUTLINING A GIVEN BLOCK.THE FIRST INDEX SPECIFIES THE
1      C---- THE ELEMENT NUMBER (MAXIMUM NUMBER OF ELEMENTS IS 1500). THE SEC-
1      C---- OND INDEX TELLS WHICH GLOBAL NODE NUMBER CORRESPONDS TO A LOCAL
1      C---- NODE NUMBER. THE LOCAL NODE NUMBER ALWAYS STARTS AT THE LOWER
1      C---- LEFT HAND CORNER OF THE ELEMENT. THE NODE NUMBERS PROCEED AROUND
1      C---- THE ELEMENT IN A COUNTERCLOCKWISE FASHION.
1      C
1      C---- IANG(J) THIS ARRAY DEFINES ALL THE ANGLED SIDESOF ELEMENT J. A
1      C---- VALUE OF J INDICATES THAT THERE ARE NOT ANY ANGLED SIDES. A
1      C---- NEGATIVE NUMBER INDICATES THE PRESENCE OF AN ANGLED SIDE.
1      C
1      C---- NCOL(J) AN ARRAY USED BY THE GRAPHICS ROUTINE. THIS ARRAY
1      C---- INDICATES THE COLOR THAT A REGION SHOULD BE SHADED.
1      C
1      C---- NDGRAF: A FLAG VARIABLE USED BY THE GRAPHICS ROUTINE. IT MUST
1      C---- BE SET EQUAL TO 1 FOR THE GRAPHICS ROUTINE TO BE CALLED.
1      C
1      C---- J3: NUMBER OF REGIONS THAT THE FIRST BEAM ENCOUNTERS.
1      C
1      C---- J4: NUMBER OF REGIONS THAT THE SECOND BEAM ENCOUNTERS.
1      C
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 03 OF 22

MESHREP2

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C---- J: A COUNTER VARIABLE USED TO KEEP TRACK OF WHICH REGION THE
1 C---- LASER BEAM IS IN.
1 C----
1 C---- IFLAG5: A FLAG VARIABLE USED TO INDICATE THAT AN ADJACENT
1 C---- REGION HAS NOT BEEN FOUND.
1 C----
1 C---- IFLAG6: A FLAG VARIABLE USED TO INDICATE THAT THE LASER BEAM
1 C---- DID NOT EXIT FROM AN ALLOWABLE SIDE OF A REGION.
1 C----
1 C---- IFLAG7: A FLAG VARIABLE USED TO INDICATE THAT A PHYSICAL SOLUTION
1 C---- DOES NOT EXIST
1 C----
1 C---- IFLAG8: A FLAG VARIABLE USED TO INDICATE THAT A SECOND ANGLED
1 C---- REGION HAS BEEN FOUND.
1 C----
1 C---- IFLAG9: A FLAG VARIABLE USED TO INDICATE THET THE LASER BEAM
1 C---- DID NOT EXIT FROM AN ALLOWABLE SIDE OF A REGION.
1 C----
1 C----
1 C---- MATNO(J): AN USED AS FLAG TO INDICATE AN EXIT ELEMENT
1 C----
1 C---- TCORD: THE TWO DIMENSIONAL ARRAY CONTIANING THE
1 C---- COORDINATES OF THE INPUT BOUNDARY POINTS.
1 C----
1 C----
1 C---- SHALF: THE LASER BEAM HALF ANGLE.
1 C----
1 C---- SCXADJ IS A VARIABLE USED BY THE DISSPLA GRAPHICS PACKAGE TO
1 C---- CONTROL THE SIZE OF THE PLOT IN THE X DIRECTION.
1 C----
1 C---- SCYADJ IS A VARIABLE USED BY THE DISSPLA GRAPHICS PACKAGE TO
1 C---- CONTROL THE SIZE OF THE PLOT IN THE Y DIRECTION.
1 C----
1 C---- XENT1(J): AN ARRAY WHICH LISTS THE X COORDINATE OF THE POINT AT
1 C---- WHCIH THE FIRST LASER BEAM ENTERS REGION J.
1 C----
1 C---- YENT1(J): AN ARRAY WHICH LISTS THE Y COORDINATE OF THE POINT AT
1 C---- WHCIH THE FIRST LASER BEAM ENTERS REGION J.
1 C----
1 C---- XENT2(J): AN ARRAY WHICH LISTS THE X COORDINATE OF THE POINT AT
1 C---- WHCIH THE SECOND LASER BEAM ENTERS REGION J.
1 C----
1 C---- YENT2(J): AN ARRAY WHICH LISTS THE Y COORDINATE OF THE POINT AT
1 C---- WHCIH THE SECOND LASER BEAM ENTERS REGION J.
1 C----
1 C---- XEXT1(J): AN ARRAY WHICH LISTS THE X COORDINATE OF THE POINT AT
1 C---- WHCIH THE FIRST LASER BEAM EXITS REGION J.
1 C----
1 C---- YEXT1(J): AN ARRAY WHICH LISTS THE Y COORDINATE OF THE POINT AT
1 C---- WHCIH THE FIRST LASER BEAM EXITS REGION J.
1 C----
1 C---- XEXT2(J): AN ARRAY WHICH LISTS THE X COORDINATE OF THE POINT AT
1 C---- WHCIH THE SECOND LASER BEAM EXITS REGION J.
```



PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 04 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C---- YEXT2(J): AN ARRAY WHICH LISTS THE Y COORDINATE OF THE POINT AT
1 C---- WHCIH THE SECOND LASER BEAM EXITS REGION J.
1 C----
1 C---- THETA(J): DIRECTION ANGLE OF THE LASER BEAM WHILE IN REGION
1 C---- J.
1 C----
1 C---- TINDX(I):THE INDEX OF REFRACTION FOR REGION J.
1 C----
1 C---- TINW: THE IN DEX OF REFRACTION FOR WATER
1 C----
1 C---- TINP: THE INDEX OF REFRACTION FOR PLEXIGLASS.
1 C----
1 C---- XTEMP: X COORDINATE OF THE SPECIFIED PROBE VOLUME LOCATION
1 C----
1 C---- YTEMP: Y COORDINATE OF THE SPECIFIED PROBE VOLUME LOCATION.
1 C----
1 C---- READ AND PRINT THE TITLE OF THE MESH
1 C
7 READ(5,900) NTITLE 203
7 WRITE (6,901) NTITLE 204
1 C
1 C---- READ IN THE INFOMATION DEFINING THE OUTLINE OF THE MESH
1 C
7 READ (5,905) NPOIN,NELEM 206
7 WRITE (6,910) NPOIN,NELEM 207
7 WRITE (6,920) 305
7 WRITE (6,925) 307
1 C
1 C---- READ IN AND WRITE THE CONNECTIVITY MATRIX OF THE POINTS OUTLINING
1 C---- THE MESH.
1 C
7 DO 10 IELEM=1,NELEM 401
7 READ (5,905) NUMEL,(INODS(NUMEL,INODE),INODE=1,8), 402
6 IMATNO(NUMEL),NCOL(NUMEL)
4 10 WRITE(6,926) NUMEL,(INODS(NUMEL,INODE),INODE=1,8), 402
6 IMATNO(NUMEL)
7 WRITE(6,999)
7 DO 15 I=1,NELEM
10 READ(5,1001) (LNADJ(I,J),J=1,20),TINDX(I)
10 WRITE(6,1001) (LNADJ(I,J),J=1,20),TINDX(I)
3 15 CONTINUE
10 WRITE(6,1002)
7 DO 17 I=1,NELEM
10 READ(5,1003) IANG(I)
10 WRITE(6,1003) I,IANG(I)
3 17 CONTINUE
1 C
1 C---- READ IN AND WRITE THE COORDINATES OF THE NODE POINTS OUTLINING THE
1 C---- BOUNDARY OF THE MESH.
1 C
7 WRITE (6,930) 403
7 WRITE (6,935) 404
7 DO 20 IPOIN=1,NPOIN 407
7 READ (5,940) JPOIN,(TCORD(JPOIN,IDIME),IDIME=1,2)
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 05 OF 22

MESHREP2

TART  
COL

```
-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8-----

4      20 WRITE (6,941) JPOIN,(TCORD(JPOIN,IDIME),IDIME=1,2)
1      C
1      C---- READ IN THE INITIAL LASER DATA
1      C
7          J=1
7          READ(5,960) NREGIO(J),XENT1(NREGIO(J)),YENT1(NREGIO(J)),SHALF,
6          *TINW,TINP
7          WRITE(6,963) TINW,TINP
1      C
1      C---- READ IN GRAPHICS DATA
1      C
7          READ(5,950) NDGRAF
7          READ (5,955) SCXADJ,SCYADJ
7          RETURN
3      900 FORMAT (12A4) 205
3      901 FORMAT (///,1X,'*****',12A4,'*****',/) 205
3      905 FORMAT (11I5) 208
3      910 FORMAT (/,6X,'AUTOMATIC DATA GENERATION FROM',I4,' LOCATION', 301
6          1' POINTS AND',I3,' DATA BLOCKS') 302
3      920 FORMAT (/,6X,'DATA BLOCKS') 306
3      925 FORMAT (/,1' BLOCK NO.',22X,'DEFINITION POINTS',36X,'FLAG') 308
3      926 FORMAT(1X,I8,5X,8(I5,2X),5X,I5)
3      930 FORMAT (/,6X,'LOCATION OF POINTS') 405
3      935 FORMAT (/,4X,' POINT NO',5X,'X-COORD.',10X,'Y-COORD') 406
3      940 FORMAT (I10,2F15.5) 408
3      941 FORMAT (1X,I10,3X,F15.5,3X,F15.5) 408
3      950 FORMAT(2I5)
3      955 FORMAT(7F10.4)
3      960 FORMAT(I5,5F10.5)
3      963 FORMAT(/,' INDEX OF REFRACTION FOR WATER= ',D15.5,3X,
6          *'INDEX OF REFRACTION FOR PLEXIGLASS= ',D15.5)
3      999 FORMAT(' ELEMENT NUMBER ,ADJACENT ELEMENTS,INDEX OF REFRACTION')
2      1001 FORMAT(20I3,F10.3)
2      1002 FORMAT(' ELEMNT NUMBER, ANGLED SIDE')
2      1003 FORMAT(2(2X,I5))
7      END 501
1      C *****
7      SUBROUTINE DISSPL
1      C *****
1      C
7      IMPLICIT REAL*8(A-H,O-Z)
7      COMMON TCORD(2000,2), 205
6      *XENT1(50),YENT1(50),XEXT1(50),YEXT1(50),THETA(50),
6      *TINDX(50),XENT2(50),YENT2(50),XEXT2(50),YEXT2(50),
6      *SCXADJ,SCYADJ,SHALF,TINW,TINP,XTEMP,YTEMP,
6      *MATNO(1501),NPOIN,NELEM,
6      *LNADJ(50,20),NREGIO(50),NREGI2(50),IANG(50),
6      *INODS(1501,8),
6      *NTITLE(10),NCOL(100),NDGRAF,
6      *J3,J4,J,
6      *IFLAG5,IFLAG6,IFLAG7,IFLAG8,IFLAG9
7      REAL*4 COORD1(400),COORD2(400),WORK(6000)
7      KGRAPH=0
1      C
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 06 OF 22

MESHREP2

START  
COL

```
-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8
1 C---- THIS ROUTINE DRAWS THE GENERATED MESH USING THE DISSPLA GRAPHICS 00040000
1 C---- SYSTEM.
1 C
7 CALL DIGEST 00040000
7 CALL NOBRDR
1 C
1 C---- THIS COMMAND SETS THE PHYSICAL LOCATION OF THE CORRDIATE (0,0)
1 C ON THE PLOT. FOR THIS CASE THE PLOT ORIGIN IS LOCATED 0.75 INCHES
1 C---- FROM THE LEFT EDGE AND 0.75 INCHES FROM THE BOTTOM.
1 C
7 XPHYS=0.75 00050000
7 YPHYS=0.75 00110000
7 CALL PHYSOR(XPHYS,YPHYS) 00350000
1 C 00400000
1 C---- THIS COMMAND SETS THE TOTAL SIZE OF PLOTTING AREA. 00410000
1 C 00420000
7 CALL PAGE(11.9375,8.500) 00430000
73 00440000
7 XPAGE=6.5 00450000
7 YPAGE=6.5 00460000
1 C 00600000
1 C---- THE FOLLOWING DO LOOP DETERMINES THE STARTING POINT, 00610000
1 C---- STEP SIZE, AND ENDPOINT FOR THE X AXIS AND Y AXISES. 00620000
1 C 00630000
7 YMAX=TCORD(1,2) 00640000
7 YMIN=TCORD(1,2) 00650000
7 XMAX=TCORD(1,1) 00660000
7 XMIN=TCORD(1,1) 00670000
7 DO 10 I=1,NPOIN 00680000
10 IF(XMAX.LT.TCORD(I,1))XMAX=TCORD(I,1) 00690000
10 IF(XMIN.GT.TCORD(I,1))XMIN=TCORD(I,1) 00700000
10 IF(YMAX.LT.TCORD(I,2))YMAX=TCORD(I,2) 00710000
10 IF(YMIN.GT.TCORD(I,2))YMIN=TCORD(I,2) 00720000
3 10 CONTINUE 00730000
1 C
1 C---- THE CODE DETERIMNES WHCIH OF THE FIGURE DIMENSIONS IS THE LARGEST
1 C
7 SCALE1=XMAX-XMIN 00740000
7 SCALE2=YMAX-YMIN 00750000
7 SCALE3=SCALE2/SCALE1
7 SCALE4=SCALE1/SCALE2
1 C
1 C---- THE CODE ADJUSTS THE OTHER DIMENSION SO THAT THE FIGURE WILL BE
1 C---- DRAWN TO SCALE AND SO THAT ALL OF IT WILL FIT ON THE PAGE.
1 C
7 IF(SCALE3.GT.1.0) GO TO 15
7 YPAGE=YPAGE*SCALE3
7 GO TO 16
3 15 XPAGE=XPAGE*SCALE4
1 C
1 C---- IF FOR SOME REASON YOU DO NOT WANT THE FIGURE DRAWN TO SCALE,USE
1 C THE VARIABLES SCXADJ AND SCXYADJ TO ADJUST THE SCALE OF THE X AND
1 C Y AXIS. A VALUE OF 1.0 FOR SCXADJ AND SCYADJ MEANS THAT SCALE FOR
1 C X AND Y AXIS WILL BE THE SAME. A VALUE OF 1.0 FOR SCXADJ
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 07 OF 22

MESHREP2

TART  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
1 C AND 2.0 FOR SCYADJ MEANS THAT THE SCALE OF THE Y AXIS WILL BE
1 C TWICE THE SCALE OF THE X AXIS. A VALUE OF 1.0 FOR SCYADJ
1 C AND 2.0 FOR SCXADJ MEANS THAT THE SCALE OF THE X AXIS WILL BE
1 C----- TWICE THE SCALE OF THE Y AXIS.
1 C
1 C
3 16 XPAGE=XPAGE*SCXADJ
7 YPAGE=YPAGE*SCYADJ
1 C 00470000
1 C 00470000
1 C----- THIS COMMAND MAKES THE FIGURE FIT WITHIN THE PLOTTING
1 C----- AREA. 00480000
1 C 00490000
1 C 00500000
1 C 00500000
7 CALL AREA2D(XPAGE,YPAGE)
1 C
1 C
1 C--- DISSPLA HEADING COMMAND
1 C
1 C
7 CALL HEADIN(NTITLE,100,3,1) 00590000
7 XSTEP=(XMAX-XMIN)/10. 00740000
7 YSTEP=(YMAX-YMIN)/10. 00750000
1 C 00760000
1 C 00760000
1 C----- THIS COMMAND SETS THE SCALE OF THE GRAPH ACCORDING TO VARIALBES IN00770000
1 C----- THE ARGUMENT.
1 C
1 C 00780000
1 C 00780000
7 CALL GRAF(XMIN,XSTEP,XMAX,YMIN,YPAGE,YMAX) 00790000
1 C
1 C
1 C----- THIS SECTION OF THE GRAPHICS ROUTINE DRAWS THE INPUT BLOCK AND
1 C----- COLORS IT.
1 C
1 C
7 DO 42 IBLOC=1,NELEM
1 C
1 C----- SET UP THE COORDINATE ARRAYS TO OUTLINE THE BLOCK.
1 C
10 DO 35 ISIDE=1,8
16 COORD1(ISIDE)=TCORD(INODS(IBLOC,ISIDE),1)
16 COORD2(ISIDE)=TCORD(INODS(IBLOC,ISIDE),2)
3 30 CONTINUE
3 35 CONTINUE
1 C
1 C
1 C----- THE STARTING POINTS AND END POINTS FOR THE OUTLINE MUST BE THE
1 C----- SAME. THE CODE ADJUSTS THE OUTLINE ARRAYS TO REFLECT THIS.
1 C
1 C
10 COORD1(ISIDE)=TCORD(INODS(IBLOC,1),1)
10 COORD2(ISIDE)=TCORD(INODS(IBLOC,1),2)
3 40 CONTINUE
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 08 OF 22

MESHREP2

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C
1 C
1 C---- THE CODE COLORS IN THE INPUT BLOCK ONLY IF A COMMAND IS GIVEN
1 C      TO DO THIS IN A CERTAIN COLOR.  IF NO COLOR, IS GIVEN THE CODE
1 C      ASSUMES THE USER DOES NOT WANT THE INPUT BLOCK SHADED IN. A
1 C      DEFALUT VALUE OF 0 FOR COLOR INSTRUCTS THE CODE TO NOT SHADE
1 C---- IN THE INPUT BLOCK.
1 C
1 C
10      IF(NCOL(IBLOC).EQ.0)GOTO 42
10      IF(NCOL(IBLOC).EQ.8)NCOL(IBLOC)=0
10      CALL NEWPEN(NCOL(IBLOC))
1 C
1 C
1 C---- THE CODE USES THE DISSPLA SHADE COMMAND TO COLOR THE BLOCK IN.
1 C
1 C
10      CALL SHADE(COORD1,COORD2,ISIDE,90.0,0.010,1,WORK,6000)
3      42 CONTINUE
1 C
1 C
1 C---- THE CODE NOW DRAWS THE MESH ON TOP OF INPUT BLOCK.  IT
1 C      ACCOMPLISHES THIS TASK BY CONNECTING POINTS. THE CODE GOES THROUGH
1 C      THE ELEMENT CONNECTIVITY MATRIX AND DRAWS A LINE CONNMECTING EACH
1 C---- ONE OF THE NODE POINTS IN THE PROPER FASHION..
1 C
1 C
7      DO 60 IBLOC=1,NELEM
10      DO 50 INODE=1,9
13      IPLOT2=INODE
13      IF(INODE.EQ.9)IPLOT2=1
13      NNPOIN=INODS(IBLOC,IPLOT2)
13      COORD1(INODE)=TCORD(NNPOIN,1)
13      COORD2(INODE)=TCORD(NNPOIN,2)
3      50 CONTINUE
7      CALL NEWPEN(1)
10      DO 55 I=1,8
13      II=I+1
13      CALL RLVEC(COORD1(I),COORD2(I),COORD1(II),COORD2(II),0)
3      55 CONTINUE
3      60 CONTINUE
7      CALL NEWPEN(6)
1 C
1 C---- NOW DRAW THE PATH OF THE FIRST LASER BEAM
1 C
10      DO 65 I3=1,J4
13      II=2
13      I=1
13      COORD1(I)=XENT1(NREGIO(I3))
13      COORD2(I)=YENT1(NREGIO(I3))
13      COORD1(II)=XEXT1(NREGIO(I3))
13      COORD2(II)=YEXT1(NREGIO(I3))
13      CALL RLVEC(COORD1(I),COORD2(I),COORD1(II),COORD2(II),0)
3      65 CONTINUE
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 09 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C
1 C---- NOW DRAW THE PATH OF THE SECOND LASER BEAM
1 C
10 DO 85 I3=1,J3
13 II=2
13 I=1
13 COORD1(I)=XENT2(NREGI2(I3))
13 COORD2(I)=YENT2(NREGI2(I3))
13 COORD1(II)=XEXT2(NREGI2(I3))
13 COORD2(II)=YEXT2(NREGI2(I3))
13 CALL RLVEC(COORD1(I),COORD2(I),COORD1(II),COORD2(II),0)
3 85 CONTINUE
7 CALL ENDPL(0)
7 CALL DONEPL(0) 00010000
7 RETURN
7 END
1 C *****
7 SUBROUTINE LASER 203
1 C *****
1 C
7 IMPLICIT REAL*8(A-H,O-Z)
7 COMMON TCORD(2000,2), 205
6 *XENT1(50),YENT1(50),XEXT1(50),YEXT1(50),THETA(50),
6 *TINDX(50),XENT2(50),YENT2(50),XEXT2(50),YEXT2(50),
6 *SCXADJ,SCYADJ,SHALF,TINW,TINP,XTEMP,YTEMP,
6 *MATNO(1501),NPOIN,NELEM,
6 *LNADJ(50,20),NREGIO(50),NREGI2(50),IANG(50),
6 *INODS(1501,8),
6 *NTITLE(10),NCOL(100),NDGRAF,
6 *J3,J4,J,
6 *IFLAG5,IFLAG6,IFLAG7,IFLAG8,IFLAG9
7 COMMON /REG/SLOPE2,B2,THPLEX,THWAT,IFLAG,IFLAG2,ITEMP
1 C
1 C---- THIS SUBROUTINE INITIALIZES THE LASER DATA. IT CALLS THE OTHER
1 C---- TWO OTHER LASER ROUTINES WHICH TRACE THE PATH OF THE BEAM.
1 C
1 C----
1 C---- LOCAL SUBROUTINE VARIABLES
1 C----
1 C---- SLOPE2: THE SLOPE OF A SIDE OF AN ELEMENT. IT IS USED IN
1 C---- CALCULATING THE EQUATION FOR A SIDE OF AN ELEMENT.
1 C----
1 C---- B2: THE Y INTERCEPT OF THE EQUATION OF FOR AN
1 C---- ELEMENT.
1 C----
1 C---- THPLEX: THE DIRECTION ANLGE OF THE LASER BEAM IN THE PLEXIGLASS.
1 C---- ( ASSUMES NO ANGLED SURFACE).
1 C----
1 C---- THWAT: THE DIRECTION ANLGE OF THE LASER BEAM IN THE WATER.
1 C---- ( ASSUMES NO ANGLED SURFACE).
1 C----
1 C---- IFLAG: A FLAG VARIABLE USED TO INDICATE IF THE LASER BEAM HAS
1 C---- ENTERED A BOUNDARY REGION.
1 C----
```

```

1 C-----1-----2-----3-----4-----5-----6-----7-----8
2 COL
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
10
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 11 OF 22

MESHREP2

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
7       IFLAG=0
7       Y1=YEXT1(NREGION(J))
7       DO 40 I=2,J
10      NREGION(J)=0
1 40    CONTINUE
7       J=1
7       SHALF=-SHALF
1  C
1  C---- COMPUTE HALF ANGLE OF THE LASER IN WATER AND PLEXIGLASS ASSUMING
1  C---- NO ANGLED SURFACES
1  C
7       THWAT=DARSIN(1./TINW*DSIN(SHALF))
7       THETA(NREGION(J))=THWAT
7       THPLEX=DARSIN(1.000/TINP*DSIN(SHALF))
7       CALL YPOINT
7       IF(IFLAG5.EQ.1) GOTO 681
7       IF(IFLAG6.EQ.1) GOTO 685
7       IF(IFLAG7.EQ.1) GOTO 690
7       IF(IFLAG8.EQ.1) GOTO 693
7       IF(IFLAG9.EQ.1) GOTO 696
7       Y2=YEXT1(NREGION(J))
7       DO 42 I=2,J
10      NREGION(J)=0
1 42    CONTINUE
1  C
1  C---- CALCULATE EXIT POINT FOR THE FIRST BEAM ASSUMING NO ANGLED
1  C---- SURFACES
1  C
2 45    CONTINUE
7       READ(5,995)IBLOC,NTPOIN
7       IF(IBLOC.EQ.0)GO TO 800
7       DO 500 I5=1,NTPOIN
7       IFLAG=0
7       J=1
7       NREGION(J)=IBLOC
7       READ(5,1200) XENT1(NREGION(J)),YENT1(NREGION(J))
7       SHALF=DABS(SHALF)
1  C
1  C---- COMPUTE HALF ANGLE OF THE LASER IN WATER AND PLEXIGLASS ASSUMING
1  C---- NO ANGLED SURFACES
1  C
7       THPLEX=DARSIN(1.000/TINP*DSIN(SHALF))
7       THWAT=DARSIN(1./TINW*DSIN(SHALF))
7       THETA(NREGION(J))=THWAT
7       IBEAM=1
7       CALL YPOINT
7       IF(IFLAG5.EQ.1) GOTO 681
7       IF(IFLAG6.EQ.1) GOTO 685
7       IF(IFLAG7.EQ.1) GOTO 690
7       IF(IFLAG8.EQ.1) GOTO 693
7       IF(IFLAG9.EQ.1) GOTO 696
1  C
1  C---- STORE THE POINTS THROUGH WHICH THE FIRST BEAM ENTERS AND EXITS
1  C---- EACH REGION.  THESE WILL BE SUBSEQUENTLY USED IN THE GRAPHICS
```



PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 12 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C---- ROUTINE
1 C
7 ANGL1=THETA(NREGIO(1))
7 IFLAG=0
7 J3=J
7 DO 60 I=1,J3
7 NREGI2(I)=NREGIO(I)
7 YEXT2(NREGI2(I))=YEXT1(NREGIO(I))
7 YENT2(NREGI2(I))=YENT1(NREGIO(I))
7 XEXT2(NREGI2(I))=XEXT1(NREGIO(I))
7 XENT2(NREGI2(I))=XENT1(NREGIO(I))
7 NREGIO(I)=0
7 NREGIO(1)=NREGI2(1)
1 60 CONTINUE
1 C
1 C---- NOW COMPUTE THE PATH FOR THE SECOND BEAM
1 C
7 J=1
7 SHALF=-SHALF
1 C
1 C---- COMPUTE HALF ANGLE OF THE LASER IN WATER AND PLEXIGLASS ASSUMING
1 C---- NO ANGLED SURFACES
1 C
7 THWAT=DARSIN(1./TINW*DSIN(SHALF))
7 THPLEX=DARSIN(1.000/TINP*DSIN(SHALF))
7 THETA(NREGIO(J))=THWAT
7 CALL YPOINT
7 IF(IFLAG5.EQ.1) GOTO 681
7 IF(IFLAG6.EQ.1) GOTO 685
7 IF(IFLAG7.EQ.1) GOTO 690
7 IF(IFLAG8.EQ.1) GOTO 693
7 IF(IFLAG9.EQ.1) GOTO 696
7 ANGL2=THETA(NREGIO(1))
7 J4=J
1 C
1 C---- NOW COMPUTE THE ACTUAL HALF ANGLE OF THE LASER BEAMS IN WATER
1 C
7 THALF=(ANGL1-ANGL2)/2.0D0
1 C
1 C---- NOW COMPUTE THE DIRECTION OF THE VELOCITY VECTOR
1 C
7 TDIR=90.0D0*3.141592654D0/180.0D0+((ANGL1+ANGL2)/2.0D0)
7 THALF=THALF*180.0D0/3.141592654D0
7 TDIR=TDIR*180.0D0/3.141592654D0
7 SHALF=-SHALF
1 C
1 C---- NOW CALCULATE HOW FAR THE LASER SHOULD BE MOVED FROM THE
1 C---- POSITION SO THAT WE CAN MEASURE AT THE DESIRED POINT.
1 C
7 YREF=(Y1+Y2)/2.0D0
7 SEP1=(Y1-Y2)/2.0D0
7 YCENT=(YEXT2(NREGI2(J3))+YEXT1(NREGIO(J4)))/2.0D0
7 YCENT=YCENT-YREF
7 XCEN1=(YEXT2(NREGI2(J3))-YEXT1(NREGIO(J4)))/2.0D0
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 13 OF 22

MESHREP2

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
7      XCENT=(SEP1-XCEN1)/DTAN(SHALF)
1      C
1      C---- PRINT OUT THE RESULTS
1      C
7      SHAL2=SHALF*180.0D0/3.141592654D0
7      WRITE(6,950)
7      WRITE(6,951) THALF,TDIR,SHAL2
7      WRITE(6,968) XENT1(NREGIO(1)),YENT1(NREGIO(1))
7      WRITE(6,967) YCENT,XCENT
7      WRITE(15,970) XENT1(NREGIO(1)),YENT1(NREGIO(1)),XCENT,YCENT,
6      *X11,Y11,THALF,TDIR
1      500  CONTINUE
7      GO TO 45
1      681  CONTINUE
7      WRITE(6,950)
7      WRITE(6,968) XENT1(NREGIO(1)),YENT1(NREGIO(1))
7      WRITE(6,966)
7      XENT1(NREGIO(1))=0.0
7      YENT1(NREGIO(1))=0.0
7      XCENT=0.0
7      YCENT=0.0
7      THALF=0.0
7      TDIR=0.0
7      WRITE(15,970) XENT1(NREGIO(1)),YENT1(NREGIO(1)),XCENT,YCENT,
6      *X11,Y11,THALF,TDIR
7      GO TO 45
1      685  CONTINUE
7      WRITE(6,950)
7      WRITE(6,968) XENT1(NREGIO(1)),YENT1(NREGIO(1))
7      WRITE(6,1250)
7      XENT1(NREGIO(1))=0.0
7      YENT1(NREGIO(1))=0.0
7      XCENT=0.0
7      YCENT=0.0
7      THALF=0.0
7      TDIR=0.0
7      WRITE(15,970) XENT1(NREGIO(1)),YENT1(NREGIO(1)),XCENT,YCENT,
6      *X11,Y11,THALF,TDIR
7      GO TO 45
1      690  CONTINUE
7      WRITE(6,950)
7      WRITE(6,968) XENT1(NREGIO(1)),YENT1(NREGIO(1))
7      WRITE(6,1150)
7      XENT1(NREGIO(1))=0.0
7      YENT1(NREGIO(1))=0.0
7      XCENT=0.0
7      YCENT=0.0
7      THALF=0.0
7      TDIR=0.0
7      WRITE(15,970) XENT1(NREGIO(1)),YENT1(NREGIO(1)),XCENT,YCENT,
6      *X11,Y11,THALF,TDIR
7      GO TO 45
1      693  CONTINUE
7      WRITE(6,950)
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 14 OF 22

MESHREP2

TART  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
7      WRITE(6,968) XENT1(NREGIO(1)),YENT1(NREGIO(1))
7      WRITE(6,1040)
7      XENT1(NREGIO(1))=0.0
7      YENT1(NREGIO(1))=0.0
7      XCENT=0.0
7      YCENT=0.0
7      THALF=0.0
7      TDIR=0.0
7      WRITE(15,970) XENT1(NREGIO(1)),YENT1(NREGIO(1)),XCENT,YCENT,
6      *X11,Y11,THALF,TDIR
7      GO TO 45
1 696  CONTINUE
7      WRITE(6,950)
7      WRITE(6,968) XENT1(NREGIO(1)),YENT1(NREGIO(1))
7      WRITE(6,1041)
7      XENT1(NREGIO(1))=0.0
7      YENT1(NREGIO(1))=0.0
7      XCENT=0.0
7      YCENT=0.0
7      THALF=0.0
7      TDIR=0.0
7      WRITE(15,970) XENT1(NREGIO(1)),YENT1(NREGIO(1)),XCENT,YCENT,
6      *X11,Y11,THALF,TDIR
7      GO TO 45
1 800  CONTINUE
7      RETURN
1 950  FORMAT(// ' ')
1 951  FORMAT(' ALTERED HALF ANGLE =',2X,D15.5,' ANGLE OF VELOCITY VECTOR
6      *(MEASURED FROM THE HORIZONTAL)=',2X,D15.5,/,
6      *' HALF ANGLE OF THE LASER IN AIR',2X,D15.5)
1 966  FORMAT(' ERROR: NO ADJACENT NREGIO FOUND',2(2X,I5))
1 967  FORMAT(' DELTA Y =',F15.5,' DELTA X = ',F15.5)
1 968  FORMAT(' MEASUREMENT POINT IS X = ',D15.5,' Y =',D15.5)
1 969  FORMAT(' REFERENCE POINT IS X=',D15.5,2X,' Y=',D15.5,/,
6      *,' HALF ANGLE OF THE BEAM IN WATER WITH NO ANGLED SURFACES =',
6      *D15.5)
1 970  FORMAT(6(2X,D10.3),/,2(2X,D15.8))
1 995  FORMAT(2I10)
1 1040 FORMAT(' HAVE ENTERED A DIFFERENT ANGLED REGION, OR HAVE ENTERED
6      *A SECOND ANGLED REGION ---NO SOLUITON EXISTS')
1 1041 FORMAT(' ERROR NO EXIT POINT HAS BEEN FOUND')
1 1150 FORMAT(' DID NOT ENTER ORIGINAL ANGLED REGION')
1 1200 FORMAT( D15.5,D15.5)
1 1250 FORMAT(' HAVE EXITED FROM THE WRONG SIDE OF A REGION')
7      END
1  C      *****
7      SUBROUTINE YPOINT
1  C      *****
7      IMPLICIT REAL*8(A-H,O-Z)
7      COMMON TCORD(2000,2),
6      *XENT1(50),YENT1(50),XEXT1(50),YEXT1(50),THETA(50),
6      *XTINDX(50),XENT2(50),YENT2(50),XEXT2(50),YEXT2(50),
6      *SCXADJ,SCYADJ,SHALF,TINW,TINP,XTEMP,YTEMP,
6      *MATNO(1501),NPOIN,NELEM,
```

203

205

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 15 OF 22

MESHREP2

TART  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
6      *LNADJ(50,20),NREGIO(50),NREGI2(50),IANG(50),
6      *INODS(1501,8),
6      *NTITLE(10),NCOL(100),NDGRAF,
6      *J3,J4,J,
6      *IFLAG5,IFLAG6,IFLAG7,IFLAG8,IFLAG9
7      COMMON /REG/SLOPE2,B2,THPLEX,THWAT,IFLAG,IFLAG2,ITEMP
1      C
1      C---- THIS SUBROUTINE DETERMINES THE EXIT POINT OF THE LASER BEAM AS
1      C---- LEAVES ONE REGION AND ENTERS ANOTHER REGION.
1      C
1      C---- THIS SUBROUTINE DETERMINES THE EXIT POINT OF THE LASER BEAM AS
1      C---- LEAVES ONE REGION AND ENTERS ANOTHER REGION.
1      C
1      C---- SET UP SOME INITIAL FLAG VARIABLES
1      C
1      C---- IFLAG2: INDICATES IF AN ANGLED REGION HAS BEEN FOUND.
1      C
1      C---- IFLAG3: KEEPS TRACK OF THE FIRST ANGLED REGION ENCOUNTERED.
1      C
1      C---- JCHEC: A FLAG VARIABLE USED TO KEEP TRACK OF THE NUMBER OF
1      C---- ANGLED REGIONS FOUND.
1      C
1      C---- ITEMp: A TEMPORARY VARIABLE USED BY SUBROUTINE YPOINT. THIS
1      C---- VARIABLE KEEPS TRACK OF WHICH ELEMENT THE BEAM IS IN AS THE
1      C---- CODE WORKS ITS WAY THROUGH THE VARIOUS REGIONS.
1      C
1      C---- SLOPE1: THE CODE DETERMINES A LINEAR EQUATION WHICH DESCRIBES THE
1      C---- PATH OF THE LASER BEAM THROUGH EACH REGION. SLOPE1 IS THE SLOPE
1      C---- OF THIS EQUATION.
1      C
1      C---- B1: THE CODE DETERMINES A LINEAR EQUATION WHICH DESCRIBES THE
1      C---- PATH OF THE LASER BEAM THROUGH EACH REGION. B1 IS THE Y INTERCEPT
1      C---- OF THIS EQUATION.
1      C
1      C---- XINT: THE X COORDINATE OF THE CALCULATED POINT AT WHICH THE LASER
1      C---- BEAM EXITS THE REGION.
1      C
1      C---- YINT: THE Y COORDINATE OF THE CALCULATED POINT AT WHICH THE LASER
1      C---- BEAM EXITS THE REGION
1      C
1      C---- IFLAG3: A VARIABLE WHICH KEEPS TRACK OF THE FIRST ANGLED REGION
1      C---- ENCOUNTERED.
1      C
1      C---- ALPH2: THE ANGLE BETWEEN A SLANTED SIDE OF AN ELEMENT AND THE
1      C---- HORIZONTAL.
7      JCHEC=0
7      IFLAG3=0
7      IFLAG7=0
7      IFLAG8=0
7      IFLAG9=0
1 10  CONTINUE
7      IF(J.LT.2)GO TO 20
1      C
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 16 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C---- DETERMINE THE HALF ANGLE OF THE LASER BEAM FOR THE CURRENT REGION
1 C
7   THETA(NREGIO(J))=DARSIN(TINDX(NREGIO(J-1))/TINDX(NREGIO(J))*
6   *DSIN(THETA(NREGIO(J-1))))
1 15 CONTINUE
1 20 CONTINUE
1 C
1 C---- DETERMINE THE EQUATION WHICH DESCRIBES THE PATH OF THE RAY
1 C---- IN THE GIVEN REGION
7   SLOPE1=DTAN(THETA(NREGIO(J)))
7   B1=YENT1(NREGIO(J))-SLOPE1*XENT1(NREGIO(J))
1 C
1 21 CONTINUE
7   I2=1
7   I3=3
7   DO 110 I=1,3
1 C
1 C---- FOR A GIVEN SIDE OF THE CURRENT REGION, DETERMINE YMAX,YMIN,XMAX,
1 C---- AND XMIN FOR THAT SIDE.
1 C
7   YMAX=DMAX1(TCORD(INODS(NREGIO(J),I2),2),TCORD(INODS(NREGIO(J),I3),
6   *2))
7   YMIN=DMIN1(TCORD(INODS(NREGIO(J),I2),2),TCORD(INODS(NREGIO(J),I3),
6   *2))
7   XMAX=DMAX1(TCORD(INODS(NREGIO(J),I2),1),TCORD(INODS(NREGIO(J),I3),
6   *1))
7   XMIN=DMIN1(TCORD(INODS(NREGIO(J),I2),1),TCORD(INODS(NREGIO(J),I3),
6   *1))
1 C
1 C---- DETERMINE IF THIS SIDE IS A SIDE OF CONSTANT X, CONSTANT Y, OR IF
1 C---- THE SIDE IS SLOPED.
1 C
10  IF(TCORD(INODS(NREGIO(J),I2),1).EQ.TCORD(INODS(NREGIO(J),I3),
6   * 1))GO TO 30
10  IF(TCORD(INODS(NREGIO(J),I2),2).EQ.TCORD(INODS(NREGIO(J),I3),
6   * 2))GO TO 40
10  SLOPE2=(TCORD(INODS(NREGIO(J),I2),2)-TCORD(INODS(NREGIO(J),I3),
6   * 2))/(TCORD(INODS(NREGIO(J),I2),1)-TCORD(INODS(NREGIO(J),I3),1)
6   * )
10  B2=TCORD(INODS(NREGIO(J),I2),2)-SLOPE2*TCORD(INODS(NREGIO(J),I2
6   * ),1)
1 C
1 C---- DETERMINE THE EQUATION OF THE SLOPED SIDE. USING THIS EQUATION AND
1 C---- THE EQUATION FOR THE RAY, DETERMINE THE INTERSECTION POINT. THEN
1 C---- CHECK TO SEE IF THIS INTERSECTION POINT FALLS WITHIN THE BOUNDARY
1 C---- OF THE REGION (LABEL 100).
1 C
10  DCRAM=SLOPE1-SLOPE2
10  YNUM=B1*SLOPE2*(-1.0)+B2*SLOPE1
10  XNUM=B2-B1
10  YINT=YNUM/DCRAM
10  XINT=XNUM/DCRAM
10  GO TO 100
1 C
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 17 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C---- SINCE X IS CONSTANT ALONG A SIDE, PLUG THIS VALUE OF X INTO THE
1 C---- EQUATION FOR THE RAY AND DETERMINE THE VALUE OF Y. THEN CHECK TO
1 C---- SEE IF THIS INTERSECTION POINT FALLS WITHIN THE BOUNDARY OF THE
1 C---- REGION (LABEL 100).
1 C
1 30      CONTINUE
10      XINT=TCORD(INODS(NREGION(J),I2),1)
10      YINT=B1+SLOPE1*XINT
10      SLOPE2=-1.0D70
10      B2=-1.0D70
10      GO TO 100
1 C
1 C---- SINCE Y IS CONSTANT ALONG A SIDE, PLUG THIS VALUE OF Y INTO THE
1 C---- EQUATION FOR THE RAY AND DETERMINE THE VALUE OF X. THEN CHECK TO
1 C---- SEE IF THIS INTERSECTION POINT FALLS WITHIN THE BOUNDARY OF THE
1 C---- REGION (LABEL 100).
1 C
1 40      CONTINUE
10      YINT=TCORD(INODS(NREGION(J),I2),2)
10      XINT=(YINT-B1)/SLOPE1
10      SLOPE2=1.0D70
10      B2=1.0D70
1 100     CONTINUE
10      DDIF=YENT1(NREGION(J))
10      DDI2=XENT1(NREGION(J))
10      IF(DABS(DDI2).LT.0.001D0)DDI2=1.0D0
10      IF(DABS(DDIF).LT.0.001D0)DDIF=1.0D0
10      DDIF=(YINT-YENT1(NREGION(J)))/DDIF
10      DDI2=(XINT-XENT1(NREGION(J)))/DDI2
10      IF(SLOPE1.GT.0.0D0.AND.YINT.LT.YENT1(NREGION(J)))GO TO 109
10      IF(SLOPE1.LT.0.0D0.AND.YINT.GT.YENT1(NREGION(J)))GO TO 109
10      IF(DABS(DDIF).LT.0.0001D0.AND.DABS(DDI2).LT.0.0001D0)
6      *   GO TO 109
10      IF(YINT.LE.YMAX.AND.YINT.GE.YMIN.AND.XINT.LE.XMAX.AND.
6      *   XINT.GE.XMIN)GO TO 120
1 109     CONTINUE
10      IF(I.EQ.3)GO TO 130
10      I2=I2+2
10      I3=I3+2
1 110     CONTINUE
1 120     CONTINUE
7      XEXT1(NREGION(J))=XINT
7      YEXT1(NREGION(J))=YINT
7      GO TO 140
1 C
1 C---- ONCE THE EXIT POINT FOR REGION J IS FOUND, DETERMINE THE NEXT
1 C---- REGION INTO WHICH THE RAY IS ENTERING.
1 C
1 130     CONTINUE
7      IFLAG9=1
7      RETURN
1 140     CONTINUE
1 C
1 C---- CHECK TO MAKE SURE THAT WE ARE NOT ALREADY IN THE LAST REGION.
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 18 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C-----
7 IF(IFLAG.EQ.1)GO TO 500
7 CALL REGI
7 IF(IFLAG2.GT.0)GO TO 900
7 GO TO 10
1 500 CONTINUE
1 C
1 C----- IF THE BEAM ENTERED AN ANGLED REGION BEFORE THE CODE ADJUSTED
1 C----- THE HALF ANGLE, CHECK TO MAKE SURE THAT THE BEAM ENTERED THIS
1 C----- SAME ANGLED REGION AFTER THE HALF ANGLE WAS ADJUSTED.
1 C
7 IF(IFLAG3.GT.0)GO TO 1100
7 RETURN
1 900 CONTINUE
1 C
1 C----- BECAUSE THIS IS AN ANGLED REGION, THE CODE NOW CHECKS FOR THE
1 C----- FOLLOWING:
1 C----- (1) IS THIS THE FIRST TIME AN ANGLED REGION HAS
1 C----- BEEN ENCOUNTERED?
1 C----- (2) HAVE TWO OR MORE ANGLED REGIONS BEEN ENCOUNTERED?
1 C
7 IF(IFLAG3.NE.IFLAG2.AND.JCHEC.NE.0)GO TO 1000
7 IF(IFLAG3.EQ.IFLAG2.AND.JCHEC.EQ.1)GO TO 1050
1 C
1 C----- IF THE CODE MAKES TO HERE THIS IS THE FIRST TIME AN ANGLED REGION
1 C----- HAS BEEN ENCOUNTERED.
1 C
7 ALPH2=DATAN(SLOPE2)
7 IF(SLOPE2.LT.0.0D0)ALPH2=3.141592654D0+ALPH2
7 JCHEC=1
7 IFLAG3=IFLAG2
1 C
1 C----- THE CODE NOW ADJUSTS THE HALF ANGLE OF THE LASER BEAM IN WATER.
1 C----- TO DO THIS, THE CODE DETERMINES THE ORDER IN WHICH THE BEAM
1 C----- ENTERS AN ANGLED SURFACE, I.E., DOES THE BEAM ENTER A REGION
1 C----- WHERE THE ANGLED INTERFACE HAS WATER ON THE LEFT AND PLEXIGLASS
1 C----- ON THE RIGHT? OR DOES THE BEAM ENTER A REGION WITH WATER ON THE
1 C----- RIGHT AND PLEXIGLASS ON THE LEFT?
1 C
7 D1=TINDX(NREGIO(J))-TINP
7 D2=TINDX(ITEMP)-TINW
7 IF(DABS(D1).LT.1.0D-05.AND.DABS(D2).LT.1.0D-05)
6 *GO TO 910
7 THETA(NREGIO(1))=DARSIN(TINP/TINW*DSIN(THPLEX+1.5707963D0-
6 *ALPH2))+ALPH2-1.5707963D0
7 GO TO 920
1 910 CONTINUE
7 TPLEX=DARSIN(TINW/TINP*DSIN(THWAT+1.5707963D0-ALPH2))+ALPH2-
6 *1.5707963D0
7 THETA(NREGIO(1))=DARSIN(TINP/TINW*DSIN(TPLEX))
1 920 CONTINUE
1 C
1 C----- REDO ALL CALCULATIONS WITH THE CORRECTED ANGLE.
1 C
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 19 OF 22

MESHREP2

TART  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
7      J=1
7      GO TO 10
1 1000  CONTINUE
7      IFLAG8=1
7      RETURN
1 1050  CONTINUE
1      C
1      C---- NOW FOR THE ANGLED REGION WHICH HAS A VERTICAL SURFACE ON THE
1      C---- RIGHT AND AN ANGLED SURFACE ON THE LEFT, SET THE HALF ANGLE
1      C---- OF THE LASER TO ITS KNOWN VALUE.
1      C
7      JCHEC=JCHEC+1
7      J2=J
7      J=J+1
7      NREGIO(J)=ITEMP
7      YENT1(ITEMP)=YEXT1(NREGIO(J2))
7      XENT1(ITEMP)=XEXT1(NREGIO(J2))
7      D11=TINDX(ITEMP)-TINP
7      D12=TINDX(ITEMP)-TINW
7      IFLAG3=0
7      IF(D11.LT.1.0D-05)THETA(ITEMP)=THPLEX
7      IF(D12.LT.1.0D-05)THETA(ITEMP)=THWAT
7      GO TO 15
1 1100  CONTINUE
7      IFLAG7=1
7      RETURN
7      END
1      C *****
7      SUBROUTINE REGI
1      C *****
1      C
1      C---- FOR A RAY WITH A KNOWN EXIT POINT IN A REGION, THIS SUBROUTINE
1      C---- DETERMINES THE NEXT REGION WHICH THE BEAM WILL ENTER.
1      C
7      IMPLICIT REAL*8(A-H,O-Z)
7      COMMON TCORD(2000,2),
6      *XENT1(50),YENT1(50),XEXT1(50),YEXT1(50),THETA(50),
6      *TINDX(50),XENT2(50),YENT2(50),XEXT2(50),YEXT2(50),
6      *SCXADJ,SCYADJ,SHALF,TINW,TINP,XTEMP,YTEMP,
6      *MATNO(1501),NPOIN,NELEM,
6      *LNADJ(50,20),NREGIO(50),NREGI2(50),IANG(50),
6      *INODS(1501,8),
6      *NTITLE(10),NCOL(100),NDGRAF,
6      *J3,J4,J,
6      *IFLAG5,IFLAG6,IFLAG7,IFLAG8,IFLAG9
7      COMMON /REG/SLOPE2,B2,THPLEX,THWAT,IFLAG,IFLAG2,ITEMP
1      C----
1      C---- LOCAL SUBROUTINE VARIABLES
1      C----
1      C---- ITEMP: SEE SUBROUTINE YPOINT
1      C----
1      C---- SLOP2: SLOPE FOR SIDE I5 OF REGION ITEMP
1      C----
1      C---- B8: Y INTERCEPT FOR SIDE I5 OF REGION ITEMP
```

203

205



PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 20 OF 22

MESHREP2

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C----
7 IFLAG2=0
7 IFLAG5=0
7 IFLAG6=0
7 DO 600 I=1,20
10 ITEMP=LNADJ(NREGION(J),I)
10 IF(ITEMP.EQ.0)GO TO 601
10 IF(ITEMP.EQ.NREGION(J))GO TO 600
1 C
1 C---- DETERMINE THE MAXIMUM AND MINIMUM BOUNDARIES OF THE
1 C---- ADJACENT REGIONS.
1 C
7 YMAX=DMAX1(TCORD(INODS(ITEMP,2),5),TCORD(INODS(ITEMP,7),
6 *2))
7 YMIN=DMIN1(TCORD(INODS(ITEMP,1),2),TCORD(INODS(ITEMP,3),
6 *2))
7 XMAX=DMAX1(TCORD(INODS(ITEMP,3),1),TCORD(INODS(ITEMP,5),
6 *1))
7 XMIN=DMIN1(TCORD(INODS(ITEMP,1),1),TCORD(INODS(ITEMP,7),
6 *1))
7 DO 598 I5=1,3
1 C
1 C---- CHECK EACH SIDE OF THE ELEMENT AND CHECK TO SEE IF THE SIDE IS
1 C---- HORIZONTAL, VERTICAL OR SLANTED.
1 C
10 IF(I5.EQ.1)I2=1
10 IF(I5.EQ.1)I3=3
10 IF(I5.EQ.2)I2=5
10 IF(I5.EQ.2)I3=7
10 IF(I5.EQ.3)I2=7
10 IF(I5.EQ.3)I3=1
10 IF(TCORD(INODS(ITEMP,I2),1).EQ.TCORD(INODS(ITEMP,I3),
6 * 1))GO TO 30
10 IF(TCORD(INODS(ITEMP,I2),2).EQ.TCORD(INODS(ITEMP,I3),
6 * 2))GO TO 40
1 C
1 C---- FOR THE GIVEN REGION AND SIDE, COMPUTE THE EQUATION FOR THIS SIDE.
1 C
10 SLOP2=(TCORD(INODS(ITEMP,I2),2)-TCORD(INODS(ITEMP,I3),
6 * 2))/(TCORD(INODS(ITEMP,I2),1)-TCORD(INODS(ITEMP,I3),1)
6 * )
10 B8=TCORD(INODS(ITEMP,I2),2)-SLOP2*TCORD(INODS(ITEMP,I2
6 * ),1)
10 GO TO 100
1 C
1 C FOR X CONSTANT ALONG A SIDE
1 C
1 C
1 30 CONTINUE
10 SLOP2=-1.0D70
10 B8=-1.0D70
10 GO TO 100
1 C
1 C FOR Y CONSTANT ALONG AN EDGE
1 C
```

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 21 OF 22

MESHREP2

TART  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
1 40 CONTINUE
10 SLOP2=1.0D70
10 B8=1.0D70
1 100 CONTINUE
1 C
1 C---- CHECK TO SEE IF THE EQUATION FOR THIS PARTICULAR SIDE OF THIS
1 C---- PARTICULAR ELEMENT MATCHES THE EQUATION OF THE KNOWN SIDE.
1 C
10 DIFF1=(SLOPE2-SLOP2)/SLOPE2
10 DIFF2=(B2-B8)/B2
10 IF(DABS(DIFF1).LT.1.0D-02.AND.DABS(DIFF2).LT.1.0D-02)GO TO 590
10 GO TO 595
1 590 CONTINUE
1 C
1 C---- THE EQUATIONS FOR THE TWO SIDES MATCHED, SO NOW CHECK TO
1 C---- MAKE SURE THAT THE EXIT POINTS FALL WITHIN THE SUSPECTED REGION.
1 C
10 IF(YEXT1(NREGIO(J)).LE.YMAX.AND.YEXT1(NREGIO(J)).GE.YMIN.AND.
6 * XEXT1(NREGIO(J)).LE.XMAX.AND.XEXT1(NREGIO(J)).GE.XMIN)GO TO 700
1 595 CONTINUE
1 598 CONTINUE
1 600 CONTINUE
1 601 CONTINUE
7 RETURN
1 700 CONTINUE
1 C
1 C---- CHECK TO SEE IF THIS IS AN ANGLED REGION.
1 C
7 IF(I5.EQ.1)NSIDE=-1
7 IF(I5.EQ.2)NSIDE=-3
7 IF(I5.EQ.3)NSIDE=-4
7 IF(IANG(ITEMP).EQ.NSIDE)GO TO 800
7 J2=J
7 J=J+1
7 NREGIO(J)=ITEMP
7 YENT1(ITEMP)=YEXT1(NREGIO(J2))
7 XENT1(ITEMP)=XEXT1(NREGIO(J2))
7 IF(MATNO(ITEMP).LT.0)IFLAG=1
7 RETURN
1 800 CONTINUE
1 C
1 C---- CHECK THE FOLLOWING:
1 C---- (1) MAKE SURE THAT THE RAY ENTERS ON SIDE
1 C---- 4, OR THAT THE INDICES OF REFRACTION
1 C---- ARE THE SAME.
1 C
7 IF(IANG(ITEMP).EQ.-4.AND.
6 *TINDX(ITEMP).NE.TINDX(NREGIO(J)))GO TO 820
7 IF(TINDX(ITEMP).NE.TINDX(NREGIO(J)))GO TO 830
7 J2=J
7 J=J+1
7 NREGIO(J)=ITEMP
7 YENT1(ITEMP)=YEXT1(NREGIO(J2))
7 XENT1(ITEMP)=XEXT1(NREGIO(J2))
```

DATE: 84/09/06  
TIME: 10:29  
PAGE: 22 OF 22

MEMBER: MESHREP2  
LEVEL: 01.21  
USERID: T5712

PROJECT: T5712  
LIBRARY: PLOT  
TYPE: DATA

START COL 1-----2-----3-----4-----5-----6-----7-----8

|   |                              |
|---|------------------------------|
| 7 | IF(MATNO(ITEMP).LT.0)IFLAG=1 |
| 7 | RETURN                       |
| 1 | CONTINUE                     |
| 7 | IFLAG2=NREGIO(J)             |
| 7 | RETURN                       |
| 1 | CONTINUE                     |
| 7 | RETURN                       |
| 7 | END                          |

## IX. APPENDIX C

An analysis determining the path of a laser beam through a plexiglas cylinder sitting inside a plexiglas box has already been performed [C1]. This analysis is extended here to include multiple cylinders. Figures C-1 through C-6 outline the equations for two cylinders. Although it is not shown in this appendix, these equations can easily be extended to multiple cylinders using indicial notation.

Figure C-1 is a cross-sectional view of two vertical cylinders sitting inside a plexiglas box. The point  $P(x,y)$  has been chosen as the point at which velocity measurements will be made. The remaining angles and distances specified in Figure C-1 have been defined in Table C-I.

Figure C-2 is a close up of the inner cylinder which contains the specified measurement point. By drawing a radius from the origin through the point at which the laser beam intersects the inner radius of the inner cylinder, it can be observed that two right triangles with a common side are formed. As shown in Figure C-2 a relationship for  $\alpha_{1,1,1}$  in terms of  $R_p$ ,  $R_{1,1}$ ,  $B$ , and  $ALPH4G$  can be obtained from these two triangles. At the inner radius of the inner cylinder, Snell's law can be applied to determine  $\alpha_{1,1,2}$ . The resulting relationship for  $\alpha_{1,1,2}$  is also shown in Figure C-2.

Figure C-3 shows the path of the laser beam through the first cylinder. By examining the figure, it can be observed that two right triangles with a common side are formed. From these two triangles a relationship can be obtained for  $\alpha_{1,2,1}$ . By applying Snell's law at the outer radius of the first cylinder a relationship for  $\alpha_{1,2,2}$  can also be obtained.

Figure C-4 shows the two plexiglas cylinders. Again by examining the figure, it can be seen that two right triangles with a common side are formed. From these two triangles, a relationship for  $\alpha_{2,1,1}$  can be obtained. By applying Snell's law at the inner radius of the outer cylinder a relationship for  $\alpha_{2,1,2}$  can be obtained.

Figure C-5 shows the two plexiglas cylinders and the plexiglas box. Again by examining the figure, it will be noticed that two right triangles with a common side are formed. From these two triangles a relationship for  $\alpha_{2,2,1}$  can be obtained. By applying Snell's law at the outer radius of the outer cylinder, a relationship for  $\alpha_{2,2,2}$  can be obtained.

Many triangles are formed by the radii passing through the points at which the laser beam enters and exits each cylinder. By examining each triangle a relationship for ALPHW can be obtained. By examining these same triangles, a relationship for ANGLE can also be obtained. Relationships for ANGLE and ALPHW are shown in Figure C-5.

As shown in Figure C-5, Snell's law can be applied at the interface between the water and the plexiglas box to determine ALPHW. Snell's law can also be applied at the interface between the plexiglas box and the air to determine ALPHGH. Relationships for both ALPHW and ALPHGH are shown in Figure C-5.

At this point an equation set which completely defines the laser beam path has been determined and is listed in Table C-II. However, a direct solution is not possible.

The computer program cylinder uses an iterative technique to solve the equation set. The basic approach is to assume a value for ALPH4G, and then to use equations (C-1) through (C-14) to calculate ALPHGH. Once a value of ALPH4G is obtained which gives a value of ALPHGH sufficiently close to the true value the iteration is stopped.

Figure C-6 is a drawing of the outer cylinder and the plexiglas box. This figure shows how the relationship for  $Y_1$  is obtained.

- 
- C1. Hanle, D. D., "In Vitro Fluid Dynamics of Prosthetic Aortic Heart Valves in Steady and Pulsatile Flow", Ph.D. Thesis, California Institute of Technology, Pasadena, California, 1984.

TABLE C-1

DEFINITION OF NOMENCLATURE

|                  |   |                                                                                                                                                                                                                                                                                                |
|------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x                | = | x coordinate of laser beam crossing point                                                                                                                                                                                                                                                      |
| y                | = | y coordinate of laser beam crossing point                                                                                                                                                                                                                                                      |
| R <sub>p</sub>   | = | radius of laser beam crossing point                                                                                                                                                                                                                                                            |
| R <sub>i,j</sub> | = | radius of a particular cylinder. i indicates the cylinder (from center outwards). j indicates which radius (1 means inner radius, 2 means outer radius)                                                                                                                                        |
| $\alpha_{i,j,k}$ | = | angle that the laser beam makes with respect to the normal at the cylinder-water interface. i indicates the cylinder (from center outwards). j indicates inner or outer radius (1 means inner radius, 2 means outer radius). k indicates the angle (1 means inner angle, 2 means outer angle). |
| ALPHW            | = | direction angle for the laser beam in the water between the outer cylinder and the plexiglas box                                                                                                                                                                                               |
| ALPHP            | = | direction angle for the laser beam in the plexiglas box                                                                                                                                                                                                                                        |
| ALPH4G           | = | direction angle of the laser beam in the fluid at the beam crossing.                                                                                                                                                                                                                           |
| ALPHGH           | = | Half angle of the LDA in air.                                                                                                                                                                                                                                                                  |
| y <sub>1</sub>   | = | y coordinate of the point at which the laser beam exits the plexiglas box.                                                                                                                                                                                                                     |
| D                | = | distance between the origin and the inside of the plexiglas wall.                                                                                                                                                                                                                              |
| t                | = | thickness of the plexiglas box                                                                                                                                                                                                                                                                 |
| ANGLE            | = | angle between the line from the origin through the point where the laser beam exits the outermost cylinder, and the horizontal.                                                                                                                                                                |
| i                | = | number of cylidners.                                                                                                                                                                                                                                                                           |

TABLE C-II  
EQUATIONS WHICH DESCRIBE THE PATH OF A  
LASER BEAM THROUGH CYLINDRICALLY LAYERED MEDIA

$$(C-1) \quad \beta = \text{INVTAN } (y/x)$$

$$(C-2) \quad R_p = x / \cos (\beta)$$

$$(C-3) \quad \alpha_{1,1,1} = \text{INVSIN} \left[ \frac{R_p}{R_{1,1}} \sin [\beta - \text{ALPH4G}] \right]$$

$$(C-4) \quad \alpha_{1,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\alpha_{1,1,1}) \right]$$

$$(C-5) \quad \alpha_{1,2,1} = \text{INVSIN} \left[ \frac{R_{1,1}}{R_{1,2}} \sin (\alpha_{1,1,2}) \right]$$

$$(C-6) \quad \alpha_{1,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin (\alpha_{1,2,1}) \right]$$

$$(C-7) \quad \alpha_{2,1,1} = \text{INVSIN} \left[ \frac{R_{1,2}}{R_{2,1}} \sin (\alpha_{1,2,2}) \right]$$

$$(C-8) \quad \alpha_{2,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\alpha_{2,1,1}) \right]$$

$$(C-9) \quad \alpha_{2,2,1} = \text{INVSIN} \left[ \frac{R_{2,1}}{R_{2,2}} \sin (\alpha_{2,1,2}) \right]$$

$$(C-10) \quad \alpha_{2,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin (\alpha_{2,2,1}) \right]$$

$$\alpha_{i,1,1} = \text{INVSIN} \left[ \frac{R_{(i-1),2}}{R_{i,1}} \sin (\alpha_{(i-1),2,2}) \right]$$

$$\alpha_{i,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\alpha_{i,1,1}) \right]$$

$$\alpha_{i,2,1} = \text{INVSIN} \left[ \frac{R_{i,1}}{R_{i,2}} \sin (\alpha_{i,1,2}) \right]$$

$$\alpha_{i,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin (\alpha_{i,2,1}) \right]$$

TABLE C-II (cont'd)

EQUATIONS WHICH DESCRIBE THE PATH OF A  
LASER BEAM THROUGH CYLINDRICALLY LAYERED MEDIA

$$(C-11) \quad \text{ALPHW} = \text{ALPH4G} + \alpha_{1,1,1} - \alpha_{1,1,2} + \alpha_{1,2,1} - \alpha_{1,2,2} \\ + \alpha_{2,1,1} + \alpha_{2,1,2} + \alpha_{2,2,1} - \alpha_{2,2,2} \\ \dots\dots\dots + \alpha_{i,1,1} - \alpha_{i,1,2} + \alpha_{i,2,1} - \alpha_{i,2,2}$$

$$(C-12) \quad \text{ALPHP} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin (\text{ALPHW}) \right]$$

$$(C-13) \quad \text{ALPHGH} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{air}}} \sin (\text{ALPHP}) \right]$$

$$(C-14) \quad \text{ANGLE} = \text{ALPHW} + \alpha_{i,2,2}$$

$$(C-15) \quad Y1 = R_{i,2} * \sin (\text{ANGLE}) + [D - R_{i,2} \cos (\text{ANGLE})] * [\tan (\text{ALPHW})] \\ + t * \tan (\text{ALPHP})$$



# CYLINDRICALLY LAYERED INTERFACES





FIGURE C-1

(ONLY INNER CYLINDER IS SHOWN)

$$\beta = \text{INVTAN} \left( \frac{y}{x} \right)$$

$$R_p = \frac{x}{\cos(\beta)}$$



From Geometry

$$\alpha_{1,1,1} = \text{INVSIN} \left[ \frac{R_p}{R_{1,1}} \sin(\beta - \text{ALPH4G}) \right]$$


From Snell's law

$$\alpha_{1,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin \alpha_{1,1,1} \right]$$

---- laser beam

FIGURE C-2

# DETERMINATION OF $\alpha_{1,2,1}$ and $\alpha_{1,2,2}$



From Geometry

$$\alpha_{1,2,1} = \text{INVSIN} \left[ \frac{R_{1,1}}{R_{1,2}} \sin \alpha_{1,1,2} \right]$$


From Snell's Law

$$\alpha_{1,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plexiglas}}}{n_{\text{water}}} \sin \alpha_{1,2,1} \right]$$

FIGURE C-3

# DETERMINATION OF $\alpha_{2,2,1}$ and $\alpha_{2,1,2}$

(OUTER BOX IS NOT SHOWN)



From Geometry

$$\alpha_{2,1,1} = \text{INVSIN} \left[ \frac{R_{1,2}}{R_{2,1}} \sin \alpha_{1,2,2} \right]$$

From Snell's law

$$\alpha_{2,1,2} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plexiglas}}} \sin \alpha_{2,1,1} \right]$$

--- laser beam

FIGURE C-4

# DETERMINATION OF $\alpha_{2,2,1}$ , $\alpha_{2,2,2}$ , ALPHW, ALPHP, ALPHGH

from Geometry

$$\alpha_{2,2,1} = \text{INVSIN} \left[ \frac{R_{2,1}}{R_{2,2}} \sin \alpha_{2,1,2} \right]$$

from Snell's law

$$\alpha_{2,2,2} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{water}}} \sin \alpha_{2,2,1} \right]$$

$$\text{ALPHP} = \text{INVSIN} \left[ \frac{n_{\text{water}}}{n_{\text{plex}}} \sin(\text{ALPHW}) \right]$$

$$\text{ALPHGH} = \text{INVSIN} \left[ \frac{n_{\text{plex}}}{n_{\text{air}}} \sin(\text{ALPHP}) \right]$$

from simple addition of angles

$$\text{ALPHW} = \text{ALPH4G}$$

$$\alpha_{1,1,1} - \alpha_{1,1,2} + \alpha_{1,2,1} - \alpha_{1,2,2}$$

$$\alpha_{2,1,1} - \alpha_{2,1,2} + \alpha_{2,2,1} - \alpha_{2,2,2}$$

$$\text{ANGLE} = \text{ALPHW} + \alpha_{2,2,2}$$




FIGURE C-5

DETERMINATION OF THE Y COORDINATE AT WHICH THE  
LASER BEAM EXITS THE PLEXIGLAS BOX

$$Y11 = R \cdot \sin(\text{ANGLE})$$

$$Y12 = [D - R22 \cos(\text{ANGLE})] \cdot \tan(\text{ALPHW})$$

$$Y13 = T \cdot \tan(\text{ALPHP})$$

$$Y1 = Y11 + Y12 + Y13$$




FIGURE C-6

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 01 OF 09

LDFT8

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C
1 C
1 C      APPENDIX D
1 C      (FORTRAN LISITING OF PROGRAM CYLINDER)
1 C
1 C
1 C
1 C*****
1 C      PROGRAM CYLINDER
1 C*****
1 C
9      IMPLICIT REAL*8(A-H,O-Z)
9      COMMON R(4,2),ALPH(4,2,2),TINW,TINP,ERR,ALPHH,ALPHP,RP,
6      * ALPHW,T,D,TINA,ANG1(11),ANG2(11),BETA,NTITLE(10),IS
1 C
9      READ(5,10) NTITLE
1 10      FORMAT(12A4)
9      ERR=0.00001D0
1 C----
1 C----      READ IN DATA
1 C----
1 C----      DEFINITION OF VARIABLES
1 C----
1 C----      XO= X COORDINATE OF REFERENCE POINT
1 C----
1 C----      YO= Y COORDINATE OF REFERENCE POINT
1 C----
1 C----      X= X COORDINATE OF DATA POINT
1 C----
1 C----      Y= Y COORDINATE OF DATA POINT
1 C----
1 C----      T = THICKNESS OF PLEXIGLASS WALL
1 C----
1 C----      D = DISTANCE FROM CENTER OF TUBE TO PLEXIGLASS WALL
1 C----
1 C----      TINW = INDEX OF REFRACTION FOR WATER
1 C----
1 C----      TINA = INDEX OF REFRACTION FOR AIR
1 C----
1 C----      TINP = INDEX OF REFRACTION FOR PLEXIGLASS
1 C----
1 C----      ALPHH= LASER DOPPLER ANEMONETER HALF ANGLE IN AIR
1 C----
9      READ(5,20) XO,YO,X,Y
9      WRITE(6,19) XO,YO,X,Y
1 19      FORMAT(' REFEDRENCE POINT: XO= ',D15.5,5X,' YO=',D15.5,/,
6      * ' DATA POINT : X= ',D15.5,' Y= ',D15.5)
9      READ(5,20) T,D
1 20      FORMAT(4D15.8)
9      READ(5,21) TINW,TINA,TINP,ALPHH
1 21      FORMAT(4D15.8)
9      DO 35 I=1,4
12      READ(5,30) (R(I,J),J=1,2)
12      WRITE(6,32) I,(R(I,J),J=1,2)
1 30      FORMAT(2D15.5)
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 02 OF 09

LDFT8

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 32      FORMAT(' CYLINDER',2X,I5,2X,'INNER RADIUS=',D15.5,2X,  
6 *      'OUTER RADIUS=',D15.5)  
1 35      CONTINUE  
1 C-----  
1 C----- DETERMINE HOW MANY CYLINDERS ARE PRESENT  
1 C-----  
7 IS=4  
7 IF(R(4,2).LT.0.00001D0)IS=3  
7 IF(R(3,2).LT.0.00001D0)IS=2  
7 IF(R(2,2).LT.0.00001D0)IS=1  
9 ALPHH=ALPHH/180.0*3.141592654D0  
9 ALPHHT = ALPHH  
1 C-----  
1 C----- COMPUTE PATH OF LASER BEAMS FOR REFERENCE POINT  
1 C-----  
9 CALL ANGLE(X0,Y0,ALPHHT,ALPH4G)  
9 H0 = HCALC(ALPHHT,ALPH4G)  
9 ALPHHT = -ALPHH  
9 CALL ANGLE(X0,Y0,ALPHHT,ALPH4G)  
9 H01 = HCALC(ALPHHT,ALPH4G)  
9 ALPHHT = ALPHH  
1 C-----  
1 C----- COMPUTE PATH OF LASER BEAMS FOR ACTUAL DATA POINT  
1 C-----  
9 CALL ANGLE(X,Y,ALPHHT,ALPH4G)  
9 H1 = HCALC(ALPHHT,ALPH4G)  
9 ANG1(1)=BETA  
9 ANG1(2)=ALPH4G+ALPH(1,1,1)  
9 ANG1(3)=ANG1(2)-ALPH(1,1,2)+ALPH(1,2,1)  
9 ANG1(4)=ANG1(3)-ALPH(1,2,2)+ALPH(2,1,1)  
9 ANG1(5)=ANG1(4)-ALPH(2,1,2)+ALPH(2,2,1)  
9 ANG1(6)=ANG1(5)-ALPH(2,2,2)+ALPH(3,1,1)  
9 ANG1(7)=ANG1(6)-ALPH(3,1,2)+ALPH(3,2,1)  
9 ANG1(8)=ANG1(7)-ALPH(3,2,2)+ALPH(4,1,1)  
9 ANG1(9)=ALPHW+ALPH(IS,2,2)  
9 ANG1(10)=ALPHW  
9 ANG1(11)=ALPHP  
9 A1=ALPH4G  
9 ALPHHT = -ALPHH  
9 CALL ANGLE(X,Y,ALPHHT,ALPH4G)  
9 ANG2(1)=BETA  
9 ANG2(2)=ALPH4G+ALPH(1,1,1)  
9 ANG2(3)=ANG2(2)-ALPH(1,1,2)+ALPH(1,2,1)  
9 ANG2(4)=ANG2(3)-ALPH(1,2,2)+ALPH(2,1,1)  
9 ANG2(5)=ANG2(4)-ALPH(2,1,2)+ALPH(2,2,1)  
9 ANG2(6)=ANG2(5)-ALPH(2,2,2)+ALPH(3,1,1)  
9 ANG2(7)=ANG2(6)-ALPH(3,1,2)+ALPH(3,2,1)  
9 ANG2(8)=ANG2(7)-ALPH(3,2,2)+ALPH(4,1,1)  
9 ANG2(9)=ALPHW+ALPH(IS,2,2)  
9 ANG2(10)=ALPHW  
9 ANG2(11)=ALPHP  
9 A2=ALPH4G  
9 H2 = HCALC(ALPHHT,ALPH4G)  
1 C-----
```



PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 03 OF 09

LDFT8

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
1 C---- COMPUTE HOW FAR THE LASER MUST BE MOVED FROM THE REFERENCE POINT
1 C----
9 HRZ      = (((H1-H2)/2.0-(H0-H01)/2.0)/DTAN(ALPHH))
9 HRZ      = -HRZ
9 VRT      = ((H1+H2)/2.0)-((H0+H01)/2.0)
1 C----
1 C---- COMPUTE THE NEW LDA HALF ANGLE IN THE FLUID MEDIUM
1 C----
9 TDIR=(A1-A2)/2.0
9 TDIR=TDIR*180.0/3.141592654
1 C----
1 C---- COMPUTE THE DIRECTION OF THE VELOCITY VECTOR IN THE FLUID
1 C---- MEDIUM
1 C----
9 TDIR2=3.141592654/2.0+(A1+A2)/2.0
9 TDIR2=TDIR2*180.0/3.141592654
1 C----
1 C---- PRINT OUT THE RESULTS
1 C----
9 WRITE(6,100)HRZ,VRT
9 WRITE(6,115)TDIR,TDIR2
1 100.  FORMAT(' LASER MUST BE MOVED ',D15.5,' IN THE HORIZONTAL ',
6 * 'DIRECTION',/, ' LASER MUST BE MOVED ',D15.5,' IN THE VERTICAL '
6 * ',DIRECTION')
1 115  FORMAT(' HALF ANGLE OF THE TWO BEAMS IN THE FLUID MEDIUM',
6 * ',D15.5,/, ' DIRECTION OF THE VELOCITY VECTOR ',D15.5)
1 C----
1 C---- PLOT THE RESULTS
1 C----
9 CALL DISSPL
9 STOP
9 END
1 C
9 SUBROUTINE ANGLE(X,Y,ALPHHT,ALPH4G)
9 IMPLICIT REAL*8(A-H,O-Z)
9 COMMON R(4,2),ALPH(4,2,2),TINW,TINP,ERR,ALPHH,ALPH,RP,
6 * ALPHW,T,D,TINA,ANG1(11),ANG2(11),BETA,NTITLE(10),IS
1 C----
1 C---- THIS ROUTINE CALCULATES THE ANGLE ASSOCIATED WITH THE BEAM
1 C----CROSSING. A REGULA FALSI METHOD IS USED TO SOLVE THE EQUATION SET.
1 C----
9 IFLAG = 0
9 ALPH4G = 0.0
1 25  CALL GEOM(X,Y,ALPH4G,ALPHGH)
9 IF (ALPHGH .GE. ALPHHT) GO TO 15
9 ALPHB = ALPHGH
9 ALPH42 = ALPH4G
9 ALPH4G = ALPH42+ALPHH/2.0
9 IFLAG = 1
9 GO TO 25
1 15  ALPHA = ALPHGH
9 ALPH41 = ALPH4G
9 IF (IFLAG .EQ. 1) GO TO 35
9 ALPH4G = ALPH41-ALPHH/2.0
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 04 OF 09

LDFT8

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

```
9      GO TO 25
1 35    ALPH4G = ALPH42+(ALPH41-ALPH42)/(ALPHA-ALPHB)*(ALPHHT-ALPHB)
9      CALL GEOM(X,Y,ALPH4G,ALPHGH)
9      IF (DABS(ALPHGH-ALPHHT) .LT. ERR) RETURN
9      IF (ALPHHT .GE. ALPHGH) GO TO 45
9      ALPHA = ALPHGH
9      ALPH41 = ALPH4G
9      GO TO 35
1 45    ALPHB = ALPHGH
9      ALPH42 = ALPH4G
9      GO TO 35
9      END

9      SUBROUTINE GEOM(X,Y,ALPH4G,ALPHGH)
1  C
1  C---- THIS ROUTINE CALCULATES THE VARIOUS ANGLES PERTINENT TO THE
1  C---- FLOW SECTION GEOMETRY GIVEN THE LATEST GUESS OF THE ANGLE
1  C---- ASSOCIATED WITH THE BEAM CROSSING.
1  C
9      IMPLICIT REAL*8(A-H,O-Z)
9      COMMON R(4,2),ALPH(4,2,2),TINW,TINP,ERR,ALPHH,ALPHP,RP,
6      * ALPHW,T,D,TINA,ANG1(11),ANG2(11),BETA,NTITLE(10),IS
1  C----
9      ALPH(1,1,1)=0.0
9      ALPH(1,1,2)=0.0
9      ALPH(1,2,1)=0.0
9      ALPH(1,2,2)=0.0
9      ALPH(2,1,1)=0.0
9      ALPH(2,1,2)=0.0
9      ALPH(2,2,1)=0.0
9      ALPH(2,2,2)=0.0
9      ALPH(3,1,1)=0.0
9      ALPH(3,1,2)=0.0
9      ALPH(3,2,1)=0.0
9      ALPH(3,2,2)=0.0
9      ALPH(4,1,1)=0.0
9      ALPH(4,1,2)=0.0
9      ALPH(4,2,1)=0.0
9      ALPH(4,2,2)=0.0
1  C----
9      IF (X .EQ. 0.0) GO TO 15
9      BETA = DATAN(Y/X)
9      RP = X/DCOS(BETA)
9      GO TO 25
1 15    BETA = 3.141592654/2.0
9      RP = Y
1  C----
1 25    ALPH(1,1,1)=DARSIN(RP/R(1,1)*DSIN(BETA-ALPH4G))
9      ALPH(1,1,2)=DARSIN(TINW/TINP*DSIN(ALPH(1,1,1)))
9      ALPH(1,2,1)=DARSIN(R(1,1)/R(1,2)*DSIN(ALPH(1,1,2)))
9      ALPH(1,2,2)=DARSIN(TINP/TINW*DSIN(ALPH(1,2,1)))
9      IF(R(2,2).LT.0.00001D0)GO TO 50
9      ALPH(2,1,1)=DARSIN(R(1,2)/R(2,1)*DSIN(ALPH(1,2,2)))
9      ALPH(2,1,2)=DARSIN(TINW/TINP*DSIN(ALPH(2,1,1)))
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 05 OF 09

LDFT8

START  
COL

```
-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8
9      ALPH(2,2,1)=DARSIN(R(2,1)/R(2,2)*DSIN(ALPH(2,1,2)))
9      ALPH(2,2,2)=DARSIN(TINP/TINW*DSIN(ALPH(2,2,1)))
9      IF(R(3,2).LT.0.00001)GO TO 50
9      ALPH(3,1,1)=DARSIN(R(2,2)/R(3,1)*DSIN(ALPH(2,2,2)))
9      ALPH(3,1,2)=DARSIN(TINW/TINP*DSIN(ALPH(3,1,1)))
9      ALPH(3,2,1)=DARSIN(R(3,1)/R(3,2)*DSIN(ALPH(3,1,2)))
9      ALPH(3,2,2)=DARSIN(TINP/TINW*DSIN(ALPH(3,2,1)))
9      IF(R(4,2).LT.0.00001)GO TO 50
9      ALPH(4,1,1)=DARSIN(R(3,2)/R(4,1)*DSIN(ALPH(3,2,2)))
9      ALPH(4,1,2)=DARSIN(TINW/TINP*DSIN(ALPH(4,1,1)))
9      ALPH(4,2,1)=DARSIN(R(4,1)/R(4,2)*DSIN(ALPH(4,1,2)))
9      ALPH(4,2,2)=DARSIN(TINP/TINW*DSIN(ALPH(4,2,1)))
1 50    CONTINUE
9      ALPHW=ALPH4G+ALPH(1,1,1)-ALPH(1,1,2)+ALPH(1,2,1)-ALPH(1,2,2)
6      * +ALPH(2,1,1)-ALPH(2,1,2)+ALPH(2,2,1)-ALPH(2,2,2)
6      * +ALPH(3,1,1)-ALPH(3,1,2)+ALPH(3,2,1)-ALPH(3,2,2)
6      * +ALPH(4,1,1)-ALPH(4,1,2)+ALPH(4,2,1)-ALPH(4,2,2)
9      ALPHP=DARSIN(TINW/TINP*DSIN(ALPHW))
9      ALPHGH=DARSIN(TINP/TINA*DSIN(ALPHP))
1  C----
9      RETURN
9      END

1  C----
9      FUNCTION HCALC(ALPHHT,ALPH4G)
9      IMPLICIT REAL*8(A-H,O-Z)
9      COMMON R(4,2),ALPH(4,2,2),TINW,TINP,ERR,ALPHH,ALPHP,RP,
6      * ALPHW,T,D,TINA,ANG1(11),ANG2(11),BETA,NTITLE(10),IS
1  C----
1  C---- THIS SUBROUTINE CALCULATES THE Y COORDINATE OF THE LASER BEAM AT
1  C---- THE PLEXIGLASS WALL
1  C----
9      ANGLE = ALPHW+ALPH(IS,2,2)
9      HCALC = R(IS,2)*DSIN(ANGLE)+(D-R(IS,2)*DCOS(ANGLE))*DTAN(ALPHW
6      * ) + T*DTAN(ALPHP)
9      RETURN
1  C
9      END

1  C
7  SUBROUTINE DISSPL
1  C
7  IMPLICIT REAL*8(A-H,O-Z)
9  COMMON R(4,2),ALPH(4,2,2),TINW,TINP,ERR,ALPHH,ALPHP,RP,
6  * ALPHW,T,D,TINA,ANG1(11),ANG2(11),BETA,NTITLE(10),IS
7  REAL*4 COORD1(1450),COORD2(1450),WORK(9000)
7  KGRAPH=0
1  C
1  C---- THIS ROUTINE DRAWS THE LASER BEAMS AND TEST SECTION USING THE      00040000
1  C---- DISSPLA GRAPHICS SYSTEM.                                          00040000
1  C
7  CALL DIGEST
7  CALL NOBRDR
1  C
1  C---- THIS COMMAND SETS THE PHYSICAL LOCATION OF THE CORRDIATE (0,0)
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 06 OF 09

LDFT8

START  
COL

```
-----1-----2-----3-----4-----5-----6-----7-----8
1 C      ON THE PLOT.  FOR THIS CASE THE PLOT ORIGIN IS LOCATED 0.75 INCHES
1 C---- FROM THE LEFT EDGE AND 0.75 INCHES FROM THE BOTTOM.
1 C
7       XPHYS=0.75                                00050000
7       YPHYS=0.75                                00110000
7       CALL PHYSOR(XPHYS,YPHYS)                  00350000
1 C
1 C---- THIS COMMAND SETS THE TOTAL SIZE OF PLOTTING AREA.      00400000
1 C
1 C
7       CALL PAGE(11.9375,8.500)                  00410000
7
73      00420000
7       XPAGE=6.5                                00430000
7       YPAGE=6.5                                00440000
7       YMAX1=R(IS,2)*DSIN(ANG1(9))+(D-R(IS,2)*DCOS(ANG1(9)))*DTAN(ANG1(10
7       *))+T*DTAN(ANG1(11))                      00450000
7       YMIN1=R(IS,2)*DSIN(ANG2(9))+(D-R(IS,2)*DCOS(ANG2(9)))*DTAN(ANG2(10
7       *))+T*DTAN(ANG2(11))                      00460000
7       YMAX=D+T
7       YMIN=-(D+T)
7       XMIN=-(D+T)
7       XMAX=D+T
1 C
1 C---- THIS COMMAND MAKES THE FIGURE FIT WITHIN THE PLOTTING 00470000
1 C---- AREA.                                                  00480000
1 C
1 C
7       CALL AREA2D(XPAGE,YPAGE)                  00490000
7
73      00500000
1 C
1 C--- DISSPLA HEADING COMMAND
1 C
7       CALL HEADIN(HTITLE,100,3,1)              00590000
7       XSTEP=1.0
7       YSTEP=1.0
1 C
1 C
1 C
1 C
1 C
1 C
7       CALL GRAF(XMIN,XSTEP,XMAX,YMIN,YSTEP,YMAX) 00760000
7
73      00760000
1 C
1 C
1 C---- THIS COMMAND SETS THE SCALE OF THE GRAPH ACCORDING TO VARIALBES IN00770000
1 C---- THE ARGUMENT.
1 C
1 C
1 C
7       CALL GRAF(XMIN,XSTEP,XMAX,YMIN,YSTEP,YMAX) 00780000
7
73      00780000
1 C
1 C
1 C
1 C
1 C
1 C
7       CALL NEWPEN(2)                                00790000
7
73      00790000
1 C
1 C
1 C---- THIS SECTION OF THE GRAPHICS ROUTINE DRAWS THE INPUT BLOCK AND
1 C---- COLORS IT.
1 C
1 C
1 C
7       CALL NEWPEN(2)
1 C
1 C---- THIS SECTION DRAWS THE CYLINDER
1 C
1 C
7       DO 200 J1=1,4
9         II=0
10        DO 150 J2=1,2
13          DTHET=360.0/180.0*3.141592654D0/720.0
13          TH=0.0
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 07 OF 09

LDFT8

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
13      DO 100 I=1,720
16      II=1+II
16      COORD1(II)=R(J1,J2)*DCOS(TH)
16      COORD2(II)=R(J1,J2)*DSIN(TH)
16      TH=TH+DTHET
1 100    CONTINUE
13      TH=TH+DTHET
16      II=1+II
13      COORD1(II)=R(J1,J2)*DCOS(TH)
13      COORD2(II)=R(J1,J2)*DSIN(TH)
1 150    CONTINUE
10      CALL SHADE(COORD1,COORD2,II,90.0,0.010,1,WORK,9000)
1 200    CONTINUE
1 C-----
1 C----- THIS SECTION DRAWS THE PLEXIGLASS WALL
1 C-----
7      COORD1(1)=D
7      COORD2(1)=-R(IS,2)
7      COORD1(2)=D+T
7      COORD2(2)=-R(IS,2)
7      COORD1(3)=D+T
7      COORD2(3)=R(IS,2)
7      COORD1(4)=D
7      COORD2(4)=R(IS,2)
7      COORD1(5)=D
7      COORD2(5)=-R(IS,2)
10      II=5
10      CALL SHADE(COORD1,COORD2,II,90.0,0.010,1,WORK,9000)
1 C-----
1 C----- THIS SECTION DRAWS THE LASER BEAMS
1 C-----
7      CALL NEWPEN(4)
7      COORD1(1)=RP*DCOS(ANG1(1))
7      COORD2(1)=RP*DSIN(ANG1(1))
7      COORD1(2)=R(1,1)*DCOS(ANG1(2))
7      COORD2(2)=R(1,1)*DSIN(ANG1(2))
13      DO 92 I=1,11
1 92      CONTINUE
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(1,1)*DCOS(ANG1(2))
7      COORD2(1)=R(1,1)*DSIN(ANG1(2))
7      COORD1(2)=R(1,2)*DCOS(ANG1(3))
7      COORD2(2)=R(1,2)*DSIN(ANG1(3))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
13      IF(R(2,2).LT.0.00001D0)GO TO 50
7      COORD1(1)=R(1,2)*DCOS(ANG1(3))
7      COORD2(1)=R(1,2)*DSIN(ANG1(3))
7      COORD1(2)=R(2,1)*DCOS(ANG1(4))
7      COORD2(2)=R(2,1)*DSIN(ANG1(4))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(2,1)*DCOS(ANG1(4))
7      COORD2(1)=R(2,1)*DSIN(ANG1(4))
7      COORD1(2)=R(2,2)*DCOS(ANG1(5))
7      COORD2(2)=R(2,2)*DSIN(ANG1(5))
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 08 OF 09

LDFT8

TART  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
13      IF(R(3,2).LT.0.00001D0)GO TO 50
7      COORD1(1)=R(2,2)*DCOS(ANG1(5))
7      COORD2(1)=R(2,2)*DSIN(ANG1(5))
7      COORD1(2)=R(3,1)*DCOS(ANG1(6))
7      COORD2(2)=R(3,1)*DSIN(ANG1(6))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(3,1)*DCOS(ANG1(6))
7      COORD2(1)=R(3,1)*DSIN(ANG1(6))
7      COORD1(2)=R(3,2)*DCOS(ANG1(7))
7      COORD2(2)=R(3,2)*DSIN(ANG1(7))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
13      IF(R(4,2).LT.0.00001D0)GO TO 50
7      COORD1(1)=R(3,2)*DCOS(ANG1(7))
7      COORD2(1)=R(3,2)*DSIN(ANG1(7))
7      COORD1(2)=R(4,1)*DCOS(ANG1(8))
7      COORD2(2)=R(4,1)*DSIN(ANG1(8))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(4,1)*DCOS(ANG1(8))
7      COORD2(1)=R(4,1)*DSIN(ANG1(8))
7      COORD1(2)=R(4,2)*DCOS(ANG1(9))
7      COORD2(2)=R(4,2)*DSIN(ANG1(9))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
1 50    CONTINUE
7      COORD1(1)=R(15,2)*DCOS(ANG1(9))
7      COORD2(1)=R(15,2)*DSIN(ANG1(9))
7      COORD1(2)=D
7      COORD2(2)=YMAX1-T*DTAN(ANG1(11))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=D
7      COORD2(1)=YMAX1-T*DTAN(ANG1(11))
7      COORD1(2)=D+T
7      COORD2(2)=YMAX1
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=RP*DCOS(ANG2(1))
7      COORD2(1)=RP*DSIN(ANG2(1))
7      COORD1(2)=R(1,1)*DCOS(ANG2(2))
7      COORD2(2)=R(1,1)*DSIN(ANG2(2))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(1,1)*DCOS(ANG2(2))
7      COORD2(1)=R(1,1)*DSIN(ANG2(2))
7      COORD1(2)=R(1,2)*DCOS(ANG2(3))
7      COORD2(2)=R(1,2)*DSIN(ANG2(3))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
13      IF(R(2,2).LT.0.00001D0)GO TO 70
7      COORD1(1)=R(1,2)*DCOS(ANG2(3))
7      COORD2(1)=R(1,2)*DSIN(ANG2(3))
7      COORD1(2)=R(2,1)*DCOS(ANG2(4))
7      COORD2(2)=R(2,1)*DSIN(ANG2(4))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(2,1)*DCOS(ANG2(4))
7      COORD2(1)=R(2,1)*DSIN(ANG2(4))
7      COORD1(2)=R(2,2)*DCOS(ANG2(5))
7      COORD2(2)=R(2,2)*DSIN(ANG2(5))
```

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: LDFT8  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:28  
PAGE: 09 OF 09

LDFT8

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

```
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
13      IF(R(3,2).LT.0.00001D0)GO TO 70
7      COORD1(1)=R(2,2)*DCOS(ANG2(5))
7      COORD2(1)=R(2,2)*DSIN(ANG2(5))
7      COORD1(2)=R(3,1)*DCOS(ANG2(6))
7      COORD2(2)=R(3,1)*DSIN(ANG2(6))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(3,1)*DCOS(ANG2(6))
7      COORD2(1)=R(3,1)*DSIN(ANG2(6))
7      COORD1(2)=R(3,2)*DCOS(ANG2(7))
7      COORD2(2)=R(3,2)*DSIN(ANG2(7))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
13      IF(R(4,2).LT.0.00001D0)GO TO 70
7      COORD1(1)=R(3,2)*DCOS(ANG2(7))
7      COORD2(1)=R(3,2)*DSIN(ANG2(7))
7      COORD1(2)=R(4,1)*DCOS(ANG2(8))
7      COORD2(2)=R(4,1)*DSIN(ANG2(8))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=R(4,1)*DCOS(ANG2(8))
7      COORD2(1)=R(4,1)*DSIN(ANG2(8))
7      COORD1(2)=R(4,2)*DCOS(ANG2(9))
7      COORD2(2)=R(4,2)*DSIN(ANG2(9))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
1 70  CONTINUE
7      COORD1(1)=R(1S,2)*DCOS(ANG2(9))
7      COORD2(1)=R(1S,2)*DSIN(ANG2(9))
7      COORD1(2)=D
7      COORD2(2)=YMIN1-T*DTAN(ANG2(11))
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      COORD1(1)=D
7      COORD2(1)=YMIN1-T*DTAN(ANG2(11))
7      COORD1(2)=D+T
7      COORD2(2)=YMIN1
13      CALL RLVEC(COORD1(1),COORD2(1),COORD1(2),COORD2(2),0)
7      CALL ENDPL(0)
7      CALL DONEPL(0)
7      RETURN
7      END
```

00010000

PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 01 OF 08

MARK26

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

21 APPENDIX E  
11 (INPUT DATA FILE FOR FIGURES 16-18)

1 MARK 22 BOTTOM FITTING INSERTS

|   |     |     |     |     |     |     |     |     |     |    |   |
|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|---|
| 3 | 225 | 44  | 8   | 2   |     |     |     |     |     |    |   |
| 5 | 1   | 5   | 6   | 7   | 19  | 32  | 31  | 30  | 18  | 1  | 2 |
| 5 | 2   | 3   | 4   | 5   | 9   | 15  | 14  | 11  | 8   | 1  | 2 |
| 5 | 3   | 11  | 12  | 13  | 17  | 23  | 22  | 21  | 16  | 1  | 2 |
| 5 | 4   | 21  | 23  | 24  | 26  | 30  | 29  | 28  | 25  | 1  | 2 |
| 5 | 5   | 1   | 2   | 3   | 20  | 28  | 108 | 27  | 10  | 1  | 0 |
| 5 | 6   | 30  | 31  | 32  | 38  | 52  | 50  | 48  | 47  | 1  | 2 |
| 5 | 7   | 30  | 36  | 37  | 46  | 45  | 44  | 43  | 35  | 1  | 2 |
| 5 | 8   | 28  | 29  | 30  | 35  | 43  | 42  | 41  | 34  | 1  | 2 |
| 5 | 9   | 27  | 108 | 28  | 34  | 41  | 40  | 39  | 33  | 1  | 0 |
| 4 | 10  | 39  | 40  | 41  | 54  | 112 | 58  | 55  | 53  | 1  | 0 |
| 4 | 11  | 41  | 43  | 45  | 215 | 218 | 217 | 216 | 214 | 1  | 2 |
| 4 | 12  | 45  | 48  | 49  | 114 | 105 | 104 | 103 | 113 | 1  | 0 |
| 4 | 13  | 49  | 51  | 52  | 115 | 107 | 106 | 105 | 114 | 1  | 2 |
| 4 | 14  | 55  | 56  | 57  | 63  | 67  | 66  | 65  | 62  | 1  |   |
| 4 | 15  | 65  | 66  | 67  | 71  | 75  | 74  | 73  | 70  | 1  | 0 |
| 4 | 16  | 73  | 74  | 75  | 81  | 85  | 84  | 83  | 80  | 1  | 0 |
| 4 | 17  | 57  | 58  | 59  | 64  | 69  | 68  | 67  | 63  | 1  | 2 |
| 4 | 18  | 67  | 68  | 69  | 72  | 77  | 76  | 75  | 71  | 1  | 2 |
| 4 | 19  | 75  | 76  | 77  | 82  | 87  | 86  | 85  | 81  | 1  | 2 |
| 4 | 20  | 59  | 60  | 61  | 79  | 89  | 88  | 87  | 78  | 1  | 0 |
| 4 | 21  | 110 | 111 | 112 | 92  | 101 | 100 | 99  | 91  | 1  | 0 |
| 4 | 22  | 61  | 109 | 110 | 91  | 99  | 98  | 97  | 90  | 1  | 2 |
| 4 | 23  | 83  | 86  | 89  | 94  | 97  | 96  | 95  | 93  | 1  | 0 |
| 4 | 24  | 208 | 209 | 116 | 137 | 213 | 212 | 211 | 210 | 1  | 0 |
| 4 | 25  | 140 | 141 | 142 | 146 | 150 | 149 | 213 | 145 | 1  | 0 |
| 4 | 26  | 148 | 149 | 150 | 154 | 167 | 161 | 156 | 153 | 1  | 0 |
| 4 | 27  | 118 | 119 | 120 | 139 | 144 | 143 | 142 | 138 | 1  | 2 |
| 4 | 28  | 120 | 121 | 122 | 173 | 205 | 204 | 203 | 172 | 1  | 0 |
| 4 | 29  | 122 | 123 | 124 | 174 | 207 | 206 | 205 | 173 | 1  | 2 |
| 4 | 30  | 126 | 127 | 128 | 131 | 133 | 136 | 207 | 125 | 1  | 0 |
| 4 | 31  | 128 | 129 | 130 | 132 | 135 | 134 | 133 | 131 | -1 | 2 |
| 4 | 32  | 142 | 143 | 144 | 147 | 152 | 151 | 150 | 146 | 1  | 2 |
| 4 | 33  | 150 | 151 | 152 | 155 | 169 | 168 | 167 | 154 | 1  | 2 |
| 4 | 34  | 165 | 166 | 167 | 182 | 201 | 200 | 199 | 181 | 1  | 0 |
| 4 | 35  | 164 | 163 | 165 | 181 | 199 | 198 | 197 | 180 | 1  | 2 |
| 4 | 36  | 160 | 162 | 164 | 180 | 197 | 196 | 195 | 179 | 1  | 0 |
| 4 | 37  | 158 | 159 | 160 | 179 | 195 | 194 | 193 | 178 | 1  | 2 |
| 4 | 38  | 156 | 157 | 158 | 171 | 177 | 176 | 175 | 170 | 1  | 0 |
| 4 | 39  | 175 | 176 | 177 | 185 | 188 | 187 | 186 | 184 | 1  | 0 |
| 4 | 40  | 186 | 187 | 188 | 190 | 193 | 192 | 191 | 189 | 1  | 0 |
| 4 | 41  | 116 | 117 | 118 | 138 | 142 | 141 | 140 | 137 | 1  | 0 |
| 4 | 42  | 167 | 168 | 169 | 183 | 203 | 202 | 201 | 182 | 1  | 2 |
| 4 | 43  | 216 | 217 | 218 | 220 | 223 | 222 | 221 | 219 | 1  | 0 |
| 4 | 44  | 221 | 222 | 223 | 225 | 120 | 119 | 118 | 224 | 1  | 2 |
| 3 | 1   | 2   | 4   | 6   | 30  |     |     |     |     |    |   |
| 3 | 2   | 1   | 3   | 5   |     |     |     |     |     |    |   |

1.490  
1.490



PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 02 OF 08

MARK26

START  
COL

|   | 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8           |
|---|----|----|----|----|----|----|----|-------------|
| 3 | 3  | 4  | 2  | 5  |    |    |    |             |
| 3 | 4  | 3  | 5  | 8  | 1  |    |    |             |
| 3 | 5  | 2  | 3  | 4  | 9  |    |    |             |
| 3 | 6  | 7  | 12 | 13 | 1  | 4  | 30 |             |
| 3 | 7  | 11 | 8  | 6  |    |    |    |             |
| 3 | 8  | 9  | 4  | 7  | 11 |    |    |             |
| 3 | 9  | 5  | 8  | 10 |    |    |    |             |
| 2 | 10 | 9  | 8  | 11 | 21 | 22 | 20 | 17 14 43 44 |
| 2 | 11 | 10 | 8  | 12 | 7  | 21 | 43 |             |
| 2 | 12 | 11 | 6  | 13 | 43 | 44 | 28 |             |
| 2 | 13 | 12 | 6  | 30 | 29 |    |    |             |
| 2 | 14 | 10 | 17 | 15 |    |    |    |             |
| 2 | 15 | 14 | 18 | 16 |    |    |    |             |
| 2 | 16 | 15 | 19 | 23 |    |    |    |             |
| 2 | 17 | 14 | 18 | 10 | 20 |    |    |             |
| 2 | 18 | 15 | 17 | 20 | 19 |    |    |             |
| 2 | 19 | 16 | 23 | 20 | 18 |    |    |             |
| 2 | 20 | 17 | 18 | 19 | 23 | 22 | 10 |             |
| 2 | 21 | 22 | 10 | 44 | 41 |    |    |             |
| 2 | 22 | 20 | 23 | 21 | 10 | 41 |    |             |
| 2 | 23 | 16 | 19 | 20 | 22 | 41 |    |             |
| 2 | 24 | 23 | 25 | 41 |    |    |    |             |
| 2 | 25 | 24 | 41 | 26 | 32 |    |    |             |
| 2 | 26 | 25 | 38 | 37 | 36 | 35 | 34 | 33          |
| 2 | 27 | 41 | 32 | 33 | 28 | 44 |    |             |
| 2 | 28 | 27 | 33 | 42 | 29 | 12 | 32 |             |
| 2 | 29 | 28 | 30 | 13 |    |    |    |             |
| 2 | 30 | 29 | 13 | 6  | 1  | 31 |    |             |
| 2 | 31 | 30 |    |    |    |    |    |             |
| 2 | 32 | 25 | 33 | 28 | 27 |    |    |             |
| 2 | 33 | 26 | 42 | 28 | 32 |    |    |             |
| 2 | 34 | 35 | 42 | 26 |    |    |    |             |
| 2 | 35 | 36 | 34 | 26 |    |    |    |             |
| 2 | 36 | 37 | 35 | 26 |    |    |    |             |
| 2 | 37 | 38 | 39 | 40 | 26 | 36 |    |             |
| 2 | 38 | 39 | 37 | 26 |    |    |    |             |
| 2 | 39 | 40 | 37 | 38 |    |    |    |             |
| 2 | 40 | 39 | 37 |    |    |    |    |             |
| 2 | 41 | 24 | 25 | 27 | 23 | 22 | 21 |             |
| 2 | 42 | 34 | 28 | 33 |    |    |    |             |
| 2 | 43 | 10 | 44 | 12 | 11 |    |    |             |
| 2 | 44 | 21 | 27 | 12 | 43 | 10 |    |             |
| 7 | 0  |    |    |    |    |    |    |             |
| 6 | -4 |    |    |    |    |    |    |             |
| 6 | -4 |    |    |    |    |    |    |             |
| 6 | -4 |    |    |    |    |    |    |             |
| 6 | -2 |    |    |    |    |    |    |             |
| 6 | -4 |    |    |    |    |    |    |             |
| 6 | -1 |    |    |    |    |    |    |             |
| 6 | -4 |    |    |    |    |    |    |             |
| 6 | -2 |    |    |    |    |    |    |             |
| 7 | 0  |    |    |    |    |    |    |             |
| 7 | 0  |    |    |    |    |    |    |             |
| 7 | 0  |    |    |    |    |    |    |             |

PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 03 OF 08

MARK26

START  
COL

-----1-----2-----3-----4-----5-----6-----7-----8

|    |    |          |         |  |
|----|----|----------|---------|--|
| 7  | 0  |          |         |  |
| 6  | -2 |          |         |  |
| 7  | 0  |          |         |  |
| 6  | -2 |          |         |  |
| 6  | -4 |          |         |  |
| 7  | 0  |          |         |  |
| 6  | -4 |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 6  | -3 |          |         |  |
| 6  | -2 |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 6  | -4 |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 6  | -4 |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 7  | 0  |          |         |  |
| 10 | 1  | 0.00     | 0.00    |  |
| 10 | 2  | 0.79260  | 0.00    |  |
| 10 | 3  | 1.5852   | 0.00    |  |
| 10 | 4  | 1.6501   | 0.00    |  |
| 10 | 5  | 1.7150   | 0.00    |  |
| 10 | 6  | 2.0140   | 0.00    |  |
| 10 | 7  | 2.3120   | 0.00    |  |
| 10 | 8  | 1.5297   | 0.63375 |  |
| 10 | 9  | 1.7150   | 0.63375 |  |
| 9  | 10 | 0.00     | 1.20125 |  |
| 9  | 11 | 1.4743   | 1.26750 |  |
| 9  | 12 | 1.537154 | 1.26750 |  |
| 9  | 13 | 1.6000   | 1.26750 |  |
| 9  | 14 | 1.594654 | 1.26750 |  |
| 9  | 15 | 1.7150   | 1.26750 |  |
| 9  | 16 | 1.46293  | 1.20125 |  |
| 9  | 17 | 1.60000  | 1.39750 |  |
| 9  | 18 | 1.71550  | 1.20125 |  |
| 9  | 19 | 2.31200  | 1.20125 |  |
| 9  | 20 | 1.480104 | 1.20125 |  |
| 9  | 21 | 1.451560 | 1.5275  |  |
| 9  | 22 | 1.56250  | 1.5275  |  |

PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 04 OF 08

MARK26

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

|   |    |         |          |
|---|----|---------|----------|
| 9 | 23 | 1.6000  | 1.5275   |
| 9 | 24 | 1.7150  | 1.5275   |
| 9 | 25 | 1.41328 | 1.9650   |
| 9 | 26 | 1.7150  | 1.9650   |
| 9 | 27 | 0.00    | 2.4025   |
| 9 | 28 | 1.375   | 2.4025   |
| 9 | 29 | 1.545   | 2.4025   |
| 9 | 30 | 1.715   | 2.4025   |
| 9 | 31 | 2.0135  | 2.4025   |
| 9 | 32 | 2.3120  | 2.4025   |
| 9 | 33 | 0.00    | 2.49625  |
| 9 | 34 | 1.46875 | 2.49625  |
| 9 | 35 | 1.71500 | 2.49625  |
| 9 | 36 | 1.7775  | 2.465    |
| 9 | 37 | 1.8400  | 2.5275   |
| 9 | 38 | 2.3120  | 2.5275   |
| 9 | 39 | 0.00    | 2.59     |
| 9 | 40 | 0.78125 | 2.59     |
| 9 | 41 | 1.56250 | 2.59     |
| 9 | 42 | 1.63875 | 2.59     |
| 9 | 43 | 1.71500 | 2.59     |
| 9 | 44 | 1.77750 | 2.59     |
| 9 | 45 | 1.84000 | 2.59     |
| 9 | 46 | 1.84000 | 2.558750 |
| 9 | 47 | 1.80875 | 2.49625  |
| 9 | 48 | 1.90250 | 2.59     |
| 9 | 49 | 2.06200 | 2.59     |
| 9 | 50 | 2.10725 | 2.59     |
| 9 | 51 | 2.187   | 2.59     |
| 9 | 52 | 2.312   | 2.59     |
| 9 | 53 | 0.00    | 3.16     |
| 9 | 54 | 1.5625  | 3.16     |
| 9 | 55 | 0.00    | 3.73     |
| 9 | 56 | 0.3250  | 3.73     |
| 9 | 57 | 0.65    | 3.73     |
| 9 | 58 | 0.70    | 3.73     |
| 9 | 59 | 0.75    | 3.73     |
| 9 | 60 | 0.9885  | 3.73     |
| 9 | 61 | 1.2270  | 3.73     |
| 9 | 62 | 0.00    | 3.85125  |
| 9 | 63 | 0.580   | 3.85125  |
| 9 | 64 | 0.75    | 3.85125  |
| 9 | 65 | 0.00    | 3.9725   |
| 9 | 66 | 0.255   | 3.97250  |
| 9 | 67 | 0.51    | 3.9725   |
| 9 | 68 | 0.630   | 3.9725   |
| 9 | 69 | 0.750   | 3.9725   |
| 9 | 70 | 0.00    | 4.035    |
| 9 | 71 | 0.510   | 4.035    |
| 9 | 72 | 0.750   | 4.035    |
| 9 | 73 | 0.00    | 4.0975   |
| 9 | 74 | 0.255   | 4.0975   |
| 9 | 75 | 0.510   | 4.0975   |
| 9 | 76 | 0.630   | 4.0975   |

PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 05 OF 08

MARK26

| START<br>COL | 1   | 2       | 3 | 4       | 5 | 6 | 7 | 8 |
|--------------|-----|---------|---|---------|---|---|---|---|
| 9            | 77  | 0.750   |   | 4.0975  |   |   |   |   |
| 9            | 78  | 0.750   |   | 3.9450  |   |   |   |   |
| 9            | 79  | 1.227   |   | 3.9450  |   |   |   |   |
| 9            | 80  | 0.000   |   | 4.12875 |   |   |   |   |
| 9            | 81  | 0.54125 |   | 4.12875 |   |   |   |   |
| 9            | 82  | 0.75000 |   | 4.12875 |   |   |   |   |
| 9            | 83  | 0.000   |   | 4.16000 |   |   |   |   |
| 9            | 84  | 0.28625 |   | 4.16000 |   |   |   |   |
| 9            | 85  | 0.57250 |   | 4.16000 |   |   |   |   |
| 9            | 86  | 0.66125 |   | 4.16000 |   |   |   |   |
| 9            | 87  | 0.75000 |   | 4.16000 |   |   |   |   |
| 9            | 88  | 0.98850 |   | 4.16000 |   |   |   |   |
| 9            | 89  | 1.22700 |   | 4.16000 |   |   |   |   |
| 9            | 90  | 1.22700 |   | 4.25500 |   |   |   |   |
| 9            | 91  | 1.35750 |   | 4.25500 |   |   |   |   |
| 9            | 92  | 1.56250 |   | 4.25500 |   |   |   |   |
| 9            | 93  | 0.00000 |   | 4.47000 |   |   |   |   |
| 9            | 94  | 1.22700 |   | 4.47000 |   |   |   |   |
| 9            | 95  | 0.0     |   | 4.78000 |   |   |   |   |
| 9            | 96  | 0.61350 |   | 4.78000 |   |   |   |   |
| 9            | 97  | 1.22700 |   | 4.78000 |   |   |   |   |
| 9            | 98  | 1.29225 |   | 4.78000 |   |   |   |   |
| 9            | 99  | 1.35750 |   | 4.78000 |   |   |   |   |
| 8            | 100 | 1.46000 |   | 4.78000 |   |   |   |   |
| 8            | 101 | 1.56250 |   | 4.78000 |   |   |   |   |
| 8            | 102 | 1.70125 |   | 4.78000 |   |   |   |   |
| 8            | 103 | 1.84000 |   | 4.78000 |   |   |   |   |
| 8            | 104 | 1.95100 |   | 4.78000 |   |   |   |   |
| 8            | 105 | 2.06200 |   | 4.78000 |   |   |   |   |
| 8            | 106 | 2.18700 |   | 4.78000 |   |   |   |   |
| 8            | 107 | 2.31200 |   | 4.78000 |   |   |   |   |
| 8            | 108 | 0.68750 |   | 2.40250 |   |   |   |   |
| 8            | 109 | 1.29225 |   | 3.730   |   |   |   |   |
| 8            | 110 | 1.35750 |   | 3.730   |   |   |   |   |
| 8            | 111 | 1.46000 |   | 3.730   |   |   |   |   |
| 8            | 112 | 1.56250 |   | 3.730   |   |   |   |   |
| 8            | 113 | 1.840   |   | 3.730   |   |   |   |   |
| 8            | 114 | 2.062   |   | 3.730   |   |   |   |   |
| 8            | 115 | 2.312   |   | 3.730   |   |   |   |   |
| 8            | 116 | 0.451   |   | 4.780   |   |   |   |   |
| 8            | 117 | 1.00675 |   | 4.780   |   |   |   |   |
| 8            | 118 | 1.56250 |   | 4.780   |   |   |   |   |
| 8            | 119 | 1.70125 |   | 4.780   |   |   |   |   |
| 8            | 120 | 1.84000 |   | 4.780   |   |   |   |   |
| 8            | 121 | 1.95100 |   | 4.780   |   |   |   |   |
| 8            | 122 | 2.06200 |   | 4.780   |   |   |   |   |
| 8            | 123 | 2.1870  |   | 4.780   |   |   |   |   |
| 8            | 124 | 2.3120  |   | 4.780   |   |   |   |   |
| 8            | 125 | 2.312   |   | 4.125   |   |   |   |   |
| 8            | 126 | 2.312   |   | 0.000   |   |   |   |   |
| 8            | 127 | 4.156   |   | 0.000   |   |   |   |   |
| 8            | 128 | 6.000   |   | 0.000   |   |   |   |   |
| 8            | 129 | 6.125   |   | 0.000   |   |   |   |   |
| 8            | 130 | 6.250   |   | 0.000   |   |   |   |   |

PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 06 OF 08

MARK26

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

|   |     |          |          |
|---|-----|----------|----------|
| 8 | 131 | 6.000    | 4.215    |
| 8 | 132 | 6.250    | 4.125    |
| 8 | 133 | 6.000    | 8.430    |
| 8 | 134 | 6.125    | 8.430    |
| 8 | 135 | 6.250    | 8.430    |
| 8 | 136 | 4.156    | 8.430    |
| 8 | 137 | 0.451    | 5.368750 |
| 8 | 138 | 1.56250  | 5.368750 |
| 8 | 139 | 1.84000  | 5.368750 |
| 8 | 140 | 0.451    | 5.95750  |
| 8 | 141 | 1.006750 | 5.95750  |
| 8 | 142 | 1.56250  | 5.95750  |
| 8 | 143 | 1.70125  | 5.95750  |
| 8 | 144 | 1.8400   | 5.9575   |
| 8 | 145 | 0.45100  | 6.05875  |
| 8 | 146 | 1.66625  | 6.05875  |
| 8 | 147 | 1.84000  | 6.05875  |
| 8 | 148 | 0.65350  | 6.16000  |
| 8 | 149 | 1.32925  | 6.16000  |
| 8 | 150 | 1.7700   | 6.160    |
| 8 | 151 | 1.805    | 6.160    |
| 8 | 152 | 1.840    | 6.160    |
| 8 | 153 | 0.6535   | 6.345    |
| 8 | 154 | 1.77000  | 6.345    |
| 8 | 155 | 1.84000  | 6.345    |
| 8 | 156 | 0.6535   | 6.530    |
| 8 | 157 | 0.8255   | 6.530    |
| 8 | 158 | 0.9975   | 6.530    |
| 8 | 159 | 1.087    | 6.530    |
| 8 | 160 | 1.17650  | 6.530    |
| 8 | 161 | 1.21175  | 6.530    |
| 8 | 162 | 1.31125  | 6.530    |
| 8 | 163 | 1.5230   | 6.530    |
| 8 | 164 | 1.446    | 6.530    |
| 8 | 165 | 1.60     | 6.530    |
| 8 | 166 | 1.685    | 6.530    |
| 8 | 167 | 1.770    | 6.530    |
| 8 | 168 | 1.805    | 6.530    |
| 8 | 169 | 1.840    | 6.530    |
| 8 | 170 | 0.65350  | 6.980    |
| 8 | 171 | 0.9975   | 6.980    |
| 8 | 172 | 1.840    | 6.6050   |
| 8 | 173 | 2.062    | 6.6050   |
| 8 | 174 | 2.312    | 6.6050   |
| 8 | 175 | 0.6535   | 7.430    |
| 8 | 176 | 0.8255   | 7.430    |
| 8 | 177 | 0.9975   | 7.430    |
| 8 | 178 | 0.9975   | 7.480    |
| 8 | 179 | 1.17650  | 7.480    |
| 8 | 180 | 1.44600  | 7.480    |
| 8 | 181 | 1.60000  | 7.480    |
| 8 | 182 | 1.77000  | 7.480    |
| 8 | 183 | 1.84000  | 7.480    |
| 8 | 184 | 0.72425  | 7.730    |

PROJECT: T5712  
LIBRARY: EDIT  
TYPE: DATA

MEMBER: MARK26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/07  
TIME: 10:16  
PAGE: 07 OF 08

MARK26

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

|    |     |         |         |     |      |       |  |
|----|-----|---------|---------|-----|------|-------|--|
| 8  | 185 | 0.99750 | 7.730   |     |      |       |  |
| 8  | 186 | 0.7950  | 8.030   |     |      |       |  |
| 8  | 187 | 0.89625 | 8.030   |     |      |       |  |
| 8  | 188 | 0.9975  | 8.030   |     |      |       |  |
| 8  | 189 | 0.795   | 8.230   |     |      |       |  |
| 8  | 190 | 0.9975  | 8.230   |     |      |       |  |
| 8  | 191 | 0.795   | 8.430   |     |      |       |  |
| 8  | 192 | 0.89625 | 8.430   |     |      |       |  |
| 8  | 193 | 0.9975  | 8.430   |     |      |       |  |
| 8  | 194 | 1.807   | 8.430   |     |      |       |  |
| 8  | 195 | 1.17650 | 8.430   |     |      |       |  |
| 8  | 196 | 1.31125 | 8.430   |     |      |       |  |
| 8  | 197 | 1.44600 | 8.430   |     |      |       |  |
| 8  | 198 | 1.523   | 8.430   |     |      |       |  |
| 8  | 199 | 1.60    | 8.430   |     |      |       |  |
| 8  | 200 | 1.685   | 8.430   |     |      |       |  |
| 8  | 201 | 1.770   | 8.430   |     |      |       |  |
| 8  | 202 | 1.805   | 8.430   |     |      |       |  |
| 8  | 203 | 1.840   | 8.430   |     |      |       |  |
| 8  | 204 | 1.951   | 8.430   |     |      |       |  |
| 8  | 205 | 2.062   | 8.430   |     |      |       |  |
| 8  | 206 | 2.187   | 8.430   |     |      |       |  |
| 8  | 207 | 2.312   | 8.430   |     |      |       |  |
| 8  | 208 | 0.000   | 4.780   |     |      |       |  |
| 8  | 209 | 0.22550 | 4.780   |     |      |       |  |
| 8  | 210 | 0.0     | 5.00550 |     |      |       |  |
| 8  | 211 | 0.0     | 5.70900 |     |      |       |  |
| 8  | 212 | 0.22550 | 5.93450 |     |      |       |  |
| 8  | 213 | 0.45100 | 6.16000 |     |      |       |  |
| 8  | 214 | 1.56250 | 2.76500 |     |      |       |  |
| 8  | 215 | 1.84000 | 2.76500 |     |      |       |  |
| 8  | 216 | 1.56250 | 2.94000 |     |      |       |  |
| 8  | 217 | 1.70125 | 2.94000 |     |      |       |  |
| 8  | 218 | 1.84000 | 2.94000 |     |      |       |  |
| 8  | 219 | 1.56250 | 3.25000 |     |      |       |  |
| 8  | 220 | 1.84000 | 3.25000 |     |      |       |  |
| 8  | 221 | 1.56250 | 3.56000 |     |      |       |  |
| 8  | 222 | 1.70125 | 3.56000 |     |      |       |  |
| 8  | 223 | 1.84000 | 3.56000 |     |      |       |  |
| 8  | 224 | 1.56250 | 4.17000 |     |      |       |  |
| 8  | 225 | 1.84000 | 4.17000 |     |      |       |  |
| 4  | 10  | 0.00    | 3.16    | 5.5 | 1.33 | 1.490 |  |
| 5  | 1   |         |         |     |      |       |  |
| 8  |     | 1.0     | 1.0     |     |      |       |  |
| 9  | 20  |         | 1       |     |      |       |  |
| 9  |     | 0.98550 | 3.945   |     |      |       |  |
| 10 | 0   |         |         |     |      |       |  |

PROJECT: T5712  
LIBRARY: TAPE  
TYPE: DATA

MEMBER: CIRC26  
LEVEL: 01.99  
USERID: T5712

DATE: 84/09/06  
TIME: 10:29  
PAGE: 01 OF 01

CIRC26

START  
COL

-----+-----1-----+-----2-----+-----3-----+-----4-----+-----5-----+-----6-----+-----7-----+-----8

24  
14  
1  
13  
12  
12  
12  
12  
12  
12

APPENDIX F

(INPUT DATA FILE FOR FIGURES 19-26)

CYLINDRICAL TEST CASES

|      |        |      |      |
|------|--------|------|------|
| 0.7  | 0.0    | -0.3 | 0.72 |
| 0.25 | 5.00   |      |      |
| 1.33 | 1.0    | 1.49 | 5.5  |
| 3.70 | 4.00   |      |      |
| 0.80 | 1.0000 |      |      |
| 1.70 | 2.00   |      |      |
| 2.70 | 3.00   |      |      |